



The XePersian *Package*

Documentation for *version 16.3*

to my Master, Ferdowsi The Great

If you want to report any bugs or typos and corrections in the documentation, or ask for any new features, or suggest any improvements, or ask any questions about the package, then please do not send any direct email to me; I will not answer any direct email. Instead please use the issue tracker:

<https://github.com/persian-tex/xepersian/issues>

In doing so, please always explain your issue well enough, always include a minimal working example showing the issue, and always choose the appropriate label for your query (i.e. if you are reporting any bugs, choose 'Bug' label).

Copyright (c) 2008–2015 Vafa Khalighi

Permission is granted to distribute and/or modify *both the documentation and the code* under the conditions of the L^AT_EX Project Public License, either version 1.3c of this license or (at your option) any later version.

The XePersian *Package*

Persian for \LaTeX 2 ϵ , using Xe \TeX engine

Documentation for [version 16.3](#)

Vafa Khalighi
persian-tex@tug.org

November 14, 2015

Contents

1	Introduction	4			
1.1	Important Notes	4			
1.2	XePersian Info On The Terminal and In The Log File	4			
2	Basics	5			
2.1	Loading The Package	5			
2.2	XePersian's Symbol	6			
2.3	Commands for Version number, and Date of The Package	6			
2.4	Options of The Package	6			
2.4.1	<code>defaultlatinfontfeatures</code> Option	6	2.6.1	Basic Font Commands	39
2.4.2	<code>extrafootnotefeatures</code> Option	6	2.6.2	Defining Extra Persian and Latin Fonts	39
2.4.3	Kashida Option	7	2.6.3	Choosing Persian Sans Font	40
2.4.4	<code>quickindex</code> Option	7	2.6.4	Choosing Persian Mono Font	40
2.4.5	<code>quickindex-variant1</code> Option	7	2.6.5	Choosing Persian Iranic Font	40
2.4.6	<code>quickindex-variant2</code> Option	7	2.6.6	Choosing Persian Navar Font	40
2.4.7	<code>localise</code> Option	7	2.6.7	Choosing Persian Pook Font	40
2.4.8	Localizations of the keys and key values of <code>graphicx</code> package	35	2.6.8	Choosing Persian Sayeh Font	40
2.4.9	Localizations of font features and font feature options	36	2.6.9	Choosing Latin Sans Font	40
2.5	A Sample Input \TeX File	38	2.6.10	Choosing Latin Mono Font	40
2.6	Font Commands	38	3	Latin and Persian Environment	41
			3.1	<code>latinitems</code> and <code>parsiitems</code> environments	41
			3.2	Short Latin and Persian Texts	41
			3.3	Miscellaneous Commands	41
			3.4	New Commands	42
			3.5	Additional Counters	42
			3.6	Things To Know About <code>\setdigitfont</code> , <code>\setmathsfdigitfont</code> , and <code>\setmathttdigitfont</code>	43

4	New Conditionals	43	7	xepersian implementation	55
4.1	Shell escape (or write18) conditional	43	7.1	algorithmic-xepersian.def	55
5	Bilingual Captions	43	7.2	algorithm-xepersian.def	56
5.1	Support For Various Packages	44	7.3	amsart-xepersian.def	56
5.1.1	Things You Should Know about Support For enumerate Package	44	7.4	amsbook-xepersian.def	57
5.2	Index Generation	44	7.5	appendix-xepersian.def	58
5.3	Converting Your FarsiT _E X Files To XePersian or Unicode	44	7.6	article-xepersian.def	59
6	Extra Packages And Classes	45	7.7	artikel1-xepersian.def	59
6.1	Magazine Typesetting	45	7.8	artikel2-xepersian.def	59
6.1.1	Introduction	45	7.9	artikel3-xepersian.def	59
6.1.2	Usage	45	7.10	backref-xepersian.def	59
6.1.3	Front Page	45	7.11	bidituftesidenote-xepersian.def	60
6.1.4	Inside	47	7.12	bidimoderncv-xepersian.def . . .	61
6.1.5	The article environment	47	7.13	boek3-xepersian.def	61
6.1.6	The editorial environment	48	7.14	boek-xepersian.def	62
6.1.7	The shortarticle environment	49	7.15	bookest-xepersian.def	62
6.1.8	Commands between articles	49	7.16	book-xepersian.def	62
6.1.9	Customization	49	7.17	breqn-xepersian.def	62
6.1.10	Front Page	50	7.18	latex-localise-commands-xepersian.def	63
6.1.11	Inside The Magazine	51	7.19	color-localise-xepersian.def . . .	82
6.1.12	Class Options	52	7.20	xepersian-localise-commands-xepersian.def	82
6.2	Typesetting Multiple-choice Questions	52	7.21	enumerate-xepersian.def	84
6.2.1	Introduction	52	7.22	latex-localise-environments-xepersian.def	84
6.2.2	Usage	53	7.23	xepersian-localise-environments-xepersian.def	85
6.2.3	Loading The Package	53	7.24	extarticle-xepersian.def	85
6.2.4	Creating Questions	53	7.25	extbook-xepersian.def	85
6.2.5	The question Environment	53	7.26	extrafootnotefeatures-xepersian.def	86
6.2.6	Question Numbers	53	7.27	extreport-xepersian.def	86
6.2.7	The Form and the Mask	54	7.28	flowfram-xepersian.def	86
6.2.8	Typesetting corrections	54	7.29	footnote-xepersian.def	87
6.2.9	Important Note	54	7.30	framed-xepersian.def	89
6.3	Customising The Package	54	7.31	glossaries-xepersian.def	89
6.3.1	The question environment	55	7.32	hyperref-xepersian.def	89
6.3.2	The Form and the Mask	55	7.33	imsproc-xepersian.def	90
6.3.3	The correction	55	7.34	kashida-xepersian.def	93
			7.35	listings-xepersian.def	94
			7.36	loadingorder-xepersian.def . . .	94
			7.37	localise-xepersian.def	95
			7.38	memoir-xepersian.def	96
			7.39	latex-localise-messages-xepersian.def	97
			7.40	minitoc-xepersian.def	97
			7.41	latex-localise-misc-xepersian.def	97
			7.42	natbib-xepersian.def	104
			7.43	packages-localise-xepersian.def	109



7.44	parsidigits.map	112	7.53	tkz-linknodes-xepersian.def	115
7.45	rapport1-xepersian.def	113	7.54	tocloft-xepersian.def	116
7.46	rapport3-xepersian.def	113	7.55	xepersian.sty	116
7.47	refrep-xepersian.def	113	7.56	xepersian-magazine.cls	132
7.48	report-xepersian.def	113	7.57	xepersian-mathsdigitspec.sty	149
7.49	scrartcl-xepersian.def	113	7.58	xepersian-multiplechoice.sty	154
7.50	scrbook-xepersian.def	114	7.59	xepersian-persiancal.sty	157
7.51	scrreprt-xepersian.def	115			
7.52	soul-xepersian.def	115	8	Change History	195



1 Introduction

XePersian is a package for typesetting Persian/English documents with Xe \LaTeX . The package includes adaptations for use with many other commonly-used packages.

1.1 Important Notes

- ☞ The XePersian package only works with Xe \TeX engine.
- ☞ Before reading this documentation, you should have read the documentation of the bidi package. The XePersian package automatically loads bidi package with `RTLdocument` option enabled and hence any commands that bidi package offers, is also available in XePersian package. Here, in this documentation, we will not repeat any of bidi package's commands.
- ☞ In previous versions ($\leq 1.0.3$) of XePersian, a thesis class provided for typesetting thesis. As of version 1.0.4, we no longer provide this class because we are not familiar with specification of a thesis in Iran and even if we were, the specifications are different from University to University. XePersian is a general package like \LaTeX and should not provide any class for typesetting thesis. So if you really want to have a class file for typesetting thesis, then you should ask your University/department to write one for you.

1.2 XePersian Info On The Terminal and In The Log File

If you use XePersian package to write any input \TeX document, and then run `xelatex` on your document, in addition to what bidi package writes to the terminal and to the log file, the XePersian package also writes some information about itself to the terminal and to the log file, too. The information is something like:

```
*****
*
* xepersian package (Persian for LaTeX, using XeTeX engine)
*
* Description: The package supports Persian
* typesetting, using fonts provided in the
* distribution.
*
* Copyright (c) 2008--2015 Vafa Khalighi
*
* v16.3, 2015/11/14
*
* License: LaTeX Project Public License, version
* 1.3c or higher (your choice)
*
* Location on CTAN: /macros/xetex/latex/xepersian
*
* Issue tracker: https://github.com/persian-tex/xepersian/issues
```



*
 * Support: persian-tex@tug.org

2 Basics

2.1 Loading The Package

You can load the package in the ordinary way;

```
\usepackage [Options] {xepersian}
```

Where options of the package are explained later in [subsection 2.4](#).

When loading the package, it is important to know that:

- ❶ xepersian should be the last package that you load, because otherwise you are certainly going to overwrite bidi and XePersian package's definitions and consequently, you will not get the expected output.

- ❷ In fact, in addition to bidi, XePersian also makes sure that some specific packages are loaded before bidi and XePersian; these are those packages that bidi and XePersian modifies them for bidirectional and Persian/English typesetting.

If you load XePersian before any of these packages, then you will get an error saying that you should load XePersian or bidi as your last package. When it says that you should load bidi package as your last package, it really means that you should load XePersian as your last package as bidi package is loaded automatically by XePersian package.

For instance, consider the following minimal example:

```
1 \documentclass{minimal}
2 \usepackage{xepersian}
3 \usepackage{enumerate}
4 \settextfont{XB Niloofar}
5 \begin{document}
6 این فقط یک آزمایش است
7 \end{document}
```

Where enumerate is loaded after XePersian. If you run xelatex on this document, you will get an error which looks like this:

```
! Package xepersian Error: Oops! you have loaded package enumerate
after xepersian package. Please load package enumerate before
xepersian package, and then try to run xelatex on your document
again.
```

```
See the xepersian package documentation for explanation.
Type H <return> for immediate help.
```



```
...
1.5 \begin{document}
?
```

2.2 XePersian's Symbol

As you may know lion symbolizes T_EX but lion does not symbolizes XePersian. **Simorgh**¹ (shown on the first page of this documentation) symbolizes XePersian.

2.3 Commands for Version number, and Date of The Package

```
\xepersianversion \xepersiandate
```

☞ `\xepersianversion` gives the current version of the package.

☞ `\xepersiandate` gives the current date of the package.

```
1 \documentclass{article}
2 \usepackage{xepersian}
3 \settextfont{XB Niloofar}
4 \begin{document}
5 \begin{latin}
6 This is typeset by \textsf{\XePersian} package, \xepersianversion,
7 \xepersiandate.
8 \end{latin}
9 \end{document}
```

2.4 Options of The Package

There are few options:

2.4.1 defaultlatinfontfeatures Option

```
defaultlatinfontfeatures=<value>
```

The `defaultlatinfontfeatures` option allows you to pass font features to the main Latin font. `<value>` is a set of font features.

2.4.2 extrafootnotefeatures Option

This is just the `extrafootnotefeatures` Option of `bidi` package. If you enable this option, you can typeset footnotes in paragraph form or in multi-columns (from two-columns to ten-columns). For more details, please read the manual of `bidi` package.

¹**Simorgh** is an Iranian benevolent, mythical flying creature which has been shown on the titlepage of this documentation. For more details see <http://en.wikipedia.org/wiki/Simurgh>



2.4.3 Kashida Option

If you pass Kashida option to the package, you will use Kashida for stretching words for better output quality and getting rid of underfull or overfull `\hbox` messages. Note that you can not use Kashida option when you are using Nastaliq-like font (well, you still can use Kashida option when you use any Nastaliq-like font, but I can not guarantee high quality output!).

The following two commands are provided when you activate the Kashida option:

`\KashidaOn` `\KashidaOff`

☞ `\KashidaOn` enables Kashida and is active by default when Kashida option is activated.

☞ `\KashidaOff` disables Kashida.

2.4.4 quickindex Option

When you generally want to prepare index for your Persian documents, you need to first run `xelatex`, then `xindy`, and again `xelatex` on your document respectively, which is very time consuming. The `quickindex` option gives you the index with only and only one run of `xelatex`. To use this feature, you will need to run `xelatex --shell-escape` on your \TeX document; otherwise you get an error which indicates that shell escape (or `write18`) is not enabled.

This option is now obsolete and equivalent to `quickindex-variant2` option.

2.4.5 quickindex-variant1 Option

Same as `quickindex` Option but uses variant one (in which $\tilde{}$ is grouped under $\bar{}$) for sorting Persian alphabets.

2.4.6 quickindex-variant2 Option

Same as `quickindex` Option but uses variant two (in which $\tilde{}$ is a separate letter) for sorting Persian alphabets.

2.4.7 localise Option

This option allows you to use most frequently-used \LaTeX commands and environments in Persian, almost like what \TeX -e-Parsi offers. This is still work in progress and we wish to add lots more Persian equivalents of \LaTeX and \TeX commands and environments. The Persian equivalents of \LaTeX and \TeX commands are shown in [Table 1](#), The Persian equivalents of XePersian commands are shown in [Table 2](#), Persian equivalents of \LaTeX environments are shown in [Table 3](#) and Persian equivalents of XePersian environments are shown in [Table 4](#)



Please note that the Persian equivalents of \LaTeX and \TeX commands and environments are only available after loading xepersian package. This means that you have to write all commands or environments that come before `\usepackage{xepersian}`, in its original form, i.e. `\documentclass`.

Not only you can use Persian equivalents of \LaTeX and \TeX commands and environments, but still original \LaTeX and \TeX commands and environments work too.

The \TeX \LaTeX and XePersian commands and environments and their Persian equivalents listed in Table 1, Table 2, Table 3 and Table 4 is not the whole story; If any command and environment in Table 1, Table 2, Table 3 and Table 4 have a starred version, their starred version also work. For example in Table 1, the Persian equivalent of `\chapter` is `فصل`. I know that `\chapter` has a starred version, so this means `*فصل` is also the Persian equivalent of `\chapter*`. Is that clear?

However there is more; you can localise any other commands/environments you want. You can use the following commands to localise your own commands/environments:

```
\eqcommand{<command-name in Persian>}{<original LaTeX command-name>}
\eqenvironment{<environment-name in Persian>}{<original LaTeX environment-name>}
```

Table 1: The Equivalent \LaTeX and \TeX Commands

Command in \TeX or \LaTeX	Equivalent Persian Command
<code>\@arstrut</code>	<code>\شمع جدول</code>
<code>\above</code>	<code>\فوق</code>
<code>\abovedisplaysshortskip</code>	<code>\فاصله کوتاه بالای نمایش</code>
<code>\abovedisplayskip</code>	<code>\فاصله بالای نمایش</code>
<code>\abstractname</code>	<code>\عنوان چکیده</code>
<code>\accent</code>	<code>\اکسنت</code>
<code>\active</code>	<code>\فعال</code>
<code>\addcontentsline</code>	<code>\بیفزاسطر فهرست</code>
<code>\addpenalty</code>	<code>\اضافه بر جریمه</code>
<code>\address</code>	<code>\نشانی</code>
<code>\addtocontents</code>	<code>\بیفزابه فهرست</code>
<code>\addtocounter</code>	<code>\اضافه بر شمارنده</code>
<code>\addtolength</code>	<code>\اضافه بر بعد</code>
<code>\addvspace</code>	<code>\بیفزافضای و</code>
<code>\adjdemerits</code>	<code>\تنظیم بدنمایی</code>
<code>\advance</code>	<code>\بیفزابر</code>
<code>\afterassignment</code>	<code>\بعد از انتساب</code>
<code>\aftergroup</code>	<code>\بعد از گروه</code>
<code>\aleph</code>	<code>\الف</code>
<code>\aliasfontfeature</code>	<code>\خصیصه مستعار قلم</code>
<code>\aliasfontfeatureoption</code>	<code>\انتخاب خصیصه مستعار قلم</code>

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
\allowbreak	\شکستی
\alloc@	\تخصی@
\allocationnumber	\تخصیص یافته
\allowdisplaybreaks	\شکست نمایش مجاز
\Alph	\حروف بزرگ
\alph	\حروف کوچک
\alsiname	\نام همچنین
\and	\و
\angle	\زاویه
\appendixname	\عنوان پیوست
\approx	\تقریب
\arabic	\عربی
\arg	\آرگ
\arrayrulecolor	\رنگ خط جدول
\arraycolsep	\فاصله ستونهای آرایه
\arrayrulewidth	\ضخامت خط جدول
\arraystretch	\کشیدگی آرایه
\AtBeginDocument	\در آغاز نوشتار
\AtEndDocument	\در پایان نوشتار
\AtEndOfClass	\در انتهای طبقه
\AtEndOfPackage	\در انتهای سبک
\author	\نویسنده
\backmatter	\مطلب پشت
\backslash	\شکاف پشت
\badness	\بدنمایی
\bar	\میله
\baselineskip	\فاصله کرسی
\baselinestretch	\کشش فاصله کرسی
\batchmode	\پردازش دسته ای
\begin	\شروع
\beginL	\شروع چپ
\beginR	\شروع راست
\begingroup	\شروع گروه
\belowdisplayshortskip	\فاصله کوتاه پایین نمایش
\belowdisplayskip	\فاصله پایین نمایش
\bf	\سیاه
\bfdefault	\پیش فرض سیاه
\bfseries	\شمایل سیاه
\bgroup	\شرگروه
\bibitem	\مرجوع

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
<code>\bibliography</code>	\کتاب نامه
<code>\bibliographystyle</code>	\سبک کتاب نامه
<code>\bibname</code>	\عنوان کتاب نامه
<code>\bigskip</code>	\پرش بلند
<code>\bigskipamount</code>	\مقدار پرش بلند
<code>\botfigrule</code>	\خط پایین شناور
<code>\botmark</code>	\علامت پایین
<code>\bottompageskip</code>	\کادر تا پایین
<code>\bottomfraction</code>	\نسبت پایین
<code>\box</code>	\کادر
<code>\boxmaxdepth</code>	\حد اکثر عمق کادر
<code>\break</code>	\شکن
<code>\bullet</code>	\گلوله
<code>@cclv</code>	\دوپن@پنج
<code>@ccclvi</code>	\دوپن@شش
<code>\caption</code>	\شرح
<code>\catcode</code>	\کدرده
<code>\cc</code>	\رونوشت
<code>\ccname</code>	\نام رونوشت
<code>\cdot</code>	\نقطه وسط
<code>\cdots</code>	\نقاط وسط
<code>\centering</code>	\تنظیم از وسط
<code>\centerline</code>	\خط وسط
<code>\ch@ck</code>	\چک@ن
<code>\chapter</code>	\فصل
<code>\chaptername</code>	\عنوان فصل
<code>\char</code>	\نویسه
<code>\chardef</code>	\تعریف نویسه
<code>\CheckCommand</code>	\برسی فرمان
<code>\cite</code>	\مرجع
<code>\ClassError</code>	\خطای طبقه
<code>\ClassInfo</code>	\اطلاع طبقه
<code>\ClassWarning</code>	\هشدار طبقه
<code>\ClassWarningNoLine</code>	\هشدار طبقه بی سطر
<code>\cleaders</code>	\نشانگر مرکزی
<code>\cleardoublepage</code>	\دو صفحه پاک
<code>\clearpage</code>	\صفحه پاک
<code>\cline</code>	\خط ناپر
<code>\closein</code>	\ببندورودی
<code>\closeout</code>	\ببند خروجی

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
<code>\closing</code>	\بستن
<code>\clubpenalty</code>	\جریمه سر بند
<code>\clubsuit</code>	\خاج
<code>\colbotmark</code>	\علامت پایین ستون اول
<code>\colfirstmark</code>	\علامت اول ستون اول
<code>\color</code>	\رنگ
<code>\colorbox</code>	\کادر رنگ
<code>\coltopmark</code>	\علامت بالای ستون اول
<code>\columncolor</code>	\رنگ ستون
<code>\columnsep</code>	\بین ستون
<code>\columnwidth</code>	\پهنای ستون
<code>\columnseprule</code>	\خط بین ستون
<code>\contentsline</code>	\سطر فهرست
<code>\contentsname</code>	\عنوان فهرست مطالب
<code>\copy</code>	\کپی
<code>\copyright</code>	\حق تالیف
<code>\count</code>	\شمار
<code>\count@</code>	\شمار@
<code>\countdef</code>	\تعریف شمار
<code>\cr</code>	\سخ
<code>\crrc</code>	\سخ سخ
<code>\csname</code>	\نام فرمان
<code>\CurrentOption</code>	\گزینه جاری
<code>\dashbox</code>	\کادر بینابین
<code>\dashv</code>	\بینابین ع
<code>\@date</code>	\@تاریخ
<code>\date</code>	\تاریخ
<code>\day</code>	\روز
<code>\dblbotfigrule</code>	\خط پایین شناور پهن
<code>\dblbottomfraction</code>	\نسبت پهن پایین
<code>\dblfigrule</code>	\خط بالای شناور پهن
<code>\dblfloatpagefraction</code>	\نسبت صفحه شناور پهن
<code>\dblfloatsep</code>	\فاصله بین شناور پهن
<code>\dblftntlocatecode</code>	\کد مکان غیرهما نطور
<code>\dbltextfloatsep</code>	\فاصله متن و شناور پهن
<code>\dbltopfraction</code>	\نسبت پهن بالا
<code>\DeclareFixedFont</code>	\اعلان قلم ثابت
<code>\DeclareGraphicsExtensions</code>	\اعلان پسوند گرافیک
<code>\DeclareGraphicsRule</code>	\اعلان دستور گرافیک
<code>\DeclareOldFontCommand</code>	\اعلان فرمان قلم قدیمی

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
<code>\DeclareOption</code>	<code>\اعلان گزینه</code>
<code>\DeclareRobustCommand</code>	<code>\اعلان فرمان قوی</code>
<code>\DeclareSymbolFont</code>	<code>\اعلان قلم علائم</code>
<code>\deadcycles</code>	<code>\دور بسته</code>
<code>\def</code>	<code>\تر</code>
<code>\define@key</code>	<code>\تعریف@کلید</code>
<code>\definecolor</code>	<code>\تعریف رنگ</code>
<code>\deg</code>	<code>\درجه</code>
<code>\delcode</code>	<code>\کد جداساز</code>
<code>\delimiter</code>	<code>\جداساز</code>
<code>\delimiterfactor</code>	<code>\ضریب جداساز</code>
<code>\depth</code>	<code>\گودی</code>
<code>\diamondsuit</code>	<code>\خشت</code>
<code>\dim</code>	<code>\بعد</code>
<code>\dimen</code>	<code>\بعد</code>
<code>\dimen@</code>	<code>\بعد@</code>
<code>\dimen@i</code>	<code>\بعد@یک</code>
<code>\dimen@ii</code>	<code>\بعد@دو</code>
<code>\dimendef</code>	<code>\تعریف بعد</code>
<code>\discretionary</code>	<code>\تیره گذاری</code>
<code>\displaybreak</code>	<code>\شکست نمایش</code>
<code>\displayindent</code>	<code>\تورفتگی نمایش</code>
<code>\displaystyle</code>	<code>\سبک نمایش</code>
<code>\displaywidth</code>	<code>\عرض نمایش</code>
<code>\divide</code>	<code>\تقسیم</code>
<code>\documentclass</code>	<code>\طبقه نوشتار</code>
<code>\do</code>	<code>\کن</code>
<code>\dospecials</code>	<code>\تعویض کدها</code>
<code>\dot</code>	<code>\نقطه</code>
<code>\doteq</code>	<code>\نقطه مساوی</code>
<code>\dotfill</code>	<code>\پر نقطه</code>
<code>\dots</code>	<code>\نقاط</code>
<code>\doublebox</code>	<code>\کادر دولا</code>
<code>\doublerulesepcolor</code>	<code>\رنگ فاصله دو خط جدول</code>
<code>\doublerulesep</code>	<code>\فاصله بین دو خط</code>
<code>\downarrow</code>	<code>\فلش پایین</code>
<code>\dp</code>	<code>\عمق</code>
<code>\dump</code>	<code>\تخلیه</code>
<code>\edef</code>	<code>\ترگ</code>
<code>\egroup</code>	<code>\پاگروه</code>

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
<code>\eject</code>	<code>\انتهای فاصله</code>
<code>\else</code>	<code>\اگر نه</code>
<code>\em</code>	<code>\تاکید</code>
<code>\emergencystretch</code>	<code>\کشش لاجرم</code>
<code>\emph</code>	<code>\موکد</code>
<code>\@empty</code>	<code>\@پوچ</code>
<code>\empty</code>	<code>\پوچ</code>
<code>\emptyset</code>	<code>\مجموعه پوچ</code>
<code>\end</code>	<code>\پایان</code>
<code>\endL</code>	<code>\پایان چپ</code>
<code>\endR</code>	<code>\پایان راست</code>
<code>\endcsname</code>	<code>\پایان نام فرمان</code>
<code>\endfirsthead</code>	<code>\پایان اولین سر</code>
<code>\endfoot</code>	<code>\پایان پا</code>
<code>\endgraf</code>	<code>\ته بند</code>
<code>\endgroup</code>	<code>\پایان گروه</code>
<code>\endhead</code>	<code>\پایان سر</code>
<code>\endinput</code>	<code>\پایان ورودی</code>
<code>\endlastfoot</code>	<code>\پایان آخرین پا</code>
<code>\enlargethispage</code>	<code>\گسترش این صفحه</code>
<code>\endline</code>	<code>\ته سطر</code>
<code>\endlinechar</code>	<code>\نویسه ته سطر</code>
<code>\enspace</code>	<code>\ان دوری</code>
<code>\enskip</code>	<code>\ان فاصله</code>
<code>\eqcommand</code>	<code>\فرمان جانشین</code>
<code>\eqenvironment</code>	<code>\محیط جانشین</code>
<code>\eqref</code>	<code>\ارجاع فر</code>
<code>\errhelp</code>	<code>\کمک خطا</code>
<code>\errmessage</code>	<code>\پیام خطا</code>
<code>\errorcontextlines</code>	<code>\سطر متن خطا</code>
<code>\errorstopmode</code>	<code>\پردازش توقف خطا</code>
<code>\escapechar</code>	<code>\نویسه ویژه</code>
<code>\euro</code>	<code>\یورو</code>
<code>\evensidemargin</code>	<code>\حاشیه زوج</code>
<code>\everycr</code>	<code>\هرسخ</code>
<code>\everydisplay</code>	<code>\هرنمایش</code>
<code>\everyhbox</code>	<code>\هرکادر</code>
<code>\everyjob</code>	<code>\هرکار</code>
<code>\everymath</code>	<code>\هرریاضی</code>
<code>\everypar</code>	<code>\هربند</code>

Continued on next page



Command in T_EX or L^AT_EX Equivalent Persian Command

\everyvbox	\هرکادرو
\ExecuteOptions	\اجرای گزینه ها
\exhyphenpenalty	\جریمه اضافی تیره بندی
\expandafter	\بگستر پس از
\extracolsep	\فاصله اضافی بین ستونها
\@firstofone	\@اولی از یک
\@firstoftwo	\@اولی از دو
\f@ur	\چ@ار
\fam	\خانواده
\fancy page	\صفحه تجملی
\fbox	\کادر با
\fboxrule	\ضخامت کادر با
\fboxsep	\حاشیه کادر با
\fcolorbox	\کادر با رنگ
\fi	\رگ
\figurename	\عنوان شکل
\filbreak	\پرشکن
\fill	\پر
\firstmark	\علامت اول
\flat	\پهن
\floatpagefraction	\نسبت صفحه شناور
\floatingpenalty	\جریمه شناور
\floatsep	\فاصله بین شناور
\flushbottom	\تنظیم از پایین
\fmtname	\شکل بندی
\fmtversion	\رده شکل بندی
\fnsymbol	\نشانه
\font	\قلم
\fontdimen	\بعد قلم
\fontencoding	\رمزینه قلم
\fontfamily	\فامیل قلم
\fontname	\نام قلم
\fontseries	\شماریل قلم
\fontshape	\شکل قلم
\fontsize	\اندازه قلم
\footheight	\بلندای پایین صفحه
\footins	\درج زیرنویس
\footnote	\زیرنویس
\footnotemark	\علامت زیرنویس
\footnoterule	\خط زیرنویس

Continued on next page



Command in T_EX or L^AT_EX Equivalent Persian Command

\footnotesep	\فاصله تازیرنویس
\footnotesize	\اندازه زیرنویس
\footnotetext	\متن زیرنویس
\footskip	\فاصله تا پایین صفحه
\frame	\فریم
\framebox	\کادر با خط
\frenchspacing	\فواصل یکنواخت لاتین
\frontmatter	\مطلب پیش
\futurelet	\بعد بگذار
\@gobble	\@خورجریصانه
\@gobbletwo	\@خورجریصانه دو
\@gobblefour	\@خورجریصانه چهار
\@gtempa	\@عاقبت آ
\@gtempb	\@عاقبت ب
\gdef	\ترع
\GenericInfo	\الگوی اطلاع
\GenericWarning	\الگوی هشدار
\GenericError	\الگوی خطا
\global	\عام
\globaldefs	\تعاریف عام
\glossary	\لغت نامه
\glossaryentry	\فقره فرهنگ
\goodbreak	\خوش شکن
\graphpaper	\کاغذگراف
\guillemotleft	\گیومه چپ
\guillemotright	\گیومه راست
\guilsinglleft	\گیومه تکی چپ
\guilsinglright	\گیومه تکی راست
\halign	\ردیف ا
\hang	\بروتو
\hangafter	\بعد از سطر
\hangindent	\تورفتگی ثابت
\hbadness	\بدنمایی ا
\hbox	\کادرا
\headheight	\بلندای سرصفحه
\headsep	\فاصله از سرصفحه
\headtoname	\سربه نام
\heartsuit	\دل
\height	\بلندا
\hfil	\پرا

Continued on next page



Command in T_EX or L^AT_EX Equivalent Persian Command

<code>\hfill</code>	<code>\</code> پررا
<code>\hfilneg</code>	<code>\</code> رفع‌پرا
<code>\hfuzz</code>	<code>\</code> پرزاقفی
<code>\hideskip</code>	<code>\</code> فاصله مخفی
<code>\hidewidth</code>	<code>\</code> عرض پنهان
<code>\hline</code>	<code>\</code> خط‌پر
<code>\hoffset</code>	<code>\</code> حاشیه ا
<code>\holdinginserts</code>	<code>\</code> حفظ درج
<code>\hrboxsep</code>	<code>\</code> فاصله اگر
<code>\hrule</code>	<code>\</code> خط ا
<code>\hrulefill</code>	<code>\</code> پرخط ا
<code>\hsize</code>	<code>\</code> طول سطر
<code>\hskip</code>	<code>\</code> فاصله ا
<code>\hspace</code>	<code>\</code> فضای ا
<code>\hss</code>	<code>\</code> هر دو
<code>\ht</code>	<code>\</code> ارتفاع
<code>\huge</code>	<code>\</code> بزرگ
<code>\Huge</code>	<code>\</code> بزرگ تر
<code>\hyperlink</code>	<code>\</code> ابر پیوند
<code>\hypersetup</code>	<code>\</code> بارگذاری ابر
<code>\hypertarget</code>	<code>\</code> هدف ابر
<code>\hyphenation</code>	<code>\</code> تیره‌بندی
<code>\hyphenchar</code>	<code>\</code> نویسه تیره
<code>\hyphenpenalty</code>	<code>\</code> جریمه تیره‌بندی
<code>\@ifclassloaded</code>	<code>\</code> @گر کلاس فراخوانی شده
<code>\@ifdefinable</code>	<code>\</code> @گر ترشدنی
<code>\@ifnextchar</code>	<code>\</code> @گر نویسه بعدی
<code>\@ifpackageloaded</code>	<code>\</code> @گر سبک فراخوانی شده
<code>\@ifstar</code>	<code>\</code> @گر ستاره
<code>\@ifundefined</code>	<code>\</code> @گر تعریف نشده
<code>\if</code>	<code>\</code> گر
<code>\if@tempswa</code>	<code>\</code> گر @سواقت آ
<code>\ifcase</code>	<code>\</code> گر انواع
<code>\ifcat</code>	<code>\</code> گر رده
<code>\ifdefined</code>	<code>\</code> گر تعریف شده
<code>\ifdim</code>	<code>\</code> گر بعد
<code>\ifeof</code>	<code>\</code> گر ته‌پرونده
<code>\iff</code>	<code>\</code> گر ر
<code>\iffalse</code>	<code>\</code> گر نادرست
<code>\IfFileExists</code>	<code>\</code> گر پرونده موجود

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
<code>\ifhbox</code>	\گرکادرا
<code>\ifhmode</code>	\گرحالت ا
<code>\ifinner</code>	\گردرونی
<code>\ifmmode</code>	\گرحالت ریاضی
<code>\ifnum</code>	\گرعدد
<code>\ifodd</code>	\گرفرد
<code>\ifthenelse</code>	\گرآنگاه دیگر
<code>\iftrue</code>	\گردرست
<code>\ifvbox</code>	\گرکادرو
<code>\ifvmode</code>	\گرحالت و
<code>\ifvoid</code>	\گرتهی
<code>\ifx</code>	\گرتام
<code>\ignorespaces</code>	\فاصله خالی رانده بگير
<code>\immediate</code>	\فوری
<code>\include</code>	\شامل
<code>\includegraphics</code>	\درج تصویر
<code>\includeonly</code>	\مشمولین
<code>\indent</code>	\تورفتگی
<code>\index</code>	\درنمایه
<code>\indexentry</code>	\استعلام
<code>\indexname</code>	\عنوان نمایه
<code>\indexspace</code>	\فاصله رهنما
<code>\input</code>	\ورودی
<code>\InputIfFileExists</code>	\ورودپرونده گرموجود
<code>\inputlineno</code>	\شماره سطرورودی
<code>\insert</code>	\درج
<code>\insertpenalties</code>	\جریمه درج
<code>\interfootnotelinepenalty</code>	\جریمه بین سطرهای زیرنویس
<code>\interdisplaylinepenalty</code>	\جریمه بین سطرهای نمایش
<code>\interlinepenalty</code>	\جریمه بین سطرها
<code>\intertext</code>	\متن داخلی
<code>\intertextsep</code>	\فاصله شناورد رمتن
<code>\invisible</code>	\مخفی
<code>\itdefault</code>	\پیش فرض ای
<code>\itshape</code>	\شکل ایتالیک
<code>\item</code>	\فقره
<code>\itemindent</code>	\تورفتگی فقره
<code>\itemsep</code>	\فاصله فقره
<code>\iterate</code>	\تکرارکن
<code>\itshape</code>	\شکل ای

Continued on next page



Command in T_EX or L^AT_EX Equivalent Persian Command

<code>\jobname</code>	<code>\نام کار</code>
<code>\jot</code>	<code>\قلب</code>
<code>\kern</code>	<code>\دوری</code>
<code>\kill</code>	<code>\الگو</code>
<code>\label</code>	<code>\برچسب</code>
<code>\labelenumi</code>	<code>\برچسب شمارش یک</code>
<code>\labelenumii</code>	<code>\برچسب شمارش دو</code>
<code>\labelenumiii</code>	<code>\برچسب شمارش سه</code>
<code>\labelenumiv</code>	<code>\برچسب شمارش چهار</code>
<code>\labelitemi</code>	<code>\برچسب فقره یک</code>
<code>\labelitemii</code>	<code>\برچسب فقره دو</code>
<code>\labelitemiii</code>	<code>\برچسب فقره سه</code>
<code>\labelitemiv</code>	<code>\برچسب فقره چهار</code>
<code>\labelsep</code>	<code>\فاصله از برچسب</code>
<code>\labelwidth</code>	<code>\پهنای برچسب</code>
<code>\language</code>	<code>\زبان</code>
<code>\large</code>	<code>\درشت</code>
<code>\Large</code>	<code>\درشت تر</code>
<code>\LARGE</code>	<code>\درشت درشت</code>
<code>\lastbox</code>	<code>\آخرین کادر</code>
<code>\lastkern</code>	<code>\آخرین دوری</code>
<code>\lastpenalty</code>	<code>\آخرین جریمه</code>
<code>\lastskip</code>	<code>\آخرین فاصله</code>
<code>\LaTeX</code>	<code>\لاتک</code>
<code>\LaTeXe</code>	<code>\لاتک ای</code>
<code>\lccode</code>	<code>\کدکوچک</code>
<code>\ldots</code>	<code>\نقاط خ</code>
<code>\leaders</code>	<code>\نشانگر</code>
<code>\leavevmode</code>	<code>\ترک و</code>
<code>\left</code>	<code>\چپ</code>
<code>\leftmargin</code>	<code>\حاشیه چپ</code>
<code>\leftmargini</code>	<code>\حاشیه چپ یک</code>
<code>\leftmarginii</code>	<code>\حاشیه چپ دو</code>
<code>\leftmarginiii</code>	<code>\حاشیه چپ سه</code>
<code>\leftmarginiv</code>	<code>\حاشیه چپ چهار</code>
<code>\leftmarginv</code>	<code>\حاشیه چپ پنج</code>
<code>\leftmarginvi</code>	<code>\حاشیه چپ شش</code>
<code>\leftmark</code>	<code>\علامت چپ</code>
<code>\leftpageskip</code>	<code>\کادر تا چپ</code>
<code>\leftskip</code>	<code>\فاصله ابتدای سطر</code>

Continued on next page



Command in T_EX or L^AT_EX Equivalent Persian Command

\let	\بگذار
\line	\سطر
\linebreak	\سطرشکن
\linepenalty	\جریمه سطر
\lineskip	\فاصله سطرها
\lineskiplimit	\حد فاصله سطر
\linespread	\کشش فاصله سطر
\linethickness	\ضخامت خط
\linewidth	\پهنای سطر
\listfigurename	\عنوان فهرست اشکال
\listfiles	\لیست پرونده ها
\listoffigures	\فهرست اشکال
\listoftables	\فهرست جداول
\listparindent	\تورفتگی بند لیست
\listtablename	\عنوان فهرست جداول
\LoadClass	\بارکن طبقه
\LoadClassWithOptions	\بارکن طبقه با گزینه
\location	\مکان
\long	\بلند
\loop	\حلقه
\looseness	\گسیختگی
\lower	\انتقال بپایین
\@makeother	\@دیگر
\@m	\@زار
\@M	\ده@زار
\@Mi	\ده@زاریک
\@Mii	\ده@زاردو
\@Miii	\ده@زارسه
\@Miv	\ده@زارچهار
\@MM	\بیس@زار
\m@ne	\من@a
\mag	\بزرگ نمایی
\magstep	\گام
\magstephalf	\نیم گام
\mainmatter	\مطلب اصلی
\makeatletter	\ات حرف
\makeatother	\ات دیگر
\makebox	\کادر بی خط
\makeglossary	\ساخت فرهنگ
\makeindex	\تهیه نمایه

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
<code>\makelabel</code>	\ساخت برچسب
<code>\makelabels</code>	\ساخت برچسب ها
<code>\MakeLowercase</code>	\ساخت حروف کوچک
<code>\maketitle</code>	\عنوان ساز
<code>\MakeUppercase</code>	\ساخت حروف بزرگ
<code>\marginpar</code>	\در حاشیه
<code>\marginparpush</code>	\فاصله دو حاشیه
<code>\marginparsep</code>	\فاصله تا حاشیه
<code>\marginparwidth</code>	\پهنای حاشیه
<code>\mark</code>	\علامت
<code>\markboth</code>	\علامت در دو طرف
<code>\markright</code>	\علامت در راست
<code>\mathaccent</code>	\اعراب ریاضی
<code>\mathchar</code>	\نویسه ریاضی
<code>\mathchardef</code>	\تعریف نویسه ریاضی
<code>\mathcode</code>	\کد ریاضی
<code>\mathrm</code>	\ریاضی رومن
<code>\maxdeadcycles</code>	\حد اکثر تکرار
<code>\maxdepth</code>	\حد اکثر عمق صفحه
<code>\maxdimen</code>	\بعد بیشین
<code>\mbox</code>	\کادر بی
<code>\mdseries</code>	\شمایل نازک
<code>\meaning</code>	\معنا
<code>\mediumseries</code>	\نازک
<code>\medmuskip</code>	\فاصله متوسط ریاضی
<code>\medskip</code>	\پرش متوسط
<code>\medskipamount</code>	\مقدار پرش متوسط
<code>\medspace</code>	\فضای متوسط
<code>\message</code>	\پیام
<code>\MessageBreak</code>	\پیام شکن
<code>\minrowclearance</code>	\حد اقل فاصله ردیف
<code>\mkern</code>	\دوری ریاضی
<code>\month</code>	\ماه
<code>\moveleft</code>	\انتقال بچپ
<code>\moveright</code>	\انتقال بر راست
<code>\mskip</code>	\فاصله ریاضی
<code>\m@th</code>	\ری @ ضی
<code>\multicolumn</code>	\چند ستونی
<code>\multiply</code>	\ضرب
<code>\multispan</code>	\چند ادغام

Continued on next page



Command in T_EX or L^AT_EX Equivalent Persian Command

<code>\muskip</code>	<code>\ميوفاصله</code>
<code>\muskipdef</code>	<code>\تعريف ميوفاصله</code>
<code>\@namedef</code>	<code>\@ترنام</code>
<code>\@nameuse</code>	<code>\@کاربردنام</code>
<code>\@ne</code>	<code>\یک@</code>
<code>\name</code>	<code>\نام</code>
<code>\natural</code>	<code>\طبيعي</code>
<code>\nearrow</code>	<code>\باريك</code>
<code>\nearrower</code>	<code>\باريکتر</code>
<code>\NeedsTeXFormat</code>	<code>\شکلبندی مورد نیاز</code>
<code>\neg</code>	<code>\منفی</code>
<code>\negmedspace</code>	<code>\فضای متوسط منفی</code>
<code>\negthickspace</code>	<code>\فضای ضخیم منفی</code>
<code>\negthinspace</code>	<code>\دوری کوچک منفی</code>
<code>\newboolean</code>	<code>\بولی نو</code>
<code>\newbox</code>	<code>\کادر جدید</code>
<code>\newcommand</code>	<code>\فرمان نو</code>
<code>\newcount</code>	<code>\شمار جدید</code>
<code>\newcounter</code>	<code>\شمارنده جدید</code>
<code>\newdimen</code>	<code>\بعد جدید</code>
<code>\newenvironment</code>	<code>\محیط نو</code>
<code>\newfam</code>	<code>\خانواده جدید</code>
<code>\newfont</code>	<code>\قلم نو</code>
<code>\newhelp</code>	<code>\کمک جدید</code>
<code>\newif</code>	<code>\گر جدید</code>
<code>\newinsert</code>	<code>\درج جدید</code>
<code>\newlabel</code>	<code>\برچسب جدید</code>
<code>\newlength</code>	<code>\تعریف بعد جدید</code>
<code>\newline</code>	<code>\سطر جدید</code>
<code>\newlinechar</code>	<code>\نویسه سطر جدید</code>
<code>\newmuskip</code>	<code>\ميوفاصله جديد</code>
<code>\newpage</code>	<code>\صفحه جديد</code>
<code>\newread</code>	<code>\بخوان جديد</code>
<code>\newsavebox</code>	<code>\تعريف کادر جديد</code>
<code>\newskip</code>	<code>\فاصله جديد</code>
<code>\newtheorem</code>	<code>\قضيه جديد</code>
<code>\newtoks</code>	<code>\جزء جديد</code>
<code>\newwrite</code>	<code>\بنويس جديد</code>
<code>\noalign</code>	<code>\بی ردیف</code>
<code>\nobreak</code>	<code>\نشکن</code>

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
<code>\nobreakspace</code>	<code>\فاصله نشکستی</code>
<code>\nocite</code>	<code>\بدون سند</code>
<code>\noexpand</code>	<code>\نگستر</code>
<code>\nofiles</code>	<code>\بدون پرونده</code>
<code>\noindent</code>	<code>\بدون تورفتگی</code>
<code>\nointerlineskip</code>	<code>\بی فاصله سطر</code>
<code>\nolimits</code>	<code>\بدون حد</code>
<code>\nolinebreak</code>	<code>\سطرنشکن</code>
<code>\nonstopmode</code>	<code>\پردازش بدون توقف</code>
<code>\nonfrenchspacing</code>	<code>\فواصل متعارف لاتین</code>
<code>\nonumber</code>	<code>\بدون شماره</code>
<code>\nopagebreak</code>	<code>\صفحه نشکن</code>
<code>\normalbaselines</code>	<code>\کرسیهای متعارف</code>
<code>\normalbaselineskip</code>	<code>\فاصله کرسی متعارف</code>
<code>\normalcolor</code>	<code>\رنگ عادی</code>
<code>\normalfont</code>	<code>\قلم عادی</code>
<code>\normallineskip</code>	<code>\فاصله سطرمتعارف</code>
<code>\normallineskiplimit</code>	<code>\حد فاصله سطرمتعارف</code>
<code>\normalmarginpar</code>	<code>\در حاشیه عادی</code>
<code>\normalsize</code>	<code>\اندازه عادی</code>
<code>\notag</code>	<code>\بدون اتیکت</code>
<code>\null</code>	<code>\نول</code>
<code>\nullfont</code>	<code>\قلم تهی</code>
<code>\number</code>	<code>\عدد</code>
<code>\numberline</code>	<code>\سطر عددی</code>
<code>\numberwithin</code>	<code>\شماره مطابق</code>
<code>\@evenfoot</code>	<code>\پایین صفحه زوج</code>
<code>\@evenhead</code>	<code>\بالای صفحه زوج</code>
<code>\@oddfoot</code>	<code>\پایین صفحه فرد</code>
<code>\@oddhead</code>	<code>\بالای صفحه فرد</code>
<code>\@outeqntrue</code>	<code>\شماره بیرون درست</code>
<code>\@outeqnfalse</code>	<code>\شماره بیرون نادرست</code>
<code>\obeylines</code>	<code>\سطر به سطر</code>
<code>\obeyspaces</code>	<code>\فضا فعال</code>
<code>\oddsidemargin</code>	<code>\حاشیه فرد</code>
<code>\offinterlineskip</code>	<code>\سطور بی فاصله</code>
<code>\omit</code>	<code>\حذف</code>
<code>\@onlypreamble</code>	<code>\@تنهادرپیش در آمد</code>
<code>\onecolumn</code>	<code>\یک ستون</code>
<code>\onlynotes</code>	<code>\تنهایداشت ها</code>

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
\onlyslides	\تنها اسلایدها
\openin	\بازکن ورودی
\openout	\بازکن خروجی
\OptionNotUsed	\گزینه مصرف نشده
\or	\یا
\outer	\برونی
\output	\صفحه بندی
\outputpenalty	\جریمه صفحه بندی
\overfullrule	\علامت سرریز
\@preamblecmds	\@فرمان های پیش در آمد
\p@	\@پو
\PackageError	\خطای سبک
\PackageInfo	\اطلاع سبک
\PackageWarning	\هشدار سبک
\PackageWarningNoLine	\هشدار سبک بی سطر
\pagebreak	\صفحه شکن
\pagecolor	\رنگ صفحه
\pagedepth	\عمق صفحه
\pagefillllstretch	\کشش پررر صفحه
\pagefilllstretch	\کشش پرر صفحه
\pagefilstretch	\کشش پر صفحه
\pagegoal	\غایت صفحه
\pagename	\نام صفحه
\pagenumbering	\شماره گذاری صفحه
\pageref	\رجوع صفحه
\pagerulewidth	\ضخامت خط صفحه
\pageshrink	\فشرده گی صفحه
\pagestretch	\کشش صفحه
\pagestyle	\سبک صفحه
\pagetotal	\جمع صفحه
\paperheight	\بلندای کاغذ
\paperwidth	\پهنای کاغذ
\par	\بند
\paragraph	\پارا گراف
\parallel	\موازی
\parbox	\کادر پار
\parfillskip	\فاصله ته بند
\parindent	\تورفتگی سر بند
\parsep	\فاصله بند لیست
\parshape	\شکل بند

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
<code>\parskip</code>	<code>\فاصله‌بند</code>
<code>\part</code>	<code>\بخش</code>
<code>\partname</code>	<code>\عنوان‌بخش</code>
<code>\partopsep</code>	<code>\فاصله‌بالای لیست‌بند</code>
<code>\PassOptionToClass</code>	<code>\ارسال گزینه به کلاس</code>
<code>\PassOptionToPackage</code>	<code>\ارسال گزینه به پکیج</code>
<code>\path</code>	<code>\مسیر</code>
<code>\patterns</code>	<code>\الگوها</code>
<code>\pausing</code>	<code>\مکث</code>
<code>\penalty</code>	<code>\جریمه</code>
<code>\phantom</code>	<code>\غیب</code>
<code>\poptabs</code>	<code>\الگوی قبلی</code>
<code>\postdisplaypenalty</code>	<code>\جریمه پس نمایش</code>
<code>\predisplaydirection</code>	<code>\جهت پیش نمایش</code>
<code>\predisplaypenalty</code>	<code>\جریمه پیش نمایش</code>
<code>\predisplaysize</code>	<code>\اندازه پیش نمایش</code>
<code>\pretolerance</code>	<code>\پیش حد‌بدنمایی</code>
<code>\prevdepth</code>	<code>\عمق قبلی</code>
<code>\prevgraf</code>	<code>\بند قبلی</code>
<code>\printindex</code>	<code>\نمایه در اینجا</code>
<code>\ProcessOptions</code>	<code>\پردازش گزینه‌ها</code>
<code>\protect</code>	<code>\تأمین</code>
<code>\providecommand</code>	<code>\تهیه فرمان</code>
<code>\ProvidesClass</code>	<code>\آماده سازی طبقه</code>
<code>\ProvidesFile</code>	<code>\آماده سازی پرونده</code>
<code>\ProvidesPackage</code>	<code>\آماده سازی سبک</code>
<code>\pushtabs</code>	<code>\ثبت الگو</code>
<code>\quad</code>	<code>\کواد</code>
<code>\qqquad</code>	<code>\کو کواد</code>
<code>\@outputpagerestore</code>	<code>\@بازآیی خروج صفحه</code>
<code>\radical</code>	<code>\رادی‌کال</code>
<code>\raggedbottom</code>	<code>\پایین بی تنظیم</code>
<code>\raggedleft</code>	<code>\تنظیم از راست</code>
<code>\raggedright</code>	<code>\تنظیم از چپ</code>
<code>\raise</code>	<code>\انتقال ببالا</code>
<code>\raisebox</code>	<code>\بالا بر</code>
<code>\raisetag</code>	<code>\ترفع اتیکت</code>
<code>\rangle</code>	<code>\زاویه ر</code>
<code>\rceil</code>	<code>\سقف ر</code>
<code>\read</code>	<code>\بخوان</code>

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
<code>\ref</code>	<code>\رجوع</code>
<code>\reflectbox</code>	<code>\کادرقرینه</code>
<code>\refname</code>	<code>\عنوان مراجع</code>
<code>\refstepcounter</code>	<code>\گام شمارنده مرجع</code>
<code>\relax</code>	<code>\راحت</code>
<code>\removeatlastskip</code>	<code>\رفع آخرین فاصله</code>
<code>\renewcommand</code>	<code>\فرمان ازنو</code>
<code>\renewenvironment</code>	<code>\محیط ازنو</code>
<code>\repeat</code>	<code>\ازنو</code>
<code>\RequirePackage</code>	<code>\سبک موردنیاز</code>
<code>\RequirePackageWithOptions</code>	<code>\سبک موردنیاز با گزینه</code>
<code>\resizebox</code>	<code>\کادرکشیده</code>
<code>\reversemarginpar</code>	<code>\در حاشیه معکوس</code>
<code>\rfloor</code>	<code>\کف ر</code>
<code>\right</code>	<code>\راست</code>
<code>\rightmargin</code>	<code>\حاشیه راست</code>
<code>\rightmark</code>	<code>\علامت راست</code>
<code>\rightpageskip</code>	<code>\کادر تا راست</code>
<code>\rightskip</code>	<code>\فاصله انتهای سطر</code>
<code>\rmdefault</code>	<code>\رومن عادی</code>
<code>\rmfamily</code>	<code>\فامیل رومن</code>
<code>\Roman</code>	<code>\رومن بزرگ</code>
<code>\roman</code>	<code>\رومن کوچک</code>
<code>\romannumeral</code>	<code>\عدد رومی</code>
<code>\rotatebox</code>	<code>\کادر چرخان</code>
<code>\rowcolor</code>	<code>\رنگ ردیف</code>
<code>\rule</code>	<code>\خط</code>
<code>\@secondoftwo</code>	<code>\@دومی ازدو</code>
<code>\@spaces</code>	<code>\@فضاها</code>
<code>\samepage</code>	<code>\همین صفحه</code>
<code>\savebox</code>	<code>\مقدار کادر</code>
<code>\sbox</code>	<code>\مقکادر</code>
<code>\scalebox</code>	<code>\کادر اندازه</code>
<code>\scdefault</code>	<code>\پیش فرض تمام بزرگ</code>
<code>\scshape</code>	<code>\شکل تمام بزرگ</code>
<code>\scriptfont</code>	<code>\قلم توان</code>
<code>\scriptscriptfont</code>	<code>\قلم توان توان</code>
<code>\scriptscriptstyle</code>	<code>\سبک ته نوشت ته نوشت</code>
<code>\scriptsize</code>	<code>\اندازه پانویس</code>
<code>\scriptstyle</code>	<code>\سبک ته نوشت</code>

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
\scrollmode	\پردازش گذری
\section	\قسمت
\secdef	\تعریف قسمت
\see	\ببینید
\seealso	\نیز ببینید
\seename	\نام ببینید
\selectfont	\قلم بردار
\setboolean	\تنظیم بولی
\setbox	\درکادر
\setcounter	\مقدار شمارنده
\setkeys	\مقدار کلیدها
\setlength	\مقدار بعد
\setminus	\تنظیم منها
\SetSymbolFont	\تعریف قلم علائم
\settodepth	\تنظیم به عمق
\settoheight	\تنظیم به ارتفاع
\settowidth	\مقدار بعد به اندازه
\sfcode	\کد ضریب فاصله
\sfdefault	\پیش فرض س ف
\sffamily	\فامیل سن سریف
\shadowbox	\کادر سایه دار
\sharp	\تیز
\shipout	\بفرست
\shortstack	\پشته کوتاه
\show	\نمایش بده
\showbox	\نمایش بده کادر
\showboxbreadth	\میزان نمایش کادر
\showboxdepth	\عمق نمایش کادر
\showlists	\نمایش بده لیستها
\showthe	\نمایش بده محتوای
\simplefontmode	\حالت ساده قلم
\sist@n	\شانزد @
\skewchar	\نویسه اریب
\skip	\فاصله
\skip@	\فاصل @
\skipdef	\تعریف فاصله
\sl	\خوابیده
\sldefault	\پیش فرض خو
\slshape	\شکل خوابیده
\sloppy	\راحت چین

Continued on next page



Command in T_EX or L^AT_EX Equivalent Persian Command

<code>\slshape</code>	\شمايل خو
<code>\small</code>	\کو چک
<code>\smallskip</code>	\پرش کوتاه
<code>\smallskipamount</code>	\مقدار پرش کوتاه
<code>\smash</code>	\کوب
<code>\smile</code>	\لبخند
<code>\snglftlocatencode</code>	\کدمکان همانطور
<code>\space</code>	\فضا
<code>\spacefactor</code>	\ضریب فاصله
<code>\spaceskip</code>	\فاصله کلمات
<code>\spadesuit</code>	\پیک
<code>\span</code>	\ادغام
<code>\special</code>	\ویژه
<code>\splitmaxdepth</code>	\حد اکثر عمق ستون
<code>\splittopskip</code>	\فاصله بالای ستون
<code>\star</code>	\ستاره
<code>\stepcounter</code>	\گام شمارنده
<code>\stretch</code>	\کشی
<code>\string</code>	\رشته
<code>\strut</code>	\شمع
<code>\strutbox</code>	\کادر شمع
<code>\subitem</code>	\زیر بند
<code>\subparagraph</code>	\زیر پاراگراف
<code>\subsection</code>	\زیر قسمت
<code>\substack</code>	\زیر پشته
<code>\subsubitem</code>	\زیر زیر بند
<code>\subsubsection</code>	\زیر زیر قسمت
<code>\subset</code>	\زیر مجموعه
<code>\subseteq</code>	\زیر مجموعه مسا
<code>\supereject</code>	\منتهای صفحه
<code>\suppressfloats</code>	\حذف مکان شناور
<code>\@tempa</code>	\@موقت آ
<code>\@tempb</code>	\@موقت ب
<code>\@tempc</code>	\@موقت پ
<code>\@tempd</code>	\@موقت ت
<code>\@tempe</code>	\@موقت ث
<code>\@tempboxa</code>	\@کادرقت آ
<code>\@tempcnta</code>	\@شماقت آ
<code>\@tempcntb</code>	\@شماقت ب
<code>\@tempdima</code>	\@بعدقت آ

Continued on next page



Command in T_EX or L^AT_EX Equivalent Persian Command

\@tempdimb	\@بعدقتب
\@tempdimc	\@بعدقتپ
\@tempskipa	\@فاقتآ
\@tempskipb	\@فاقتب
\@tempswafalse	\@سواقتآنادرست
\@tempswatrue	\@سواقتآدرست
\@temptokena	\@جزقتآ
\@thefnmark	\انگ زیرنویس
\@thirdofthree	\@سومی ازسه
\tabbingsep	\فاصله جاگذاری
\tabcolsep	\فاصله بین ستونها
\tableofcontents	\فهرست مطالب
\tablename	\عنوان جدول
\tabskip	\فاصله ستونها
\tabularnewline	\ته سطرجدول
\tag	\اتیکت
\telephone	\تلفن
\TeX	\تک
\text	\متن
\textbullet	\گلوله متنی
\textfont	\قلم متن
\textemdash	\ام دش متنی
\textendash	\ان دش متنی
\textexclamdown	\تعجب وارونه متنی
\textperiodcentered	\نقطه وسط متنی
\textquestiondown	\سوال وارونه متنی
\textquotedblleft	\نقل چپ متنی دولا
\textquotedblright	\نقل راست متنی دولا
\textquoteleft	\نقل متنی چپ
\textquoteright	\نقل متنی راست
\textvisiblespace	\فضای نمایان متنی
\textbackslash	\شکافت پشت متنی
\textbar	\میله متنی
\textgreater	\بزرگ ترممتنی
\textless	\کمترمتنی
\textbf	\متن سیاه
\textcircled	\مدورمتنی
\textcolor	\رنگ متن
\textcompwordmark	\نشان کلمه مرکب متن
\textfloatsep	\فاصله متن و شناور

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
<code>\textfraction</code>	\نسبت متن
<code>\textheight</code>	\بلندای متن
<code>\textindent</code>	\متن تورفته
<code>\textit</code>	\متن ایتالیک
<code>\textmd</code>	\متن نازک
<code>\textnormal</code>	\متن نرمال
<code>\textregistered</code>	\ثبتي متني
<code>\textrm</code>	\متن رومن
<code>\textsc</code>	\متن تمام بزرگ
<code>\textsf</code>	\متن سن سریف
<code>\textsl</code>	\متن خوابیده
<code>\textstyle</code>	\سبك متني
<code>\textsuperscript</code>	\بالا نویس متني
<code>\texttrademark</code>	\علامت تجاری متني
<code>\texttt</code>	\متن تایپ
<code>\textup</code>	\متن ایستاده
<code>\textwidth</code>	\پهنای متن
<code>\thanks</code>	\زیرنویس عنوان
<code>\the</code>	\محتوای
<code>\thempfn</code>	\این زیرنویس
<code>\thicklines</code>	\خط ها ضخیم
<code>\thickmuskip</code>	\فاصله زیاد ریاضی
<code>\thinmuskip</code>	\فاصله کم ریاضی
<code>\thickspace</code>	\فضا ضخیم
<code>\thinlines</code>	\خط ها نازک
<code>\thinspace</code>	\دوری کوچک
<code>\thisfancy page</code>	\این صفحه تجملی
<code>\thispage style</code>	\سبك این صفحه
<code>\thr@@</code>	\سه @
<code>\tilde</code>	\مد
<code>\tiny</code>	\ظریف
<code>\time</code>	\زمان
<code>\times</code>	\ضرب در
<code>\title</code>	\عنوان
<code>\to</code>	\به
<code>\today</code>	\امروز
<code>\toks</code>	\جزء
<code>\toksdef</code>	\تعریف جزء
<code>\tolerance</code>	\حد بدنامی
<code>\top</code>	\بالا

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
<code>\topfigrule</code>	<code>\خط بالای شناور</code>
<code>\topfraction</code>	<code>\نسبت بالا</code>
<code>\topmargin</code>	<code>\حاشیه بالا</code>
<code>\topmark</code>	<code>\علامت بالا</code>
<code>\toppageskip</code>	<code>\کادر تا بالا</code>
<code>\topsep</code>	<code>\فاصله بالای لیست</code>
<code>\topskip</code>	<code>\فاصله بالا</code>
<code>\totalheight</code>	<code>\بلندای کل</code>
<code>\tracingall</code>	<code>\ردگیری کل</code>
<code>\tracingcommands</code>	<code>\ردگیری فرامین</code>
<code>\tracinglostchars</code>	<code>\ردگیری حروف</code>
<code>\tracingmacros</code>	<code>\ردگیری ماکروها</code>
<code>\tracingonline</code>	<code>\ردگیری نمایشی</code>
<code>\tracingoutput</code>	<code>\ردگیری صفحه بندی</code>
<code>\tracingpages</code>	<code>\ردگیری صفحات</code>
<code>\tracingparagraphs</code>	<code>\ردگیری بندها</code>
<code>\tracingrestores</code>	<code>\ردگیری بازگردانی</code>
<code>\tracingstats</code>	<code>\ردگیری آمارها</code>
<code>\triangle</code>	<code>\مثلث</code>
<code>\ttdefault</code>	<code>\پیش فرض تایپ</code>
<code>\ttfamily</code>	<code>\فامیل تایپ</code>
<code>\tw@</code>	<code>\دو@</code>
<code>\twocolumn</code>	<code>\دو ستون</code>
<code>\typein</code>	<code>\در نویسی</code>
<code>\typeout</code>	<code>\بر نویسی</code>
<code>\uccode</code>	<code>\کد بزرگ</code>
<code>\uchyph</code>	<code>\تیره بندی بزرگ</code>
<code>\undefined</code>	<code>\تعریف نشده</code>
<code>\underline</code>	<code>\زیر خط</code>
<code>\unhbox</code>	<code>\بی کادر</code>
<code>\unhcopy</code>	<code>\بی کپی</code>
<code>\unitlength</code>	<code>\واحد طول</code>
<code>\unkern</code>	<code>\برگشت دوری</code>
<code>\unpenalty</code>	<code>\برگشت جریمه</code>
<code>\unskip</code>	<code>\برگشت فاصله</code>
<code>\unvbox</code>	<code>\بی کادرو</code>
<code>\unvcopy</code>	<code>\بی کپی و</code>
<code>\updefault</code>	<code>\پیش فرض ایستاده</code>
<code>\upshape</code>	<code>\شکل ایستاده</code>
<code>\usebox</code>	<code>\از کادر</code>

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
\usecounter	\باشمارشگر
\usefont	\گزینه‌ش قلم
\usepackage	\سبک لازم
\@vobeyspaces	\@فضاهای فعال
\@void	\@تهی
\vadjust	\تنظیم و
\valign	\ردیف و
\value	\محتوای شمارنده
\vbadness	\بدنمایی و
\vbox	\کادر و
\vcenter	\کادر وسط
\verb	\همانطور
\vfil	\پرو
\vfill	\پررو
\vfilneg	\رفع پرو
\vfuzz	\پر زعمودی
\visible	\نمایان
\vline	\خط عمود
\voffset	\حاشیه و
\voidb@x	\ک@در تهی
\vpageref	\ارجاع صفحه ع
\vrbboxsep	\فاصله وگرد
\vref	\ارجاع ع
\vrule	\خط و
\vsize	\طول صفحه
\vskip	\فاصله و
\vspace	\فضای و
\vsplit	\شکست و
\vss	\هر دو و
\vtop	\کادر گود
\wd	\عرض
\whiledo	\مادام بکن
\widehat	\کلاه پهن
\widetilde	\مد پهن
\widowpenalty	\جریمه ته بند
\width	\پهنا
\wlog	\در کارنامه
\write	\بنویس
\@xobeysp	\@فضای لاتین
\@xxxii	\سی@دو

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
\xdef	\ترگع
\xleaders	\نشانگر گسترشی
\xspaceskip	\فاصله اضافی کلمات
\year	\سال
\z@	\@فر
\z@skip	\@فر فاصله

Table 2: The Equivalent XePersian Commands

Command in XePersian	Equivalent Persian Command
\autofootnoterule	\خط زیرنویس خودکار
\AutoMathsDigits	\اعداد فرمولها خودکار
\DefaultMathsDigits	\اعداد فرمولها لاتین
\deflatinfont	\تعریف قلم لاتین
\defpersianfont	\تعریف قلم پارسی
\hboxL	\کادر چپ
\hboxR	\کادر راست
\keyval@eq@alias@key	\معادل @ کلید
\Latincite	\مرجع لاتین
\latinfont	\قلم لاتین
\latintoday	\امروز لاتین
\leftfootnoterule	\خط زیرنویس چپ
\lr	\متن لاتین
\LRE	\چپ براست
\LTRdblcol	\دوستونی چپ
\LTRfootnote	\پانویس
\LTRfootnotetext	\متن پانویس
\LTRthanks	\پانویس عنوان
\persianday	\روز پارسی
\persianfont	\قلم پارسی
\PersianMathsDigits	\اعداد فرمولها پارسی
\persianmonth	\ماه پارسی
\persianyear	\سال پارسی
\plq	\علامت چپ نقل قول پارسی
\prq	\علامت راست نقل قول پارسی
\rightfootnoterule	\خط زیرنویس راست
\rl	\متن پارسی
\RLE	\راست بچپ
\RTLdblcol	\دوستونی راست
\RTLfootnote	\پانویست

Continued on next page



Command in XePersian	Equivalent Persian Command
<code>\RTLfootnotetext</code>	\متن پانوشته
<code>\RTLthanks</code>	\پانوشته عنوان
<code>\@SepMark</code>	\@علامت بین
<code>\SepMark</code>	\علامت بین
<code>\setdefaultbibitems</code>	\بگذار امرجوعات عادی
<code>\setdefaultmarginpar</code>	\بگذار در حاشیه عادی
<code>\setdigitfont</code>	\گزینش قلم اعداد فرمولها
<code>\setfootnoteLR</code>	\بگذار زیرنویس چپ
<code>\setfootnoteRL</code>	\بگذار زیرنویس راست
<code>\setlatintextfont</code>	\گزینش قلم لاتین متن
<code>\setLTR</code>	\بگذار متن چپ
<code>\setLTRbibitems</code>	\بگذار امرجوعات چپ
<code>\setLTRmarginpar</code>	\بگذار در حاشیه چپ
<code>\setRTL</code>	\بگذار متن راست
<code>\setRTLbibitems</code>	\بگذار امرجوعات راست
<code>\setRTLmarginpar</code>	\بگذار در حاشیه راست
<code>\settextfont</code>	\گزینش قلم متن
<code>\textwidthfootnoterule</code>	\خط زیرنویس پهنای متن
<code>\twocolumnstableofcontents</code>	\فهرست مطالب دو ستونی
<code>\unsetfootnoteRL</code>	\نگذار زیرنویس راست
<code>\unsetLTR</code>	\نگذار متن چپ
<code>\unsetRTL</code>	\نگذار متن راست
<code>\vboxL</code>	\کادر واز چپ
<code>\vboxR</code>	\کادر واز راست
<code>\XeLaTeX</code>	\زی لاتک
<code>\XePersian</code>	\زی پرشین
<code>\xepersianversion</code>	\گونه زی پرشین
<code>\xepersiandate</code>	\تاریخ گونه زی پرشین
<code>\XeTeX</code>	\زی تک

Table 3: The Equivalent \LaTeX Environments

Environment in \LaTeX	Equivalent Persian Environment
<code>abstract</code>	چکیده
<code>appendix</code>	پیوست
<code>array</code>	آرایه
<code>center</code>	وسط چین
<code>description</code>	توضیح
<code>displaymath</code>	ریاضی نمایشی
<code>document</code>	نوشتار
<code>enumerate</code>	شمارش
<code>figure</code>	شکل

Continued on next page



Environment in \LaTeX	Equivalent Persian Environment
figure*	شکل*
filecontents	محتوای پرونده
filecontents*	محتوای پرونده*
flushleft	چپ چین
flushright	راست چین
itemize	فقرات
letter	نامه
list	لیست
longtable	جدول دراز
lrbox	کادر رج
math	ریاضی
matrix	ماتریس
minipage	صفحه کوچک
multicols	چندستونی ها
multline	چند خطی
note	یادداشت
overlay	انباشتن
picture	تصویر
quotation	اقتباس
quote	نقل
slide	اسلاید
sloppypar	پارنا مرتب
split	شکافتن
subarray	زیر آرایه
tabbing	جاگذاری
table	لوح
table*	لوح*
tabular	جدول
tabular*	جدول*
thebibliography	مراجع
theindex	محتوای نمایه
titlepage	صفحه عنوان
trivlist	لیست بدوی
verbatim	همانطور که هست
verbatim*	همانطور که هست*
verse	شعر

Table 4: The Equivalent XePersian Environments

Environment in XePersian	Equivalent Persian Environment
latin	لاتین
LTR	متن چپ

Continued on next page



Environment in XePersian	Equivalent Persian Environment
LTRitems	دسته‌بندی چپ
persian	پارسی
RTL	متن راست
RTLitems	دسته‌بندی راست

Localisation of position arguments. Some environments like `tabular` and some commands like `\parbox` have an argument which specifies the position. Table [Table 5](#) shows their localisations.

Table 5: The Equivalent \LaTeX position arguments

Position argument in \LaTeX	Equivalent Persian position argument
b	ز
c	و
C	س
h	ا
H	آ
J	ت
l	چ
L	ف
m	م
p	پ
P	ص
r	ر
R	ا
s	ک
t	ب

☞ There are two ps in [Table 5](#), first p and its Persian equivalent پ stand for paragraph (used in `tabular` and similar environments) and the second p and its Persian equivalent ص stand for page (used in float-like environments).

2.4.8 Localizations of the keys and key values of `graphicx` package

The equivalent Persian keys and key values of `graphicx` package is shown in [Table 6](#) and [Table 7](#) respectively.

Table 6: Persian Equivalent keys of `graphicx` package

Original Key	Equivalent Persian Key
draft	پیش نویس
origin	مبدأ
clip	بی اضافه
keepaspectratio	حفظ تناسب
natwidth	پهنای طبیعی

Continued on next page



Original Key	Equivalent Persian Key
natheight	بلندای طبیعی
bb	مختصات
viewport	محدوده نمایش
trim	حذف اطراف
angle	زاویه
width	پهنا
height	بلندا
totalheight	بلندای کل
scale	ضریب
type	نوع
ext	پسوند
read	خواندنی
command	فرمان
x	طول
y	عرض
units	واحد

Table 7: Persian Equivalent key values of graphicx package

Original Key value	Equivalent Persian Key value
b	ز
B	ک
false	نادرست
l	چ
r	ر
t	ب
true	درست

2.4.9 Localizations of font features and font feature options

The equivalent Persian font features and font feature options is shown in [Table 8](#) and [Table 9](#) respectively.

Table 8: Persian Equivalent font features

Original font feature	Equivalent Persian font feature
ExternalLocation	مکان خارجی
ExternalLocation	مسیر
Renderer	تحويل دهنده
BoldFont	قلم سیاه
Language	زبان
Script	خط
UprightFont	قلم عمودی
ItalicFont	قلم ایتالیک

Continued on next page



Original font feature	Equivalent Persian font feature
BoldItalicFont	قلم ایتالیک سیاه
SlantedFont	قلم خوابیده
BoldSlantedFont	قلم خوابیده سیاه
SmallCapsFont	قلم کلاه کوچک
UprightFeatures	ویژگی های قلم عمودی
BoldFeatures	ویژگی های قلم سیاه
ItalicFeatures	ویژگی های قلم ایتالیک
BoldItalicFeatures	ویژگی های قلم ایتالیک سیاه
SlantedFeatures	ویژگی های قلم خوابیده
BoldSlantedFeatures	ویژگی های قلم خوابیده سیاه
SmallCapsFeatures	ویژگی های قلم کلاه کوچک
SizeFeatures	ویژگی های اندازه
Scale	ضریب
WordSpace	فضای کلمه
PunctuationSpace	فضای نقطه گذاری
FontAdjustment	تنظیم قلم
LetterSpace	فضای حرف
HyphenChar	نویسه تیره
Color	رنگ
Opacity	کدری
Mapping	نگاشت
Weight	سنگینی
Width	پهنا
OpticalSize	اندازه چشمی
FakeSlant	خوابیده تقلبی
FakeStretch	کشش تقلبی
FakeBold	سیاه تقلبی
AutoFakeSlant	خوابیده تقلبی خودکار
AutoFakeBold	سیاه تقلبی خودکار
Ligatures	دو یا چند حرف متصل به هم
Alternate	متناوب
Variant	گوناگون
Variant	مجموعه سبکی
CharacterVariant	گوناگونی نویسه
Style	سبک
Annotation	یادداشت
RawFeature	ویژگی های کال
CharacterWidth	پهنای نویسه
Numbers	ارقام
Contextuals	متنی

Continued on next page



Original font feature	Equivalent Persian font feature
Diacritics	تفکیک کننده ها
Letters	حروف
Kerning	دوری
VerticalPosition	موقعیت عمودی
Fractions	کسر

Table 9: Persian Equivalent font feature options

font feature	font feature option	Persian font feature option
Language	Default	پیش فرض
Language	Parsi	پارسی
Script	Parsi	پارسی
Script	Latin	لاتین
Style	MathScript	اسکرپیت ریاضی
Style	MathScriptScript	اسکرپیت اسکرپیت ریاضی

2.5 A Sample Input T_EX File

```

1 \documentclass{article}
2 \usepackage{xepersian}
3 \settextfont{XB Niloofar}
4 \title{یک سند نمونه}
5 \author{نام نویسنده}
6 \begin{document}
7 \maketitle
8 \tableofcontents
9 \part{عنوان بخش}
10 ...
11 \section{عنوان قسمت}
12 ...
13 \subsection{عنوان زیرقسمت}
14 ...
15 \subsubsection{عنوان زیر زیرقسمت}
16 ...
17 \end{document}

```

2.6 Font Commands



2.6.1 Basic Font Commands

```
\settextfont [Options] {\font name}  
\setlatintextfont [Options] {\font name}  
\setdigitfont [Options] {\font name}  
\setmathsfdigitfont [Options] {\font name}  
\setmathttdigitfont [Options] {\font name}
```

- ☞ Options in any font command in this documentation are anything that fontspec package provides as the option of loading fonts, except Script and Mapping.
- ☞ `\settextfont` will choose the default font for Persian texts of your document.
- ☞ `\setlatintextfont` will choose the font for Latin texts of your document. If you do not use this command at all, the default T_EX font (fonts used in this documentation) will be used for Latin texts of your document.
- ☞ `\setdigitfont` will choose the Persian font for digits in math mode. By default, digits in math mode will appear in Persian form.
- ☞ `\setmathsfdigitfont` will choose the Persian font for digits in math mode inside `\mathsf`. By using this command, digits in math mode inside `\mathsf` will appear in Persian form and if you do not use this command at all, you will get default T_EX font for digits in math mode inside `\mathsf` and digits appear in their original form (Western).
- ☞ `\setmathttdigitfont` will choose the Persian font for digits in math mode inside `\mathtt`. By using this command, digits in math mode inside `\mathtt` will appear in Persian form and if you do not use this command at all, you will get default T_EX font for digits in math mode inside `\mathtt` and digits appear in their original form (Western).

2.6.2 Defining Extra Persian and Latin Fonts

```
\defpersianfont\CS [Options] {\font name}  
\deflatinfont\CS [Options] {\font name}
```

- ☞ With `\defpersianfont`, you can define extra Persian fonts.

```
\defpersianfont\Nastaliq[Scale=1]{IranNastaliq}
```

In this example, we define `\Nastaliq` to stand for IranNastaliq font.

- ☞ With `\deflatinfont`, you can define extra Latin fonts.

```
\deflatinfont\junicode[Scale=1]{Junicode}
```

In this example, we define `\junicode` to stand for Junicode font.



2.6.3 Choosing Persian Sans Font

```
\setpersiansansfont [Options] {\font name}  
\persiansffamily \textpersiansf{\text}
```

2.6.4 Choosing Persian Mono Font

```
\setpersianmonofont [Options] {\font name}  
\persianttfamily \textpersiantt{\text}
```

2.6.5 Choosing Persian Iranic Font

```
\setiraniconfont [Options] {\font name}  
\iranicfamily \textiranicon{\text}
```

2.6.6 Choosing Persian Navar Font

```
\setnavarfont [Options] {\font name}  
\navarfamily \textnavar{\text}
```

2.6.7 Choosing Persian Pook Font

```
\setpookfont [Options] {\font name}  
\pookfamily \textpook{\text}
```

2.6.8 Choosing Persian Sayeh Font

```
\setsayehfont [Options] {\font name}  
\sayehfamily \textsayeh{\text}
```

2.6.9 Choosing Latin Sans Font

```
\setlatinsansfont [Options] {\font name}  
\sffamily \textsf{\text}
```

2.6.10 Choosing Latin Mono Font

```
\setlatinmonofont [Options] {\font name}  
\ttfamily \texttt{\text}
```



3 Latin and Persian Environment

```
\begin{latin} <text> \end{latin}  
\begin{persian} <text> \end{persian}
```

☞ `latin` environment both changes direction of the paragraphs to LTR and font to Latin font.

☞ `persian` environment both changes direction of the Paragraphs to RTL and font to Persian font.

3.1 `latinitems` and `parsiitems` environments

```
\begin{latinitems}  
  \item <text>  
  ...  
\end{latinitems}
```

☞ `latinitems` environment is similar to `LTRitems` environment but changes the font to Latin font.

```
\begin{parsiitems}  
  \item <text>  
  ...  
\end{parsiitems}
```

☞ `parsiitems` environment is similar to `RTLitems` environment but changes the font to Persian font.

3.2 Short Latin and Persian Texts

```
\lr{<text>} \rl{<text>}
```

☞ With `\lr` command, you can typeset short LTR texts.

☞ With `\rl` command, you can typeset short RTL texts.

3.3 Miscellaneous Commands

```
\persianyear \persianmonth \persianday  
\today \latintoday \twocolumnstableofcontents \XePersian  
\plq \prq
```

☞ `\persianyear` is Persian equivalent of `\year`.



- ☞ `\persianmonth` is Persian equivalent of `\month`.
- ☞ `\persianday` is Persian equivalent of `\day`.
- ☞ `\today` typesets current Persian date and `\latintoday` typesets current Latin date.
- ☞ `\twocolumnstableofcontents` typesets table of contents in two columns. This requires that you have loaded `multicol` package before `XePersian` package, otherwise an error will be issued.
- ☞ `\XePersian` typesets XePersian's logo.
- ☞ `\plq` and `\prq` typeset Persian left quote and Persian right quote respectively.

3.4 New Commands

`\Latincite`

- ☞ `\Latincite` functions exactly like `\cite` command with only one difference; the reference to biblabel item is printed in Latin font in the text.

3.5 Additional Counters

XePersian defines several additional counters to what already \LaTeX offers. These counters are `harfi`, `adadi`, and `tartibi`. In addition, the following commands are also provided:

`\harfinumeral{⟨integer⟩}` `\adadinumeral{⟨integer⟩}` `\tartibinumeral{⟨integer⟩}`

- ☞ The range of `harfi` counter is integers between 1 and 32 (number of the Persian alphabets) and `adadi` and `tartibi` counters, are integers between 0 and 999,999,999.
- ☞ For `harfi` counter, if you give an integer bigger than 32 or a negative integer (if you give integer 0, it returns nothing), then you get error and for `adadi` and `tartibi` counters, if you give an integer bigger than 999,999,999, then you get an error message.
- ☞ For `adadi` and `tartibi` counters, if you give an integer less than 0 (a negative integer), then `adadi` and `tartibi` counters return **adadi** and **tartibi** form of the integer 0, respectively.
- ☞ `\harfinumeral` returns the **harfi** form of $\langle integer \rangle$, where $1 \leq integer \leq 32$ and `\adadinumeral`, and `\tartibinumeral` return **adadi**, and **tartibi** form of $\langle integer \rangle$ respectively, where $0 \leq integer \leq 999,999,999$.



3.6 Things To Know About `\setdigitfont`, `\setmathsfdigitfont`, and `\setmathttdigitfont`

`\DefaultMathsDigits \PersianMathsDigits \AutoMathsDigits`

- ☞ As we discussed before, `\setdigitfont` will choose the Persian font for digits in math mode. By default, digits in math mode will appear in Persian form.
 - ☞ As we discussed before, `\setmathsfdigitfont`, and `\setmathttdigitfont` will choose the Persian sans serif and typewriter fonts for digits in math mode. By using this command, digits in math mode will appear in Persian form and if you do not use this command at all, you will get default T_EX font for digits in math mode and digits appear in their original form (Western).
- If you use `\setdigitfont`, `\setmathsfdigitfont`, and `\setmathttdigitfont`, then you should know that:

- ☞ By default, `\AutoMathsDigits` is active, which means that in Persian mode, you get Persian digits in math mode and in Latin mode, you get T_EX's default font and digits in math mode.
- ☞ If you use `\PersianMathsDigits` anywhere, you will overwrite XePersian's default behaviour and you will always get Persian digits in math mode.
- ☞ If you use `\DefaultMathsDigits` anywhere, again you will overwrite XePersian's default behaviour and you will always get T_EX's default font and digits in math mode.

4 New Conditionals

4.1 Shell escape (or `write18`) conditional

```
\ifwritexviii
  <material when Shell escape (or write18) is enabled>
\else
  <material when Shell escape (or write18) is not enabled>
\fi
```

5 Bilingual Captions

XePersian sets caption bilingually. This means if you are in RTL mode, you get Persian caption and if you are in LTR mode, you get English caption.



5.1 Support For Various Packages

In addition to what bidi package supports, XePersian also support a few packages. This support is more about language aspect rather than directionality. These packages are algorithmic, algorithm, enumerate, and backref packages.

5.1.1 Things You Should Know about Support For enumerate Package

The enumerate package gives the enumerate environment an optional argument which determines the style in which the counter is printed.

An occurrence of one of the tokens A, a, I, i, or 1 produces the value of the counter printed with (respectively) \Alph, \alph, \Roman, \roman or \arabic.

In addition with the extra support that XePersian provides, an occurrence of one of the tokens l, ی, or ت produces the value of the counter printed with (respectively) \harfi, \adadi, or \tartibi.

These letters may be surrounded by any strings involving any other T_EX expressions, however the tokens A, a, I, i, 1, l, ی, ت must be inside a {} group if they are not to be taken as special.

To see an Example, please look at enumerate package documentation.

5.2 Index Generation

For generating index, you are advised to use xindy program, any other program such as makeindex is not recommended.

5.3 Converting Your FarsiT_EX Files To XePersian or Unicode

There is a python program written by Mostafa Vahedi that enables you to convert FarsiT_EX files to XePersian or unicode. This program can be found in doc folder with the name ftxe-0.12.py. To convert your FarsiT_EX files to XePersian, put ftxe-0.12.py in the same directory that your FarsiT_EX file is, and then open a terminal/command prompt and do the following:

```
python ftxe-0.12.py file.ftx file.tex
```

This will convert your file.ftx (FarsiT_EX file) to file.tex (XePersian file).

The general syntax of using the python script is as follow:

```
python ftxe-0.12.py [-r] [-s] [-x] [-u] input-filename1 input-filename2
```

Where

-r (DEFAULT) recursively consider files included in the given files

-s do not recursively consider files

-x (DEFAULT) insert XePersian related commands



-u only convert to unicode (and not to XePersian)

Please note that the python script will not work with versions of python later than 2.6. So you are encouraged to use version 2.6 of python to benefit from this python script.

6 Extra Packages And Classes

6.1 Magazine Typesetting

6.1.1 Introduction

xepersian-magazine class allows you to create magazines, newspapers and any other types of papers. The output document has a front page and as many inner pages as desired. Articles appear one after another, telling the type, number of columns, heading, subheading, images, author and so forth. It is possible to change the aspect of (almost) everything therefore it is highly customisable. Commands to add different titles, headings and footers are also provided.

6.1.2 Usage

To create² a magazine just load the class as usual³, with

```
\documentclass [Options] {xepersian-magazine}
```

at the beginning of your source file. The class options are described in [subsubsection 6.1.12](#).

From this point it is possible to include packages and renew class commands described in [subsubsection 6.1.9](#).

6.1.3 Front Page

As every magazine, xepersian-magazine has its own front page. It includes main headings, an index, the magazine logo and other useful information. This environment should be the first you use within xepersian-magazine class but it is not mandatory.

```
\firstimage \firstarticle
```

The first two commands you can use inside the `frontpage` environment are `\firstimage` and `\firstarticle` which include, respectively, the main image and the main heading in the front page. The first one takes two arguments $\langle image \rangle$ and $\langle description \rangle$. Notice that second argument is optional and it declares the image

²For a sample file, please look at `magazine-sample.tex` in the doc folder

³You also need to load `graphicx`, `xunicode` and `xepersian` packages respectively, after loading the document class and choose fonts for the main text, Latin text and digits in maths formulas. For more detail see [section 2](#) of the documentation.



caption; *<image>* defines the relative path to the image. In order to include the first piece of article use

```
\firstarticle{<title>}{<opening>}{<time>}
```

first two arguments are mandatory and represent heading and the opening paragraph. Last argument is optional (you can leave it blank) and indicates the time when article happened.

```
\secondarticle
```

The second piece of article is included using the command `\secondarticle` just as the first article. The main difference are that this second piece has two more arguments and it does not include an image.

```
\secondarticle{<title>}{<subtitle>}{<opening>}{<pagesof>}{<time>}
```

The new arguments *<subtitle>* and *<pagesof>* define a subtitle and the name of the section for this piece of article.

```
\thirdarticle
```

The third piece of article is the last one in the xepersian-magazine front page. It works like the `\secondarticle`.

```
\thirdarticle{<title>}{<subtitle>}{<opening>}{<pagesof>}{<time>}
```

The arguments meaning is the same as `\secondarticle` command.

The front page includes three information blocks besides the news: `indexblock` which contains the index, `authorblock` which includes information about the author and a `weatherblock` containing a weather forecast. All these three environments are mostly a frame in the front page therefore they can be redefined to fit your personal wishes but I kept them to give an example and to respect the original xepersian-magazine format.

```
\indexitem
```

The `indexblock` environment contains a manually edited index of xepersian-magazine. It takes one optional argument *<title>* and places a title over the index block. To add entries inside the index just type

```
\indexitem{<title>}{<reference>}
```

inside the environment. The *<title>* is the index entry text and the *<reference>* points to a article inside xepersian-magazine. It will be more clear when you read [subsub-](#)



[section 6.1.4](#). In order to get a correct output, it is necessary to leave a blank line between index items.

The `authorblock` environment can include whatever you would like. I called it `authorblock` because I think it is nice to include some author reference in the front page: who you are, why are you doing this... This environment creates a frame box in the bottom right corner of the front page with your own logo at the top.

```
\weatheritem
```

Finally, the `weatherblock` lets you include a weather forecast. It takes one optional argument $\langle title \rangle$ that places a title over the weather block. It can fit up to three weather icons with maximum and minimum temperatures, description and name. To add each of the weather entries type the following

```
\weatheritem{\langle image \rangle}{\langle day-name \rangle}{\langle max \rangle} {\langle min \rangle}{\langle short-des \rangle}
```

The first argument includes the path to the weather icon (i.e. sunny or rainy), $\langle day-name \rangle$ like Monday, $\langle max \rangle$ and $\langle min \rangle$ are the highest and lowest day temperatures and $\langle short-des \rangle$ is a brief description of the weather condition: partly cloudy, sunny and windy ...

6.1.4 Inside

Once we have created the front page we should include all articles inside our magazine. `xepersian-magazine` arranges all articles one after each other, expanding headings all over the page and splitting the article text in the number of columns we wish. There are three different environments to define a piece of article: the `article` environment described in [subsubsection 6.1.5](#), the `editorial` environment [subsubsection 6.1.6](#) for opinion articles and the `shortarticle` environment explained in [subsubsection 6.1.7](#).

6.1.5 The article environment

The main environment to include a piece of article is called `article`. It takes four arguments that set up the headings and structure of the article.

```
\begin{article}{\langle num-of-columns \rangle}{\langle title \rangle}{\langle subtitle \rangle} {\langle pagesof \rangle}{\langle label \rangle}  
...{\langle text \rangle}...  
\end{article}
```

The first argument $\langle num-of-columns \rangle$ sets the number of columns the article will be divided whereas $\langle label \rangle$ is used when pointing an article from the index in the front page. The rest of the arguments are easy to understand.

Inside the `article` environment, besides the main text of the article, it is possible to include additional information using several class commands.




```
\authorandplace \timestamp
```

The `\authorandplace{author}{place}` inserts the name of the editor and the place where the article happened in the way many magazines do. Another useful command is `\timestamp{time}` which includes the time and a separator just before the text. These two commands should be used before the text because they type the text as the same place they are executed.

```
\image
```

To include images within the text of an article, xepersian-magazine provides an `\image` command. Since multicols package does not provide any float support for its multicols environment, I created a macro that includes an image only if that is possible, calculating if there is enough space for the image. It is not the best solution but it works quite well and I could not find a better one. To include an image use the command and its two arguments: the relative path to the image and a short description.

```
\image{image}{description}
```

```
\columntitle \expandedtitle
```

Within the text of the article, it is possible to add column and expanded titles. The main difference between them is that the first one keeps inside the width of an article column whereas the second expands all over the width of the page, breaking all the columns. Their use is analogous, as follows

```
\columntitle{type}{text}  
\expandedtitle{type}{text}
```

These two commands use fancybox package features. That is why there are five different types of titles which correspond mainly with fancybox ones: shadowbox, doublebox, ovalbox, Ovalbox and lines.

6.1.6 The editorial environment

In addition to the editorial article environment, one can use the editorial environment to create editorial or opinion texts. The main feature is that it transforms the style of the heading. Although this environment accepts all the commands article takes, it does not make any sense to use the `\authorandplace` command within it since it includes an author argument. To create an editorial text use



```
\begin{editorial}{\langle num-of-columns \rangle}{\langle title \rangle}{\langle author \rangle}{\langle label \rangle}
...{\langle text \rangle}...
\end{editorial}
```

All arguments have the same meaning as article environment (see [subsubsection 6.1.5](#)).

6.1.7 The shortarticle environment

The shortarticle environment creates a block of short article. Although it has its own title and subtitle, each piece of article within it may have a title. To use it just type:

```
\begin{shortarticle}{\langle num-of-columns \rangle}{\langle title \rangle}{\langle subtitle \rangle}{\langle label \rangle}
...{\langle text \rangle}...
\shortarticleitem{\langle title \rangle}{\langle text \rangle}
...
\end{shortarticle}
```

You can also specify the number of columns of the block like editorial and article environments. To add a piece of article inside the shortarticle use the `\shortarticleitem`, indicating a title and the text of the issue.

6.1.8 Commands between articles

```
\articlesep \newsection
```

There are two commands you can use among the articles inside xepersian-magazine: `\articlesep` and `\newsection`. The first one does not take any parameter and just draws a line between two articles. The second changes the content of `\xepersian@section` to the new *`\section name`*. From the point it is used, all articles which follow will be grouped within the new section.

```
\newsection{\langle section name \rangle}
```

6.1.9 Customization

xepersian-magazine includes many commands which can be used to customize its aspect, from the front page to the last page. I will list them grouped so it is easy to find them. Treat them as standard \LaTeX commands, using `\renewcommand` to change their behaviour.



6.1.10 Front Page

```
\customlogo \customminilogo \custommagazinename
```

When creating a magazine, everyone wants to show its own logo instead of xepersian-magazine default heading. To achieve this, you need to put the following command at the preamble of your document:

```
\customlogo{<text>}  
\customminilogo{<text>}  
\custommagazinename{<text>}
```

```
\edition \editionformat
```

The edition text has to be declared in the preamble of the document. One important thing to know is that `\author`, `\date` and `\title` have no effect inside xepersian-magazine since the magazine date is taken from `\today` command and the other two are only for the title page (if using `\maketitle`).

```
\indexFormat \indexEntryFormat \indexEntryPageTxt  
\indexEntryPageFormat \indexEntrySeparator
```

When defining the index in the front page, there are several commands to customize the final index style. `\indexFormat` sets the format of the title; `\indexEntryFormat`, the format of each index entry; `\indexEntryPageTxt` and `\indexEntryPageFormat` lets you define which is the text that goes with the page number and its format. Finally, xepersian-magazine creates a thin line between index entries, you can redefine it using `\indexEntrySeparator`. To get the index with `\xepersian@indexwidth` is provided.

```
\weatherFormat \weatherTempFormat \weatherUnits
```

Relating to the weather block, the title format can be changed redefining `\weatherFormat`. In order to customize the format of the temperature numbers and their units it is necessary to redefine `\weatherTempFormat` and `\weatherUnits` respectively.

```
\*TitleFormat \*SubtitleFormat \*TextFormat
```

The main article that appear in the front page can change their formats. To obtain that there are three standard commands to modify the title, subtitle and text style. You just have to replace the star (*) with first, second or third depending on which article you are editing. Note that first piece of article has no subtitle therefore it does not make any sense to use the non-existent command `\firstSubtitleFormat`.



```
\pictureCaptionFormat \pagesFormat
```

Two other elements to configure are the picture captions and the pages or section format in the entire document. To proceed just redefine the macros `\pictureCaptionFormat` and `\pagesFormat`.

6.1.11 Inside The Magazine

```
\innerTitleFormat \innerSubtitleFormat \innerAuthorFormat  
\innerPlaceFormat
```

The articles inside `xepersian-magazine` may have a different format from the ones in the front page. To change their title or subtitle format redefine `\innerTitleFormat` and `\innerSubtitleFormat`. The article text format matches the document general definition. When using the `\authorandplace` command, you might want to change the default style. Just renew `\innerAuthorFormat` and `\innerPlaceFormat` to get the results.

```
\timestampTxt \timestampSeparator \timestampFormat
```

The `\timestamp` command described in [subsubsection 6.1.5](#) lets you introduce the time of the event before the article text. You can configure its appearance by altering several commands: `\timestampTxt` which means the text after the timestamp; `\timestampSeparator` which defines the element between the actual timestamp and the beginning of the text and, finally, `\timestampFormat` to change the entire timestamp format.

```
\innerTextFinalMark
```

`xepersian-magazine` puts a small black square at the end of the article. As I wanted to create a highly customizable \LaTeX class I added the macro `\innerTextFinalMark` to change this black square. This item will appear always following the last character of the text with the `~` character.

```
\minraggedcols \raggedFormat
```

The `\minraggedcols` counter is used to tell `xepersian-magazine` when article text should be ragged instead of justified. The counter represents the minimum number of columns that are needed in order to use ragged texts. For example, if `\minraggedcols` is set to 3, all articles with 3 columns or more will be ragged. Articles with 1, 2 columns will have justified text. By default, `\minraggedcols` is set to 4.

The `\raggedFormat` macro can be redefined to fit user ragged style. Default value is `\RaggedLeft`.



```
\heading \foot
```

xepersian-magazine includes package fancyhdr for changing headings and footers. Although it is possible to use its own commands to modify xepersian-magazine style, there are two commands to change headings and foot appearance. Place them in the preamble of your xepersian-magazine document.

```
\heading{\left}\{center}\{right}\  
\foot{\left}\{center}\{right}
```

If you still prefer to use fancyhdr macros, use them after the `frontpage` environment. xepersian-magazine by default places no headers and footers. If you want headers and footers, then after loading xepersian package, you should write `\pagestyle{fancy}` at the preamble of your document.

6.1.12 Class Options

The xepersian-magazine class is in itself an alteration of the standard article class, thus it inherits most of its class options but twoside, twocolumn, notitlepage and a4paper. If you find problems when loading other article features, please let me know to fix it. There are also five own options that xepersian-magazine implements.

a3paper (false) This option makes xepersian-magazine 297 mm width by 420 mm height. This option is implemented because the standard article class does not allow this document size.

9pt (false) Allows the 9pt font size that article class does not include (default is 10pt).

columnlines columnlines (false) Adds lines between columns in the entire xepersian-magazine. The default line width is 0.1pt but it is possible to change this by setting length `\columnlines` in the preamble.

showgrid (false) This option is only for developing purposes. Because the front page has a personal design using the textpos package, I created this grid to make easier the layout.

6.2 Typesetting Multiple-choice Questions

6.2.1 Introduction

xepersian-multiplechoice is a package for making multiple choices questionnaires under \LaTeX . A special environment allows you to define questions and possible answers. You can specify which answers are correct and which are not. xepersian-multiplechoice not only formats the questions for you, but also generates a “form” (a grid that your students will have to fill in), and a “mask” (the same grid, only with correct answers properly checked in). You can then print the mask on a slide and correct the questionnaires more easily by superimposing the mask on top of students’ forms.



6.2.2 Usage

Here we now explain the usage of this package, however there are four example files, namely `test-question-only.tex`, `test-solution-form.tex`, `test-empty-form.tex` and `test-correction.tex`, available in `doc` folder that you may want to look at.

6.2.3 Loading The Package

You can load the package as usual by:

```
\usepackage [Options] {xepersian-multiplechoice}
```

The available options are described along the text, where appropriate.

6.2.4 Creating Questions

Here's a simple example demonstrating how to produce a new question:

```
1 \begin{question}{سؤال}
2 \false \ جواب
3 \true ۲ جواب
4 \false ۳ جواب
5 \false ۴ جواب
6 \end{question}
7 \begin{correction}
8 جواب واقعی و علت اینکه این جواب، جواب واقعی هست
9 \end{correction}
```

6.2.5 The question Environment

The `question` environment allows you to insert questions into your document. It takes one mandatory argument which specifies the actual question's text. The question will be displayed in a frame box, the size of the line.

```
\true \false
```

The proposed answers are displayed below the question in a list fashion (the question environment is a list-based one). Instead of using `\item` however, use either `\true` or `\false` to insert a possible answer.

6.2.6 Question Numbers

The `question` environment is associated with a \TeX counter named `question`. This counter stores the number of the next (or current) question. It is initialized to 1, and automatically incremented at the end of `question` environments. You might want to use it to format question titles. For instance, you could decide that each question belongs to a subsection in the `article` class, and use something like this before each question: `\subsection*{Question \thethequestion}`



6.2.7 The Form and the Mask

`\makeform \makemask`

Based on the questions appearing in your document, xepersian-multiplechoice has the ability to generate a “form” (a grid that your students will have to fill in), and a “mask” (the same grid, only with correct answers properly checked in). This can make the correction process easier.

To generate a form and a mask, use the macros `\makeform` and `\makemask`. xepersian-multiplechoice uses two auxiliary files to build them. These files have respectively an extension of `frm` and `msk`. If you use these macros, you will need two passes of L^AT_EX in order to get a correctly formatted document.

6.2.8 Typesetting corrections

The “correction” mode allows you to automatically typeset and distribute corrections to your students. These corrections are slightly modified versions of your questionnaire: each possible answer is prefixed with a small symbol (a visual clue) indicating whether the answer was correct or wrong. In addition, you can typeset explanations below each question.

To activate the correction mode, use the `correction` option. It is off by default.

To typeset explanations below the questions, use the `correction` environment (no argument). The contents of this environment is displayed only in correction mode. In normal mode, it is simply discarded.

In addition, note that xepersian-multiplechoice cancels the actions performed by `\makeform` and `\makemask` in `correction` mode. This is to avoid further edition of the source when typesetting a correction.

6.2.9 Important Note

Currently, xepersian-multiplechoice requires that you provide a constant number of proposed answers across all questions in your xepersian-multiplechoice. This is something natural when you want to build forms, but this might be too restrictive otherwise, I’m not sure, so it is possible that this restriction will be removed in future versions.

Currently, there is a built-in mechanism for checking that the number of proposed answers remains constant: when xepersian-multiplechoice encounters the first occurrence of the `question` environment, it remembers the number of proposed answers from there. Afterwards, any noticed difference in subsequent occurrences will generate an error. As a consequence, you never have to tell xepersian-multiplechoice explicitly what that number is.

6.3 Customising The Package



6.3.1 The question environment

```
\questionspace \answerstitlefont \answernumberfont
```

`\questionspace` is the amount of extra vertical space to put under the question, before the list of proposed answers. This is a \LaTeX length that defaults to 0pt. Before the list of possible answers, a short title is displayed (for English, it reads “Possible answers:”). The `\answerstitlefont` macro takes one mandatory argument which redefines the font to use for the answers title. By default, `\bfseries` is used. Each proposed answer in the list is numbered automatically (and alphabetically). The `\answernumberfont` macro takes one mandatory argument which redefines the font to use for displaying the answer number. By default, `\bfseries` is used.

6.3.2 The Form and the Mask

```
\headerfont \X
```

The `\headerfont` macro takes one mandatory argument which redefines the font to use for the headers (first line and first column) of the form and mask arrays. By default, `\bfseries` is used.

In the mask, correct answers are checked in by filling the corresponding cell with an “X” character. If you want to change this, call the `\X` macro with one (mandatory) argument.

6.3.3 The correction

```
\truesymbol \falsesymbol
```

In correction mode, labels in front of answers are modified to give a visual clue about whether the answer was correct or wrong. By default, a cross and a small arrow are used. You can change these symbols by using the `\truesymbol` and `\falsesymbol` macros. For instance, you could give a fancier look to your correction by using the `pifont` package and issuing:

```
\truesymbol{\ding{'063}~}  
\falsesymbol{\ding{'067}~}
```

```
\correctionstyle
```

The appearance of the contents of the correction environment can be adjusted by using the `\correctionstyle` macro. By default, `\itshape` is used.

7 xepersian implementation

7.1 algorithmic-xepersian.def




```

1 \ProvidesFile{algorithmic-xepersian.def}[2010/07/25 v0.2 adaptations for algorithmic package]
2 \def\algorithmicrequire{\if@RTL\textbf{   }\else\textbf{Require:}\fi}
3 \def\algorithmicensure{\if@RTL\textbf{   }\else\textbf{Ensure:}\fi}

```

7.2 algorithm-xepersian.def

```

4 \ProvidesFile{algorithm-xepersian.def}[2010/07/25 v0.2 adaptations for algorithm package]
5 \def\ALG@name{\if@RTL else\      Algorithm\fi}
6 \def\ALGS@name{      }
7 \def\listalgorithmname{\if@RTL      \ALGS@name\else List of \ALG@name s\fi}

```

7.3 amsart-xepersian.def

```

8 \ProvidesFile{amsart-xepersian.def}[2013/04/26 v0.3 adaptations for amsart class]
9 \renewcommand \thepart {\@tartibi\c@part}
10 \def\appendix{\par\c@section\z@ \c@subsection\z@
11   \let\sectionname\appendixname
12   \def\thesection{\@harfi\c@section}}
13
14 \long\def\@footnotetext#1{%
15   \insert\footins{%
16     \if@RTL@footnote\@RTLtrue\else\@RTLfalse\fi%
17     \normalfont\footnotesize
18     \interlinepenalty\interfootnotelinepenalty
19     \splittopskip\footnotesep \splitmaxdepth \dp\strutbox
20     \floatingpenalty\@MM \hsize\columnwidth
21     \@parboxrestore \parindent\normalparindent \sloppy
22     \protected@edef\@currentlabel{%
23       \csname p@footnote\endcsname\@thefnmark}%
24     \@makefnmark{%
25       \rule\z@\footnotesep\ignorespaces\if@RTL@footnote#1\else\latinfont#1\fi\unskip\strut\par}}
26
27
28
29
30
31 \long\def\@RTLfootnotetext#1{%
32   \insert\footins{%
33     \@RTLtrue%
34     \normalfont\footnotesize
35     \interlinepenalty\interfootnotelinepenalty
36     \splittopskip\footnotesep \splitmaxdepth \dp\strutbox
37     \floatingpenalty\@MM \hsize\columnwidth
38     \@parboxrestore \parindent\normalparindent \sloppy
39     \protected@edef\@currentlabel{%
40       \csname p@footnote\endcsname\@thefnmark}%
41     \@makefnmark{%
42       \rule\z@\footnotesep\ignorespaces\persianfont #1\unskip\strut\par}}}
43
44
45

```



```

46
47
48
49
50 \long\def\@LTRfootnotetext#1{%
51   \insert\footins{%
52     \@RTLfalse%
53     \normalfont\footnotesize
54     \interlinepenalty\interfootnotelinepenalty
55     \splittopskip\footnotesep \splitmaxdepth \dp\strutbox
56     \floatingpenalty\@MM \hsize\columnwidth
57     \@parboxrestore \parindent\normalparindent \sloppy
58     \protected@edef\@currentlabel{%
59       \csname p@footnote\endcsname\@thefnmark}%
60     \@makefnptext{%
61       \rule\z@\footnotesep\ignorespaces\latinfont #1\unskip\strut\par}}
62
63
64 \footdir@temp\footdir@ORG@xepersian@amsart@footnotetext\@footnotetext{\bidi@footdir@footnote}%
65 \footdir@temp\footdir@ORG@xepersian@amsart@RTLfootnotetext\@RTLfootnotetext{R}%
66 \footdir@temp\footdir@ORG@xepersian@amsart@LTRfootnotetext\@LTRfootnotetext{L}%
67

```

7.4 amsbook-xepersian.def

```

68 \ProvidesFile{amsbook-xepersian.def}[2013/04/26 v0.4 adaptations for amsbook class]
69 \def\frontmatter{\cleardoublepage\pagenumbering{harfi}}
70 \renewcommand \thepart {\@tartibi@c@part}
71 \def\appendix{\par
72   \c@chapter\z@ \c@section\z@
73   \let\chaptername\appendixname
74   \def\thechapter{\@harfi\c@chapter}}
75
76 \long\def\@footnotetext#1{%
77   \insert\footins{%
78     \if@RTL@footnote\@RTLtrue\else\@RTLfalse\fi%
79     \normalfont\footnotesize
80     \interlinepenalty\interfootnotelinepenalty
81     \splittopskip\footnotesep \splitmaxdepth \dp\strutbox
82     \floatingpenalty\@MM \hsize\columnwidth
83     \@parboxrestore \parindent\normalparindent \sloppy
84     \protected@edef\@currentlabel{%
85       \csname p@footnote\endcsname\@thefnmark}%
86     \@makefnptext{%
87       \rule\z@\footnotesep\ignorespaces\if@RTL@footnote#1\else\latinfont#1\fi\unskip\strut\par}}
88
89
90
91
92

```



```

93 \long\def\@RTLfootnotetext#1{%
94   \insert\footins{%
95     \RTLtrue%
96     \normalfont\footnotesize
97     \interlinepenalty\interfootnotelinepenalty
98     \splittopskip\footnotesep \splitmaxdepth \dp\strutbox
99     \floatingpenalty\@MM \hsize\columnwidth
100    \@parboxrestore \parindent\normalparindent \sloppy
101    \protected@edef\@currentlabel{%
102      \csname p@footnote\endcsname\@thefnmark}%
103    \@makefntext{%
104      \rule\z@\footnotesep\ignorespaces\persianfont #1\unskip\strut\par}}
105
106
107
108
109
110
111
112 \long\def\@LTRfootnotetext#1{%
113   \insert\footins{%
114     \RTLfalse%
115     \normalfont\footnotesize
116     \interlinepenalty\interfootnotelinepenalty
117     \splittopskip\footnotesep \splitmaxdepth \dp\strutbox
118     \floatingpenalty\@MM \hsize\columnwidth
119     \@parboxrestore \parindent\normalparindent \sloppy
120     \protected@edef\@currentlabel{%
121       \csname p@footnote\endcsname\@thefnmark}%
122     \@makefntext{%
123       \rule\z@\footnotesep\ignorespaces\latinfont #1\unskip\strut\par}}
124
125 \footdir@temp\footdir@ORG@xepersian@amsbook@footnotetext\@footnotetext{\bidi@footdir@footnote}
126 \footdir@temp\footdir@ORG@xepersian@amsbook@RTLfootnotetext\@RTLfootnotetext{R}%
127 \footdir@temp\footdir@ORG@xepersian@amsbook@LTRfootnotetext\@LTRfootnotetext{L}%
128

```

7.5 appendix-xepersian.def

```

129 \ProvidesFile{appendix-xepersian.def}[2015/02/01 v0.1 adaptations for appendix package]
130 \renewcommand{\@resets@pp}{\par
131   \@ppsavesec
132   \stepcounter{@pps}
133   \setcounter{section}{0}%
134   \if@chapter@pp
135     \setcounter{chapter}{0}%
136     \renewcommand\@chapapp{\appendixname}%
137     \renewcommand\thechapter{\@harfi@c@chapter}%
138   \else
139     \setcounter{subsection}{0}%

```



```

140 \renewcommand\thesection{\@harfi\c@section}%
141 \fi
142 \restoreapp
143 }

```

7.6 article-xepersian.def

```

144 \ProvidesFile{article-xepersian.def}[2010/07/25 v0.2 adaptations for standard article class]
145 \renewcommand \thepart {\@tartibi\c@part}
146 \renewcommand\appendix{\par
147 \setcounter{section}{0}%
148 \setcounter{subsection}{0}%
149 \gdef\thesection{\@harfi\c@section}}

```

7.7 artikel1-xepersian.def

```

150 \ProvidesFile{artikel1-xepersian.def}[2010/07/25 v0.1 adaptations for artikel1 class]
151 \renewcommand*\thepart{\@tartibi\c@part}
152 \renewcommand*\appendix{\par
153 \setcounter{section}{0}%
154 \setcounter{subsection}{0}%
155 \gdef\thesection{\@harfi\c@section}}

```

7.8 artikel2-xepersian.def

```

156 \ProvidesFile{artikel2-xepersian.def}[2010/07/25 v0.1 adaptations for artikel2 class]
157 \renewcommand*\thepart{\@tartibi\c@part}
158 \renewcommand*\appendix{\par
159 \setcounter{section}{0}%
160 \setcounter{subsection}{0}%
161 \gdef\thesection{\@harfi\c@section}}

```

7.9 artikel3-xepersian.def

```

162 \ProvidesFile{artikel3-xepersian.def}[2010/07/25 v0.1 adaptations for artikel3 class]
163 \renewcommand*\thepart{\@tartibi\c@part}
164 \renewcommand*\appendix{\par
165 \setcounter{section}{0}%
166 \setcounter{subsection}{0}%
167 \gdef\thesection{\@harfi\c@section}}

```

7.10 backref-xepersian.def

```

168 \ProvidesFile{backref-xepersian.def}[2010/07/25 v0.1 adaptations for backref package]
169 \def\backrefpagesname{\if@RTL else\ pages\fi}
170 \def\BR@Latincitex[#1]#2{%
171 \BRorg@Latincitex[#1]#2}%
172 \ifBR@verbose
173 \PackageInfo{backref}{back Latin cite \string`#2\string'}%
174 \fi
175 \Hy@backout{#2}%
176 }
177 \AtBeginDocument{%

```



```

178 \@ifundefined{NAT@parse}{%
179   \global\let\BRorg@Latincitex\@Latincitex
180   \global\let\@Latincitex\BR@Latincitex
181 }{%
182   \@ifpackageloaded{hyperref}{}%
183   \def\hyper@natlinkstart#1{\Hy@backout{#1}}%
184 }%
185 \PackageInfo{backref}{** backref set up for natbib **}%
186 }%
187 }%

```

7.11 bidentuftsidenote-xepersian.def

```

188 \ProvidesFile{bidentuftsidenote-xepersian.def}[2014/12/28 v0.2 xepersian changes to bidentuftsidenote]
189 \setLTRcitationfont{\@bidentuftsidenote@marginfont\latinfont}
190 \long\def\@LTRbidentuftsidenote@sidenote[#1][#2]#3{%
191   \let\cite\@bidentuftsidenote@infootnote@cite% use the in-sidenote \cite command
192   \gdef\@bidentuftsidenote@citations{}% clear out any old citations
193   \ifthenelse{\NOT\isempty{#2}}{%
194     \gsetlength{\@bidentuftsidenote@sidenote@vertical@offset}{#2}%
195   }{%
196     \gsetlength{\@bidentuftsidenote@sidenote@vertical@offset}{0pt}%
197   }%
198   \ifthenelse{\isempty{#1}}{%
199     % no specific footnote number provided
200     \stepcounter\@mpfn%
201     \protected@xdef\@thefnmark{\thempfn}%
202     \@footnotemark\@LTRfootnotetext[\@bidentuftsidenote@sidenote@vertical@offset]{\latinfont#3}%
203   }{%
204     % specific footnote number provided
205     \begingroup%
206       \csname c@\@mpfn\endcsname #1\relax%
207       \unrestored@protected@xdef\@thefnmark{\thempfn}%
208     \endgroup%
209     \@footnotemark\@LTRfootnotetext[\@bidentuftsidenote@sidenote@vertical@offset]{\latinfont#3}%
210   }%
211   \@bidentuftsidenote@print@citations% print any citations
212   \let\cite\@bidentuftsidenote@normal@cite% go back to using normal in-text \cite command
213   \unskip\ignorespaces% remove extra white space
214   \kern-\multiplefootnotemarker% remove \kern left behind by sidenote
215   \kern\multiplefootnotemarker\relax% add new \kern here to replace the one we yanked
216 }
217 \long\def\@RTLbidentuftsidenote@sidenote[#1][#2]#3{%
218   \let\cite\@bidentuftsidenote@infootnote@cite% use the in-sidenote \cite command
219   \gdef\@bidentuftsidenote@citations{}% clear out any old citations
220   \ifthenelse{\NOT\isempty{#2}}{%
221     \gsetlength{\@bidentuftsidenote@sidenote@vertical@offset}{#2}%
222   }{%
223     \gsetlength{\@bidentuftsidenote@sidenote@vertical@offset}{0pt}%
224   }%

```



```

225 \ifthenelse{\isempty{#1}}{%
226   % no specific footnote number provided
227   \stepcounter\@mpfn%
228   \protected@xdef\@thefnmark{\thempfn}%
229   \@footnotemark\@RTLfootnotetext[\@bidityftesidenote@sidenote@vertical@offset]{\persianfont#
230 }{%
231   % specific footnote number provided
232   \begingroup%
233     \csname c@\@mpfn\endcsname #1\relax%
234     \unrestored@protected@xdef\@thefnmark{\thempfn}%
235   \endgroup%
236   \@footnotemark\@RTLfootnotetext[\@bidityftesidenote@sidenote@vertical@offset]{\persianfont#
237 }%
238 \@bidityftesidenote@print@citations%          print any citations
239 \let\cite\@bidityftesidenote@normal@cite%      go back to using normal in-text \cite command
240 \unskip\ignorespaces%                          remove extra white space
241 \kern-\multiplefootnotemarker%                remove \kern left behind by sidenote
242 \kern\multiplefootnotemarker\relax% add new \kern here to replace the one we yanked
243 }
244 \renewcommand\LTRmarginnote[2][Opt]{%
245   \let\cite\@bidityftesidenote@infootnote@cite% use the in-sidenote \cite command
246   \gdef\@bidityftesidenote@citations{}%        clear out any old citations
247   \LTRbidityftesidenotemarginpar{\hbox{}}\vspace*{#1}\@bidityftesidenote@marginnote@font\latinfont
248   \@bidityftesidenote@print@citations%          print any citations
249   \let\cite\@bidityftesidenote@normal@cite%      go back to using normal in-text \cite command
250 }
251 \renewcommand\RTLmarginnote[2][Opt]{%
252   \let\cite\@bidityftesidenote@infootnote@cite% use the in-sidenote \cite command
253   \gdef\@bidityftesidenote@citations{}%        clear out any old citations
254   \RTLbidityftesidenotemarginpar{\hbox{}}\vspace*{#1}\@bidityftesidenote@marginnote@font\persianfont
255   \@bidityftesidenote@print@citations%          print any citations
256   \let\cite\@bidityftesidenote@normal@cite%      go back to using normal in-text \cite command
257 }

```

7.12 bidimoderncv-xepersian.def

```

258 \ProvidesFile{bidimoderncv-xepersian.def}[2010/07/25 v0.1 adaptations for bidimoderncv class]
259 \def\refname{\if@RTL else\    Publications\fi}

```

7.13 boek3-xepersian.def

```

260 \ProvidesFile{boek3-xepersian.def}[2010/07/25 v0.1 adaptations for boek3 class]
261 \renewcommand*\thepart{\@tartibi\c@part}
262 \renewcommand*\frontmatter{%
263   \cleardoublepage
264   \@mainmatterfalse
265   \pagenumbering{harfi}}
266 \renewcommand*\appendix{\par
267   \setcounter{chapter}{0}%
268   \setcounter{section}{0}%
269   \gdef\@chapapp{\appendixname}%

```



```
270 \gdef\thechapter{\@harfi\c@chapter}}
```

7.14 boek-xepersian.def

```
271 \ProvidesFile{boek-xepersian.def}[2010/07/25 v0.1 adaptations for boek class]
272 \renewcommand*\thepart{\@tartibi\c@part}
273 \renewcommand*\frontmatter{%
274   \cleardoublepage
275   \@mainmatterfalse
276   \pagenumbering{harfi}}
277 \renewcommand*\appendix{\par
278   \setcounter{chapter}{0}%
279   \setcounter{section}{0}%
280   \gdef\@chapapp{\appendixname}%
281   \gdef\thechapter{\@harfi\c@chapter}}
```

7.15 bookest-xepersian.def

```
282 \ProvidesFile{bookest-xepersian.def}[2010/07/25 v0.1 adaptations for bookest class]
283 \renewcommand \thepart {\@tartibi\c@part}
284 \renewcommand\appendix{\par
285   \setcounter{chapter}{0}%
286   \setcounter{section}{0}%
287   \gdef\@chapapp{\appendixname}%
288   \gdef\thechapter{\@harfi\c@chapter}
289 }%end appendix
```

7.16 book-xepersian.def

```
290 \ProvidesFile{book-xepersian.def}[2010/07/25 v0.2 adaptations for standard book class]
291 \renewcommand\frontmatter{%
292   \cleardoublepage
293   \@mainmatterfalse
294   \pagenumbering{harfi}}
295 \renewcommand \thepart {\@tartibi\c@part}
296 \renewcommand\appendix{\par
297   \setcounter{chapter}{0}%
298   \setcounter{section}{0}%
299   \gdef\@chapapp{\appendixname}%
300   \gdef\thechapter{\@harfi\c@chapter}
301 }%end appendix
```

7.17 breqn-xepersian.def

```
302 \ProvidesFile{breqn-xepersian.def}[2010/07/25 v0.1 adaptations for breqn package]
303 \def\@dmath[#1]{\if@RTL\@RTLfalse\addfontfeatures{Mapping=farsidigits}\fi%
304   \everydisplay\expandafter{\the\everydisplay \display@setup}%
305   \if@noskipsec \leavevmode \fi
306   \if@inlabel \leavevmode \global\@inlabelfalse \fi
307   \if\eq@group\else\eq@prelim\fi
308   \setkeys{breqn}{#1}%
309   \the\eqstyle
310   \eq@setnumber
```



```

311 \begingroup
312 \eq@setup@a
313 \eq@startup
314 }
315 \def\@dgroup[#1]{\if@RTL\@RTLfalse\addfontfeatures{Mapping=farsidigits}\fi%
316 \let\eq@group\@True \global\let\eq@GRP@first@dmath\@True
317 \global\GRP@queue\@emptytoks \global\setbox\GRP@box\box\voidb@x
318 \global\let\GRP@label\@empty
319 \global\grp@wdL\z@\global\grp@wdR\z@\global\grp@wdT\z@
320 \global\grp@linewidth\z@\global\grp@wdNum\z@
321 \global\let\grp@eqs@numbered\@False
322 \global\let\grp@aligned\@True
323 \global\let\grp@shiftnumber\@False
324 \eq@prelim
325 \setkeys{breqn}{#1}%
326 \if\grp@hasNumber \grp@setnumber \fi
327 }
328 \def\@dseries[#1]{\if@RTL\@RTLfalse\addfontfeatures{Mapping=farsidigits}\fi%
329 \let\display@setup\dseries@display@setup
330 % Question: should this be the default for dseries???
331 \global\eq@wdCond\z@
332 \@dmath[layout={M},#1]%
333 \mathsurround\z@\@math \penalty\@Mi
334 \let\endmath\ends@math
335 \def\premath{%
336 \ifdim\lastskip<.3em \unskip
337 \else\ifnum\lastpenalty<\@M \dquad\fi\fi
338 }%
339 \def\postmath{\unpenalty\eq@addpunct \penalty\intermath@penalty \dquad \@ignoretrue}%
340 \ignorespaces
341 }

```

7.18 latex-localise-commands-xepersian.def

```

342 \ProvidesFile{latex-localise-commands-xepersian.def}[2014/02/05 v0.3 Persian localisation of LaTeX]
343 \eqcommand{ }{@arstrut}
344 \eqcommand{ }{above}
345 \eqcommand{ }{abovedisplayshortskip}
346 \eqcommand{ }{abovedisplayskip}
347 \eqcommand{ }{abstractname}
348 \eqcommand{ }{accent}
349 \eqcommand{ }{active}
350 \eqcommand{ }{addcontentsline}
351 \eqcommand{ }{addpenalty}
352 \eqcommand{ }{address}
353 \eqcommand{ }{addtocontents}
354 \eqcommand{ }{addtocounter}
355 \eqcommand{ }{addtolength}
356 \eqcommand{ }{addvspace}
357 \eqcommand{ }{adjdemerits}

```




```

358 \eqcommand{      }{advance}
359 \eqcommand{      }{afterassignment}
360 \eqcommand{      }{aftergroup}
361 \eqcommand{ }{aleph}
362 \eqcommand{      }{aliasfontfeature}
363 \eqcommand{      }{aliasfontfeatureoption}
364 \eqcommand{      }{allowbreak}
365 \eqcommand{ @}{alloc@}
366 \eqcommand{      }{allocationnumber}
367 \eqcommand{      }{allowdisplaybreaks}
368 \eqcommand{      }{Alph}
369 \eqcommand{      }{alph}
370 \eqcommand{      }{alsoname}
371 \eqcommand{ }{and}
372 \eqcommand{      }{angle}
373 \eqcommand{      }{appendixname}
374 \eqcommand{      }{approx}
375 \eqcommand{      }{arabic}
376 \eqcommand{ }{arg}
377 \eqcommand{      }{arrayrulecolor}
378 \eqcommand{      }{arraycolsep}
379 \eqcommand{      }{arrayrulewidth}
380 \eqcommand{      }{arraystretch}
381 \eqcommand{      }{AtBeginDocument}
382 \eqcommand{      }{AtEndDocument}
383 \eqcommand{      }{AtEndOfClass}
384 \eqcommand{      }{AtEndOfPackage}
385 \eqcommand{      }{author}
386 \eqcommand{      }{backmatter}
387 \eqcommand{      }{backslash}
388 \eqcommand{      }{badness}
389 \eqcommand{ }{bar}
390 \eqcommand{      }{baselineskip}
391 \eqcommand{      }{baselinestretch}
392 \eqcommand{      }{batchmode}
393 \eqcommand{ }{begin}
394 \eqcommand{      }{beginL}
395 \eqcommand{      }{beginR}
396 \eqcommand{      }{begingroup}
397 \eqcommand{      }{belowdisplayshortskip}
398 \eqcommand{      }{belowdisplayskip}
399 \eqcommand{ }{bf}
400 \eqcommand{      }{bfdefault}
401 \eqcommand{      }{bfseries}
402 \eqcommand{      }{bgroup}
403 \eqcommand{ }{bibitem}
404 \eqcommand{      }{bibliography}
405 \eqcommand{      }{bibliographystyle}
406 \eqcommand{      }{bibname}
407 \eqcommand{      }{bigskip}

```



```

408 \eqcommand{      }{bigskipamount}
409 \eqcommand{      }{botfigrule}
410 \eqcommand{      }{botmark}
411 \eqcommand{      }{bottompageskip}
412 \eqcommand{      }{bottomfraction}
413 \eqcommand{ }{box}
414 \eqcommand{      }{boxmaxdepth}
415 \eqcommand{ }{break}
416 \eqcommand{ }{bullet}
417 \eqcommand{ @ }{@cclv}
418 \eqcommand{ @ }{@cclvi}
419 \eqcommand{ }{caption}
420 \eqcommand{ }{catcode}
421 \eqcommand{ }{cc}
422 \eqcommand{      }{ccname}
423 \eqcommand{      }{cdot}
424 \eqcommand{      }{cdots}
425 \eqcommand{      }{centering}
426 \eqcommand{ }{centerline}
427 \eqcommand{ @ }{ch@ck}
428 \eqcommand{ }{chapter}
429 \eqcommand{      }{chaptername}
430 \eqcommand{ }{char}
431 \eqcommand{      }{chardef}
432 \eqcommand{      }{CheckCommand}
433 \eqcommand{ }{cite}
434 \eqcommand{      }{ClassError}
435 \eqcommand{      }{ClassInfo}
436 \eqcommand{      }{ClassWarning}
437 \eqcommand{      }{ClassWarningNoLine}
438 \eqcommand{      }{cleaders}
439 \eqcommand{      }{cleardoublepage}
440 \eqcommand{      }{clearpage}
441 \eqcommand{ }{cline}
442 \eqcommand{      }{closein}
443 \eqcommand{      }{closeout}
444 \eqcommand{ }{closing}
445 \eqcommand{      }{clubpenalty}
446 \eqcommand{ }{clubsuit}
447 \eqcommand{      }{colbotmark}
448 \eqcommand{      }{colfirstmark}
449 \eqcommand{ }{color}
450 \eqcommand{      }{colorbox}
451 \eqcommand{      }{coltopmark}
452 \eqcommand{      }{columncolor}
453 \eqcommand{      }{columnsep}
454 \eqcommand{      }{columnwidth}
455 \eqcommand{      }{columnseprule}
456 \eqcommand{      }{contentsline}
457 \eqcommand{      }{contentsname}

```



```

458 \eqcommand{ }{copy}
459 \eqcommand{ }{copyright}
460 \eqcommand{ }{count}
461 \eqcommand{ @}{count@}
462 \eqcommand{ }{countdef}
463 \eqcommand{ }{cr}
464 \eqcommand{ }{crr}
465 \eqcommand{ }{csname}
466 \eqcommand{ }{CurrentOption}
467 \eqcommand{ }{dashbox}
468 \eqcommand{ }{dashv}
469 \eqcommand{@ }{date}
470 \eqcommand{ }{date}
471 \eqcommand{ }{day}
472 \eqcommand{ }{dblbotfigrule}
473 \eqcommand{ }{dblbottomfraction}
474 \eqcommand{ }{dblfigrule}
475 \eqcommand{ }{dblfloatpagefraction}
476 \eqcommand{ }{dblfloatsep}
477 \eqcommand{ }{dblftntlocatecode}
478 \eqcommand{ }{dbltextfloatsep}
479 \eqcommand{ }{dbltopfraction}
480 \eqcommand{ }{DeclareFixedFont}
481 \eqcommand{ }{DeclareGraphicsExtensions}
482 \eqcommand{ }{DeclareGraphicsRule}
483 \eqcommand{ }{DeclareOldFontCommand}
484 \eqcommand{ }{DeclareOption}
485 \eqcommand{ }{DeclareRobustCommand}
486 \eqcommand{ }{DeclareSymbolFont}
487 \eqcommand{ }{deadcycles}
488 \eqcommand{ }{def}
489 \eqcommand{ @ }{define@key}
490 \eqcommand{ }{definecolor}
491 \eqcommand{ }{deg}
492 \eqcommand{ }{delcode}
493 \eqcommand{ }{delimiter}
494 \eqcommand{ }{delimiterfactor}
495 \eqcommand{ }{depth}
496 \eqcommand{ }{diamondsuit}
497 \eqcommand{ }{dim}
498 \eqcommand{ }{dimen}
499 \eqcommand{ @}{dimen@}
500 \eqcommand{ @ }{dimen@i}
501 \eqcommand{ @ }{dimen@ii}
502 \eqcommand{ }{dimendef}
503 \eqcommand{ }{discretionary}
504 \eqcommand{ }{displaybreak}
505 \eqcommand{ }{displayindent}
506 \eqcommand{ }{displaystyle}
507 \eqcommand{ }{displaywidth}

```



```

508 \eqcommand{ }{divide}
509 \eqcommand{ }{documentclass}
510 \eqcommand{ }{do}
511 \eqcommand{ }{dospecials}
512 \eqcommand{ }{dot}
513 \eqcommand{ }{doteq}
514 \eqcommand{ }{dotfill}
515 \eqcommand{ }{dots}
516 \eqcommand{ }{doublebox}
517 \eqcommand{ }{doublerulesepcolor}
518 \eqcommand{ }{doublerulesep}
519 \eqcommand{ }{downarrow}
520 \eqcommand{ }{dp}
521 \eqcommand{ }{dump}
522 \eqcommand{ }{edef}
523 \eqcommand{ }{egroup}
524 \eqcommand{ }{eject}
525 \eqcommand{ }{else}
526 \eqcommand{ }{em}
527 \eqcommand{ }{emergencystretch}
528 \eqcommand{ }{emph}
529 \eqcommand{@ }{@empty}
530 \eqcommand{ }{empty}
531 \eqcommand{ }{emptyset}
532 \eqcommand{ }{end}
533 \eqcommand{ }{endL}
534 \eqcommand{ }{endR}
535 \eqcommand{ }{endcsname}
536 \eqcommand{ }{endfirsthead}
537 \eqcommand{ }{endfoot}
538 \eqcommand{ }{endgraf}
539 \eqcommand{ }{endgroup}
540 \eqcommand{ }{endhead}
541 \eqcommand{ }{endinput}
542 \eqcommand{ }{endlastfoot}
543 \eqcommand{ }{enlargethispage}
544 \eqcommand{ }{endline}
545 \eqcommand{ }{endlinechar}
546 \eqcommand{ }{enspace}
547 \eqcommand{ }{enskip}
548 \eqcommand{ }{eqcommand}
549 \eqcommand{ }{eqenvironment}
550 \eqcommand{ }{eqref}
551 \eqcommand{ }{errhelp}
552 \eqcommand{ }{errmessage}
553 \eqcommand{ }{errorcontextlines}
554 \eqcommand{ }{errorstopmode}
555 \eqcommand{ }{escapechar}
556 \eqcommand{ }{euro}
557 \eqcommand{ }{evensidemargin}

```



```

558 \eqcommand{ }{everycr}
559 \eqcommand{ }{everydisplay}
560 \eqcommand{ }{everyhbox}
561 \eqcommand{ }{everyjob}
562 \eqcommand{ }{everymath}
563 \eqcommand{ }{everypar}
564 \eqcommand{ }{everyvbox}
565 \eqcommand{ }{ExecuteOptions}
566 \eqcommand{ }{exhyphenpenalty}
567 \eqcommand{ }{expandafter}
568 \eqcommand{ }{extracolsep}
569 \eqcommand{@ }{@firstofone}
570 \eqcommand{@ }{@firstoftwo}
571 \eqcommand{ @ }{f@ur}
572 \eqcommand{ }{fam}
573 \eqcommand{ }{fancypage}
574 \eqcommand{ }{fbox}
575 \eqcommand{ }{fboxrule}
576 \eqcommand{ }{fboxsep}
577 \eqcommand{ }{fcolorbox}
578 \eqcommand{ }{fi}
579 \eqcommand{ }{figurename}
580 \eqcommand{ }{filbreak}
581 \eqcommand{ }{fill}
582 \eqcommand{ }{firstmark}
583 \eqcommand{ }{flat}
584 \eqcommand{ }{floatpagefraction}
585 \eqcommand{ }{floatingpenalty}
586 \eqcommand{ }{floatsep}
587 \eqcommand{ }{flushbottom}
588 \eqcommand{ }{fmtname}
589 \eqcommand{ }{fmtversion}
590 \eqcommand{ }{fnsymbol}
591 \eqcommand{ }{font}
592 \eqcommand{ }{fontdimen}
593 \eqcommand{ }{fontencoding}
594 \eqcommand{ }{fontfamily}
595 \eqcommand{ }{fontname}
596 \eqcommand{ }{fontseries}
597 \eqcommand{ }{fontshape}
598 \eqcommand{ }{fontsize}
599 \eqcommand{ }{footheight}
600 \eqcommand{ }{footins}
601 \eqcommand{ }{footnote}
602 \eqcommand{ }{footnotemark}
603 \eqcommand{ }{footnoterule}
604 \eqcommand{ }{footnotesep}
605 \eqcommand{ }{footnotesize}
606 \eqcommand{ }{footnotetext}
607 \eqcommand{ }{footskip}

```



```

608 \eqcommand{ }{frame}
609 \eqcommand{ }{framebox}
610 \eqcommand{ }{frenchspacing}
611 \eqcommand{ }{frontmatter}
612 \eqcommand{ }{futurelet}
613 \eqcommand{@ }{@gobble}
614 \eqcommand{@ }{@gobbletwo}
615 \eqcommand{@ }{@gobblefour}
616 \eqcommand{@ }{@gtempa}
617 \eqcommand{@ }{@gtempb}
618 \eqcommand{ }{gdef}
619 \eqcommand{ }{GenericInfo}
620 \eqcommand{ }{GenericWarning}
621 \eqcommand{ }{GenericError}
622 \eqcommand{ }{global}
623 \eqcommand{ }{globaldefs}
624 \eqcommand{ }{glossary}
625 \eqcommand{ }{glossaryentry}
626 \eqcommand{ }{goodbreak}
627 \eqcommand{ }{graphpaper}
628 \eqcommand{ }{guillemotleft}
629 \eqcommand{ }{guillemotright}
630 \eqcommand{ }{guilsinglleft}
631 \eqcommand{ }{guilsinglright}
632 \eqcommand{ }{halign}
633 \eqcommand{ }{hang}
634 \eqcommand{ }{hangafter}
635 \eqcommand{ }{hangindent}
636 \eqcommand{ }{hbadness}
637 \eqcommand{ }{hbox}
638 \eqcommand{ }{headheight}
639 \eqcommand{ }{headsep}
640 \eqcommand{ }{headtoname}
641 \eqcommand{ }{heartsuit}
642 \eqcommand{ }{height}
643 \eqcommand{ }{hfil}
644 \eqcommand{ }{hfill}
645 \eqcommand{ }{hfilneg}
646 \eqcommand{ }{hfuzz}
647 \eqcommand{ }{hideskip}
648 \eqcommand{ }{hidewidth}
649 \bidi@csletcs{ }{hline}% this is an exception
650 \eqcommand{ }{hoffset}
651 \eqcommand{ }{holdinginserts}
652 \eqcommand{ }{hrboxsep}
653 \eqcommand{ }{hrule}
654 \eqcommand{ }{hrulefill}
655 \eqcommand{ }{hsize}
656 \eqcommand{ }{hskip}
657 \eqcommand{ }{hspace}

```



```

658 \eqcommand{ }{hss}
659 \eqcommand{ }{ht}
660 \eqcommand{ }{huge}
661 \eqcommand{ }{Huge}
662 \eqcommand{ }{hyperlink}
663 \eqcommand{ }{hypersetup}
664 \eqcommand{ }{hypertarget}
665 \eqcommand{ }{hyphenation}
666 \eqcommand{ }{hyphenchar}
667 \eqcommand{ }{hyphenpenalty}
668 \eqcommand{@ }{@ifclassloaded}
669 \eqcommand{@ }{@ifdefinable}
670 \eqcommand{@ }{@ifnextchar}
671 \eqcommand{@ }{@ifpackageloaded}
672 \eqcommand{@ }{@ifstar}
673 \eqcommand{@ }{@ifundefined}
674 \eqcommand{ }{if}
675 \eqcommand{ @ }{if@tempswa}
676 \eqcommand{ }{ifcase}
677 \eqcommand{ }{ifcat}
678 \eqcommand{ }{ifdefined}
679 \eqcommand{ }{ifdim}
680 \eqcommand{ }{ifeof}
681 \eqcommand{ }{iff}
682 \eqcommand{ }{iffalse}
683 \eqcommand{ }{IfFileExists}
684 \eqcommand{ }{ifhbox}
685 \eqcommand{ }{ifhmode}
686 \eqcommand{ }{ifinner}
687 \eqcommand{ }{ifmmode}
688 \eqcommand{ }{ifnum}
689 \eqcommand{ }{ifodd}
690 \eqcommand{ }{ifthenelse}
691 \eqcommand{ }{iftrue}
692 \eqcommand{ }{ifvbox}
693 \eqcommand{ }{ifvmode}
694 \eqcommand{ }{ifvoid}
695 \eqcommand{ }{ifx}
696 \eqcommand{ }{ignorespaces}
697 \eqcommand{ }{immediate}
698 \eqcommand{ }{include}
699 \eqcommand{ }{includegraphics}
700 \eqcommand{ }{includeonly}
701 \eqcommand{ }{indent}
702 \eqcommand{ }{index}
703 \eqcommand{ }{indexentry}
704 \eqcommand{ }{indexname}
705 \eqcommand{ }{indexspace}
706 \eqcommand{ }{input}
707 \eqcommand{ }{InputIfFileExists}

```



```

708 \eqcommand{      }\{inputlineno\}
709 \eqcommand{      }\{insert\}
710 \eqcommand{      }\{insertpenalties\}
711 \eqcommand{      }\{interfootnotelinepenalty\}
712 \eqcommand{      }\{interdisplaylinepenalty\}
713 \eqcommand{      }\{interlinepenalty\}
714 \eqcommand{      }\{intertext\}
715 \eqcommand{      }\{intertextsep\}
716 \eqcommand{      }\{invisible\}
717 \eqcommand{      }\{itdefault\}
718 \eqcommand{      }\{itshape\}
719 \eqcommand{      }\{item\}
720 \eqcommand{      }\{itemindent\}
721 \eqcommand{      }\{itemsep\}
722 \eqcommand{      }\{iterate\}
723 \eqcommand{      }\{itshape\}
724 \eqcommand{      }\{jobname\}
725 \eqcommand{      }\{jot\}
726 \eqcommand{      }\{kern\}
727 \eqcommand{      }\{kill\}
728 \eqcommand{      }\{label\}
729 \eqcommand{      }\{labelenumi\}
730 \eqcommand{      }\{labelenumii\}
731 \eqcommand{      }\{labelenumiii\}
732 \eqcommand{      }\{labelenumiv\}
733 \eqcommand{      }\{labelitemi\}
734 \eqcommand{      }\{labelitemii\}
735 \eqcommand{      }\{labelitemiii\}
736 \eqcommand{      }\{labelitemiv\}
737 \eqcommand{      }\{labelsep\}
738 \eqcommand{      }\{labelwidth\}
739 \eqcommand{      }\{language\}
740 \eqcommand{      }\{large\}
741 \eqcommand{      }\{Large\}
742 \eqcommand{      }\{LARGE\}
743 \eqcommand{      }\{lastbox\}
744 \eqcommand{      }\{lastkern\}
745 \eqcommand{      }\{lastpenalty\}
746 \eqcommand{      }\{lastskip\}
747 \eqcommand{      }\{LaTeX\}
748 \eqcommand{      }\{LaTeXe\}
749 \eqcommand{      }\{lccode\}
750 \eqcommand{      }\{ldots\}
751 \eqcommand{      }\{leaders\}
752 \eqcommand{      }\{leavevmode\}
753 \eqcommand{      }\{left\}
754 \eqcommand{      }\{leftmargin\}
755 \eqcommand{      }\{leftmargini\}
756 \eqcommand{      }\{leftmarginii\}
757 \eqcommand{      }\{leftmarginiii\}

```




```

758 \eqcommand{      }{\leftmarginiv}
759 \eqcommand{      }{\leftmarginv}
760 \eqcommand{      }{\leftmarginvi}
761 \eqcommand{      }{\leftmark}
762 \eqcommand{      }{\leftpageskip}
763 \eqcommand{      }{\leftskip}
764 \eqcommand{ }{\let}
765 \eqcommand{ }{\line}
766 \eqcommand{ }{\linebreak}
767 \eqcommand{ }{\linepenalty}
768 \eqcommand{ }{\lineskip}
769 \eqcommand{ }{\lineskiplimit}
770 \eqcommand{ }{\linespread}
771 \eqcommand{ }{\linethickness}
772 \eqcommand{ }{\linewidth}
773 \eqcommand{ }{\listfigurename}
774 \eqcommand{ }{\listfiles}
775 \eqcommand{ }{\listoffigures}
776 \eqcommand{ }{\listoftables}
777 \eqcommand{ }{\listparindent}
778 \eqcommand{ }{\listtablename}
779 \eqcommand{ }{\LoadClass}
780 \eqcommand{ }{\LoadClassWithOptions}
781 \eqcommand{ }{\location}
782 \eqcommand{ }{\long}
783 \eqcommand{ }{\looseness}
784 \eqcommand{ }{\lower}
785 \eqcommand{@ }{@makeother}
786 \eqcommand{@ }{@m}
787 \eqcommand{ @ }{@M}
788 \eqcommand{ @ }{@Mi}
789 \eqcommand{ @ }{@Mii}
790 \eqcommand{ @ }{@Miii}
791 \eqcommand{ @ }{@Miv}
792 \eqcommand{ @ }{@MM}
793 \eqcommand{ @ }{@m@ne}
794 \eqcommand{ }{\mag}
795 \eqcommand{ }{\magstep}
796 \eqcommand{ }{\magstephalf}
797 \eqcommand{ }{\mainmatter}
798 \eqcommand{ }{\makeatletter}
799 \eqcommand{ }{\makeatother}
800 \eqcommand{ }{\makebox}
801 \eqcommand{ }{\makeglossary}
802 \eqcommand{ }{\makeindex}
803 \eqcommand{ }{\makelabel}
804 \eqcommand{ }{\makelabels}
805 \eqcommand{ }{\MakeLowercase}
806 \eqcommand{ }{\maketitle}
807 \eqcommand{ }{\MakeUppercase}

```



```

808 \eqcommand{ }{marginpar}
809 \eqcommand{ }{marginparpush}
810 \eqcommand{ }{marginparsep}
811 \eqcommand{ }{marginparwidth}
812 \eqcommand{ }{mark}
813 \eqcommand{ }{markboth}
814 \eqcommand{ }{markright}
815 \eqcommand{ }{mathaccent}
816 \eqcommand{ }{mathchar}
817 \eqcommand{ }{mathchardef}
818 \eqcommand{ }{mathcode}
819 \eqcommand{ }{mathrm}
820 \eqcommand{ }{maxdeadcycles}
821 \eqcommand{ }{maxdepth}
822 \eqcommand{ }{maxdimen}
823 \eqcommand{ }{mbox}
824 \eqcommand{ }{mdseries}
825 \eqcommand{ }{meaning}
826 \eqcommand{ }{mediumseries}
827 \eqcommand{ }{medmuskip}
828 \eqcommand{ }{medskip}
829 \eqcommand{ }{medskipamount}
830 \eqcommand{ }{medspace}
831 \eqcommand{ }{message}
832 \eqcommand{ }{MessageBreak}
833 \eqcommand{ }{minrowclearance}
834 \eqcommand{ }{mkern}
835 \eqcommand{ }{month}
836 \eqcommand{ }{moveleft}
837 \eqcommand{ }{moveright}
838 \eqcommand{ }{mskip}
839 \eqcommand{ @ }{m@th}
840 \eqcommand{ }{multicolumn}
841 \eqcommand{ }{multiply}
842 \eqcommand{ }{multispan}
843 \eqcommand{ }{muskip}
844 \eqcommand{ }{muskipdef}
845 \eqcommand{@ }{@namedef}
846 \eqcommand{@ }{@nameuse}
847 \eqcommand{ @ }{@ne}
848 \eqcommand{ }{name}
849 \eqcommand{ }{natural}
850 \eqcommand{ }{nearrow}
851 \eqcommand{ }{nearrower}
852 \eqcommand{ }{NeedsTeXFormat}
853 \eqcommand{ }{neg}
854 \eqcommand{ }{negmedspace}
855 \eqcommand{ }{negthickspace}
856 \eqcommand{ }{negthinspace}
857 \eqcommand{ }{newboolean}

```



```

858 \eqcommand{    }\{newbox}
859 \eqcommand{    }\{newcommand}
860 \eqcommand{    }\{newcount}
861 \eqcommand{    }\{newcounter}
862 \eqcommand{    }\{newdimen}
863 \eqcommand{    }\{newenvironment}
864 \eqcommand{    }\{newfam}
865 \eqcommand{    }\{newfont}
866 \eqcommand{    }\{newhelp}
867 \eqcommand{    }\{newinsert}
868 \eqcommand{    }\{newlabel}
869 \eqcommand{    }\{newlength}
870 \eqcommand{    }\{newline}
871 \eqcommand{    }\{newlinechar}
872 \eqcommand{    }\{newmuskip}
873 \eqcommand{    }\{newpage}
874 \eqcommand{    }\{newread}
875 \eqcommand{    }\{newsavebox}
876 \eqcommand{    }\{newskip}
877 \eqcommand{    }\{newtheorem}
878 \eqcommand{    }\{newtoks}
879 \eqcommand{    }\{newwrite}
880 \eqcommand{    }\{noalign}
881 \eqcommand{    }\{nobreak}
882 \eqcommand{    }\{nobreakspace}
883 \eqcommand{    }\{nocite}
884 \eqcommand{    }\{noexpand}
885 \eqcommand{    }\{nofiles}
886 \eqcommand{    }\{noindent}
887 \eqcommand{    }\{nointerlineskip}
888 \eqcommand{    }\{nolimits}
889 \eqcommand{    }\{nolinebreak}
890 \eqcommand{    }\{nonstopmode}
891 \eqcommand{    }\{nonfrenchspacing}
892 \eqcommand{    }\{nonumber}
893 \eqcommand{    }\{nopagebreak}
894 \eqcommand{    }\{normalbaselines}
895 \eqcommand{    }\{normalbaselineskip}
896 \eqcommand{    }\{normalcolor}
897 \eqcommand{    }\{normalfont}
898 \eqcommand{    }\{normallineskip}
899 \eqcommand{    }\{normallineskiplimit}
900 \eqcommand{    }\{normalmarginpar}
901 \eqcommand{    }\{normalsize}
902 \eqcommand{    }\{notag}
903 \eqcommand{    }\{null}
904 \eqcommand{    }\{nullfont}
905 \eqcommand{    }\{number}
906 \eqcommand{    }\{numberline}
907 \eqcommand{    }\{numberwithin}

```



```

908 \eqcommand{      }{@evenfoot}
909 \eqcommand{      }{@evenhead}
910 \eqcommand{      }{@oddfoot}
911 \eqcommand{      }{@oddhead}
912 \eqcommand{      }{@outeqntrue}
913 \eqcommand{      }{@outeqnfalse}
914 \eqcommand{      }{obeylines}
915 \eqcommand{      }{obeyspaces}
916 \eqcommand{      }{oddsidemargin}
917 \eqcommand{      }{offinterlineskip}
918 \eqcommand{ }{omit}
919 \eqcommand{@      }{@onlypreamble}
920 \eqcommand{      }{onecolumn}
921 \eqcommand{      }{onlynotes}
922 \eqcommand{      }{onlyslides}
923 \eqcommand{      }{openin}
924 \eqcommand{      }{openout}
925 \eqcommand{      }{OptionNotUsed}
926 \eqcommand{ }{or}
927 \eqcommand{      }{outer}
928 \eqcommand{      }{output}
929 \eqcommand{      }{outputpenalty}
930 \eqcommand{      }{overfullrule}
931 \eqcommand{@      }{@preamblecmds}
932 \eqcommand{@ }{p@}
933 \eqcommand{      }{PackageError}
934 \eqcommand{      }{PackageInfo}
935 \eqcommand{      }{PackageWarning}
936 \eqcommand{      }{PackageWarningNoLine}
937 \eqcommand{      }{pagebreak}
938 \eqcommand{      }{pagecolor}
939 \eqcommand{      }{pagedepth}
940 \eqcommand{      }{pagefilllstretch}
941 \eqcommand{      }{pagefillstretch}
942 \eqcommand{      }{pagefilstretch}
943 \eqcommand{      }{pagegoal}
944 \eqcommand{      }{pagename}
945 \eqcommand{      }{pagenumbering}
946 \eqcommand{      }{pageref}
947 \eqcommand{      }{pagerulewidth}
948 \eqcommand{      }{pageshrink}
949 \eqcommand{      }{pagestretch}
950 \eqcommand{      }{pagestyle}
951 \eqcommand{      }{pagetotal}
952 \eqcommand{      }{paperheight}
953 \eqcommand{      }{paperwidth}
954 \bidi@csdefcs{ }{par}% this is an exception since \par is redefined only in some circumstances
955 \eqcommand{      }{paragraph}
956 \eqcommand{      }{parallel}
957 \eqcommand{      }{parbox}

```



```

958 \eqcommand{      }{parfillskip}
959 \eqcommand{      }{parindent}
960 \eqcommand{      }{parsep}
961 \eqcommand{      }{parshape}
962 \eqcommand{      }{parskip}
963 \eqcommand{ }{part}
964 \eqcommand{      }{partname}
965 \eqcommand{      }{partopsep}
966 \eqcommand{      }{PassOptionToClass}
967 \eqcommand{      }{PassOptionToPackage}
968 \eqcommand{ }{path}
969 \eqcommand{      }{patterns}
970 \eqcommand{ }{pausing}
971 \eqcommand{      }{penalty}
972 \eqcommand{ }{phantom}
973 \eqcommand{      }{poptabs}
974 \eqcommand{      }{postdisplaypenalty}
975 \eqcommand{      }{predisplaydirection}
976 \eqcommand{      }{predisdisplaypenalty}
977 \eqcommand{      }{predisplaysize}
978 \eqcommand{      }{pretolerance}
979 \eqcommand{      }{prevdepth}
980 \eqcommand{      }{prevgraf}
981 \eqcommand{      }{printindex}
982 \eqcommand{      }{ProcessOptions}
983 \eqcommand{ }{protect}
984 \eqcommand{      }{providecommand}
985 \eqcommand{      }{ProvidesClass}
986 \eqcommand{      }{ProvidesFile}
987 \eqcommand{      }{ProvidesPackage}
988 \eqcommand{      }{pushtabs}
989 \eqcommand{ }{quad}
990 \eqcommand{      }{qqquad}
991 \eqcommand{@      }{@outputpagerestore}
992 \eqcommand{      }{radical}
993 \eqcommand{      }{raggedbottom}
994 \eqcommand{      }{raggedleft}
995 \eqcommand{      }{raggedright}
996 \eqcommand{      }{raise}
997 \eqcommand{      }{raisebox}
998 \eqcommand{      }{raisetag}
999 \eqcommand{      }{rangle}
1000 \eqcommand{ }{rceil}
1001 \eqcommand{      }{read}
1002 \eqcommand{ }{ref}
1003 \eqcommand{      }{reflectbox}
1004 \eqcommand{      }{refname}
1005 \eqcommand{      }{refstepcounter}
1006 \eqcommand{ }{relax}
1007 \eqcommand{      }{removelastskip}

```



```

1008 \eqcommand{      }\{renewcommand\}
1009 \eqcommand{      }\{renewenvironment\}
1010 \eqcommand{      }\{RequirePackage\}
1011 \eqcommand{      }\{RequirePackageWithOptions\}
1012 \eqcommand{      }\{resizebox\}
1013 \eqcommand{      }\{reversemarginpar\}
1014 \eqcommand{      }\{rffloor\}
1015 \eqcommand{      }\{right\}
1016 \eqcommand{      }\{rightmargin\}
1017 \eqcommand{      }\{rightmark\}
1018 \eqcommand{      }\{rightpageskip\}
1019 \eqcommand{      }\{rightskip\}
1020 \eqcommand{      }\{rmdefault\}
1021 \eqcommand{      }\{rmfamily\}
1022 \eqcommand{      }\{Roman\}
1023 \eqcommand{      }\{roman\}
1024 \eqcommand{      }\{romannumeral\}
1025 \eqcommand{      }\{rotatebox\}
1026 \eqcommand{      }\{rowcolor\}
1027 \eqcommand{      }\{rule\}
1028 \eqcommand{@      }\{@secondoftwo\}
1029 \eqcommand{@      }\{@spaces\}
1030 \eqcommand{      }\{samepage\}
1031 \eqcommand{      }\{savebox\}
1032 \eqcommand{      }\{sbox\}
1033 \eqcommand{      }\{scalebox\}
1034 \eqcommand{      }\{scdefault\}
1035 \eqcommand{      }\{scshape\}
1036 \eqcommand{      }\{setkeys\}
1037 \eqcommand{      }\{scriptfont\}
1038 \eqcommand{      }\{scriptscriptfont\}
1039 \eqcommand{      }\{scriptscriptstyle\}
1040 \eqcommand{      }\{scriptsize\}
1041 \eqcommand{      }\{scripstyle\}
1042 \eqcommand{      }\{scrollmode\}
1043 \eqcommand{      }\{section\}
1044 \eqcommand{      }\{secdef\}
1045 \eqcommand{      }\{see\}
1046 \eqcommand{      }\{seealso\}
1047 \eqcommand{      }\{seename\}
1048 \eqcommand{      }\{selectfont\}
1049 \eqcommand{      }\{setboolean\}
1050 \eqcommand{      }\{setbox\}
1051 \eqcommand{      }\{setcounter\}
1052 \eqcommand{      }\{setlength\}
1053 \eqcommand{      }\{setminus\}
1054 \eqcommand{      }\{SetSymbolFont\}
1055 \eqcommand{      }\{settodepth\}
1056 \eqcommand{      }\{settoheight\}
1057 \eqcommand{      }\{settowidth\}

```



```

1058 \eqcommand{      }{sfcode}
1059 \eqcommand{      }{sfdefault}
1060 \eqcommand{      }{sffamily}
1061 \eqcommand{      }{shadowbox}
1062 \eqcommand{ }{sharp}
1063 \eqcommand{ }{shipout}
1064 \eqcommand{ }{shortstack}
1065 \eqcommand{ }{show}
1066 \eqcommand{ }{showbox}
1067 \eqcommand{ }{showboxbreadth}
1068 \eqcommand{ }{showboxdepth}
1069 \eqcommand{ }{showlists}
1070 \eqcommand{ }{showthe}
1071 \eqcommand{ }{simplefontmode}
1072 \eqcommand{ @}{sist@n}
1073 \eqcommand{ }{skewchar}
1074 \eqcommand{ }{skip}
1075 \eqcommand{ @}{skip@}
1076 \eqcommand{ }{skipdef}
1077 \eqcommand{ }{sl}
1078 \eqcommand{ }{sldefault}
1079 \eqcommand{ }{slshape}
1080 \eqcommand{ }{sloppy}
1081 \eqcommand{ }{slshape}
1082 \eqcommand{ }{small}
1083 \eqcommand{ }{smallskip}
1084 \eqcommand{ }{smallskipamount}
1085 \eqcommand{ }{smash}
1086 \eqcommand{ }{smile}
1087 \eqcommand{ }{snglftlocatcode}
1088 \eqcommand{ }{space}
1089 \eqcommand{ }{spacefactor}
1090 \eqcommand{ }{spaceskip}
1091 \eqcommand{ }{spadesuit}
1092 \eqcommand{ }{span}
1093 \eqcommand{ }{special}
1094 \eqcommand{ }{splitmaxdepth}
1095 \eqcommand{ }{splittopskip}
1096 \eqcommand{ }{star}
1097 \eqcommand{ }{stepcounter}
1098 \eqcommand{ }{stretch}
1099 \eqcommand{ }{string}
1100 \eqcommand{ }{strut}
1101 \eqcommand{ }{strutbox}
1102 \eqcommand{ }{subitem}
1103 \eqcommand{ }{subparagraph}
1104 \eqcommand{ }{subsection}
1105 \eqcommand{ }{substack}
1106 \eqcommand{ }{subsubitem}
1107 \eqcommand{ }{subsubsection}

```



```

1108 \eqcommand{    }\{subset}
1109 \eqcommand{    }\{subseteq}
1110 \eqcommand{    }\{supereject}
1111 \eqcommand{    }\{suppressfloats}
1112 \eqcommand{@    }\{@tempa}
1113 \eqcommand{@    }\{@tempb}
1114 \eqcommand{@    }\{@tempc}
1115 \eqcommand{@    }\{@tempd}
1116 \eqcommand{@    }\{@tempe}
1117 \eqcommand{@    }\{@tempboxa}
1118 \eqcommand{@    }\{@tempcnta}
1119 \eqcommand{@    }\{@tempcntb}
1120 \eqcommand{@    }\{@tempdima}
1121 \eqcommand{@    }\{@tempdimb}
1122 \eqcommand{@    }\{@tempdimc}
1123 \eqcommand{@    }\{@tempskipa}
1124 \eqcommand{@    }\{@tempskipb}
1125 \eqcommand{@    }\{@tempswafalse}
1126 \eqcommand{@    }\{@tempswatru}
1127 \eqcommand{@    }\{@temptokena}
1128 \eqcommand{    }\{@thefnmark}
1129 \eqcommand{@    }\{@thirdofthree}
1130 \eqcommand{    }\{tabbingsep}
1131 \eqcommand{    }\{tabcolsep}
1132 \eqcommand{    }\{tableofcontents}
1133 \eqcommand{    }\{tablename}
1134 \eqcommand{    }\{tabskip}
1135 \eqcommand{    }\{tabularnewline}
1136 \eqcommand{    }\{tag}
1137 \eqcommand{    }\{telephone}
1138 \eqcommand{    }\{TeX}
1139 \eqcommand{    }\{text}
1140 \eqcommand{    }\{textbullet}
1141 \eqcommand{    }\{textfont}
1142 \eqcommand{    }\{textemdash}
1143 \eqcommand{    }\{textendash}
1144 \eqcommand{    }\{textexclamdown}
1145 \eqcommand{    }\{textperiodcentered}
1146 \eqcommand{    }\{textquestiondown}
1147 \eqcommand{    }\{textquotedblleft}
1148 \eqcommand{    }\{textquotedblright}
1149 \eqcommand{    }\{textquoteleft}
1150 \eqcommand{    }\{textquoteright}
1151 \eqcommand{    }\{textvisiblespace}
1152 \eqcommand{    }\{textbackslash}
1153 \eqcommand{    }\{textbar}
1154 \eqcommand{    }\{textgreater}
1155 \eqcommand{    }\{textless}
1156 \eqcommand{    }\{textbf}
1157 \eqcommand{    }\{textcircled}

```




```

1158 \eqcommand{ }{textcolor}
1159 \eqcommand{ }{textcompwordmark}
1160 \eqcommand{ }{textfloatsep}
1161 \eqcommand{ }{textfraction}
1162 \eqcommand{ }{textheight}
1163 \eqcommand{ }{textindent}
1164 \eqcommand{ }{textit}
1165 \eqcommand{ }{textmd}
1166 \eqcommand{ }{textnormal}
1167 \eqcommand{ }{textregistered}
1168 \eqcommand{ }{textrm}
1169 \eqcommand{ }{textsc}
1170 \eqcommand{ }{textsf}
1171 \eqcommand{ }{textsl}
1172 \eqcommand{ }{textstyle}
1173 \eqcommand{ }{textsuperscript}
1174 \eqcommand{ }{texttrademark}
1175 \eqcommand{ }{texttt}
1176 \eqcommand{ }{textup}
1177 \eqcommand{ }{textwidth}
1178 \eqcommand{ }{thanks}
1179 \eqcommand{ }{the}
1180 \eqcommand{ }{thempfn}
1181 \eqcommand{ }{thicklines}
1182 \eqcommand{ }{thickmuskip}
1183 \eqcommand{ }{thinmuskip}
1184 \eqcommand{ }{thickspace}
1185 \eqcommand{ }{thinline}
1186 \eqcommand{ }{thinspace}
1187 \eqcommand{ }{thisfancy}
1188 \eqcommand{ }{thispagestyle}
1189 \eqcommand{ @ }{thr@@}
1190 \eqcommand{ }{tilde}
1191 \eqcommand{ }{tiny}
1192 \eqcommand{ }{time}
1193 \eqcommand{ }{times}
1194 \eqcommand{ }{title}
1195 \eqcommand{ }{to}
1196 \eqcommand{ }{today}
1197 \eqcommand{ }{toks}
1198 \eqcommand{ }{toksdef}
1199 \eqcommand{ }{tolerance}
1200 \eqcommand{ }{top}
1201 \eqcommand{ }{topfigrule}
1202 \eqcommand{ }{topfraction}
1203 \eqcommand{ }{topmargin}
1204 \eqcommand{ }{topmark}
1205 \eqcommand{ }{toppageskip}
1206 \eqcommand{ }{topsep}
1207 \eqcommand{ }{topskip}

```



```

1208 \eqcommand{      }{totalheight}
1209 \eqcommand{      }{tracingall}
1210 \eqcommand{      }{tracingcommands}
1211 \eqcommand{      }{tracinglostchars}
1212 \eqcommand{      }{tracingmacros}
1213 \eqcommand{      }{tracingonline}
1214 \eqcommand{      }{tracingoutput}
1215 \eqcommand{      }{tracingpages}
1216 \eqcommand{      }{tracingparagraphs}
1217 \eqcommand{      }{tracingrestores}
1218 \eqcommand{      }{tracingstats}
1219 \eqcommand{ }{triangle}
1220 \eqcommand{ }{ttdefault}
1221 \eqcommand{ }{ttfamily}
1222 \eqcommand{ @}{tw@}
1223 \eqcommand{ }{twocolumn}
1224 \eqcommand{ }{typein}
1225 \eqcommand{ }{typeout}
1226 \eqcommand{ }{uccode}
1227 \eqcommand{ }{uchyph}
1228 \eqcommand{ }{underline}
1229 \eqcommand{ }{unhbox}
1230 \eqcommand{ }{unhcopy}
1231 \eqcommand{ }{unitlength}
1232 \eqcommand{ }{unkern}
1233 \eqcommand{ }{unpenalty}
1234 \eqcommand{ }{unskip}
1235 \eqcommand{ }{unvbox}
1236 \eqcommand{ }{unvcopy}
1237 \eqcommand{ }{updefault}
1238 \eqcommand{ }{upshape}
1239 \eqcommand{ }{usebox}
1240 \eqcommand{ }{usecounter}
1241 \eqcommand{ }{usefont}
1242 \eqcommand{ }{usepackage}
1243 \eqcommand{ @}{@vobeyspaces}
1244 \eqcommand{ @}{@void}
1245 \eqcommand{ }{vadjust}
1246 \eqcommand{ }{valign}
1247 \eqcommand{ }{value}
1248 \eqcommand{ }{vbadness}
1249 \eqcommand{ }{vbox}
1250 \eqcommand{ }{vcenter}
1251 \eqcommand{ }{verb}
1252 \eqcommand{ }{vfil}
1253 \eqcommand{ }{vfill}
1254 \eqcommand{ }{vfilneg}
1255 \eqcommand{ }{vfuzz}
1256 \eqcommand{ }{visible}
1257 \eqcommand{ }{vline}

```



```

1258 \eqcommand{ }{voffset}
1259 \eqcommand{ @ }{voidb@x}
1260 \eqcommand{ }{vpageref}
1261 \eqcommand{ }{vrboxsep}
1262 \eqcommand{ }{vref}
1263 \eqcommand{ }{vrule}
1264 \eqcommand{ }{vsize}
1265 \eqcommand{ }{vskip}
1266 \eqcommand{ }{vspace}
1267 \eqcommand{ }{vsplit}
1268 \eqcommand{ }{vss}
1269 \eqcommand{ }{vtop}
1270 \eqcommand{ }{wd}
1271 \eqcommand{ }{whiledo}
1272 \eqcommand{ }{widehat}
1273 \eqcommand{ }{widetilde}
1274 \eqcommand{ }{widowpenalty}
1275 \eqcommand{ }{width}
1276 \eqcommand{ }{wlog}
1277 \eqcommand{ }{write}
1278 \eqcommand{@ }{@xobeysp}
1279 \eqcommand{ @ }{@xxxii}
1280 \eqcommand{ }{xdef}
1281 \eqcommand{ }{xleaders}
1282 \eqcommand{ }{xspaceskip}
1283 \eqcommand{ }{year}
1284 \eqcommand{@ }{z@}
1285 \eqcommand{@ }{z@skip}

```

7.19 color-localise-xepersian.def

```

1286 color} \-localise-xepersian.def}[2011/03/01 v0.1 localising color package]
1287 0}{rgb}{ } \0,,0}
1288 1}{rgb}{ } \1,,1}
1289 1}{rgb}{ } \0,,0}
1290 0}{rgb}{ } \1,,0}
1291 0}{rgb}{ } \0,,1}
1292 1}{cmyk}{ } \0,,0,0}
1293 0}{cmyk}{ } \1,,0,0}
1294 0}{cmyk}{ } \0,,1,0}

```

7.20 xepersian-localise-commands-xepersian.def

```

1295 \ProvidesFile{xepersian-localise-commands-xepersian.def}[2012/07/25 v0.2 Persian localisation o
1296 \eqcommand{ }{autofootnoterule}
1297 \eqcommand{ }{AutoMathsDigits}
1298 \eqcommand{ }{DefaultMathsDigits}
1299 \eqcommand{ @ }{keyval@eq@alias@key}
1300 \eqcommand{ }{deflatinfont}
1301 \eqcommand{ }{defpersianfont}
1302 \eqcommand{ }{hboxL}

```



```

1303 \eqcommand{ }{hboxR}
1304 \eqcommand{ }{Latincite}
1305 \eqcommand{ }{latinfont}
1306 \eqcommand{ }{latintoday}
1307 \eqcommand{ }{leftfootnoterule}
1308 \eqcommand{ }{lr}
1309 \eqcommand{ }{LRE}
1310 \eqcommand{ }{LTRdblcol}
1311 \eqcommand{ }{LTRfootnote}
1312 \eqcommand{ }{LTRfootnotetext}
1313 \eqcommand{ }{LTRthanks}
1314 \eqcommand{ }{persianday}
1315 \eqcommand{ }{persianfont}
1316 \eqcommand{ }{PersianMathsDigits}
1317 \eqcommand{ }{persianmonth}
1318 \eqcommand{ }{persianyear}
1319 \eqcommand{ }{plq}
1320 \eqcommand{ }{prq}
1321 \eqcommand{ }{rightfootnoterule}
1322 \eqcommand{ }{rl}
1323 \eqcommand{ }{RLE}
1324 \eqcommand{ }{RTLdblcol}
1325 \eqcommand{ }{RTLfootnote}
1326 \eqcommand{ }{RTLfootnotetext}
1327 \eqcommand{ }{RTLthanks}
1328 \eqcommand{@ }{@SepMark}
1329 \eqcommand{ }{SepMark}
1330 \eqcommand{ }{setdefaultbibitems}
1331 \eqcommand{ }{setdefaultmarginpar}
1332 \eqcommand{ }{setdigitfont}
1333 \eqcommand{ }{setfootnoteLR}
1334 \eqcommand{ }{setfootnoteRL}
1335 \eqcommand{ }{setlatintextfont}
1336 \eqcommand{ }{setLTR}
1337 \eqcommand{ }{setLTRbibitems}
1338 \eqcommand{ }{setLTRmarginpar}
1339 \eqcommand{ }{setRTL}
1340 \eqcommand{ }{setRTLbibitems}
1341 \eqcommand{ }{setRTLmarginpar}
1342 \eqcommand{ }{settextfont}
1343 \eqcommand{ }{textwidthfootnoterule}
1344 \eqcommand{ }{twocolumnstableofcontents}
1345 \eqcommand{ }{unsetfootnoteRL}
1346 \eqcommand{ }{unsetLTR}
1347 \eqcommand{ }{unsetRTL}
1348 \eqcommand{ }{vboxL}
1349 \eqcommand{ }{vboxR}
1350 \eqcommand{ }{XeLaTeX}
1351 \eqcommand{ }{XePersian}
1352 \eqcommand{ }{xepersianversion}

```



```

1353 \eqcommand{      }{xepersiandate}
1354 \eqcommand{  }{XeTeX}

```

7.21 enumerate-xepersian.def

```

1355 \ProvidesFile{enumerate-xepersian.def}[2010/07/25 v0.1 adaptations for enumerate package]
1356 \def\@enloop@{%
1357   \ifx \entemp@ \def\@tempa{\@enLabel\harfi } \else
1358   \ifx \entemp@ \def\@tempa{\@enLabel\adadi } \else
1359   \ifx \entemp@ \def\@tempa{\@enLabel\tartibi } \else
1360   \ifx \entemp@ \def\@tempa{\@enLabel\Alph } \else
1361   \ifx \entemp@ \def\@tempa{\@enLabel\alph } \else
1362   \ifx \entemp@ \def\@tempa{\@enLabel\roman } \else
1363   \ifx \entemp@ \def\@tempa{\@enLabel\Roman } \else
1364   \ifx \entemp@ \def\@tempa{\@enLabel\arabic} \else
1365   \ifx \@sptoken\entemp@ \let\@tempa\@enSpace \else
1366   \ifx \bgroup\entemp@ \let\@tempa\@enGroup \else
1367   \ifx \@enum@\entemp@ \let\@tempa\@gobble \else
1368   \let\@tempa\@enOther
1369   \@enhook
1370   \fi\fi\fi\fi\fi\fi\fi\fi\fi\fi\fi
1371   \@tempa}

```

7.22 latex-localise-environments-xepersian.def

```

1372 \ProvidesFile{latex-localise-environments-xepersian.def}[2010/07/25 v0.2 Persian localisation o
1373 \eqenvironment{ }{abstract}
1374 \eqenvironment{ }{appendix}
1375 \eqenvironment{ }{array}
1376 \eqenvironment{ }{center}
1377 \eqenvironment{ }{description}
1378 \eqenvironment{ }{displaymath}
1379 \eqenvironment{ }{document}
1380 \eqenvironment{ }{enumerate}
1381 \eqenvironment{ }{figure}
1382 \eqenvironment{ *}{figure*}
1383 \eqenvironment{ }{filecontents}
1384 \eqenvironment{ *}{filecontents*}
1385 \eqenvironment{ }{flushleft}
1386 \eqenvironment{ }{flushright}
1387 \eqenvironment{ }{itemize}
1388 \eqenvironment{ }{letter}
1389 \eqenvironment{ }{list}
1390 \eqenvironment{ }{longtable}
1391 \eqenvironment{ }{lrbox}
1392 \eqenvironment{ }{math}
1393 \eqenvironment{ }{matrix}
1394 \eqenvironment{ }{minipage}
1395 \eqenvironment{ }{multline}
1396 \eqenvironment{ }{note}
1397 \eqenvironment{ }{overlay}

```



```

1398 \eqenvironment{ }{picture}
1399 \eqenvironment{ }{quotation}
1400 \eqenvironment{ }{quote}
1401 \eqenvironment{ }{slide}
1402 \eqenvironment{ }{sloppypar}
1403 \eqenvironment{ }{split}
1404 \eqenvironment{ }{subarray}
1405 \eqenvironment{ }{tabbing}
1406 \eqenvironment{ }{table}
1407 \eqenvironment{ *}{table*}
1408 \eqenvironment{ }{tabular}
1409 \eqenvironment{ *}{tabular*}
1410 \eqenvironment{ }{thebibliography}
1411 \eqenvironment{ }{theindex}
1412 \eqenvironment{ }{titlepage}
1413 \eqenvironment{ }{trivlist}
1414 \eqenvironment{ }{verse}

```

7.23 xepersian-localise-environments-xepersian.def

```

1415 \ProvidesFile{xepersian-localise-environments-xepersian.def}[2010/07/25 v0.1 Persian localisati
1416 \eqenvironment{ }{latin}
1417 \eqenvironment{ }{LTR}
1418 \eqenvironment{ }{LTRitems}
1419 \eqenvironment{ }{modernpoem}
1420 \eqenvironment{ *}{modernpoem*}
1421 \eqenvironment{ }{persian}
1422 \eqenvironment{ }{RTL}
1423 \eqenvironment{ }{RTLitems}
1424 \eqenvironment{ }{traditionalpoem}
1425 \eqenvironment{ *}{traditionalpoem*}

```

7.24 extarticle-xepersian.def

```

1426 \ProvidesFile{extarticle-xepersian.def}[2010/07/25 v0.1 adaptations for extarticle class]
1427 \renewcommand\thepart {\@tartibi\c@part}
1428 \renewcommand\appendix{\par
1429 \setcounter{section}{0}%
1430 \setcounter{subsection}{0}%
1431 \gdef\thesection{\@harfi\c@section}}

```

7.25 extbook-xepersian.def

```

1432 \ProvidesFile{extbook-xepersian.def}[2010/07/25 v0.1 adaptations for extbook class]
1433 \renewcommand\frontmatter{%
1434 \cleardoublepage
1435 \@mainmatterfalse
1436 \pagenumbering{harfi}}
1437 \renewcommand \thepart {\@tartibi\c@part}
1438 \renewcommand\appendix{\par
1439 \setcounter{chapter}{0}%
1440 \setcounter{section}{0}%

```



```

1441 \gdef\@chapapp{\appendixname}%
1442 \gdef\thechapter{\@harfi\c@chapter}
1443 }%end appendix

```

7.26 extrafootnotefeatures-xepersian.def

```

1444 \ProvidesFile{extrafootnotefeatures-xepersian.def}[2012/01/01 v0.2 footnote macros for extrafootnote]
1445 \renewcommand{\foottextfont}{\footnotesize\if@RTL@footnote\else\latinfont\fi}
1446 \renewcommand{\LTRfoottextfont}{\footnotesize\latinfont}
1447 \renewcommand{\RTLfoottextfont}{\footnotesize\persianfont}

```

7.27 extreport-xepersian.def

```

1448 \ProvidesFile{extreport-xepersian.def}[2010/07/25 v0.1 adaptations for extreport class]
1449 \renewcommand\thepart {\@tartibi\c@part}
1450 \renewcommand\appendix{\par
1451 \setcounter{chapter}{0}%
1452 \setcounter{section}{0}%
1453 \gdef\@chapapp{\appendixname}%
1454 \gdef\thechapter{\@harfi\c@chapter}}

```

7.28 flowfram-xepersian.def

```

1455 \ProvidesFile{flowfram-xepersian.def}[2010/07/25 v0.1 adaptations for flowfram package]
1456 \def\@outputpage{%
1457 \begingroup
1458 \let\protect\noexpand
1459 \@resetactivechars
1460 \global\let\@if@newlist\if@newlist
1461 \global\@newlistfalse\@parboxrestore
1462 \shipout\vbox{\set@typeset@protect
1463 \aftergroup
1464 \endgroup
1465 \aftergroup
1466 \set@typeset@protect
1467 \reset@font\normalsize\normalsfcodes
1468 \let\label\@gobble
1469 \let\index\@gobble
1470 \let\glossary\@gobble
1471 \baselineskip\z@skip
1472 \lineskip\z@skip
1473 \lineskiplimit\z@
1474 \vskip\topmargin\moveright\@themargin
1475 \vbox{%
1476 \vskip\headheight
1477 \vskip\headsep
1478 \box\@outputbox
1479 }}%
1480 \global\let\if@newlist\@if@newlist
1481 \stepcounter{page}%
1482 \setcounter{displayedframe}{0}%
1483 \let\firstmark\botmark}

```



7.29 footnote-xepersian.def

```
1484 \ProvidesFile{footnote-xepersian.def}[2013/04/26 v0.4 footnote macros for xepersian package]
1485
1486
1487
1488 \long\def\@footnotetext#1{\insert\footins{%
1489   \if@RTL@footnote\@RTLtrue\else\@RTLfalse\fi%
1490   \reset@font\footnotesize
1491   \interlinepenalty\interfootnotelinepenalty
1492   \splittopskip\footnotesep
1493   \splitmaxdepth \dp\strutbox \floatingpenalty \@MM
1494   \hsize\columnwidth \@parboxrestore
1495   \protected@edef\@currentlabel{%
1496     \csname p@footnote\endcsname\@thefnmark
1497   }%
1498   \color@begingroup
1499     \makefntext{%
1500       \rule{z@\footnotesep\ignorespaces\if@RTL@footnote#1\else\latinfont#1\fi\@finalstrut\strutbox}%
1501     \color@endgroup}}%
1502
1503
1504
1505
1506
1507 \long\def\@RTLfootnotetext#1{\insert\footins{%
1508   \@RTLtrue%
1509   \reset@font\footnotesize
1510   \interlinepenalty\interfootnotelinepenalty
1511   \splittopskip\footnotesep
1512   \splitmaxdepth \dp\strutbox \floatingpenalty \@MM
1513   \hsize\columnwidth \@parboxrestore
1514   \protected@edef\@currentlabel{%
1515     \csname p@footnote\endcsname\@thefnmark
1516   }%
1517   \color@begingroup
1518     \makefntext{%
1519       \rule{z@\footnotesep\ignorespaces\persianfont #1\@finalstrut\strutbox}%
1520     \color@endgroup}}%
1521
1522
1523
1524
1525
1526 \long\def\@LTRfootnotetext#1{\insert\footins{%
1527   \@RTLfalse%
1528   \reset@font\footnotesize
1529   \interlinepenalty\interfootnotelinepenalty
1530   \splittopskip\footnotesep
1531   \splitmaxdepth \dp\strutbox \floatingpenalty \@MM
```




```

1532 \hsize\columnwidth \@parboxrestore
1533 \protected@edef\@currentlabel{%
1534     \csname p@footnote\endcsname\@thefnmark
1535 }%
1536 \color@begingroup
1537     \@makefnintext{%
1538         \rule\z@\footnotesep\ignorespaces\latinfont #1\@finalstrut\strutbox}%
1539 \color@endgroup}}%
1540
1541 \footdir@temp\footdir@ORG@xepersian@footnotetext\@footnotetext{\bidi@footdir@footnote}%
1542 \footdir@temp\footdir@ORG@xepersian@RTLfootnotetext\@RTLfootnotetext{R}%
1543 \footdir@temp\footdir@ORG@xepersian@LTRfootnotetext\@LTRfootnotetext{L}%
1544
1545
1546
1547 \long\def\@mpfootnotetext#1{%
1548 \ifbidi@autofootnoterule\ifnum\c@mpfootnote=\@ne\if@RTL@footnote\global\let\bidi@mpfootnoterule
1549 \global\setbox\@mpfootins\vbox{\if@RTL@footnote\@RTLtrue\else\@RTLfalse\fi%
1550     \unvbox\@mpfootins
1551     \reset@font\footnotesize
1552     \hsize\columnwidth
1553     \@parboxrestore
1554     \protected@edef\@currentlabel
1555         {\csname p@mpfootnote\endcsname\@thefnmark}%
1556     \color@begingroup
1557         \@makefnintext{%
1558             \rule\z@\footnotesep\ignorespaces\if@RTL@footnote#1\else\latinfont#1\fi\@finalstrut\strutbox}%
1559     \color@endgroup}}
1560
1561
1562
1563
1564
1565 \long\def\@mpRTLfootnotetext#1{%
1566 \ifbidi@autofootnoterule\ifnum\c@mpfootnote=\@ne\global\let\bidi@mpfootnoterule\right@footnot
1567 \global\setbox\@mpfootins\vbox{\@RTLtrue%
1568     \unvbox\@mpfootins
1569     \reset@font\footnotesize
1570     \hsize\columnwidth
1571     \@parboxrestore
1572     \protected@edef\@currentlabel
1573         {\csname p@mpfootnote\endcsname\@thefnmark}%
1574     \color@begingroup
1575         \@makefnintext{%
1576             \rule\z@\footnotesep\ignorespaces\persianfont #1\@finalstrut\strutbox}%
1577     \color@endgroup}}
1578
1579
1580 \long\def\@mplTRfootnotetext#1{%
1581 \ifbidi@autofootnoterule\ifnum\c@mpfootnote=\@ne\global\let\bidi@mpfootnoterule\left@footnot

```



```

1582 \global\setbox\@mpfootins\vbox{\@RTLfalse%
1583 \unvbox\@mpfootins
1584 \reset@font\footnotesize
1585 \hsize\columnwidth
1586 \@parboxrestore
1587 \protected@edef\@currentlabel
1588 {\csname p@mpfootnote\endcsname\@thefnmark}%
1589 \color@begingroup
1590 \makefnintext{%
1591 \rule\z@{\footnotesep\ignorespaces\latinfont #1\@finalstrut\strutbox}%
1592 \color@endgroup}}

```

7.30 framed-xepersian.def

```

1593 \ProvidesFile{framed-xepersian.def}[2012/06/05 v0.1 xepersian adaptations for framed package for
1594 \renewenvironment{titled-frame}[1]{%
1595 \def\FrameCommand{\fboxsep8pt\fboxrule2pt
1596 \TitleBarFrame{\textbf{#1}}}%
1597 \def\FirstFrameCommand{\fboxsep8pt\fboxrule2pt
1598 \TitleBarFrame[$\if@RTL\blacktriangleleft\else\blacktriangleright\fi$]{\textbf{#1}}}%
1599 \def\MidFrameCommand{\fboxsep8pt\fboxrule2pt
1600 \TitleBarFrame[$\if@RTL\blacktriangleleft\else\blacktriangleright\fi$]{\textbf{#1} (\if@RTL
1601 \def\LastFrameCommand{\fboxsep8pt\fboxrule2pt
1602 \TitleBarFrame{\textbf{#1} (\if@RTL else\ cont\fi)}}}%
1603 \MakeFramed{\advance\hsize-20pt \FrameRestore}}}%
1604 % note: 8 + 2 + 8 + 2 = 20. Don't use \width because the frame title
1605 % could interfere with the width measurement.
1606 {\endMakeFramed}

```

7.31 glossaries-xepersian.def

```

1607 \ProvidesFile{glossaries-xepersian.def}[2014/09/04 v0.4 xepersian adaptations for glossaries pac
1608 \glsaddprotectedpagefmt{@harfi}
1609 \glsaddprotectedpagefmt{@tartibi}
1610 \glsaddprotectedpagefmt{@adadi}

```

7.32 hyperref-xepersian.def

```

1611 \ProvidesFile{hyperref-xepersian.def}[2015/02/02 v0.6 bilingual captions for hyperref package]
1612 \def\equationautorefname{\if@RTL else\ Equation\fi}%
1613 \def\footnoteautorefname{\if@RTL else\ footnote\fi}%
1614 \def\itemautorefname{\if@RTL else\ item\fi}%
1615 \def\figureautorefname{\if@RTL else\ Figure\fi}%
1616 \def\tableautorefname{\if@RTL else\ Table\fi}%
1617 \def\partautorefname{\if@RTL else\ Part\fi}%
1618 \def\appendixautorefname{\if@RTL else\ Appendix\fi}%
1619 \def\chapterautorefname{\if@RTL else\ chapter\fi}%
1620 \def\sectionautorefname{\if@RTL else\ section\fi}%
1621 \def\subsectionautorefname{\if@RTL else\ subsection\fi}%
1622 \def\subsubsectionautorefname{\if@RTL else\ subsubsection\fi}%
1623 \def\paragraphautorefname{\if@RTL else\ paragraph\fi}%
1624 \def\subparagraphautorefname{\if@RTL else\ subparagraph\fi}%

```



```

1625 \def\FancyVerbLineautorefname{\if@RTL else\ line\fi}%
1626 \def\theoremautorefname{\if@RTL else\ Theorem\fi}%
1627 \def\pageautorefname{\if@RTL else\ page\fi}%
1628 \AtBeginDocument{%
1629 \let\HyOrg@appendix\appendix
1630 \def\appendix{%
1631 \ltx@ifundefined{chapter}%
1632 {\gdef\theHsection{\Alph{section}}}%
1633 {\gdef\theHchapter{\Alph{chapter}}}%
1634 \xdef\Hy@chapapp{\Hy@appendixstring}%
1635 \HyOrg@appendix
1636 }
1637 }
1638 \pdfstringdefDisableCommands{%
1639 \let\lr\@firstofone
1640 \let\rl\@firstofone
1641 \def\XePersian{XePersian}
1642 }
1643 \ltx@ifundefined{@resets@pp}{%
1644 }{%
1645 \let\HyOrg@resets@pp\@resets@pp
1646 \def\@resets@pp{%
1647 \ltx@ifundefined{chapter}{%
1648 \gdef\theHsection{\Hy@AlphNoErr{section}}%
1649 }{%
1650 \gdef\theHchapter{\Hy@AlphNoErr{chapter}}%
1651 }%
1652 \xdef\Hy@chapapp{\Hy@appendixstring}%
1653 \HyOrg@resets@pp
1654 }%
1655 }

```

7.33 imspc-xepersian.def

```

1656 \ProvidesFile{imspc-xepersian.def}[2015/11/14 v0.4 implementation of imspc class for xepersi
1657 \newenvironment{thebibliography}[1]{%
1658 \bibttitlestyle
1659 \normalfont\bibliofont\labelsep .5em\relax
1660 \renewcommand\theenumiv{\arabic{enumiv}}\let\p@enumiv\@empty
1661 \if@RTL\if@LTRbibitems\@RTLfalse\else\fi\else\if@RTLbibitems\@RTLtrue\else\fi\fi
1662 \list{\@biblabel{\theenumiv}}{\settowidth\labelwidth{\@biblabel{#1}}%
1663 \leftmargin\labelwidth \advance\leftmargin\labelsep
1664 \usecounter{enumiv}}%
1665 \sloppy \clubpenalty\@M \widowpenalty\clubpenalty
1666 \sfcode`\.=\@m
1667 }{%
1668 \def\@noitemerr{\@latex@warning{Empty `thebibliography' environment}}%
1669 \endlist
1670 }
1671 \def\theindex{\@restonecoltrue\if@twocolumn\@restonecolfalse\fi

```



```

1672 \columnseprule\z@ \columnsep 35\p@
1673 \@indextitlestyle
1674 \thispagestyle{plain}%
1675 \let\item\@idxitem
1676 \parindent\z@ \parskip\z@\@plus.3\p@\relax
1677 \ifRTL\raggedleft\else\raggedright\fi
1678 \hyphenpenalty\@M
1679 \footnotesize}
1680 \def\@idxitem{\par\hangindent \ifRTL-\fi2em}
1681 \def\subitem{\par\hangindent \ifRTL-\fi2em\hspace*{1em}}
1682 \def\subsubitem{\par\hangindent \ifRTL-\fi3em\hspace*{2em}}
1683 \renewcommand \thepart {\@tartibi\c@part}
1684 \def\appendix{\par\c@section\z@ \c@subsection\z@
1685 \let\sectionname\appendixname
1686 \def\thesection{\@harfi\c@section}}
1687 \def\right@footnoterule{%
1688 \kern-.4\p@
1689 \hbox to \columnwidth{\hskip \dimexpr\columnwidth-5pc\relax \hrulefill }
1690 \kern11\p@\kern-\footnotesep}
1691 \def\left@footnoterule{\kern-.4\p@
1692 \hrule\@width 5pc\kern11\p@\kern-\footnotesep}
1693 \def\@makefnmark{%
1694 \leavevmode
1695 \raise.9ex\hbox{\fontsize\sf@size\z@\normalfont\@thefnmark}}%
1696 }
1697
1698
1699
1700 \long\def\@footnotetext#1{%
1701 \insert\footins{%
1702 \ifRTL@footnote\@RTLtrue\else\@RTLfalse\fi%
1703 \normalfont\footnotesize
1704 \interlinepenalty\interfootnotelinepenalty
1705 \splittopskip\footnotesep \splitmaxdepth \dp\strutbox
1706 \floatingpenalty\@MM \hsize\columnwidth
1707 \@parboxrestore \parindent\normalparindent \sloppy
1708 \protected@edef\@currentlabel{%
1709 \csname p@footnote\endcsname\@thefnmark}%
1710 \@makefnmark}%
1711 \rule\z@\footnotesep\ignorespaces\ifRTL@footnote#1\else\latinfont#1\fi\unskip\strut\par}}
1712
1713
1714
1715
1716
1717 \long\def\@RTLfootnotetext#1{%
1718 \insert\footins{%
1719 \@RTLtrue%
1720 \normalfont\footnotesize
1721 \interlinepenalty\interfootnotelinepenalty

```



```

1722 \splittopskip\footnotesep \splitmaxdepth \dp\strutbox
1723 \floatingpenalty\@MM \hsize\columnwidth
1724 \@parboxrestore \parindent\normalparindent \sloppy
1725 \protected@edef\@currentlabel{%
1726   \csname p@footnote\endcsname\@thefnmark}%
1727 \@makefnfntext{%
1728   \rule\z@\footnotesep\ignorespaces\persianfont #1\unskip\strut\par}}
1729
1730
1731
1732
1733
1734
1735
1736 \long\def\@LTRfootnotetext#1{%
1737   \insert\footins{%
1738     \RTLfalse%
1739     \normalfont\footnotesize
1740     \interlinepenalty\interfootnotelinepenalty
1741     \splittopskip\footnotesep \splitmaxdepth \dp\strutbox
1742     \floatingpenalty\@MM \hsize\columnwidth
1743     \@parboxrestore \parindent\normalparindent \sloppy
1744     \protected@edef\@currentlabel{%
1745       \csname p@footnote\endcsname\@thefnmark}%
1746     \@makefnfntext{%
1747       \rule\z@\footnotesep\ignorespaces\latinfont #1\unskip\strut\par}}
1748
1749 \footdir@temp\footdir@ORG@xepersian@imsproc@footnotetext\@footnotetext{\bidi@footdir@footnote}
1750 \footdir@temp\footdir@ORG@xepersian@imsproc@RTLfootnotetext\@RTLfootnotetext{R}%
1751 \footdir@temp\footdir@ORG@xepersian@imsproc@LTRfootnotetext\@LTRfootnotetext{L}%
1752
1753 \def\part{\@startsection{part}{0}%
1754   \z@\linespacing\@plus\linespacing}{.5\linespacing}%
1755   {\normalfont\bfseries\if@RTL\raggedleft\else\raggedright\fi}}
1756 \def\@tocline#1#2#3#4#5#6#7{\relax
1757   \ifnum #1>\c@tocdepth % then omit
1758   \else
1759     \par \addpenalty\@secpenalty\addvspace{#2}%
1760     \begingroup \hyphenpenalty\@M
1761     \@ifempty{#4}{%
1762       \@tempdima\csname r@tocindent\@number#1\endcsname\relax
1763     }{%
1764       \@tempdima#4\relax
1765     }%
1766     \parindent\z@ \if@RTL\righskip\else\leftskip\fi#3\relax \advance\if@RTL\righskip\else\leftskip
1767     \if@RTL\leftskip\else\righskip\fi\@pnumwidth plus4em \parfillskip-\@pnumwidth
1768     #5\leavevmode\hskip-\@tempdima #6\nobreak\relax
1769     \hfil\hbox to\@pnumwidth{\@tocpagenum{#7}}\par
1770     \nobreak
1771   \endgroup

```



```

1772 \fi}
1773 \renewcommand\thesubsection {\thesection\@SepMark\arabic{subsection}}
1774 \renewcommand\thesubsubsection {\thesubsection \@SepMark\arabic{subsubsection}}
1775 \renewcommand\theparagraph {\thesubsubsection\@SepMark\arabic{paragraph}}
1776 \renewcommand\thesubparagraph {\theparagraph\@SepMark\arabic{subparagraph}}
1777 \def\maketitle{\par
1778 \topnum\z@ % this prevents figures from falling at the top of page 1
1779 \setcopyright
1780 \thispagestyle{firstpage}% this sets first page specifications
1781 \uppercase\nonmath\shorttitle
1782 \ifx\@empty\shortauthors \let\shortauthors\shorttitle
1783 \else \andify\shortauthors
1784 \fi
1785 \@maketitle@hook
1786 \begingroup
1787 \@maketitle
1788 \toks@\@xp{\shortauthors}\@temptokena\@xp{\shorttitle}%
1789 \toks4{\def\\{ \ignorespaces}}% defend against questionable usage
1790 \edef\@tempa{%
1791 \@nx\markboth{\the\toks4
1792 \@nx\MakeUppercase{\the\toks@}}{\the\@temptokena}}%
1793 \@tempa
1794 \endgroup
1795 \c@footnote\z@
1796 \cleartopmattertags
1797 }

```

7.34 kashida-xepersian.def

```

1798 \ProvidesFile{kashida-xepersian.def}[2013/11/15 v0.3 implementation of Kashida for xepersian pac
1799 \chardef\xepersian@zwj="200D % zero-width joiner
1800
1801 \chardef\xepersian@D=10 % dual-joiner class
1802 \chardef\xepersian@L=11 % lam
1803 \chardef\xepersian@R=12 % right-joiner
1804 \chardef\xepersian@A=13 % alef
1805 \chardef\xepersian@V=256 % vowel or other combining mark (to be ignored)
1806 \def\xepersian@kashida{\xepersian@zwj\nobreak%
1807 \leaders\hrule height \XeTeXglyphbounds2 \the\XeTeXcharglyph"0640 depth \XeTeXglyphbounds4 \t
1808
1809 \def\setclass#1#2{\def\theclass{#1}\def\charlist{#2}%
1810 \expandafter\dosetclass\charlist,\end}
1811 \def\dosetclass#1,#2\end{%
1812 \def\test{#1}\def\charlist{#2}%
1813 \ifx\test\empty\let\next\finishsetclass
1814 \else \XeTeXcharclass "\test = \theclass
1815 \let\next\dosetclass \fi
1816 \expandafter\next\charlist,,\end}
1817 \def\finishsetclass#1,,\end{}
1818

```



```

1819 \setclass \xepersian@A {0622,0623,0625,0627}
1820 \setclass \xepersian@R {0624,0629,062F,0630,0631,0632,0648,0698}
1821 \setclass \xepersian@D {0626,0628,062A,062B,062C,062D,062E}
1822 \setclass \xepersian@D {0633,0634,0635,0636,0637,0638,0639,063A}
1823 \setclass \xepersian@D {0640,0641,0642,0643,0645,0646,0647,0649,064A}
1824 \setclass \xepersian@D {067E,0686,06A9,06AF,06CC}
1825 \setclass \xepersian@L {0644}
1826 \setclass \xepersian@V {064B,064C,064D,064E,064F,0650,0651,0652}
1827
1828 \XeTeXinterchartoks \xepersian@D \xepersian@D = {\xepersian@kashida}
1829 \XeTeXinterchartoks \xepersian@L \xepersian@D = {\xepersian@kashida}
1830 \XeTeXinterchartoks \xepersian@D \xepersian@L = {\xepersian@kashida}
1831 \XeTeXinterchartoks \xepersian@L \xepersian@L = {\xepersian@kashida}
1832 \XeTeXinterchartoks \xepersian@D \xepersian@R = {\xepersian@kashida}
1833 \XeTeXinterchartoks \xepersian@D \xepersian@A = {\xepersian@kashida}
1834 \XeTeXinterchartoks \xepersian@L \xepersian@R = {\xepersian@kashida}
1835 \XeTeXinterchartoks \xepersian@L \xepersian@A = {}
1836
1837 \newcommand{\KashidaOn}{\XeTeXinterchartokenstate=1}
1838 \newcommand{\KashidaOff}{\XeTeXinterchartokenstate=0}
1839 \KashidaOn

```

7.35 listings-xepersian.def

```

1840 \ProvidesFile{listings-xepersian.def}[2014/07/17 v0.3 bilingual captions for listings package]
1841 \def\lstlistingname{\if@RTL else\ Listing\fi}
1842 \def\lstlistlistingname{\if@RTL else\ Listings\fi}

```

7.36 loadingorder-xepersian.def

```

1843 \ProvidesFile{loadingorder-xepersian.def}[2012/01/01 v0.3 making sure that xepersian is the last]
1844 \bidi@isloaded{algorithmic}
1845 \bidi@isloaded{algorithm}
1846 \bidi@isloaded{backref}
1847 \bidi@isloaded{enumerate}
1848 \bidi@isloaded{tocloft}
1849 \bidi@isloaded{url}
1850 \AtBeginDocument{
1851   \if@bidi@algorithmicloaded@else
1852     \bidi@isloaded[\PackageError{xepersian}{Oops! you have loaded package algorithmic after xepersian}{}]
1853   \fi%
1854   \if@bidi@algorithmloaded@else
1855     \bidi@isloaded[\PackageError{xepersian}{Oops! you have loaded package algorithm after xepersian}{}]
1856   \fi%
1857   \if@bidi@backrefloaded@else
1858     \bidi@isloaded[\PackageError{xepersian}{Oops! you have loaded package backref after xepersian}{}]
1859   \fi%
1860   \if@bidi@enumerateloading@else
1861     \bidi@isloaded[\PackageError{xepersian}{Oops! you have loaded package enumerate after xepersian}{}]
1862   \fi%
1863   \if@bidi@tocloftloaded@else

```



```

1864 \bidi@isloaded[\PackageError{xepersian}{Oops! you have loaded package tocloft after xepersian
1865 \fi%
1866 \if@bidi@urlloaded@else
1867 \bidi@isloaded[\PackageError{xepersian}{Oops! you have loaded package url after xepersian pack
1868 \fi%
1869 }

```

7.37 localise-xepersian.def

```

1870 \ProvidesFile{localise-xepersian.def}[2014/07/10 v0.2b Persian localisation of LaTeX2e]
1871 \newcommand{\makezwnjletter}{\catcode`\=11\relax}
1872 \makezwnjletter
1873 \newcommand*{\eqcommand}[2]{\if@bidi@csprimitive{#2}{\bidi@csletcs{#1}{#2}}{\bidi@csdefcs{#1}{#2}}}
1874 \newcommand*{\eqenvironment}[2]{\newenvironment{#1}{\csname#2\endcsname}{\csname end#2\endcsname}}
1875 \@ifpackageloaded{keyval}{%
1876 \newcommand*{\keyval@eq@alias@key}[4][KV]{%
1877 \bidi@csletcs{#1@#2@#3}{#1@#2@#4}%
1878 \bidi@csletcs{#1@#2@#3@default}{#1@#2@#4@default}}%
1879 }{\@ifpackageloaded{xkeyval}{%
1880 \newcommand*{\keyval@eq@alias@key}[4][KV]{%
1881 \bidi@csletcs{#1@#2@#3}{#1@#2@#4}%
1882 \bidi@csletcs{#1@#2@#3@default}{#1@#2@#4@default}}%
1883 }{}}
1884 \input{latex-localise-commands-xepersian.def}
1885 \input{xepersian-localise-commands-xepersian.def}
1886 \input{latex-localise-environments-xepersian.def}
1887 \input{xepersian-localise-environments-xepersian.def}
1888 \input{latex-localise-messages-xepersian.def}
1889 \input{latex-localise-misc-xepersian.def}
1890 \input{packages-localise-xepersian.def}
1891 \aliasfontfeature{ExternalLocation}{ }
1892 \aliasfontfeature{ExternalLocation}{ }
1893 \aliasfontfeature{Renderer}{ }
1894 \aliasfontfeature{BoldFont}{ }
1895 \aliasfontfeature{Language}{ }
1896 \aliasfontfeature{Script}{ }
1897 \aliasfontfeature{UprightFont}{ }
1898 \aliasfontfeature{ItalicFont}{ }
1899 \aliasfontfeature{BoldItalicFont}{ }
1900 \aliasfontfeature{SlantedFont}{ }
1901 \aliasfontfeature{BoldSlantedFont}{ }
1902 \aliasfontfeature{SmallCapsFont}{ }
1903 \aliasfontfeature{UprightFeatures}{ }
1904 \aliasfontfeature{BoldFeatures}{ }
1905 \aliasfontfeature{ItalicFeatures}{ }
1906 \aliasfontfeature{BoldItalicFeatures}{ }
1907 \aliasfontfeature{SlantedFeatures}{ }
1908 \aliasfontfeature{BoldSlantedFeatures}{ }
1909 \aliasfontfeature{SmallCapsFeatures}{ }
1910 \aliasfontfeature{SizeFeatures}{ }

```




```

1911 \aliasfontfeature{Scale}{ }
1912 \aliasfontfeature{WordSpace}{ }
1913 \aliasfontfeature{PunctuationSpace}{ }
1914 \aliasfontfeature{FontAdjustment}{ }
1915 \aliasfontfeature{LetterSpace}{ }
1916 \aliasfontfeature{HyphenChar}{ }
1917 \aliasfontfeature{Color}{ }
1918 \aliasfontfeature{Opacity}{ }
1919 \aliasfontfeature{Mapping}{ }
1920 \aliasfontfeature{Weight}{ }
1921 \aliasfontfeature{Width}{ }
1922 \aliasfontfeature{OpticalSize}{ }
1923 \aliasfontfeature{FakeSlant}{ }
1924 \aliasfontfeature{FakeStretch}{ }
1925 \aliasfontfeature{FakeBold}{ }
1926 \aliasfontfeature{AutoFakeSlant}{ }
1927 \aliasfontfeature{AutoFakeBold}{ }
1928 \aliasfontfeature{Ligatures}{ }
1929 \aliasfontfeature{Alternate}{ }
1930 \aliasfontfeature{Variant}{ }
1931 \aliasfontfeature{Variant}{ }
1932 \aliasfontfeature{CharacterVariant}{ }
1933 \aliasfontfeature{Style}{ }
1934 \aliasfontfeature{Annotation}{ }
1935 \aliasfontfeature{RawFeature}{ }
1936 \aliasfontfeature{CharacterWidth}{ }
1937 \aliasfontfeature{Numbers}{ }
1938 \aliasfontfeature{Contextuals}{ }
1939 \aliasfontfeature{Diacritics}{ }
1940 \aliasfontfeature{Letters}{ }
1941 \aliasfontfeature{Kerning}{ }
1942 \aliasfontfeature{VerticalPosition}{ }
1943 \aliasfontfeature{Fractions}{ }
1944 \aliasfontfeatureoption{Language}{Default}{ }
1945 \aliasfontfeatureoption{Language}{Parsi}{ }
1946 \aliasfontfeatureoption{Script}{Parsi}{ }
1947 \aliasfontfeatureoption{Script}{Latin}{ }
1948 \aliasfontfeatureoption{Style}{MathScript}{ }
1949 \aliasfontfeatureoption{Style}{MathScriptScript}{ }

```

7.38 memoir-xepersian.def

```

1950 \ProvidesFile{memoir-xepersian.def}[2010/07/25 v0.1 adaptations for memoir class]
1951 \renewcommand{\@memfront}{%
1952   \@smemfront\pagenumbering{harfi}}
1953 \renewcommand{\setthesection}{\thechapter\@SepMark\harfi{section}}
1954 \renewcommand*{\thebook}{\@tartibi\c@book}
1955 \renewcommand*{\thepart}{\@tartibi\c@part}
1956 \renewcommand{\appendix}{\par
1957   \setcounter{chapter}{0}%

```



```

1958 \setcounter{section}{0}%
1959 \gdef\@chapapp{\appendixname}%
1960 \gdef\thechapter{\@harfi\c@chapter}%
1961 \anappendixtrue}

```

7.39 latex-localise-messages-xepersian.def

```

1962 latex} \-localise-messages-xepersian.def}[2011/03/01 v0.1 localising LaTeX2e messages]

```

7.40 minitoc-xepersian.def

```

1963 \ProvidesFile{minitoc-xepersian.def}[2010/07/25 v0.1 bilingual captions for minitoc package]
1964 \def\ptctitle{\if@RTL else\ Table of Contents\fi}%
1965 \def\plftitle{\if@RTL else\ List of Figures\fi}%
1966 \def\pltttitle{\if@RTL else\ List of Tables\fi}%
1967 \def\mtctitle{\if@RTL else\ Contents\fi}%
1968 \def\mlftitle{\if@RTL else\ Figures\fi}%
1969 \def\mltttitle{\if@RTL else\ Tables\fi}%
1970 \def\stctitle{\if@RTL else\ Contents\fi}%
1971 \def\slftitle{\if@RTL else\ Figures\fi}%
1972 \def\sltttitle{\if@RTL else\ Tables\fi}%

```

7.41 latex-localise-misc-xepersian.def

```

1973 \ProvidesFile{latex-localise-misc-xepersian.def}[2012/01/01 v0.2 miscellaneous Persian localisa
1974 %}1# \ \
1975 \@ \ @ \ \
1976 \1# \
1977 \1# @\
1978 \1# @\
1979 {@ \ \
1980 %}2#1# @\ \
1981 %1# \ @\ \ \ \ \
1982 \2# \ @\ \
1983 {{2#1# \}}
1984 undefined\ \ \
1985
1986 %{ \ \ \ \1#} \ \} \1# \ \
1987 \ { \ \ \
1988 \ \ \
1989
1990
1991 \ \ \ \%} \#1
1992 \1#} \ \ \% \
1993 \ \ \
1994 }%
1995 \
1996 \ \ \
1997 }
1998 \= \ \
1999
2000

```



```

2001 \@ifdefinitionfileloaded{latex-xetex-bidi}{%
2002 \def\@xfloat #1[#2]{%
2003   \@nodoocument
2004   \def \@captive {#1}%
2005   \def \@fps {#2}%
2006   \@onelevel@sanitize \@fps
2007   \def \reserved@a {!}%
2008   \ifx \reserved@a \@fps
2009     \@fpsadddefault
2010   \else
2011     \ifx \@fps \@empty
2012       \@fpsadddefault
2013     \fi
2014   \fi
2015   \ifhmode
2016     \@bsphack
2017     \@floatpenalty -\@Mii
2018   \else
2019     \@floatpenalty-\@Miii
2020   \fi
2021 \ifinner
2022   \@parmoderr\@floatpenalty\z@
2023 \else
2024   \@next\@currbox\@freelist
2025   {%
2026     \@tempcnta \sixt@@n
2027     \expandafter \@tfor \expandafter \reserved@a
2028       \expandafter : \expandafter =\@fps
2029     \do
2030     {%
2031       \if \reserved@a h%
2032         \ifodd \@tempcnta
2033       \else
2034         \advance \@tempcnta \@ne
2035       \fi
2036     \fi
2037     \if \reserved@a %
2038       \ifodd \@tempcnta
2039     \else
2040       \advance \@tempcnta \@ne
2041     \fi
2042   \fi
2043   \if \reserved@a t%
2044     \@setfpsbit \tw@
2045   \fi
2046   \if \reserved@a %
2047     \@setfpsbit \tw@
2048   \fi
2049   \if \reserved@a b%
2050     \@setfpsbit 4%

```



```

2051         \fi
2052         \if \reserved@a %
2053             \@setfpsbit 4%
2054         \fi
2055         \if \reserved@a p%
2056             \@setfpsbit 8%
2057         \fi
2058         \if \reserved@a %
2059             \@setfpsbit 8%
2060         \fi
2061         \if \reserved@a !%
2062             \ifnum \@tempcnta>15
2063                 \advance\@tempcnta -\sixt@@n\relax
2064             \fi
2065         \fi
2066     }%
2067     \@tempcntb \csname ftype@\@capytype \endcsname
2068     \multiply \@tempcntb \@xxxii
2069     \advance \@tempcnta \@tempcntb
2070     \global \count\@currbox \@tempcnta
2071 }%
2072 \@fltovf
2073 \fi
2074 \global \setbox\@currbox
2075     \color@vbox
2076     \normalcolor
2077     \vbox \bgroup
2078         \hsize\columnwidth
2079         \@parboxrestore
2080         \@floatboxreset
2081 }
2082 \let\bm@ \bm@c
2083 \let\bm@ \bm@l
2084 \let\bm@ \bm@r
2085 \let\bm@ \bm@b
2086 \let\bm@ \bm@t
2087 \let\bm@ \bm@s
2088 \long\def\@iiiparbox#1#2[#3]#4#5{%
2089     \leavevmode
2090     \@pboxswfalse
2091     \ifRTLtab\@bidi@list@minipage@parbox@not@nobtrue\fi
2092     \ifRTL\if#1t\@bidi@list@minipage@parboxtrue\else\if#1b\@bidi@list@minipage@parboxtrue\else\fi
2093     \setlength\@tempdima{#4}%
2094     \@begin@tempboxa\vbox{\hsize\@tempdima\@parboxrestore#5\@par}%
2095     \ifx\relax#2\else
2096         \setlength\@tempdimb{#2}%
2097         \edef\@parboxto{to\the\@tempdimb}%
2098     \fi
2099     \if#1b\vbox
2100     \else\if#1\vbox

```



```

2101 \else\if #1t\vtop
2102 \else\if vtop\ #1
2103 \else\ifmode\vccenter
2104 \else\@pboxswtrue $\vccenter
2105 \fi\fi\fi\fi\fi
2106 \@parboxto{\let\hss\vss\let\unhbox\unvbox
2107 \csname bm@#3\endcsname}%
2108 \if@pboxsw \m@th$\fi
2109 \@end@tempboxa}
2110 \def\@iiiminipage#1#2[#3]#4{%
2111 \leavevmode
2112 \@pboxswfalse
2113 \if@RTLtab\@bidi@list@minipage@parbox@not@nobtrue\fi
2114 \if@RTL\if#1t\@bidi@list@minipage@parboxtrue\else\if#1b\@bidi@list@minipage@parboxtrue\else
2115 \setlength\@tempdima{#4}%
2116 \def\@mpargs{{#1}{#2}[#3]{#4}}%
2117 \setbox\@tempboxa\vbox\bgroup
2118 \color@begingroup
2119 \hsize\@tempdima
2120 \textwidth\hsize \columnwidth\hsize
2121 \@parboxrestore
2122 \def\@mpfn{mpfootnote}\def\thempfn{\thempfootnote}\c@mpfootnote\z@
2123 \let\@footnotetext\@mpfootnotetext
2124 \let\@LTRfootnotetext\@mpLTRfootnotetext
2125 \let\@RTLfootnotetext\@mpRTLfootnotetext
2126 \let\@listdepth\@mplistdepth \@mplistdepth\z@
2127 \@minipagerestore
2128 \@setminipage}
2129 \def\@testpach#1{\@chclass \ifnum \@lastchclass=\tw@ 4 \else
2130 \ifnum \@lastchclass=3 5 \else
2131 \z@ \if #1c\@chnum \z@ \else
2132 \if chnum@ #1 \z@ \else
2133 \if \if@RTLtab#1r\else#1l\fi\@chnum \@ne \else
2134 \if \if@RTLtab#1 \else#1 \fi\@chnum \@ne \else
2135 \if \if@RTLtab#1l\else#1r\fi\@chnum \tw@ \else
2136 \if \if@RTLtab#1 \else#1 \fi\@chnum \tw@ \else
2137 \@chclass \if #1|\@ne \else
2138 \if #1@\tw@ \else
2139 \if #1p3 \else
2140 \if 3 #1 \else \z@ \@preamerr 0\fi
2141 \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi
2142 \fi}%
2143 {}
2144 \@ifdefinitionfileloaded{array-xetex-bidi}{%
2145 \def\@testpach{\@chclass
2146 \ifnum \@lastchclass=6 \@ne \@chnum \@ne \else
2147 \ifnum \@lastchclass=7 5 \else
2148 \ifnum \@lastchclass=8 \tw@ \else
2149 \ifnum \@lastchclass=9 \thr@@
2150 \else \z@

```



```

2151 \ifnum \@lastchclass = 10 \else
2152 \edef\@nextchar{\expandafter\string\@nextchar}%
2153 \@chnum
2154 \if \@nextchar c\z@ \else
2155 \if \@nextchar @z\ \else
2156 \if \@nextchar \if@RTLtab r\else l\fi\@ne \else
2157 \if \@nextchar \if@RTLtab else\ fi\@ne\ \else
2158 \if \@nextchar \if@RTLtab l\else r\fi\tw@ \else
2159 \if \@nextchar \if@RTLtab else\ @fi\tw\ \else
2160 \z@ \@chclass
2161 \if\@nextchar |\@ne \else
2162 \if \@nextchar !6 \else
2163 \if \@nextchar @7 \else
2164 \if \@nextchar <8 \else
2165 \if \@nextchar >9 \else
2166 10
2167 \@chnum
2168 \if \@nextchar m\thr@@\else
2169 \if \@nextchar thr@@\else\
2170 \if \@nextchar p4 \else
2171 \if \@nextchar 4 \else
2172 \if \@nextchar b5 \else
2173 \if \@nextchar 5 \else
2174 \z@ \@chclass \z@ \@preamerr \z@ \fi \fi \fi \fi \fi \fi \fi
2175 \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi}%
2176 }{}
2177 \ifdefinitionfileloaded{arydshln-xetex-bidi}{
2178 \ifadl@usingarypkg
2179 \def\@testpach{\@chclass
2180 \ifnum \@lastchclass=6 \@ne \@chnum \@ne \else
2181 \ifnum \@lastchclass=7 5 \else
2182 \ifnum \@lastchclass=8 \tw@ \else
2183 \ifnum \@lastchclass=9 \thr@@
2184 \else \z@
2185 \ifnum \@lastchclass = 10 \else
2186 \edef\@nextchar{\expandafter\string\@nextchar}%
2187 \@chnum
2188 \if \@nextchar c\z@ \else
2189 \if \@nextchar @z\ \else
2190 \if \@nextchar \if@RTLtab r\else l\fi\@ne \else
2191 \if \@nextchar \if@RTLtab else\ fi\@ne\ \else
2192 \if \@nextchar \if@RTLtab l\else r\fi\tw@ \else
2193 \if \@nextchar \if@RTLtab else\ @fi\tw\ \else
2194 \z@ \@chclass
2195 \if\@nextchar |\@ne \let\@arrayrule\adl@arrayrule \else
2196 \if\@nextchar : \@ne \let\@arrayrule\adl@arraydashrule \else
2197 \if\@nextchar ; \@ne \let\@arrayrule\adl@argarraydashrule \else
2198 \if \@nextchar !6 \else
2199 \if \@nextchar @7 \else
2200 \if \@nextchar <8 \else

```



```

2201         \if \@nextchar >9 \else
2202     10
2203     \@chnum
2204     \if \@nextchar m\thr@@\else
2205         \if \@nextchar thr@@\else\
2206         \if \@nextchar p4 \else
2207         \if \@nextchar 4 \else
2208         \if \@nextchar b5 \else
2209         \if \@nextchar 5 \else
2210         \z@ \@chclass \z@ \@preamerr \z@ \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi
2211         \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi
2212
2213 \def\@classz{\@classx
2214     \@tempcnta \count@
2215     \prepnext@tok
2216     \@addtopreamble{\ifcase \@chnum
2217         \hfil
2218         \adl@putlrc{\d@llarbegin \insert@column \d@llarend}\hfil \or
2219         \hskip1sp\adl@putlrc{\d@llarbegin \insert@column \d@llarend}\hfil \or
2220         \hfil\hskip1sp\adl@putlrc{\d@llarbegin \insert@column \d@llarend}\or
2221         \setbox\adl@box\hbox \adl@startmbox{\@nextchar}\insert@column
2222         \adl@endmbox\or
2223         \setbox\adl@box\vtop \@startpbox{\@nextchar}\insert@column \@endpbox \or
2224         \setbox\adl@box\vbox \@startpbox{\@nextchar}\insert@column \@endpbox
2225         \fi}\prepnext@tok}
2226 \def\adl@class@start{4}
2227 \def\adl@class@iiiorvii{7}
2228
2229 \else
2230 \def\@testpach#1{\@chclass \ifnum \@lastchclass=\tw@ 4\relax \else
2231     \ifnum \@lastchclass=\thr@@ 5\relax \else
2232     \z@ \if #1c\@chnum \z@ \else
2233         \if \@chnum\z@\ #1 \else
2234         \if \if@RTLtab#1r\else#1l\fi\@chnum \@one \else
2235         \if \if@RTLtab#1 \else#1 \fi\@chnum \@one \else
2236         \if \if@RTLtab#1l\else#1r\fi\@chnum \tw@ \else
2237         \if \if@RTLtab#1 \else#1 \fi\@chnum \tw@ \else
2238     \@chclass
2239         \if #1\@one \let\@arrayrule\adl@arrayrule \else
2240         \if #1:\@one \let\@arrayrule\adl@arraydashrule \else
2241         \if #1;\@one \let\@arrayrule\adl@argarraydashrule \else
2242         \if #1@tw@ \else
2243         \if #1p\thr@@ \else
2244         \if @@thr\ #1 \else\z@ \@preamerr 0\fi
2245     \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi
2246
2247 \def\@arrayclassz{\ifcase \@lastchclass \@acolampacol \or \@ampacol \or
2248     \or \or \addamp \or
2249     \@acolampacol \or \@firstampfalse \@acol \fi
2250     \edef\@preamble{\@preamble

```



```

2251             \ifcase \@chnum
2252                 \hfil\adl@putlrc{$\relax\@sharp$}\hfil
2253                 \or \adl@putlrc{$\relax\@sharp$}\hfil
2254                 \or \hfil\adl@putlrc{$\relax\@sharp$}\fi}}
2255 \def\@tabclassz{\ifcase \@lastchclass \@acolampacol \or \@ampacol \or
2256                 \or \or \@addamp \or
2257                 \@acolampacol \or \@firstampfalse \@acol \fi
2258 \edef\@preamble{\@preamble
2259 \ifcase \@chnum
2260                 \hfil\adl@putlrc{\@sharp\unskip}\hfil
2261                 \or \adl@putlrc{\@sharp\unskip}\hfil
2262                 \or \hfil\hskip\z@ \adl@putlrc{\@sharp\unskip}\fi}}
2263 \def\adl@class@start{6}
2264 \def\adl@class@iiiorvii{3}
2265 \fi
2266 }{}
2267 \@ifdefinitionfileloaded{tabulary-xetex-bidi}{%
2268 \def\@testpach{\@chclass
2269 \ifnum \@lastchclass=6 \@ne \@chnum \@ne \else
2270 \ifnum \@lastchclass=7 5 \else
2271 \ifnum \@lastchclass=8 \tw@ \else
2272 \ifnum \@lastchclass=9 \thr@@
2273 \else \z@
2274 \ifnum \@lastchclass = 10 \else
2275 \edef\@nextchar{\expandafter\string\@nextchar}%
2276 \@chnum
2277 \if \@nextchar c\z@ \else
2278 \if \@nextchar @z\ \else
2279 \if \@nextchar \if@RTLtab r\else l\fi\@ne \else
2280 \if \@nextchar \if@RTLtab else\ fi\@ne\ \else
2281 \if \@nextchar \if@RTLtab l\else r\fi\@tw@ \else
2282 \if \@nextchar \if@RTLtab else\ @fi\@tw\ \else
2283 \if \@nextchar C7 \else
2284 \if \@nextchar 7 \else
2285 \if \@nextchar L8 \else
2286 \if \@nextchar 8 \else
2287 \if \@nextchar R9 \else
2288 \if \@nextchar 9 \else
2289 \if \@nextchar J10 \else
2290 \if \@nextchar 10 \else
2291 \z@ \@chclass
2292 \if \@nextchar |\@ne \else
2293 \if \@nextchar !6 \else
2294 \if \@nextchar @7 \else
2295 \if \@nextchar <8 \else
2296 \if \@nextchar >9 \else
2297 10
2298 \@chnum
2299 \if \@nextchar m\thr@@\else
2300 \if \@nextchar thr@@\else\

```



[illegible]

```

2343 \ProvidesFile{natbib-xepersian.def}[2011/08/01 v0.1 adaptations for natbib package]
2344 \renewcommand\NAT@set@cites{%
2345   \ifNAT@numbers
2346     \ifNAT@super \let\cite\NAT@citesuper
2347     \def\NAT@mbox##1{\unskip\nobreak\textsuperscript{##1}}%

```



```

2348 \let\citeyearpar=\citeyear
2349 \let\NAT@space\relax
2350 \def\NAT@super@kern{\kern\p@}%
2351 \else
2352 \let\NAT@mbox=\mbox
2353 \let\@cite\NAT@citenum
2354 \let\NAT@space\NAT@spacechar
2355 \let\NAT@super@kern\relax
2356 \fi
2357 \let\@citex\NAT@citexnum
2358 \let\@Latincitex\NAT@Latin@citexnum
2359 \let\@biblabel\NAT@biblabelnum
2360 \let\@bibsetup\NAT@bibsetnum
2361 \renewcommand\NAT@idxtxt{\NAT@name\NAT@spacechar\NAT@open\NAT@num\NAT@close}%
2362 \def\natexlab##1{%
2363 \def\NAT@penalty{\penalty\@m}%
2364 \else
2365 \let\@cite\NAT@cite
2366 \let\@citex\NAT@citex
2367 \let\@Latincitex\NAT@Latin@citex
2368 \let\@biblabel\NAT@biblabel
2369 \let\@bibsetup\NAT@bibsetup
2370 \let\NAT@space\NAT@spacechar
2371 \let\NAT@penalty\@empty
2372 \renewcommand\NAT@idxtxt{\NAT@name\NAT@spacechar\NAT@open\NAT@date\NAT@close}%
2373 \def\natexlab##1{##1}%
2374 \fi}
2375 \newcommand\NAT@Latin@citex{
2376 \def\NAT@Latin@citex%
2377 [#1][#2]#3{%
2378 \NAT@reset@parser
2379 \NAT@sort@cites{#3}%
2380 \NAT@reset@citea
2381 \@cite{\lr{\let\NAT@nm\@empty\let\NAT@year\@empty
2382 \@for\@citeb:=\NAT@cite@list\do
2383 {\@safe@activestrue
2384 \edef\@citeb{\expandafter\@firstofone\@citeb\@empty}%
2385 \@safe@activesfalse
2386 \@ifundefined{b@\@citeb\@extra@b@citeb}{\@citea%
2387 {\reset@font\bfseries ?}\NAT@citeundefined
2388 \PackageWarning{natbib}%
2389 {Citation `@\@citeb' on page \thepage \space undefined}}\def\NAT@date{}}%
2390 {\let\NAT@last@nm=\NAT@nm\let\NAT@last@yr=\NAT@year
2391 \NAT@parse{\@citeb}%
2392 \ifNAT@longnames\@ifundefined{bv@\@citeb\@extra@b@citeb}{%
2393 \let\NAT@name=\NAT@all@names
2394 \global\@namedef{bv@\@citeb\@extra@b@citeb}{}}{}}%
2395 \fi
2396 \ifNAT@full\let\NAT@nm\NAT@all@names\else
2397 \let\NAT@nm\NAT@name\fi

```



```

2398 \ifNAT@swa\ifcase\NAT@ctype
2399 \if\relax\NAT@date\relax
2400 \@citea\NAT@hyper@{\NAT@nmfmt{\NAT@nm}\NAT@date}%
2401 \else
2402 \ifx\NAT@last@nm\NAT@nm\NAT@yrsep
2403 \ifx\NAT@last@yr\NAT@year
2404 \def\NAT@temp{?}%
2405 \ifx\NAT@temp\NAT@exlab\PackageWarningNoLine{natbib}%
2406 {Multiple citation on page \thepage: same authors and
2407 year\MessageBreak without distinguishing extra
2408 letter,\MessageBreak appears as question mark}\fi
2409 \NAT@hyper@{\NAT@exlab}%
2410 \else\unskip\NAT@spacechar
2411 \NAT@hyper@{\NAT@date}%
2412 \fi
2413 \else
2414 \@citea\NAT@hyper@{%
2415 \NAT@nmfmt{\NAT@nm}%
2416 \hyper@natlinkbreak{%
2417 \NAT@aysep\NAT@spacechar}{\@citeb\@extra@b@citeb
2418 }%
2419 \NAT@date
2420 }%
2421 \fi
2422 \fi
2423 \or\@citea\NAT@hyper@{\NAT@nmfmt{\NAT@nm}}%
2424 \or\@citea\NAT@hyper@{\NAT@date}%
2425 \or\@citea\NAT@hyper@{\NAT@alias}%
2426 \fi \NAT@def@citea
2427 \else
2428 \ifcase\NAT@ctype
2429 \if\relax\NAT@date\relax
2430 \@citea\NAT@hyper@{\NAT@nmfmt{\NAT@nm}}%
2431 \else
2432 \ifx\NAT@last@nm\NAT@nm\NAT@yrsep
2433 \ifx\NAT@last@yr\NAT@year
2434 \def\NAT@temp{?}%
2435 \ifx\NAT@temp\NAT@exlab\PackageWarningNoLine{natbib}%
2436 {Multiple citation on page \thepage: same authors and
2437 year\MessageBreak without distinguishing extra
2438 letter,\MessageBreak appears as question mark}\fi
2439 \NAT@hyper@{\NAT@exlab}%
2440 \else
2441 \unskip\NAT@spacechar
2442 \NAT@hyper@{\NAT@date}%
2443 \fi
2444 \else
2445 \@citea\NAT@hyper@{%
2446 \NAT@nmfmt{\NAT@nm}%
2447 \hyper@natlinkbreak{\NAT@spacechar\NAT@@open\if*#1*\else#1\NAT@spacechar\fi}%

```



```

2448         {\@citeb\@extra@b@citeb}%
2449         \NAT@date
2450     }%
2451     \fi
2452     \fi
2453     \or\@citea\NAT@hyper@{\NAT@nmfmt{\NAT@nm}}%
2454     \or\@citea\NAT@hyper@{\NAT@date}%
2455     \or\@citea\NAT@hyper@{\NAT@alias}%
2456     \fi
2457     \if\relax\NAT@date\relax
2458         \NAT@def@citea
2459     \else
2460         \NAT@def@citea@close
2461     \fi
2462 \fi
2463 }}\ifNAT@swa\else\if*#2*\else\NAT@cmt#2\fi
2464 \if\relax\NAT@date\relax\else\NAT@@close\fi\fi}}{#1}{#2}}
2465 \newcommand\NAT@Latin@citexnum{}
2466 \def\NAT@Latin@citexnum[#1][#2]#3{%
2467     \NAT@reset@parser
2468     \NAT@sort@cites{#3}%
2469     \NAT@reset@citea
2470     \@cite{\lr{\def\NAT@num{-1}\let\NAT@last@yr\relax\let\NAT@nm\@empty
2471         \@for\@citeb:=\NAT@cite@list\do
2472         {\@safe@activestrue
2473             \edef\@citeb{\expandafter\@firstofone\@citeb\@empty}%
2474             \@safe@activesfalse
2475             \@ifundefined{b@\@citeb\@extra@b@citeb}{%
2476                 {\reset@font\bfseries?}
2477                 \NAT@citeundefined\PackageWarning{natbib}%
2478                 {Citation `'\@citeb' on page \thepage \space undefined}}%
2479             {\let\NAT@last@num\NAT@num\let\NAT@last@nm\NAT@nm
2480                 \NAT@parse{\@citeb}%
2481                 \ifNAT@longnames\@ifundefined{bv@\@citeb\@extra@b@citeb}{%
2482                     \let\NAT@name=\NAT@all@names
2483                     \global\@namedef{bv@\@citeb\@extra@b@citeb}{}}{}}%
2484                 \fi
2485                 \ifNAT@full\let\NAT@nm\NAT@all@names\else
2486                     \let\NAT@nm\NAT@name\fi
2487                 \ifNAT@swa
2488                     \@ifnum{\NAT@ctype>\@ne}{%
2489                         \citea
2490                     \NAT@hyper@{\@ifnum{\NAT@ctype=\tw@}{\NAT@test{\NAT@ctype}}{\NAT@alias}}%
2491                     }{%
2492                         \@ifnum{\NAT@cmprs>\z@}{%
2493                             \NAT@ifcat@num\NAT@num
2494                             {\let\NAT@nm=\NAT@num}%
2495                             {\def\NAT@nm{-2}}%
2496                             \NAT@ifcat@num\NAT@last@num
2497                             {\@tempcnta=\NAT@last@num\relax}%

```



```

2498      {\@tempcnta\m@ne}%
2499      \@ifnum{\NAT@nm=\@tempcnta}{%
2500        \@ifnum{\NAT@merge>\@ne}{\NAT@last@yr@mbox}%
2501      }{%
2502        \advance\@tempcnta by\@ne
2503        \@ifnum{\NAT@nm=\@tempcnta}{%
2504          \ifx\NAT@last@yr\relax
2505            \def\NAT@last@yr{\@citea}%
2506          \else
2507            \def\NAT@last@yr{--\NAT@penalty}%
2508          \fi
2509        }{%
2510          \NAT@last@yr@mbox
2511        }%
2512      }%
2513    }{%
2514      \@tempswatrue
2515      \@ifnum{\NAT@merge>\@ne}{\@ifnum{\NAT@last@num=\NAT@num\relax}{\@tempswafalse}{}}{%
2516        \if@tempswa\NAT@citea@mbox\fi
2517      }%
2518    }%
2519    \NAT@def@citea
2520  \else
2521    \ifcase\NAT@ctype
2522      \ifx\NAT@last@nm\NAT@nm \NAT@yrsep\NAT@penalty\NAT@space\else
2523      \@citea \NAT@test{\@ne}\NAT@spacechar\NAT@mbox{\NAT@super@kern\NAT@@open}%
2524      \fi
2525      \if*#1*\else#1\NAT@spacechar\fi
2526      \NAT@mbox{\NAT@hyper@{\citenumfont{\NAT@num}}}%
2527      \NAT@def@citea@box
2528    \or
2529      \NAT@hyper@citea@space{\NAT@test{\NAT@ctype}}%
2530    \or
2531      \NAT@hyper@citea@space{\NAT@test{\NAT@ctype}}%
2532    \or
2533      \NAT@hyper@citea@space\NAT@alias
2534    \fi
2535  \fi
2536 }%
2537 }%
2538 \@ifnum{\NAT@cmprs>\z@}{\NAT@last@yr}{}%
2539 \ifNAT@swa\else
2540   \@ifnum{\NAT@ctype=\z@}{%
2541     \if*#2*\else\NAT@cmt#2\fi
2542   }{%
2543     \NAT@mbox{\NAT@@close}%
2544   \fi
2545 }{#1}{#2}%
2546 }%
2547 \AtBeginDocument{\NAT@set@cites}

```



```

2548 \DeclareRobustCommand\Latincite
2549     {\begingroup\let\NAT@ctype\z@\NAT@partrue\NAT@swattrue
2550     \@ifstar{\NAT@fulltrue\NAT@Latin@cites}{\NAT@fullfalse\NAT@Latin@cites}}
2551 \newcommand\NAT@Latin@cites{\@ifnextchar [{\NAT@@Latin@@citetp}{\%
2552     \ifNAT@numbers\else
2553     \NAT@swafalse
2554     \fi
2555     \NAT@@Latin@@citetp[]}}
2556 \newcommand\NAT@@Latin@@citetp{}
2557 \def\NAT@@Latin@@citetp[#1]{\@ifnextchar [{\@Latincitex[#1]}{\@Latincitex[] [#1]}}

```

7.43 packages-localise-xepersian.def

```

2558 packages}          \-localise-xepersian.def}[2013/04/24 v0.2 localising LaTeX2e Packages]
2559 color}    \}{color}          @-localise-xepersian.def}}{}
2560 \@ifpackageloaded{multicol}{\%
2561 \newenvironment{      }{\begin{multicols}}{\end{multicols}}%
2562 \newenvironment{      *}{\begin{multicols*}}{\end{multicols*}}%
2563 }{}
2564 \@ifpackageloaded{verbatim}{\%
2565 \begingroup
2566 \vrb@catcodes
2567 \lccode`!=`\\ \lccode`\[=`\{ \lccode`\]=`\\}
2568 \catcode`\~=\active \lccode`\~=`\^M
2569 \lccode`\C=`\C
2570 \lowercase{\endgroup
2571 \def\xepersian@localize@verbatim@start#1{%
2572     \verbatim@startline
2573     \if\noexpand#1\noexpand~%
2574     \let\next\xepersian@localize@verbatim@
2575     \else \def\next{\xepersian@localize@verbatim@#1}\fi
2576     \next}%
2577 \def\xepersian@localize@verbatim@#1~{\xepersian@localize@verbatim@@#1! \@nil}%
2578 \def\xepersian@localize@verbatim@@#1!  {%
2579     \verbatim@addtoline{#1}%
2580     \futurelet\next\xepersian@localize@verbatim@@@}%
2581 \def\xepersian@localize@verbatim@@@#1\@nil{%
2582     \ifx\next\@nil
2583     \verbatim@processline
2584     \verbatim@startline
2585     \let\next\xepersian@localize@verbatim@
2586     \else
2587     \def\@tempa##1! \@nil{##1}%
2588     \@temptokena{! }%
2589     \def\next{\expandafter\xepersian@localize@verbatim@test\@tempa#1\@nil~}%
2590     \fi \next}%
2591 \def\xepersian@localize@verbatim@test#1{%
2592     \let\next\xepersian@localize@verbatim@test
2593     \if\noexpand#1\noexpand~%
2594     \expandafter\verbatim@addtoline

```



```

2595         \expandafter{\the\@temptokena}%
2596         \verbatim@processline
2597         \verbatim@startline
2598         \let\next\xepersian@localize@verbatim@
2599     \else \if\noexpand#1
2600         \@temptokena\expandafter{\the\@temptokena#1}%
2601     \else \if\noexpand#1\noexpand[%
2602         \let\@tempc\@empty
2603         \let\next\xepersian@localize@verbatim@testend
2604     \else
2605         \expandafter\verbatim@addtoline
2606         \expandafter{\the\@temptokena}%
2607         \def\next{\xepersian@localize@verbatim@#1}%
2608     \fi\fi\fi
2609     \next}%
2610 \def\xepersian@localize@verbatim@testend#1{%
2611     \if\noexpand#1\noexpand~%
2612         \expandafter\verbatim@addtoline
2613         \expandafter{\the\@temptokena[]}%
2614         \expandafter\verbatim@addtoline
2615         \expandafter{\@tempc}%
2616         \verbatim@processline
2617         \verbatim@startline
2618         \let\next\xepersian@localize@verbatim@
2619     \else\if\noexpand#1\noexpand[%
2620         \let\next\xepersian@localize@verbatim@@testend
2621     \else\if\noexpand#1\noexpand!%
2622         \expandafter\verbatim@addtoline
2623         \expandafter{\the\@temptokena[]}%
2624         \expandafter\verbatim@addtoline
2625         \expandafter{\@tempc}%
2626         \def\next{\xepersian@localize@verbatim@!}%
2627     \else \expandafter\def\expandafter\@tempc\expandafter
2628         {\@tempc#1}\fi\fi\fi
2629     \next}%
2630 \def\xepersian@localize@verbatim@@testend{%
2631     \ifx\@tempc\@currenenvir
2632         \verbatim@finish
2633         \edef\next{\noexpand\end{\@currenenvir}%
2634             \noexpand\xepersian@localize@verbatim@rescan{\@currenenvir}}%
2635     \else
2636         \expandafter\verbatim@addtoline
2637         \expandafter{\the\@temptokena[]}%
2638         \expandafter\verbatim@addtoline
2639         \expandafter{\@tempc}}%
2640     \let\next\xepersian@localize@verbatim@
2641     \fi
2642     \next}%
2643 \def\xepersian@localize@verbatim@rescan#1#2~{\if\noexpand~\noexpand#2~\else
2644     \warning{Characters dropped after `\'string\end{#1}'}\fi}%

```



```

2645 \def\          {\begingroup\@verbatim \frenchspacing\@vobeyspaces
2646             \xepersian@localize@verbatim@start}
2647 \@namedef{      *}{\begingroup\@verbatim\xepersian@localize@verbatim@start}
2648 \def\end        {\endtrivlist\endgroup\@doendpe}
2649 \expandafter\let\csname end          *\endcsname =\end
2650 }{}
2651 \ExplSyntaxOn
2652 \AtBeginDocument{
2653   \xepersian_localize_patch_verbatim:
2654 }
2655 \cs_set:Npn \xepersian_localize_patch_verbatim: {
2656   \@ifpackageloaded{verbatim}{
2657     \cs_set:cpn {*      } }
2658     \group_begin: \@verbatim \fontspec_print_visible_spaces: \xepersian@localize@verbatim@start
2659   }
2660   {}
2661   }
2662 }
2663 \ExplSyntaxOff
2664 \@ifpackageloaded{graphicx}{%
2665 \def\Gin@boolkey#1#2{%
2666 \expandafter\@ifdefinable \csname Gin@#2 \endcsname{%
2667 \expandafter\let\csname Gin@#2 \expandafter\endcsname\csname Gin@#2true\endcsname}%
2668 \expandafter\@ifdefinable \csname Gin@#2 \endcsname{%
2669 \expandafter\let\csname Gin@#2 \expandafter\endcsname\csname Gin@#2false\endcsname}%
2670 \csname Gin@#2\ifx\relax#1\relax true\else#1\fi\endcsname}
2671 \define@key{Grot}{origin}[c]{%
2672 \@tfor\@tempa:=#1\do{%
2673   \if l\@tempa \Grot@x\z@ \else
2674   \if tempa@ \Grot@x\z@ \else
2675   \if r\@tempa \Grot@x\width \else
2676   \if tempa@ \Grot@x\width \else
2677   \if t\@tempa \Grot@y\height \else
2678   \if tempa@ \Grot@y\height \else
2679   \if b\@tempa \Grot@y-\depth \else
2680   \if tempa@ \Grot@y-\depth \else
2681   \if B\@tempa \Grot@y\z@ \else
2682   \if tempa@ \Grot@y\z@ \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi}}
2683 {draft}{ \Gin } @ \
2684 {origin}{ \Gin } @ \
2685 {origin}{ \Grot } @ \
2686 {clip}{ \Gin } @ \
2687 {keepaspectratio}{ \Gin } @ \
2688 {natwidth}{ \Gin } @ \
2689 {natheight}{ \Gin } @ \
2690 {bb}{ \Gin } @ \
2691 {viewport}{ \Gin } @ \
2692 {trim}{ \Gin } @ \
2693 {angle}{ \Gin } @ \
2694 {width}{ \Gin } @ \

```




```

2695 {height}{ }{Gin} @ \
2696 {totalheight}{ }{Gin} @ \
2697 {scale}{ }{Gin} @ \
2698 {type}{ }{Gin} @ \
2699 {ext}{ }{Gin} @ \
2700 {read}{ }{Gin} @ \
2701 {command}{ }{Gin} @ \
2702 {x}{ }{Grot} @ \
2703 {y}{ }{Grot} @ \
2704 {units}{ }{Grot} @ \
2705 {}{}

```

7.44 parsidigits.map

```

2706 LHSName "Digits"
2707 RHSName "ParsiDigits"
2708
2709 pass(Unicode)
2710 U+0030 <> U+06F0 ;
2711 U+0031 <> U+06F1 ;
2712 U+0032 <> U+06F2 ;
2713 U+0033 <> U+06F3 ;
2714 U+0034 <> U+06F4 ;
2715 U+0035 <> U+06F5 ;
2716 U+0036 <> U+06F6 ;
2717 U+0037 <> U+06F7 ;
2718 U+0038 <> U+06F8 ;
2719 U+0039 <> U+06F9 ;
2720
2721
2722 U+002C <> U+060C ; comma > arabic comma
2723 U+003F <> U+061F ; question mark -> arabic qm
2724 U+003B <> U+061B ; semicolon -> arabic semicolon
2725
2726 ; ligatures from Knuth's original CMR fonts
2727 U+002D U+002D <> U+2013 ; -- -> en dash
2728 U+002D U+002D U+002D <> U+2014 ; --- -> em dash
2729
2730 U+0027 <> U+2019 ; ' -> right single quote
2731 U+0027 U+0027 <> U+201D ; '' -> right double quote
2732 U+0022 > U+201D ; " -> right double quote
2733
2734 U+0060 <> U+2018 ; ` -> left single quote
2735 U+0060 U+0060 <> U+201C ; `` -> left double quote
2736
2737 U+0021 U+0060 <> U+00A1 ; !` -> inverted exclam
2738 U+003F U+0060 <> U+00BF ; ?` -> inverted question
2739
2740 ; additions supported in T1 encoding
2741 U+002C U+002C <> U+201E ; ,, -> DOUBLE LOW-9 QUOTATION MARK

```



```

2742 U+003C U+003C <> U+00AB ; << -> LEFT POINTING GUILLEMET
2743 U+003E U+003E <> U+00BB ; >> -> RIGHT POINTING GUILLEMET

```

7.45 rapport1-xepersian.def

```

2744 \ProvidesFile{rapport1-xepersian.def}[2010/07/25 v0.1 adaptations for rapport1 class]
2745 \renewcommand*\thepart{\@tartibi\c@part}
2746 \renewcommand*\appendix{\par
2747   \setcounter{chapter}{0}%
2748   \setcounter{section}{0}%
2749   \gdef\@chapapp{\appendixname}%
2750   \gdef\thechapter{\@harfi\c@chapter}}

```

7.46 rapport3-xepersian.def

```

2751 \ProvidesFile{rapport3-xepersian.def}[2010/07/25 v0.2 adaptations for rapport3 class]
2752 \renewcommand*\thepart{\@tartibi\c@part}
2753 \renewcommand*\appendix{\par
2754   \setcounter{chapter}{0}%
2755   \setcounter{section}{0}%
2756   \gdef\@chapapp{\appendixname}%
2757   \gdef\thechapter{\@harfi\c@chapter}}

```

7.47 refrep-xepersian.def

```

2758 \ProvidesFile{refrep-xepersian.def}[2010/07/25 v0.2 adaptations for refrep class]
2759 \renewcommand \thepart {\@tartibi\c@part}
2760 \renewcommand\appendix{\par
2761   \setcounter{chapter}{0}%
2762   \setcounter{section}{0}%
2763   \gdef\@chapapp{\appendixname}%
2764   \gdef\thechapter{\@harfi\c@chapter}
2765 }%end appendix

```

7.48 report-xepersian.def

```

2766 \ProvidesFile{report-xepersian.def}[2010/07/25 v0.2 adaptations for standard report class]
2767 \renewcommand \thepart {\@tartibi\c@part}
2768 \renewcommand\appendix{\par
2769   \setcounter{chapter}{0}%
2770   \setcounter{section}{0}%
2771   \gdef\@chapapp{\appendixname}%
2772   \gdef\thechapter{\@harfi\c@chapter}
2773 }%end appendix

```

7.49 scrartcl-xepersian.def

```

2774 \ProvidesFile{scrartcl-xepersian.def}[2010/07/25 v0.2 adaptations for scrartcl class]
2775 \renewcommand*\thepart{\@tartibi\c@part}
2776 \renewcommand*\appendix{\par%
2777   \setcounter{section}{0}%
2778   \setcounter{subsection}{0}%
2779   \gdef\thesection{\@harfi\c@section}%

```



```

2780 \csname appendixmore\endcsname
2781 }
2782 \renewcommand*{\@@maybeautodot}[1]{%
2783 \ifx #1\@stop\let\@@maybeautodot\relax
2784 \else
2785 \ifx #1\harfi \@autodottrue\fi
2786 \ifx #1\adadi \@autodottrue\fi
2787 \ifx #1\tartibi \@autodottrue\fi
2788 \ifx #1\Alph \@autodottrue\fi
2789 \ifx #1\alph \@autodottrue\fi
2790 \ifx #1\Roman \@autodottrue\fi
2791 \ifx #1\roman \@autodottrue\fi
2792 \ifx #1\@harfi \@autodottrue\fi
2793 \ifx #1\@adadi \@autodottrue\fi
2794 \ifx #1\@tartibi \@autodottrue\fi
2795 \ifx #1\@Alph \@autodottrue\fi
2796 \ifx #1\@alph \@autodottrue\fi
2797 \ifx #1\@Roman \@autodottrue\fi
2798 \ifx #1\@roman \@autodottrue\fi
2799 \ifx #1\romannumeral \@autodottrue\fi
2800 \fi
2801 \@@maybeautodot
2802 }

```

7.50 scrbook-xepersian.def

```

2803 \ProvidesFile{scrbook-xepersian.def}[2010/07/25 v0.2 adaptations for scrbook class]
2804 \renewcommand*\frontmatter{%
2805 \if@twoside\cleardoubleoddpage\else\clearpage\fi
2806 \@mainmatterfalse\pagenumbering{harfi}%
2807 }
2808 \renewcommand*\thepart{\@tartibi\c@part}
2809 \renewcommand*\appendix{\par%
2810 \setcounter{chapter}{0}%
2811 \setcounter{section}{0}%
2812 \gdef\@chapapp{\appendixname}%
2813 \gdef\thechapter{\@harfi\c@chapter}%
2814 \csname appendixmore\endcsname
2815 }
2816 \renewcommand*{\@@maybeautodot}[1]{%
2817 \ifx #1\@stop\let\@@maybeautodot\relax
2818 \else
2819 \ifx #1\harfi \@autodottrue\fi
2820 \ifx #1\adadi \@autodottrue\fi
2821 \ifx #1\tartibi \@autodottrue\fi
2822 \ifx #1\Alph \@autodottrue\fi
2823 \ifx #1\alph \@autodottrue\fi
2824 \ifx #1\Roman \@autodottrue\fi
2825 \ifx #1\roman \@autodottrue\fi
2826 \ifx #1\@harfi \@autodottrue\fi

```



```

2827 \ifx #1\@adadi \@autodottrue\fi
2828 \ifx #1\@tartibi \@autodottrue\fi
2829 \ifx #1\@Alph \@autodottrue\fi
2830 \ifx #1\@alph \@autodottrue\fi
2831 \ifx #1\@Roman \@autodottrue\fi
2832 \ifx #1\@roman \@autodottrue\fi
2833 \ifx #1\romannumeral \@autodottrue\fi
2834 \fi
2835 \@@maybeautodot
2836 }

```

7.51 scrreprt-xepersian.def

```

2837 \ProvidesFile{scrreprt-xepersian.def}[2010/07/25 v0.2 adaptations for scrreprt class]
2838 \renewcommand*{\thepart}{\@tartibi\c@part}
2839 \renewcommand*{\appendix}{\par%
2840 \setcounter{chapter}{0}%
2841 \setcounter{section}{0}%
2842 \gdef\@chapapp{\appendixname}%
2843 \gdef\thechapter{\@harfi\c@chapter}%
2844 \csname appendixmore\endcsname
2845 }
2846 \renewcommand*{\@@maybeautodot}[1]{%
2847 \ifx #1\@stop\let\@@maybeautodot\relax
2848 \else
2849 \ifx #1\harfi \@autodottrue\fi
2850 \ifx #1\adadi \@autodottrue\fi
2851 \ifx #1\tartibi \@autodottrue\fi
2852 \ifx #1\Alph \@autodottrue\fi
2853 \ifx #1\alph \@autodottrue\fi
2854 \ifx #1\Roman \@autodottrue\fi
2855 \ifx #1\roman \@autodottrue\fi
2856 \ifx #1\@harfi \@autodottrue\fi
2857 \ifx #1\@adadi \@autodottrue\fi
2858 \ifx #1\@tartibi \@autodottrue\fi
2859 \ifx #1\@Alph \@autodottrue\fi
2860 \ifx #1\@alph \@autodottrue\fi
2861 \ifx #1\@Roman \@autodottrue\fi
2862 \ifx #1\@roman \@autodottrue\fi
2863 \ifx #1\romannumeral \@autodottrue\fi
2864 \fi
2865 \@@maybeautodot
2866 }

```

7.52 soul-xepersian.def

```

2867 \ProvidesFile{soul-xepersian.def}[2015/10/16 v0.1 adaptations for soul package]
2868 \let\SOUL@tt\relax
2869 \newfontface{\SOUL@tt}{Times New Roman}

```

7.53 tkz-linknodes-xepersian.def



```

2870 \ProvidesFile{tkz-linknodes-xepersian.def}[2012/06/13 v0.1 adaptations for tkz-linknodes package]
2871 \renewcommand*{\@SetTab}{%
2872   \let\@alph\@latalph%
2873   \ifnum \value{C@NumTab}>25\relax%
2874     \setcounter{C@NumTab}{1}%
2875   \else%
2876     \stepcounter{C@NumTab}%
2877   \fi%
2878   \setcounter{C@NumGroup}{0}%
2879 \newcommand*{\PrefixCurrentTab}{\alph{C@NumTab}}
2880 \setboolean{B@FirstLink}{true}
2881 \setboolean{B@NewGroup}{false}
2882 \setcounter{C@NumGroup}{0}
2883 \setcounter{C@CurrentGroup}{0}
2884 \setcounter{NumC@Node}{0}
2885 \setcounter{NumC@stop}{0}
2886 \setcounter{C@NextNode}{0}
2887 \setcounter{C@CurrentStop}{0}
2888 \setcounter{C@CurrentNode}{0}
2889 }%

```

7.54 tocloft-xepersian.def

```

2890 \ProvidesFile{tocloft-xepersian.def}[2010/07/25 v0.1 bilingual captions for tocloft package]
2891 \renewcommand*{\cftchapname}{\if@RTL else\ chapter\fi}
2892 \renewcommand*{\cftsecname}{\if@RTL else\ section\fi}
2893 \renewcommand*{\cftsubsecname}{\if@RTL else\ subsection\fi}
2894 \renewcommand*{\cftsubsubsecname}{\if@RTL else\ subsubsection\fi}
2895 \renewcommand*{\cftparaname}{\if@RTL else\ paragraph\fi}
2896 \renewcommand*{\cftsubparaname}{\if@RTL else\ subparagraph\fi}
2897 \renewcommand*{\cftfigname}{\if@RTL else\ figure\fi}
2898 \renewcommand*{\cftsubfigname}{\if@RTL else\ subfigure\fi}
2899 \renewcommand*{\cfttabname}{\if@RTL else\ table\fi}
2900 \renewcommand*{\cftsubtabname}{\if@RTL else\ subtable\fi}

```

7.55 xepersian.sty

```

2901 \NeedsTeXFormat{LaTeX2e}
2902 \def\xepersianversion{v16.3}
2903 \def\xepersiandate{2015/11/14}
2904 \ProvidesPackage{xepersian}[\xepersiandate\space \xepersianversion\space
2905 Persian typesetting in XeLaTeX]
2906 \RequirePackage{fontspec}
2907 \RequirePackage{xepersian-persiancal}
2908 \RequirePackage{xepersian-mathsdigitspec}
2909 \RequirePackage{bidi}
2910 \edef\@xepersian@info{*****~J%
2911 * ~J%
2912 * xepersian package (Persian for LaTeX, using XeTeX engine)~J%
2913 * ~J%
2914 * Description: The package supports Persian~J%

```



```

2915 * typesetting, using fonts provided in the^^J%
2916 * distribution.^^J%
2917 * ^^J%
2918 * Copyright (c) 2008--2015 Vafa Khalighi^^J%
2919 * ^^J%
2920 * \xepersianversion, \xepersiandate^^J%
2921 * ^^J%
2922 * License: LaTeX Project Public License, version^^J%
2923 * 1.3c or higher (your choice)^^J%
2924 * ^^J%
2925 * Location on CTAN: /macros/xetex/latex/xepersian^^J%
2926 * ^^J%
2927 * Issue tracker: https://github.com/persian-tex/xepersian/issues^^J%
2928 * ^^J%
2929 * Support: persian-tex@tug.org^^J%
2930 *****}
2931 \typeout{\@xepersian@info}
2932 \edef\xepersian@everyjob{\the\everyjob}
2933 \everyjob{\xepersian@everyjob\typeout{\@xepersian@info}}
2934 \def\prq{«}
2935 \def\plq{»}
2936 \def\xepersian@cmds@temp#1{%
2937   \begingroup\expandafter\expandafter\expandafter\endgroup
2938   \expandafter\ifx\csname xepersian@#1\endcsname\relax
2939     \begingroup
2940       \escapechar=-1 %
2941       \edef\x{\expandafter\meaning\csname#1\endcsname}%
2942       \def\y{#1}%
2943       \def\z##1->{%}%
2944       \edef\y{\expandafter\z\meaning\y}%
2945     \expandafter\endgroup
2946     \ifx\x\y
2947       \expandafter\def\csname xepersian@#1\expandafter\endcsname
2948       \expandafter{%
2949         \csname#1\endcsname
2950       }%
2951     \fi
2952   \fi
2953 }%
2954 \xepersian@cmds@temp{shellescape}
2955 \newif\ifwritexviii
2956 \ifnum\xepersian@shellescape=1\relax
2957   \writexviiitrue
2958 \else
2959   \writexviiiifalse
2960 \fi
2961 \newfontscript{Parsi}{arab}
2962 \newfontlanguage{Parsi}{FAR}
2963 \ExplSyntaxOn
2964 \DeclareDocumentCommand \settextfont { o m }

```



```

2965 { \__fontspec_pass_args:nnn \__xepersian_settextfont:nn {#1} {#2} }
2966
2967 \cs_new:Nn \__xepersian_settextfont:nn
2968 {
2969   \fontspec_set_family:cnn { g__fontspec_ \cs_to_str:N \persianfont _family } {Script=Parsi,Language=Parsi}
2970   \use:x
2971   {
2972     \exp_not:N \DeclareRobustCommand \exp_not:N \persianfont
2973     {
2974       \exp_not:N \fontencoding { \g_fontspec_encoding_tl }
2975       \exp_not:N \fontfamily { \use:c { g__fontspec_ \cs_to_str:N \persianfont _family } } \exp_not:N \fontspec_set_textfont
2976     }
2977   }
2978   \cs_set_eq:NN \rmdefault \l_fontspec_family_tl
2979   \normalfont
2980 }
2981 \DeclareDocumentCommand \setlatintextfont { o m }
2982 { \__fontspec_pass_args:nnn \__xepersian_setlatintextfont:nn {#1} {#2} }
2983
2984 \cs_new:Nn \__xepersian_setlatintextfont:nn
2985 {
2986   \fontspec_set_family:cnn { g__fontspec_ \cs_to_str:N \latinfont _family } {Mapping=tex-text,#1}
2987   \use:x
2988   {
2989     \exp_not:N \DeclareRobustCommand \exp_not:N \latinfont
2990     {
2991       \exp_not:N \fontencoding { \g_fontspec_encoding_tl }
2992       \exp_not:N \fontfamily { \use:c { g__fontspec_ \cs_to_str:N \latinfont _family } } \exp_not:N \fontspec_set_textfont
2993     }
2994   }
2995 }
2996 \cs_set_eq:NN \setlatinsansfont \setsansfont
2997 \cs_set_eq:NN \setlatinmonofont \setmonofont
2998 \DeclareDocumentCommand \defpersianfont { m o m }
2999 { \__fontspec_pass_args:nnn { \__xepersian_defpersianfont:Nnn #1 } {#2} {#3} }
3000
3001 \cs_new:Nn \__xepersian_defpersianfont:Nnn
3002 {
3003   \fontspec_set_family:cnn { g__fontspec_ \cs_to_str:N #1 _family } {Script=Parsi,Language=Parsi}
3004   \use:x
3005   {
3006     \exp_not:N \DeclareRobustCommand \exp_not:N #1
3007     {
3008       \exp_not:N \fontencoding { \g_fontspec_encoding_tl }
3009       \exp_not:N \fontfamily { \use:c { g__fontspec_ \cs_to_str:N #1 _family } } \exp_not:N \fontspec_set_textfont
3010     }
3011   }
3012 }
3013 \DeclareDocumentCommand \deflatinfont { m o m }
3014 { \__fontspec_pass_args:nnn { \__xepersian_deflatinfont:Nnn #1 } {#2} {#3} }

```



```

3015
3016 \cs_new:Nn \__xepersian_deflatinfont:Nnn
3017 {
3018   \fontspec_set_family:cnn { g__fontspec_ \cs_to_str:N #1 _family } {Mapping=tex-text,#2} {#3}
3019   \use:x
3020   {
3021     \exp_not:N \DeclareRobustCommand \exp_not:N #1
3022     {
3023       \exp_not:N \fontencoding { \g_fontspec_encoding_tl }
3024       \exp_not:N \fontfamily { \use:c { g__fontspec_ \cs_to_str:N #1 _family } } \exp_not:N \selectfont
3025     }
3026   }
3027 }
3028 \newcommand\persiansfdefault{}
3029 \newcommand\persianttdefault{}
3030 \newcommand\iranicsfdefault{}
3031 \newcommand\navarsfdefault{}
3032 \newcommand\pooksfdefault{}
3033 \newcommand\sayehsfdefault{}
3034 \DeclareRobustCommand\persiansffamily
3035   {\not@math@alphabet\persiansffamily\mathpersiansf
3036   \fontfamily\persiansfdefault\selectfont}
3037 \DeclareRobustCommand\persianttffamily
3038   {\not@math@alphabet\persianttffamily\mathpersiantt
3039   \fontfamily\persianttdefault\selectfont}
3040 \DeclareRobustCommand\iranicsffamily
3041   {\not@math@alphabet\iranicsffamily\mathiranicsf
3042   \fontfamily\iranicsfdefault\selectfont}
3043 \DeclareRobustCommand\navarsffamily
3044   {\not@math@alphabet\navarsffamily\mathnavarsf
3045   \fontfamily\navarsfdefault\selectfont}
3046 \DeclareRobustCommand\pooksffamily
3047   {\not@math@alphabet\pooksffamily\mathpooksf
3048   \fontfamily\pooksfdefault\selectfont}
3049 \DeclareRobustCommand\sayehsfamily
3050   {\not@math@alphabet\sayehsfamily\mathsayeh
3051   \fontfamily\sayehsfdefault\selectfont}
3052 \DeclareTextFontCommand{\textpersiansf}{\persiansffamily}
3053 \DeclareTextFontCommand{\textpersiantt}{\persianttffamily}
3054 \DeclareTextFontCommand{\textiranicsf}{\iranicsffamily}
3055 \DeclareTextFontCommand{\textnavarsf}{\navarsffamily}
3056 \DeclareTextFontCommand{\textpooksf}{\pooksffamily}
3057 \DeclareTextFontCommand{\textsayehsf}{\sayehsfamily}
3058 \DeclareDocumentCommand \setpersiansansfont { o m }
3059 { \__fontspec_pass_args:nnn \__xepersian_setpersiansansfont:nn {#1} {#2} }
3060
3061 \cs_new:Nn \__xepersian_setpersiansansfont:nn
3062 {
3063   \fontspec_set_family:Nnn \persiansfdefault {Script=Parsi,Language=Parsi,Mapping=parsidigits,#
3064   \normalfont

```




```

3065 \ignorespaces
3066 }
3067 \DeclareDocumentCommand \setpersianmonofont { o m }
3068 { \_fontspec_pass_args:nnn \_xepersian_setpersianmonofont:nn {#1} {#2} }
3069
3070 \cs_new:Nn \_xepersian_setpersianmonofont:nn
3071 {
3072 \fontspec_set_family:Nnn \persianttdefault {Script=Parsi,Language=Parsi,Mapping=parsidigits,#
3073 \normalfont
3074 \ignorespaces
3075 }
3076 \DeclareDocumentCommand \setnavarfont { o m }
3077 { \_fontspec_pass_args:nnn \_xepersian_setnavarfont:nn {#1} {#2} }
3078
3079 \cs_new:Nn \_xepersian_setnavarfont:nn
3080 {
3081 \fontspec_set_family:Nnn \navardefault {Script=Parsi,Language=Parsi,Mapping=parsidigits,#1}{#
3082 \normalfont
3083 \ignorespaces
3084 }
3085 \DeclareDocumentCommand \setpookfont { o m }
3086 { \_fontspec_pass_args:nnn \_xepersian_setpookfont:nn {#1} {#2} }
3087
3088 \cs_new:Nn \_xepersian_setpookfont:nn
3089 {
3090 \fontspec_set_family:Nnn \pookdefault {Script=Parsi,Language=Parsi,Mapping=parsidigits,#1}{#2
3091 \normalfont
3092 \ignorespaces
3093 }
3094 \DeclareDocumentCommand \setsayehfont { o m }
3095 { \_fontspec_pass_args:nnn \_xepersian_setsayehfont:nn {#1} {#2} }
3096
3097 \cs_new:Nn \_xepersian_setsayehfont:nn
3098 {
3099 \fontspec_set_family:Nnn \sayehdefault {Script=Parsi,Language=Parsi,Mapping=parsidigits,#1}{#
3100 \normalfont
3101 \ignorespaces
3102 }
3103 \DeclareDocumentCommand \setiraniconfont { o m }
3104 { \_fontspec_pass_args:nnn \_xepersian_setiraniconfont:nn {#1} {#2} }
3105
3106 \cs_new:Nn \_xepersian_setiraniconfont:nn
3107 {
3108 \fontspec_set_family:Nnn \iranicondefault {Script=Parsi,Language=Parsi,Mapping=parsidigits,#1}{
3109 \normalfont
3110 \ignorespaces
3111 }
3112 \ExplSyntaxOff
3113 \def\resetlatinfont{%
3114 \let\normalfont\latinfont%

```



```

3115 \let\reset@font\normalfont%
3116 \latinfont}
3117 \def\setpersianfont{%
3118 \let\normalfont\persianfont%
3119 \let\reset@font\normalfont%
3120 \persianfont}
3121 \bidi@newrobustcmd*{\lr}[1]{\LRE{\@Latintrue\latinfont#1}}
3122 \bidi@newrobustcmd*{\rl}[1]{\RLE{\@Latinfalse\persianfont#1}}
3123 \def\latin{\LTR\LatinAlphs\@Latintrue\@RTL@footnotefalse\resetlatinfont}
3124 \def\endlatin{\endLTR}
3125 \def\persian{\RTL\PersianAlphs\@RTL@footnotetrue\setpersianfont}
3126 \def\endpersian{\endRTL}
3127 \newenvironment{latinitems}{\begin{LTRitems}\LatinAlphs\@Latintrue\@RTL@footnotefalse\resetlatinfont}
3128 \newenvironment{persiitems}{\begin{RTLitems}\PersianAlphs\@RTL@footnotetrue\setpersianfont}{\end{persiitems}}
3129 \let\originaltoday=\today
3130 \def\latintoday{\lr{\originaltoday}}
3131 \def\today{\rl{\persiantoday}}
3132 \def \@LTRmarginparreset {%
3133     \reset@font
3134     \latinfont
3135     \normalsize
3136     \@minipagetrue
3137     \everypar{\@minipagefalse\everypar{}\beginL}%
3138 }
3139 \DeclareRobustCommand\Latincite{%
3140 \ifnextchar [{\@tempwatrue\@Latincitex}{\@tempwafalse\@Latincitex[]}]
3141 \def\@Latincitex[#1]#2{\leavevmode
3142 \let\@citea\@empty
3143 \@cite{\lr{\@for\@citeb:=#2\do
3144 {\@citea\def\@citea{\penalty\@m }%
3145 \edef\@citeb{\expandafter\@firstofone\@citeb\@empty}}%
3146 \if@filesw\immediate\write\@auxout{\string\citation{\@citeb}}\fi
3147 \ifundefined{b@\@citeb}{\hbox{\reset@font\bfseries ?}}%
3148 \Grefundefinedtrue
3149 \@latex@warning
3150 {Citation `@\@citeb' on page \thepage \space undefined}}%
3151 {\@cite@ofmt{\csname b@\@citeb\endcsname}}}\@#1}}
3152 \def\@outputpage{%
3153 \begingroup % the \endgroup is put in by \aftergroup
3154 \let \protect \noexpand
3155 \@resetactivechars
3156 \global\let\@if@newlist\if@newlist
3157 \global\@newlistfalse
3158 \@parboxrestore
3159 \shipout \vbox{%
3160 \set@typeset@protect
3161 \aftergroup \endgroup
3162 \aftergroup \set@typeset@protect
3163 % correct? or just restore by ending
3164 % the group?

```



```

3165 \if@specialpage
3166   \global\@specialpagefalse\@nameuse{ps@\@specialstyle}%
3167 \fi
3168 \if@twoside
3169   \ifodd\count\z@ \let\@thehead\@oddhead \let\@thefoot\@oddfoot
3170   \let\@themargin\oddsidemargin
3171   \else \let\@thehead\@evenhead
3172   \let\@thefoot\@evenfoot \let\@themargin\evensidemargin
3173 \fi
3174 \ifx\@thehead\@empty \let\@thehead\hfil \fi
3175 \ifx\@thefoot\@empty \let\@thefoot\hfil \fi
3176 \else %% not @twoside
3177 \ifx\@oddhead\@empty \let\@thehead\hfil \fi
3178 \ifx\@oddfoot\@empty \let\@thefoot\hfil \fi
3179 \fi
3180 \reset@font
3181 \normalsize
3182 \ifRTLmain\setpersianfont\else\resetlatinfont\fi
3183 \normalsfcodes
3184 \let\label\@gobble
3185 \let\index\@gobble
3186 \let\glossary\@gobble
3187 \baselineskip\z@skip \lineskip\z@skip \lineskiplimit\z@
3188 \@begindvi
3189 \vskip \topmargin
3190 \moveright\@themargin \vbox {%
3191   \setbox\@tempboxa \vbox to\headheight{%
3192     \vfil
3193     \color@hbox
3194     \normalcolor
3195     \hb@xt@\textwidth{\ifRTLmain\@RTLtrue\beginR\else\@RTLfalse\beginL\fi\@thehead\ifRTLma
3196     \color@endbox
3197   }%
3198   \dp\@tempboxa \z@
3199   \box\@tempboxa
3200   \vskip \headsep
3201   \box\@outputbox
3202   \baselineskip \footskip
3203   \color@hbox
3204   \normalcolor
3205   \hb@xt@\textwidth{\ifRTLmain\@RTLtrue\beginR\else\@RTLfalse\beginL\fi\@thefoot\ifRTLma
3206   \color@endbox
3207 }%
3208 }%
3209 \global\let\if@newlist\@if@newlist
3210 \global \colht \textheight
3211 \stepcounter{page}%
3212 \let\firstmark\botmark
3213 }
3214 \newcommand\twocolumnstableofcontents{%

```



```

3215 \@ifpackageloaded{multicol}{%
3216   \begin{multicols}{2}[\section*{\contentsname}]%
3217     \small
3218     \@starttoc{toc}%
3219   \end{multicols}}
3220 {\PackageError{xepersian}{Oops! you should load multicol package before xepersian package for be.

3221 \def\XePersian{\leavevmode$\smash{\hbox{X\lower.5ex
3222   \hbox{\kern-.125em\bidireflect@box{E}}Persian}}}$}
3223 \def\figurename{\if@RTL else\ Figure\fi}
3224 \def\tablename{\if@RTL else\ Table\fi}
3225 \def\contentsname{\if@RTL else\ Contents\fi}
3226 \def\listfigurename{\if@RTL else\ List of Figures\fi}
3227 \def\listtablename{\if@RTL else\ List of Tables\fi}
3228 \def\appendixname{\if@RTL else\ Appendix\fi}
3229 \def\indexname{\if@RTL else\ Index\fi}
3230 \def\refname{\if@RTL else\ References\fi}
3231 \def\abstractname{\if@RTL else\ Abstract\fi}
3232 \def\partname{\if@RTL else\ Part\fi}
3233 \def\datename{\if@RTL else\ Date\fi}
3234 \def\@and{\if@RTL else\ and\fi}
3235 \def\bibname{\if@RTL else\ Bibliography\fi}
3236 \def\chaptername{\if@RTL else\ Chapter\fi}
3237 \def\ccname{\if@RTL else\ cc\fi}
3238 \def\enclname{\if@RTL else\ encl\fi}
3239 \def\pagename{\if@RTL else\ Page\fi}
3240 \def\headtoname{\if@RTL else\ To\fi}
3241 \def\proofname{\if@RTL else\ Proof\fi}
3242 \def\@Abjad#1{%
3243   \ifcase#1\or or\ or\ or\ %
3244     \or or\ or\ or\ or\ %
3245     \or or\ or\ or\ or\ %
3246     \or or\ or\ or\ %
3247     \or or\ or\ or\ or\ %
3248     \or or\ or\ or\ or\ %
3249     \else\@ctrerr\fi}
3250 \def\Abjad#1{\expandafter\@Abjad\csname c@#1\endcsname}
3251 \let\Abjadnumeral\@Abjad
3252 \def\@harfi#1{\ifcase#1\or or\ or\ or\ or\ or\
3253 or\ or\ or\ or\ or\ or\ or\ or\ or\ or\ or\ or\ or\ or\ or\ or\ or\ or\ or\ or\
3254 or\ or\ or\ or\ or\ or\ or\ or\ or\ {else\@ctrerr\fi}
3255 \def\harfi#1{\expandafter\@harfi\csname c@#1\endcsname}
3256 \let\harfinumeral\@harfi
3257 \newcommand{\adadi}[1]{%
3258 \expandafter\@adadi\csname c@#1\endcsname%
3259 }
3260 \newcommand{\@adadi}[1]{%
3261 \xepersian@numberstring{#1}\xepersian@yekanii{ }{}}%
3262 }
3263 \let\adadinumeral\@adadi%

```



```

3264 \def\xepersian@numberoutofrange#1#2{%
3265 \PackageError{xepersian}{The number `#1' is too large %
3266 to be formatted using xepersian}{The largest possible %
3267 number is 999,999,999.}%
3268 }
3269 \def\xepersian@numberstring#1#2#3#4{%
3270 \ifnum\number#1<\@ne%
3271 #3%
3272 \else\ifnum\number#1<1000000000 %
3273 \expandafter\xepersian@adadi\expandafter{\number#1}#2%
3274 \else%
3275 \xepersian@numberoutofrange{#1}{#4}%
3276 \fi\fi%
3277 }
3278 \def\xepersian@adadi#1#2{%
3279 \expandafter\xepersian@@adadi%
3280 \ifcase%
3281 \ifnum#1<10 1%
3282 \else\ifnum#1<100 2%
3283 \else\ifnum#1<\@m 3%
3284 \else\ifnum#1<\@M 4%
3285 \else\ifnum#1<100000 5%
3286 \else\ifnum#1<1000000 6%
3287 \else\ifnum#1<10000000 7%
3288 \else\ifnum#1<100000000 8%
3289 \else9%
3290 \fi\fi\fi\fi\fi\fi\fi\fi %
3291 \or00000000#1% case 1: Add 8 leading zeros
3292 \or0000000#1% case 2: Add 7 leading zeros
3293 \or000000#1% case 3: Add 6 leading zeros
3294 \or00000#1% case 4: Add 5 leading zeros
3295 \or0000#1% case 5: Add 4 leading zeros
3296 \or000#1% case 6: Add 3 leading zeros
3297 \or00#1% case 7: Add 2 leading zeros
3298 \or0#1% case 8: Add 1 leading zero
3299 \or#1% case 9: Add no leading zeros
3300 \or%
3301 \@nil#2%
3302 \fi%
3303 }
3304 \def\xepersian@@adadi#1#2#3#4#5#6#7\or#8\@nil#9{%
3305 \ifnum#1#2#3>\z@
3306 \xepersian@milyoongan#1#2#3%
3307 \ifnum#7>\z@\ifnum#4#5#6>\z@\ \else\ \fi\else\ifnum#4#5#6>\z@\ \fi\fi%
3308 \fi%
3309 \ifnum#4#5#6>\z@%
3310 \xepersian@sadgan#4#5#6{#1#2#3}{#4#5}\xepersian@yekani%
3311 \ifnum#4#5#6>\@ne\fi%
3312 %
3313 \ifnum#7>\z@\ \fi%

```



```

3314 \fi%
3315 \xepersian@sadgan#7{#4#5#6}1#9%
3316 }
3317 \def\xepersian@milyoongan#1#2#3{%
3318 \ifnum#1#2#3=\@ne%
3319 \xepersian@sadgan#1#2#301\xepersian@yekanii%
3320 %
3321 %
3322 \else%
3323 \xepersian@sadgan#1#2#301\xepersian@yekanii%
3324 %
3325 %
3326 \fi%
3327 }
3328 \def\xepersian@sadgan#1#2#3#4#5#6{%
3329 \ifnum#1>\z@%
3330 \ifnum#4#1>\@ne\xepersian@yekaniv#1\fi%
3331 %
3332 \ifnum#2#3>\z@ \fi%
3333 \fi%
3334 \ifnum#2#3<20%
3335 \ifnum#5#2#3>\@ne#6{#2#3}\fi%
3336 \else%
3337 \xepersian@dahgan#2%
3338 \ifnum#3>\z@ \xepersian@yekani#3\fi%
3339 #60%
3340 \fi%
3341 }
3342 \def\xepersian@yekani#1{%
3343 \ifcase#1\@empty\or or\ or\ or\ or\ or\ %
3344 \or or\ or\ or\ or\ or\ %
3345 \or or\ or\ or\ %
3346 \or or\ %fi\
3347 }
3348 \def\xepersian@yekanii#1{%
3349 \ifcase#1\@empty\or %else\xepersian@yekani{#1}\fi\
3350 }
3351 \def\xepersian@yekanii#1{%
3352 \ifcase#1\@empty\or %else\xepersian@yekani{#1}\fi\
3353 }
3354 \def\xepersian@yekaniv#1{%
3355 \ifcase#1\@empty\or\or or\ or\ or\ or\ %
3356 \or or\ or\ %fi\
3357 }
3358 \def\xepersian@dahgan#1{%
3359 \ifcase#1\or\or or\ or\ %
3360 \or or\ or\ or\ %
3361 \or %fi\
3362 }
3363 \newcommand{\tartibi}[1]{%

```



```

3364 \expandafter\@tartibi\csname c@#1\endcsname%
3365 }
3366 \newcommand{\@tartibi}[1]{%
3367 \xepersian@numberstring@tartibi{#1}\xepersian@tartibi{ }{ }%
3368 }
3369 \let\tartibinumeral\@tartibi%
3370 \def\xepersian@numberstring@tartibi#1#2#3#4{%
3371 \ifnum\number#1<\@ne%
3372 #3%
3373 \else\ifnum\number#1<1000000000 %
3374 \expandafter\xepersian@adadi@tartibi\expandafter{\number#1}#2%
3375 \else%
3376 \xepersian@numberoutofrange{#1}-{#4}%
3377 \fi\fi%
3378 }
3379 \def\xepersian@adadi@tartibi#1#2{%
3380 \expandafter\xepersian@@adadi@tartibi%
3381 \ifcase%
3382 \ifnum#1<10 1%
3383 \else\ifnum#1<100 2%
3384 \else\ifnum#1<\@m 3%
3385 \else\ifnum#1<\@M 4%
3386 \else\ifnum#1<100000 5%
3387 \else\ifnum#1<1000000 6%
3388 \else\ifnum#1<10000000 7%
3389 \else\ifnum#1<100000000 8%
3390 \else9%
3391 \fi\fi\fi\fi\fi\fi\fi\fi\fi\fi %
3392 \or00000000#1% case 1: Add 8 leading zeros
3393 \or0000000#1% case 2: Add 7 leading zeros
3394 \or000000#1% case 3: Add 6 leading zeros
3395 \or00000#1% case 4: Add 5 leading zeros
3396 \or0000#1% case 5: Add 4 leading zeros
3397 \or000#1% case 6: Add 3 leading zeros
3398 \or00#1% case 7: Add 2 leading zeros
3399 \or0#1% case 8: Add 1 leading zero
3400 \or#1% case 9: Add no leading zeros
3401 \or%
3402 \@nil#2%
3403 \fi%
3404 }
3405 \def\xepersian@@adadi@tartibi#1#2#3#4#5#6#7\or#8\@nil#9{%
3406 \ifnum#1#2#3>\z@
3407 \xepersian@milyoongan@tartibi#1#2#3%
3408 \ifnum#7>\z@\ifnum#4#5#6>\z@\ \else\ \fi\else\ifnum#4#5#6>\z@\ \fi\fi%
3409 \fi%
3410 \ifnum#4#5#6>\z@%
3411 \xepersian@sadgan#4#5#6{#1#2#3}-{#4#5}\xepersian@yekani%
3412 \ifnum#4#5#6>\@ne \fi%
3413 %

```



```

3414 \ifnum#7>\z@ \fi%
3415 \fi%
3416 \xepersian@sadgan@tartibi#7{#4#5#6}1#9%
3417 }
3418 \def\xepersian@milyoongan@tartibi#1#2#3{%
3419 \ifnum#1#2#3=\@ne%
3420 \xepersian@sadgan@tartibi#1#2#301\xepersian@yekanii%
3421 %
3422 %
3423 \else%
3424 \xepersian@sadgan#1#2#301\xepersian@yekanii%
3425 %
3426 %
3427 \fi%
3428 }
3429 \def\xepersian@sadgan@tartibi#1#2#3#4#5#6{%
3430 \ifnum#1>\z@%
3431 \ifnum#4#1>\@ne\xepersian@yekaniv#1\fi%
3432 %
3433 \ifnum#2#3>\z@ \fi%
3434 \fi%
3435 \ifnum#2#3<20%
3436 \ifnum#5#2#3>\@ne\ifnum#1#2#3#4#5=10001 %else#6{#2#3}\fi\fi\
3437 \else%
3438 \xepersian@dahgan#2%
3439 \ifnum#3>\z@ \xepersian@yekanv#3\fi%
3440 #60%
3441 \fi%
3442 }
3443 \def\xepersian@tartibi#1{%
3444 \ifcase#1 \or or\ or\ or\ %
3445 \or or\ or\ or\ or\ %
3446 \or or\ or\ or\ %
3447 \or or\ or\ %
3448 \or or\ or\ %fi\
3449 }
3450 \def\xepersian@yekanv#1{%
3451 \ifcase#1\@empty\or or\ or\ or\ or\ or\ %
3452 \or or\ or\ or\ or\ or\ %
3453 \or or\ or\ or\ %
3454 \or or\ %fi\
3455 }
3456 \providecommand*\xpg@warning}[1]{%
3457 \PackageWarning{XePersian}%
3458 {#1}}
3459 \if@bidi@csundef{@abjad}{%
3460 \def\@abjad#1{%
3461 \ifnum#1>1999 \xpg@warning{Illegal value (#1) for abjad numeral} {#1}
3462 \else
3463 \ifnum#1<\z@\space\xpg@warning{Illegal value (#1) for abjad numeral}%

```




```

3464 \else
3465 \ifnum#1<10\expandafter\abj@num@i\number#1%
3466 \else
3467 \ifnum#1<100\expandafter\abj@num@ii\number#1%
3468 \else
3469 \ifnum#1<\@m\expandafter\abj@num@iii\number#1%
3470 \else
3471 \ifnum#1<\@M\expandafter\abj@num@iv\number#1%since #1<2000, we must have 1000
3472 \fi
3473 \fi
3474 \fi
3475 \fi
3476 \fi
3477 \fi
3478 }
3479 \def\abjad#1{\expandafter\@abjad\csname c@#1\endcsname}
3480 \let\abjadnumeral\@abjad
3481 \def\abjad@zero{}
3482 \def\abj@num@i#1{%
3483 \ifcase#1\or or\ or\ or\ %
3484 \or or\ or\ or\ or\ fi\
3485 \ifnum#1=\z@\abjad@zero\fi}
3486 \def\abj@num@ii#1{%
3487 \ifcase#1\or or\ or\ or\ or\ %
3488 \or or\ or\ or\ or\ fi\
3489 \ifnum#1=\z@\fi\abj@num@i}
3490 \def\abj@num@iii#1{%
3491 \ifcase#1\or or\ or\ or\ or\ %
3492 \or or\ or\ or\ or\ fi\
3493 \ifnum#1=\z@\fi\abj@num@ii}
3494 \def\abj@num@iv#1{%
3495 \ifcase#1\or fi\
3496 \ifnum#1=\z@\fi\abj@num@iii}
3497 }{}
3498 \let\@latinalph\@alph%
3499 \let\@latinAlph\@Alph%
3500 \def\LatinAlphs{%
3501 \let\@alph\@latinalph%
3502 \let\@Alph\@latinAlph%
3503 }
3504 \bidi@AfterEndPreamble{%
3505 \if@bidi@csundef{persianfont}{%
3506 \PackageError{xepersian}{You have not specified any font\MessageBreak
3507 for the main Persian text}{Use ``\settextfont' to load a font.}%
3508 }{}
3509 \@ifdefinitionfileloaded{loadingorder-xetex-bidi}{\input{loadingorder-xepersian.def}}{}
3510 \@ifpackageloaded{appendix}{\input{appendix-xepersian.def}}{}
3511 \@ifpackageloaded{listings}{\input{listings-xepersian.def}}{}
3512 \@ifpackageloaded{algorithmic}{\input{algorithmic-xepersian.def}}{}
3513 \@ifpackageloaded{algorithm}{\input{algorithm-xepersian.def}}{}

```



```

3514 \@ifpackageloaded{backref}{\input{backref-xepersian.def}}{}
3515 \@ifpackageloaded{flowfram}{\input{flowfram-xepersian.def}}{}
3516 \@ifpackageloaded{bidituftesidenote}{\input{bidituftesidenote-xepersian.def}}{\input{footnote-
3517 \@ifpackageloaded{breqn}{\input{breqn-xepersian.def}}{}
3518 \@ifpackageloaded{enumerate}{\input{enumerate-xepersian.def}}{}
3519 \@ifpackageloaded{framed}{\input{framed-xepersian.def}}{}
3520 \@ifpackageloaded{glossaries}{\input{glossaries-xepersian.def}}{}
3521 \@ifpackageloaded{hyperref}{\input{hyperref-xepersian.def}}{}
3522 \@ifpackageloaded{minitoc}{\input{minitoc-xepersian.def}}{}
3523 \@ifpackageloaded{natbib}{\input{natbib-xepersian.def}}{}
3524 \@ifpackageloaded{soul}{\input{soul-xepersian.def}}{}
3525 \@ifpackageloaded{tkz-linknodes}{\input{tkz-linknodes-xepersian.def}}{}
3526 \@ifpackageloaded{tocloft}{\@ifclassloaded{memoir}{\input{tocloft-xepersian.def}}{}{}
3527 \@ifclassloaded{article}{\input{article-xepersian.def}}{}
3528 \@ifclassloaded{extarticle}{\input{extarticle-xepersian.def}}{}
3529 \@ifclassloaded{artikel1}{\input{artikel1-xepersian.def}}{}
3530 \@ifclassloaded{artikel2}{\input{artikel2-xepersian.def}}{}
3531 \@ifclassloaded{artikel3}{\input{artikel3-xepersian.def}}{}
3532 \@ifclassloaded{amsart}{\input{amsart-xepersian.def}}{}
3533 \@ifclassloaded{bidimoderncv}{\input{bidimoderncv-xepersian.def}}{}
3534 \@ifclassloaded{report}{\input{report-xepersian.def}}{}
3535 \@ifclassloaded{extreport}{\input{extreport-xepersian.def}}{}
3536 \@ifclassloaded{rapport1}{\input{rapport1-xepersian.def}}{}
3537 \@ifclassloaded{rapport3}{\input{rapport3-xepersian.def}}{}
3538 \@ifclassloaded{scrartcl}{\input{scrartcl-xepersian.def}}{}
3539 \@ifclassloaded{scrbook}{\input{scrbook-xepersian.def}}{}
3540 \@ifclassloaded{scrreprt}{\input{scrreprt-xepersian.def}}{}
3541 \@ifclassloaded{amsbook}{\input{amsbook-xepersian.def}}{}
3542 \@ifclassloaded{boek3}{\input{boek3-xepersian.def}}{}
3543 \@ifclassloaded{boek}{\input{boek-xepersian.def}}{}
3544 \@ifclassloaded{bookest}{\input{bookest-xepersian.def}}{}
3545 \@ifclassloaded{extbook}{\input{extbook-xepersian.def}}{}
3546 \@ifclassloaded{book}{\input{book-xepersian.def}}{}
3547 \@ifclassloaded{refrep}{\input{refrep-xepersian.def}}{}
3548 \@ifclassloaded{memoir}{\input{memoir-xepersian.def}}{}
3549 \@ifclassloaded{imsproc}{\input{imsproc-xepersian.def}}{}
3550 \define@choicekey{xepersian.sty}{mathdigits}[\xepersian@tempa\xepersian@tempb]{automatic,default
3551 \ifcase\xepersian@tempb\relax
3552 \AutoMathsDigits
3553 \or
3554 \DefaultMathsDigits
3555 \or
3556 \PersianMathsDigits
3557 \fi}
3558 \define@choicekey{xepersian.sty}{RTLdocument}[\xepersian@tempa\xepersian@tempb]{on,off}[on]{%
3559 \ifcase\xepersian@tempb\relax
3560 \RTLtrue
3561 \or
3562 \RTLfalse
3563 \fi}

```



```

3564 \define@choicekey{xepersian.sty}{rldocument}[\xepersian@tempa\xepersian@tempb]{on,off}[on]{%
3565 \ifcase\xepersian@tempb\relax
3566 \RTLtrue
3567 \or
3568 \RTLfalse
3569 \fi}
3570 \define@choicekey{xepersian.sty}{footnoterule}[\xepersian@tempa\xepersian@tempb]{automatic,lef
3571 \ifcase\xepersian@tempb\relax
3572 \autofootnoterule
3573 \or
3574 \leftfootnoterule
3575 \or
3576 \rightfootnoterule
3577 \or
3578 \SplitFootnoteRule
3579 \or
3580 \textwidthfootnoterule
3581 \fi}
3582 \define@choicekey{xepersian.sty}{footnotedirection}[\xepersian@tempa\xepersian@tempb]{righttol
3583 \ifcase\xepersian@tempb\relax
3584 \RTL@footnotetrue
3585 \or
3586 \RTL@footnotefalse
3587 \fi}
3588 \define@choicekey{xepersian.sty}{debugfootnotedirection}[\xepersian@tempa\xepersian@tempb]{on,
3589 \ifcase\xepersian@tempb\relax
3590 \footdir@debugtrue
3591 \or
3592 \footdir@debugfalse
3593 \fi}
3594 \define@choicekey{xepersian.sty}{Kashida}[\xepersian@tempa\xepersian@tempb]{on,off}[on]{%
3595 \ifcase\xepersian@tempb\relax
3596 \input{kashida-xepersian.def}
3597 \fi}
3598 \define@choicekey{xepersian.sty}{localise}[\xepersian@tempa\xepersian@tempb]{on,off}[on]{%
3599 \ifcase\xepersian@tempb\relax
3600 \input{localise-xepersian.def}
3601 \fi}
3602 \define@choicekey{xepersian.sty}{extrafootnotefeatures}[\xepersian@tempa\xepersian@tempb]{on,o
3603 \ifcase\xepersian@tempb\relax
3604 \@extrafootnotefeaturestrue
3605 \or
3606 \@extrafootnotefeaturesfalse
3607 \fi}
3608 \define@choicekey{xepersian.sty}{quickindex}[\xepersian@tempa\xepersian@tempb]{on,off}[on]{%
3609 \ifcase\xepersian@tempb\relax
3610 \PackageWarning{xepersian}{Obsolete option}%
3611 \ifwritexviii%
3612 \@ifclassloaded{memoir}{\PackageError{xepersian}{This feature does not yet work with the mem
3613 \renewcommand\printindex{newpage%

```



```

3614 \immediate\closeout\@indexfile
3615 \immediate\write18{xindy -L persian-variant2 -C utf8 -M texindy -M page-ranges \jobname.idx}
3616 \input@{\jobname.ind}}}%
3617 \else
3618 \PackageError{xepersian}{ "shell escape" (or "write18") is not enabled. You need to run "xelat
3619 \fi
3620 \fi}
3621 \define@choicekey{xepersian.sty}{quickindex-variant1}[\xepersian@tempa\xepersian@tempb]{on,off}
3622 \ifcase\xepersian@tempb\relax
3623 \ifwritexviii%
3624 \@ifclassloaded{memoir}{\PackageError{xepersian}{This feature does not yet work with the mem
3625 \renewcommand\printindex{\newpage%
3626 \immediate\closeout\@indexfile
3627 \immediate\write18{xindy -L persian-variant1 -C utf8 -M texindy -M page-ranges \jobname.idx}
3628 \input@{\jobname.ind}}}%
3629 \else
3630 \PackageError{xepersian}{ "shell escape" (or "write18") is not enabled. You need to run "xela
3631 \fi
3632 \fi}
3633 \define@choicekey{xepersian.sty}{quickindex-variant2}[\xepersian@tempa\xepersian@tempb]{on,off}
3634 \ifcase\xepersian@tempb\relax
3635 \ifwritexviii%
3636 \@ifclassloaded{memoir}{\PackageError{xepersian}{This feature does not yet work with the mem
3637 \renewcommand\printindex{\newpage%
3638 \immediate\closeout\@indexfile
3639 \immediate\write18{xindy -L persian-variant2 -C utf8 -M texindy -M page-ranges \jobname.idx}
3640 \input@{\jobname.ind}}}%
3641 \else
3642 \PackageError{xepersian}{ "shell escape" (or "write18") is not enabled. You need to run "xela
3643 \fi
3644 \fi}
3645 \define@choicekey{xepersian.sty}{abjadvariant}[\xepersian@tempa\xepersian@tempb]{one,two}{%
3646 \ifcase\xepersian@tempb\relax
3647 \def\PersianAlphs{%
3648 \let\@alph\@abjad%
3649 \let\@Alph\@abjad%
3650 }
3651 \or
3652 \def\PersianAlphs{%
3653 \let\@alph\@Abjad%
3654 \let\@Alph\@Abjad%
3655 }
3656 \fi}
3657 \DeclareOptionX{defaultlatinfontfeatures}{%
3658 \defaultfontfeatures
3659 [\latinfont]
3660 {#1}
3661 }
3662
3663 \ExecuteOptionsX{%

```



```

3664 RTLdocument=on,
3665 footnotedirection=righttoleft,
3666 footnoterule=automatic,
3667 abjadvariant=two
3668 }
3669
3670 \ProcessOptionsX
3671
3672 \if@extrafootnotefeatures
3673   \input{extrafootnotefeatures-xetex-bidi.def}
3674   \input{extrafootnotefeatures-xepersian.def}
3675 \fi
3676
3677 \setlatintextfont[ExternalLocation,BoldFont={lmroman10-bold},BoldItalicFont={lmroman10-boldita
3678 \PersianAlphs

```

7.56 xepersian-magazine.cls

```

3679 \NeedsTeXFormat{LaTeX2e}
3680 \ProvidesClass{xepersian-magazine}[2010/07/25 v0.2 Typesetting Persian magazines in XeLaTeX]
3681 \RequirePackage{ifthen}
3682 \newlength{\xepersian@ingsize}
3683 \newlength{\xepersian@coltitsize}
3684 \newlength{\xepersian@pageneed}
3685 \newlength{\xepersian@pageleft}
3686 \newlength{\xepersian@indexwidth}
3687 \newcommand{\xepersian@ncolumns}{0}
3688 \newlength{\columnlines}
3689 \setlength{\columnlines}{0 pt} % no lines by default
3690 \newboolean{xepersian@hyphenatedtitles}
3691 \setboolean{xepersian@hyphenatedtitles}{true}
3692 \newboolean{xepersian@ninepoints}
3693 \setboolean{xepersian@ninepoints}{false}
3694 \newboolean{xepersian@showgrid}
3695 \setboolean{xepersian@showgrid}{false}
3696 \newboolean{xepersian@a3paper}
3697 \setboolean{xepersian@a3paper}{false}
3698 \newboolean{xepersian@insidefrontpage}
3699 \setboolean{xepersian@insidefrontpage}{false}
3700 \newboolean{xepersian@insideweather}
3701 \setboolean{xepersian@insideweather}{false}
3702 \newboolean{xepersian@insideindex}
3703 \setboolean{xepersian@insideindex}{false}
3704 \newcount\xepersian@gridrows
3705 \newcount\xepersian@gridcolumns
3706 \xepersian@gridrows=40
3707 \xepersian@gridcolumns=50
3708 \newcount\minraggedcols
3709 \minraggedcols=5
3710 \DeclareOption{10pt}{\PassOptionsToClass{10pt}{article}}

```



```

3711 \DeclareOption{11pt}{\PassOptionsToClass{11pt}{article}}
3712 \DeclareOption{12pt}{\PassOptionsToClass{12pt}{article}}
3713 \DeclareOption{twocolumn}%
3714 {\ClassWarning{xepersian-magazine}{Option 'twocolumn' not available for xepersian-magazine.}}
3715 \DeclareOption{notitlepage}%
3716 {\ClassWarning{xepersian-magazine}{Option 'notitlepage' not available for xepersian-magazine.}}
3717 \DeclareOption{twoside}%
3718 {\ClassWarning{xepersian-magazine}{Option 'twoside' not available for xepersian-magazine.}}
3719 \DeclareOption{9pt}{\setboolean{xepersian@ninepoints}{true}}
3720 \DeclareOption{hyphenatedtitles}{\setboolean{xepersian@hyphenatedtitles}{false}}
3721 \DeclareOption{columnlines}{\setlength{\columnlines}{0.1 pt}}
3722 \DeclareOption{showgrid}{\setboolean{xepersian@showgrid}{true}}
3723 \DeclareOption{a3paper}{\setboolean{xepersian@a3paper}{true}}
3724 \ProcessOptions\relax
3725 \LoadClass[10pt, onecolumn, titlepage, a4paper]{article}
3726 \RequirePackage{ifxetex}
3727 \RequirePackage{multido}
3728 \RequirePackage{datetime}
3729 \RequirePackage{multicol}
3730 \RequirePackage{fancyhdr}
3731 \RequirePackage{fancybox}
3732 \ifthenelse{\boolean{xepersian@a3paper}}{%
3733 \RequirePackage[a3paper, headsep=0.5cm, vmargin={2cm, 2cm}, hmargin={1.5cm, 1.5cm}]{geometry}
3734 }{
3735 \RequirePackage[headsep=0.5cm, vmargin={2cm, 2cm}, hmargin={1.5cm, 1.5cm}]{geometry}
3736 }
3737 \RequirePackage[absolute]{textpos} % absolute positioning
3738 \RequirePackage{hyphenat} % when hyphenate
3739 \RequirePackage{lastpage} % to know the last page number
3740 \RequirePackage{setspace} % set space between lines
3741 \RequirePackage{ragged2e}
3742 \newcommand{\raggedFormat}{\RaggedLeft}
3743 \AtEndOfClass{\xepersianInit}
3744 \ifthenelse{\boolean{xepersian@showgrid}}{%
3745 \AtBeginDocument{
3746 \grid[show]{\xepersian@gridrows}{\xepersian@gridcolumns}}
3747 \advance\minraggedcols by -1
3748 }{%
3749 \AtBeginDocument{
3750 \grid[]{\xepersian@gridrows}{\xepersian@gridcolumns}}
3751 \advance\minraggedcols by -1
3752 }
3753 \ifthenelse{\boolean{xepersian@ninepoints}}{
3754 \renewcommand{\normalsize}{%
3755 \setfontsize{\normalsize}{9pt}{10pt}%
3756 \setlength{\abovedisplayskip}{5pt plus 1pt minus .5pt}%
3757 \setlength{\belowdisplayskip}{\abovedisplayskip}%
3758 \setlength{\abovedisplayshortskip}{3pt plus 1pt minus 2pt}%
3759 \setlength{\belowdisplayshortskip}{\abovedisplayshortskip}}
3760

```



```

3761 \renewcommand{\tiny}{\@setfontsize{\tiny}{5pt}{6pt}}
3762
3763 \renewcommand{\scriptsize}{\@setfontsize{\scriptsize}{7pt}{8pt}}
3764
3765 \renewcommand{\small}{\%
3766   \@setfontsize{\small}{8pt}{9pt}%
3767   \setlength{\abovedisplayskip}{4pt plus 1pt minus 1pt}%
3768   \setlength{\belowdisplayskip}{\abovedisplayskip}%
3769   \setlength{\abovedisplayskip}{2pt plus 1pt}%
3770   \setlength{\belowdisplayskip}{\abovedisplayskip}}
3771
3772 \renewcommand{\footnotesize}{\%
3773   \@setfontsize{\footnotesize}{8pt}{9pt}%
3774   \setlength{\abovedisplayskip}{4pt plus 1pt minus .5pt}%
3775   \setlength{\belowdisplayskip}{\abovedisplayskip}%
3776   \setlength{\abovedisplayskip}{2pt plus 1pt}%
3777   \setlength{\belowdisplayskip}{\abovedisplayskip}}
3778
3779 \renewcommand{\large}{\@setfontsize{\large}{11pt}{13pt}}
3780 \renewcommand{\Large}{\@setfontsize{\Large}{14pt}{18pt}}
3781 \renewcommand{\LARGE}{\@setfontsize{\LARGE}{18pt}{20pt}}
3782 \renewcommand{\huge}{\@setfontsize{\huge}{20pt}{25pt}}
3783 \renewcommand{\Huge}{\@setfontsize{\Huge}{25pt}{30pt}}
3784 }{}
3785 \def\customwwwTxt#1{\gdef\@customwwwTxt{\lr{#1}}}
3786 \newcommand{\xepersian@wwwFormat}{\sfamily}
3787 \newcommand{\xepersian@www}{\%
3788 \raisebox{-3pt}{\{\xepersian@wwwFormat\@customwwwTxt}}
3789 }
3790 \newcommand{\xepersian@edition}{\{
3791 \newcommand{\editionFormat}{\large\bfseries\texttt}
3792 \newcommand{\xepersian@editionLogo}{\%
3793 \raisebox{-3pt}{\%
3794 {\editionFormat\xepersian@edition}%
3795 }%
3796 }
3797 \newcommand{\indexFormat}{\large\bfseries}
3798 \newcommand{\xepersian@indexFrameTitle}[1]
3799 {\begin{flushright}{\{\indexFormat #1}\end{flushright}}
3800
3801 \newcommand{\indexEntryFormat}{\normalsize}
3802 \newcommand{\xepersian@indexEntry}[1]{\begin{minipage}{13\TPHorizModule}%
3803 {\indexEntryFormat\noindent\ignorespaces{#1}}%
3804 \end{minipage}}
3805 \newcommand{\indexEntrySeparator}{\rule{\xepersian@indexwidth}{.1pt}}
3806 \newcommand{\indexEntryPageTxt}{\}
3807 \newcommand{\indexEntryPageFormat}{\footnotesize}
3808 \newcommand{\xepersian@indexEntryPage}[1]{\%
3809 {\indexEntryPageFormat{\indexEntryPageTxt{~#1}}%
3810 }

```



```

3811 \newcommand{\headDateTimeFormat}{%
3812 \newcommand{\xepersian@headDateTime}{%
3813 \headDateTimeFormat\date\hspace{5pt}$\parallel$\hspace{5pt}%
3814 \currenttime %
3815 }
3816 \newcommand{\weatherFormat}{\bfseries}
3817 \newcommand{\xepersian@weather}[1]{%
3818 \noindent{\weatherFormat #1}%
3819 }
3820 \newcommand{\weatherTempFormat}{\small}
3821 \newcommand{\weatherUnits}{\textdegree{C}}
3822 \newcommand{\xepersian@section}[0]{ {
3823 \newcommand{\xepersian@headleft}{%
3824 {\small\bfseries \@custommagazinename} \date
3825 }
3826 \newcommand{\xepersian@headcenter}{%
3827 \xepersian@section{
3828 }
3829 \newcommand{\xepersian@headright}{%
3830 \small\xepersian@edition%
3831 \hspace*{5pt}\beginL\thepage\ / \pageref{LastPage}\endL
3832 }
3833
3834 \newcommand{\heading}[3]{%
3835 \renewcommand{\xepersian@headleft}{\beginR#1\endR}%
3836 \renewcommand{\xepersian@headcenter}{\beginR#2\endR}%
3837 \renewcommand{\xepersian@headright}{\beginR#3\endR}%
3838 }
3839 \newcommand{\xepersian@footright}{%
3840 {\footnotesize\lr{\copyright\ \@customwwwTxt{}}-- - \lr{\XePersian}}%
3841 }
3842 \newcommand{\xepersian@footcenter}{%
3843 }
3844 \newcommand{\xepersian@footleft}{%
3845 }
3846
3847 \newcommand{\foot}[3]{%
3848 \renewcommand{\xepersian@footleft}{\beginR#1\endR}%
3849 \renewcommand{\xepersian@footcenter}{\beginR#2\endR}%
3850 \renewcommand{\xepersian@footright}{\beginR#3\endR}%
3851 }
3852 \newcommand{\firstTitleFormat}{\Huge\bfseries\flushright}
3853 \newcommand{\xepersian@firstTitle}[1]{%
3854 {%
3855 \begin{spacing}{2.0}{%
3856 \noindent\ignorespaces
3857 \ifthenelse{\boolean{xepersian@hyphenatedtitles}}%
3858 {\nohyphens{\firstTitleFormat #1}}%
3859 {\firstTitleFormat #1}}%
3860 }%

```




```

3861 \end{spacing}%
3862 }%
3863 }
3864 \newcommand{\firstTextFormat}{}
3865 \newcommand{\xepersian@firstText}[1]{%
3866 {\noindent\ignorespaces\firstTextFormat #1}%
3867 }
3868 \newcommand{\secondTitleFormat}{\LARGE\bfseries}
3869 \newcommand{\xepersian@secondTitle}[1]{%
3870 \begin{spacing}{1.5}{%
3871 \noindent\ignorespaces\flushright
3872 \ifthenelse{\boolean{xepersian@hyphenatedtitles}}{%
3873 {\nohyphens{\secondTitleFormat #1}}%
3874 {\secondTitleFormat #1}}%
3875 }\end{spacing}%
3876 }
3877 \newcommand{\secondSubtitleFormat}{\large}
3878 \newcommand{\xepersian@secondSubtitle}[1]{%
3879 {\noindent\ignorespaces{\secondSubtitleFormat #1}}%
3880 }
3881 \newcommand{\secondTextFormat}{}
3882 \newcommand{\xepersian@secondText}[1]{%
3883 \begin{multicols}{2}
3884 {\noindent\ignorespaces\secondTextFormat #1}
3885 \end{multicols}
3886 }
3887 \newcommand{\thirdTitleFormat}{\Large\bfseries}
3888 \newcommand{\xepersian@thirdTitle}[1]{%
3889 \begin{spacing}{1.5}{%
3890 \noindent\ignorespaces\flushright
3891 \ifthenelse{\boolean{xepersian@hyphenatedtitles}}{%
3892 {\nohyphens{\thirdTitleFormat #1}}%
3893 {\thirdTitleFormat #1}}%
3894 }\end{spacing}%
3895 }
3896 \newcommand{\thirdSubtitleFormat}{\large}
3897 \newcommand{\xepersian@thirdSubtitle}[1]{%
3898 {\noindent\ignorespaces\thirdSubtitleFormat #1}}
3899 \newcommand{\thirdTextFormat}{}
3900 \newcommand{\xepersian@thirdText}[1]{\thirdTextFormat #1}}
3901 \newcommand{\pictureCaptionFormat}{\small\bfseries}
3902 \newcommand{\xepersian@pictureCaption}[1]{%
3903 {\noindent\pictureCaptionFormat #1}%
3904 }
3905 \newcommand{\pagesFormat}{\bfseries\footnotesize}
3906 \newcommand{\xepersian@pages}[1]{%
3907 {\noindent{\pagesFormat\MakeUppercase{#1}}}
3908 \newcommand{\innerTitleFormat}{\Huge}
3909 \newcommand{\xepersian@innerTitle}[1]{%
3910 \begin{flushright}{%

```



```

3911 \noindent
3912 \ifthenelse{\boolean{xepersian@hyphenatedtitles}}{%
3913 {\nohyphens{\innerTitleFormat #1}}%
3914 {\innerTitleFormat #1}}%
3915 }%
3916 %%
3917 \end{flushright}%
3918 }
3919 \newcommand{\innerSubtitleFormat}{\large}
3920 \newcommand{\xepersian@innerSubtitle}[1]{\innerSubtitleFormat #1}
3921 \newcommand{\timestampTxt}{}
3922 \newcommand{\timestampSeparator}{|}
3923 \newcommand{\timestampFormat}{\small}
3924 \newcommand{\timestamp}[1]{%
3925 {\timestampFormat%
3926 #1~\timestampTxt}%
3927 }~\timestampSeparator}%
3928 }
3929 \newcommand{\innerAuthorFormat}{\footnotesize}
3930 \newcommand{\innerPlaceFormat}{\footnotesize\bfseries}
3931 \newcommand{\innerTextFinalMark}{\rule{0.65em}{0.65em}}
3932 \newcommand{\editorialTitleFormat}{\LARGE\textit}
3933 \newcommand{\xepersian@editorialTitle}[1]{\editorialTitleFormat{#1}}
3934 \newcommand{\editorialAuthorFormat}{\textsc}
3935 \newcommand{\shortarticleTitleFormat}{\LARGE\bfseries}
3936 \newcommand{\xepersian@shortarticleTitle}[1]{\shortarticleTitleFormat #1}
3937 \newcommand{\shortarticleSubtitleFormat}{\Large}
3938 \newcommand{\xepersian@shortarticleSubtitle}[1]{\shortarticleSubtitleFormat #1}
3939 \newcommand{\shortarticleItemTitleFormat}{\large\bfseries}
3940 \newcommand{\xepersian@shortarticleItemTitle}[1]{\shortarticleItemTitleFormat #1}
3941 \renewcommand{\maketitle}{\begin{titlepage}%
3942 \let\footnotesize\small
3943 \let\footnoterule\relax
3944 \let\footnote\thanks
3945 \null\vfil
3946 \vskip 60\p@
3947 \begin{center}%
3948 {\LARGE \@title \par}%
3949 \vskip 1em%
3950 {\LARGE «\xepersian@edition» \par}%
3951 \vskip 3em%
3952 {\large
3953 \lineskip .75em%
3954 \begin{tabular}[t]{c}%
3955 \@author
3956 \end{tabular}\par}%
3957 \vskip 1.5em%
3958 {\large \@date \par}%
3959 \end{center}\par
3960 \@thanks

```



```

3961 \vfil\null
3962 \end{titlepage}%
3963 \setcounter{footnote}{0}%
3964 \global\let\thanks\relax
3965 \global\let\maketitle\relax
3966 \global\let\@thanks\@empty
3967 \global\let\@author\@empty
3968 \global\let\@date\@empty
3969 \global\let\@title\@empty
3970 \global\let\title\relax
3971 \global\let\author\relax
3972 \global\let\date\relax
3973 \global\let\and\relax
3974 }
3975 \newcommand{\xepersian@say}[1]{\typeout{#1}}
3976 \newsavebox{\xepersian@fmbbox}
3977 \newenvironment{xepersian@fmpage}[1]
3978 {\begin{lrbox}{\xepersian@fmbbox}\begin{minipage}{#1}}
3979 {\end{minipage}\end{lrbox}\fbox{\usebox{\xepersian@fmbbox}}}
3980 \newcommand{\image}[2]{
3981 \vspace{5pt}
3982 \setlength{\fboxsep}{1pt}
3983 \addtolength{\xepersian@imgsize}{\columnwidth}
3984 \addtolength{\xepersian@imgsize}{-1\columnsep}
3985 \ifxetex
3986 \setlength{\xepersian@pageneed}{1.5\xepersian@imgsize}
3987 \addtolength{\xepersian@pageneed}{50pt}
3988 \ClassWarning{xepersian-magazine}{%
3989 Image #1 needs: \the\xepersian@pageneed \space %
3990 and there is left: \the\page@free\space%
3991 }
3992 \ifdim \xepersian@pageneed < \page@free
3993
3994 {\centering\fbox{%
3995 \includegraphics[width = \xepersian@imgsize,
3996 height = \xepersian@imgsize,
3997 keepaspectratio ]{#1}}}
3998 \xepersian@pictureCaption{#2}
3999
4000 \vspace{5pt}
4001 \else
4002 \ClassWarning{Image #1 needs more space!%
4003 It was not inserted!}
4004 \fi
4005 \fi
4006 }
4007 \textblockorigin{1cm}{1cm}
4008 \newdimen\xepersian@dx
4009 \newdimen\xepersian@dy
4010 \newcount\xepersian@cx

```



```

4011 \newcount\xepersian@cy
4012 \newcommand{\grid}[3][]{
4013 \xepersian@dx=\textwidth%
4014 \xepersian@dy=\textheight%
4015 \xepersian@cx=#3% %columns
4016 \xepersian@cy=#2% %rows
4017
4018 \count1=#3%
4019 \advance\count1 by 1
4020
4021 \count2=#2%
4022 \advance\count2 by 1
4023
4024 \divide\xepersian@dx by #3
4025 \divide\xepersian@dy by #2
4026
4027 \setlength{\TPHorizModule}{\xepersian@dx}
4028 \setlength{\TPVertModule}{\xepersian@dy}
4029
4030 \ifthenelse{\equal{#1}{show}}{
4031 \multido{\xepersian@nrow=0+1}{\count2}{
4032 \begin{textblock}{\xepersian@cx}(0,\xepersian@nrow)
4033 \rule[0pt]{\textwidth}{.1pt}
4034 \end{textblock}
4035 }
4036
4037 \multido{\xepersian@ncol=0+1}{\count1}{
4038 \begin{textblock}{\xepersian@cy}(\xepersian@ncol,0)
4039 \rule[0pt]{.1pt}{\textheight}
4040 \end{textblock}
4041 }
4042 }{}
4043 }
4044 \newcommand{\xepersianInit}{
4045 \setlength{\headheight}{14pt}
4046 \renewcommand{\headrulewidth}{0.4pt}
4047
4048 \pagestyle{fancy}
4049
4050 \setlength{\columnseprule}{\columnlines}
4051 \setlength{\fboxrule}{0.1 pt}
4052
4053 }
4054
4055 \def\customlogo#1{\gdef\@customlogo{\beginR#1\endR}}
4056 \def\customminilogo#1{\gdef\@customminilogo{\beginR#1\endR}}
4057 \def\custommagazine#1{\gdef\@custommagazine{\beginR#1\endR}}
4058 \newcommand{\logo}[0]{
4059 %% Heading %%
4060 \noindent\hrulefill\hspace{10pt}\xepersian@editionLogo\hspace{5pt}\xepersian@www

```



```

4061
4062 \vspace*{-3pt}
4063
4064 {\Large\bfseries \@customlogo}
4065 \hrulefill
4066 \hspace{10pt}\xepersian@headDateTime
4067
4068 }
4069 \newcommand{\minilogo}[0]{
4070 {\large\bfseries \@customminilogo}
4071
4072 \vspace*{5pt}
4073 }
4074 \newcommand{\mylogo}[1]{
4075 {\beginR#1\endR}
4076
4077 \noindent
4078 \xepersian@editionLogo\hspace{5pt}
4079 \hrulefill
4080 \hspace{5pt}\xepersian@headDateTime
4081 }
4082 \newcommand{\edition}[1]{\renewcommand{\xepersian@edition}{#1}}
4083 \newenvironment{frontpage}[0]
4084 {
4085 \setboolean{xepersian@insidefrontpage}{true}
4086 \thispagestyle{empty}
4087 \logo
4088
4089 }%
4090 {
4091 \thispagestyle{empty}
4092 \clearpage
4093 \newpage
4094 \fancyhead{}
4095 \fancyfoot{}
4096 \fancyhead[RO,LE]{\beginR\xepersian@headright\endR}
4097 \fancyhead[LO,RE]{\beginR\xepersian@headleft\endR}
4098 \fancyhead[C]{\beginR\xepersian@headcenter\endR}
4099 \fancyfoot[RO,LE]{\beginR\xepersian@footright\endR}
4100 \fancyfoot[LO,RE]{\beginR\xepersian@footleft\endR}
4101 \fancyfoot[C]{\beginR\xepersian@footcenter\endR}
4102 \renewcommand{\headrulewidth}{0.4pt}
4103 \setboolean{xepersian@insidefrontpage}{false}
4104
4105 }
4106 \newcommand{\firstarticle}[3]
4107 {
4108 \ifthenelse{\boolean{xepersian@insidefrontpage}}{%
4109 \ifthenelse{\boolean{xepersian@hyphenatedtitles}}{%
4110 \begin{textblock}{24}{22,5}

```



```

4111 }
4112 {
4113 \begin{textblock}{28}(22,5)
4114 }
4115 \vspace{-7pt}
4116 \xepersian@firstTitle{#1}
4117 \end{textblock}
4118 \begin{textblock}{29}(22,10)
4119 \vspace{5pt plus 2pt minus 2pt}
4120
4121 \xepersian@firstText{\timestamp{#3}~#2}
4122
4123 \end{textblock}
4124
4125 \begin{textblock}{50}(0,15)
4126 \rule{50\TPHorizModule}{.3pt}
4127 \end{textblock}
4128 }{%else
4129 \ClassError{xepersian-magazine}{%
4130 \protect\firstarticle\space in a wrong place.\MessageBreak
4131 \protect\firstarticle\space may only appear inside frontpage environment.
4132 }{%
4133 \protect\firstarticle\space may only appear inside frontpage environment.
4134 }%
4135 }
4136 }
4137 \newcommand{\secondarticle}[5]
4138 {
4139 \ifthenelse{\boolean{xepersian@insidefrontpage}}{%
4140 \begin{textblock}{33}(2,16)
4141 \xepersian@pages{#4}
4142 \vspace{-5pt}
4143 \xepersian@secondTitle{#1}
4144
4145 \vspace*{5pt}
4146
4147 \xepersian@secondSubtitle{#2}
4148
4149 \vspace*{-7pt}
4150
4151 \xepersian@secondText{\timestamp{#5}~#3}
4152
4153 \end{textblock}
4154
4155 \begin{textblock}{33}(2,25)
4156 \vspace{5pt plus 2pt minus 2pt}
4157
4158 \noindent\ignorespaces\rule{33\TPHorizModule}{.3pt}
4159 \end{textblock}
4160 }{%else

```



```

4161 \ClassError{xepersian-magazine}{%
4162 \protect\secondarticle\space in a wrong place.\MessageBreak
4163 \protect\secondarticle\space may only appear inside frontpage environment.
4164 }{%
4165 \protect\secondarticle\space may only appear inside frontpage environment.
4166 }%
4167 }
4168 }
4169 \newcommand{\thirdarticle}[6]
4170 {
4171 \ifthenelse{\boolean{xepersian@insidefrontpage}}{%
4172 \begin{textblock}{32}(2,26)
4173 \xepersian@pages{#5}
4174 \vspace{-5pt}
4175 \setlength{\fboxsep}{1pt}
4176 \xepersian@thirdTitle{#1}
4177
4178 \vspace*{5pt}
4179
4180 \xepersian@thirdSubtitle{#2}
4181
4182 \vspace*{5pt}
4183
4184 {\noindent\ignorespaces %
4185 \ifthenelse{\equal{#4}{}}{}}
4186
4187 \xepersian@thirdText{\timestamp{#6}~#3}
4188
4189 }
4190
4191 \vspace*{5pt}
4192
4193 \end{textblock}
4194 }{%else
4195 \ClassError{xepersian-magazine}{%
4196 \protect\thirdarticle\space in a wrong place.\MessageBreak
4197 \protect\thirdarticle\space may only appear inside frontpage environment.
4198 }{%
4199 \protect\thirdarticle\space may only appear inside frontpage environment.
4200 }%
4201 }
4202 }
4203 \newcommand{\firstimage}[2]
4204 {
4205 \ifthenelse{\boolean{xepersian@insidefrontpage}}{%
4206 \begin{textblock}{18}(2,5)
4207 \setlength{\fboxsep}{1pt}
4208 \ifxetex % only in PDF
4209 \noindent\fbox{\includegraphics[width = 18\TPHorizModule ]{#1}}
4210 \fi

```



```

4211
4212 \xepersian@pictureCaption{#2}
4213 \end{textblock}%
4214 }
4215 {\ClassError{xepersian-magazine}{%
4216 \protect\firstimage\space in a wrong place.\MessageBreak
4217 \protect\firstimage\space may only appear inside frontpage environment.
4218 }{%
4219 \protect\firstimage\space may only appear inside frontpage environment.
4220 }}
4221 }%
4222 \newcommand{\weatheritem}[5]{%
4223 \ifthenelse{\boolean{xepersian@insideweather}}{
4224 \begin{minipage}{45pt}
4225 \ifxetex
4226 \includegraphics[width=40pt]{#1}
4227 \fi
4228 \end{minipage}
4229 \begin{minipage}{50pt}
4230 \weatherTempFormat
4231 #2\\
4232 \beginL#3 $\$ #4 \lr{\weatherUnits{}}\endL\\
4233 #5
4234 \end{minipage}
4235 }{%else
4236 \ClassError{xepersian-magazine}{%
4237 \protect\weatheritem\space in a wrong place.\MessageBreak
4238 \protect\weatheritem\space may only appear inside weatherblock environment.
4239 }{%
4240 \protect\weatheritem\space may only appear inside weatherblock environment.\MessageBreak
4241 weatherblock environment may only appear inside frontpage environment.
4242 }%
4243 }
4244 }
4245 \newenvironment{weatherblock}[1]
4246 {
4247 \ifthenelse{\boolean{xepersian@insidefrontpage}}{%
4248 \setboolean{xepersian@insideweather}{true}
4249 \begin{textblock}{32}(2,38)
4250 \vspace*{-15pt}
4251
4252 \xepersian@weather{\beginR#1\endR}
4253
4254 \vspace*{5pt}
4255
4256 \noindent\begin{xepersian@fmpage}{32\TPHorizModule}
4257 \begin{minipage}{32\TPHorizModule}
4258 \hspace{5pt}
4259
4260 }{%

```




```

4261 \ClassError{xepersian-magazine}{%
4262 weatherblock in a wrong place.\MessageBreak
4263 weatherblock may only appear inside frontpage environment.
4264 }{%
4265 weatherblock may only appear inside frontpage environment.
4266 }
4267 }
4268 }%
4269 {
4270 \end{minipage}
4271 \end{xepersian@fmpage}
4272 \end{textblock}
4273 \setboolean{xepersian@insideweather}{false}
4274 }
4275 \newenvironment{authorblock}[0]
4276 {
4277 \ifthenelse{\boolean{xepersian@insidefrontpage}}{%
4278 \begin{textblock}{15}(36,35)
4279 \setlength{\fboxsep}{5pt}
4280 \begin{xepersian@fmpage}{13\TPHorizModule}
4281 \begin{minipage}{13\TPHorizModule}
4282 \centering
4283 \minilogo
4284
4285 }{%else
4286 \ClassError{xepersian-magazine}{%
4287 authorblock in a wrong place.\MessageBreak
4288 authorblock may only appear inside frontpage environment.
4289 }{%
4290 authorblock may only appear inside frontpage environment.
4291 }
4292 }
4293 }
4294 {
4295 \end{minipage}
4296 \end{xepersian@fmpage}
4297 \end{textblock}
4298 }
4299 \newenvironment{indexblock}[1]
4300 {
4301 \ifthenelse{\boolean{xepersian@insidefrontpage}}{%
4302 \setboolean{xepersian@insideindex}{true}%let's in
4303 \begin{textblock}{15}(36,16)
4304 \setlength{\xepersian@indexwidth}{13\TPHorizModule}
4305 \xepersian@indexFrameTitle{#1}
4306
4307 \setlength{\fboxsep}{5pt} %espacio entre el frame y la imagen
4308 \begin{xepersian@fmpage}{\xepersian@indexwidth}
4309 \begin{minipage}{\xepersian@indexwidth}
4310 \vspace*{10pt}

```



```

4311 }{%else
4312 \ClassError{xepersian-magazine}{%
4313 indexblock in a wrong place.\MessageBreak
4314 indexblock may only appear inside frontpage environment.
4315 }{%
4316 indexblock may only appear inside frontpage environment.
4317 }
4318 }
4319 }%
4320 {
4321 \end{minipage}
4322 \end{xepersian@fmpage}
4323 \end{textblock}
4324 \setboolean{xepersian@insideindex}{false}%let's out
4325 }
4326 \newcommand{\indexitem}[2]
4327 {
4328 \ifthenelse{\boolean{xepersian@insideindex}}{
4329 \xepersian@indexEntry{#1 \xepersian@indexEntryPage{\pageref{#2}}}
4330
4331 \vspace{0.5cm}
4332
4333 \noindent\ignorespaces\indexEntrySeparator{
4334 }{%else
4335 \ClassError{xepersian-magazine}{%
4336 \protect\indexitem\space in a wrong place.\MessageBreak
4337 \protect\indexitem\space may only appear inside indexblock environment.
4338 }{%
4339 \protect\indexitem\space may only appear inside indexblock environment.\MessageBreak
4340 indexblock environment may only appear inside frontpage environment.
4341 }%
4342 }
4343 }
4344 \newcommand{\xepersian@inexpandedtitle}[1]{
4345 \begin{minipage}{.95\textwidth}
4346 \begin{center}
4347 \noindent\Large\textbf{\beginR{#1}\endR}
4348 \end{center}
4349 \end{minipage}
4350 }
4351 \newcommand{\expandedtitle}[2]{
4352 \end{multicols}
4353
4354 \begin{center}
4355 \setlength{\fboxsep}{5pt}
4356 \setlength{\shadowsize}{2pt}
4357 \ifthenelse{\equal{#1}{shadowbox}}{%
4358 \shadowbox{%
4359 \xepersian@inexpandedtitle{#2}%
4360 }%

```



```

4361 }{}
4362 \ifthenelse{\equal{#1}{doublebox}}{%
4363 \doublebox{%
4364 \xepersian@inexpandedtitle{#2}%
4365 }%
4366 }{}
4367 \ifthenelse{\equal{#1}{ovalbox}}{%
4368 \ovalbox{%
4369 \xepersian@inexpandedtitle{#2}%
4370 }%
4371 }{}
4372 \ifthenelse{\equal{#1}{ovalbox}}{%
4373 \ovalbox{%
4374 \xepersian@inexpandedtitle{#2}%
4375 }%
4376 }{}
4377 \ifthenelse{\equal{#1}{lines}}{
4378 \hrule
4379 \vspace*{8pt}
4380 \begin{center}
4381 \noindent\Large\textbf{#2}
4382 \end{center}
4383 \vspace*{8pt}
4384 \hrule
4385 }{}
4386 \end{center}
4387
4388 \begin{multicols}{\xepersian@ncolumns{}}
4389 \ifnum \xepersian@ncolumns > \minraggedcols
4390 \raggedFormat
4391 \fi
4392 }
4393 \newcommand{\xepersian@incolumntitle}[2]{
4394 \begin{minipage}{#1}
4395 \begin{center}
4396 \noindent\normalsize\textbf{#2}
4397 \end{center}
4398 \end{minipage}
4399 }
4400
4401 \newcommand{\columnntitle}[2]{
4402 \vspace*{5pt}
4403 \begin{center}
4404 \setlength{\fboxsep}{5pt}
4405 \setlength{\shadowsize}{2pt}
4406 \addtolength{\xepersian@coltitsize}{\columnwidth}
4407 \addtolength{\xepersian@coltitsize}{-1\columnsep}
4408 \addtolength{\xepersian@coltitsize}{-5pt}
4409 \addtolength{\xepersian@coltitsize}{-1\shadowsize}
4410 \ifthenelse{\equal{#1}{shadowbox}}{%

```



```

4411 \shadowbox{%
4412 \xepersian@incolumntitle{\xepersian@coltitsize}{#2}%
4413 }%
4414 {}
4415 \ifthenelse{\equal{#1}{doublebox}}{%
4416 \doublebox{%
4417 \xepersian@incolumntitle{\xepersian@coltitsize}{#2}%
4418 }%
4419 {}
4420 \ifthenelse{\equal{#1}{ovalbox}}{%
4421 \ovalbox{%
4422 \xepersian@incolumntitle{\xepersian@coltitsize}{#2}%
4423 }%
4424 {}
4425 \ifthenelse{\equal{#1}{ovalbox}}{%
4426 \Ovalbox{%
4427 \xepersian@incolumntitle{\xepersian@coltitsize}{#2}%
4428 }%
4429 {}
4430 \ifthenelse{\equal{#1}{lines}}{
4431 \hrule
4432 \vspace*{5pt}
4433 \begin{center}
4434 \noindent\normalsize\textbf{#2}
4435 \end{center}
4436 \vspace*{5pt}
4437 \hrule
4438 }{
4439 \end{center}
4440 }
4441 \renewcommand{\date}{%
4442 \longdate{\today}%
4443 }
4444 \newcommand{\authorandplace}[2]{%
4445 \rightline{%
4446 {\innerAuthorFormat #1},\space{\innerPlaceFormat #2}%
4447 }%
4448 \par %
4449 }
4450 \newcommand{\newsection}[1]{
4451 \renewcommand{\xepersian@section}{#1}
4452 }
4453 \newenvironment{article}[5]
4454 {
4455 \xepersian@say{Adding a new piece of article}
4456 \renewcommand{\xepersian@ncolumns}{#1}
4457 \begin{multicols}{#1}[
4458 \xepersian@pages{#4}
4459 \xepersian@innerTitle{#2}%
4460 \xepersian@innerSubtitle{#3}%

```



```

4461 ] [4cm]%
4462 \label{#5}
4463 \ifnum #1 > \minraggedcols
4464 \raggedFormat
4465 \fi
4466 }
4467 {\innerTextFinalMark{}
4468 \end{multicols}
4469 }
4470 \newcommand{\articlesep}{%
4471 \setlength{\xepersian@pageneed}{16000pt}
4472 \setlength{\xepersian@pageleft}{\pagegoal}
4473 \addtolength{\xepersian@pageleft}{-\pagetotal}
4474
4475 \xepersian@say{How much left \the\xepersian@pageleft}
4476
4477 \ifdim \xepersian@pageneed < \xepersian@pageleft
4478 \xepersian@say{Not enough space}
4479 \else
4480 \xepersian@say{Adding sep line between articles}
4481 \vspace*{10pt plus 10pt minus 5pt}
4482 \hrule
4483 \vspace*{10pt plus 5pt minus 5pt}
4484 \fi
4485
4486 }
4487 \newcommand{\xepersian@editorialTit}[2]{
4488 \setlength{\arrayrulewidth}{.1pt}
4489 \begin{center}
4490 \begin{tabular}{c}
4491 \noindent
4492 \xepersian@editorialTitle{#1}
4493 \vspace{2pt plus 1pt minus 1pt}
4494 \\
4495 \hline
4496 \vspace{2pt plus 1pt minus 1pt}
4497 \\
4498 \editorialAuthorFormat{#2}
4499 \end{tabular}
4500 \end{center}
4501 }
4502 \newenvironment{editorial}[4]
4503 {
4504 \xepersian@say{Adding a new editorial}
4505 \begin{multicols}{#1}[%
4506 \xepersian@editorialTit{#2}{#3}%
4507 ] [4cm]
4508 \label{#4}
4509 \ifnum #1 > \minraggedcols
4510 \raggedFormat

```



```

4511 \fi
4512 }
4513 {
4514 \end{multicols}
4515 }
4516 \newcommand{\xepersian@shortarticleTit}[2]{
4517 \begin{center}
4518 \vbox{%
4519 \noindent
4520 \xepersian@shortarticleTitle{#1}
4521 \vspace{4pt plus 2pt minus 2pt}
4522 \hrule
4523 \vspace{4pt plus 2pt minus 2pt}
4524 \xepersian@shortarticleSubtitle{#2}
4525 }
4526 \end{center}
4527 }
4528 \newenvironment{shortarticle}[4]
4529 {
4530 \xepersian@say{Adding a short article block}
4531 \begin{multicols}{#1}[\xepersian@shortarticleTit{#2}{#3}][4cm] %
4532 \label{#4}
4533 \par %
4534 \ifnum #1 > \minraggedcols
4535 \raggedFormat
4536 \fi
4537 }
4538 {
4539 \end{multicols}
4540 }
4541 \newcommand{\shortarticleitem}[2]{
4542 \goodbreak
4543 \vspace{5pt plus 3pt minus 3pt}
4544 {\vbox{\noindent\xepersian@shortarticleItemTitle{#1}}}
4545 \vspace{5pt plus 3pt minus 3pt}
4546 {\noindent #2}\
4547 }

```

7.57 xepersian-mathsdigitspec.sty

```

4548 \NeedsTeXFormat{LaTeX2e}
4549 \ProvidesPackage{xepersian-mathsdigitspec}
4550 [2014/11/21 v1.1.0 Unicode Persian maths digits in XeLaTeX]
4551 \def\new@mathgroup{\alloc@8\mathgroup\chardef\@cclvi}
4552 \let\newfam\new@mathgroup
4553 \def\select@group#1#2#3#4{%
4554 \ifx\math@bgroup\bgroup\else\relax\expandafter\@firstofone\fi
4555 {%
4556 \ifmmode
4557 \ifnum\c@mv@\math@version\endcsname<\@cclvi

```



```

4558 \begingroup
4559 \escapechar\m@ne
4560 \getanddefine@fonts{\csname c@mv@\math@version\endcsname}#3%
4561 \globaldefs\@ne \math@fonts
4562 \endgroup
4563 \init@restore@version
4564 \xdef#1{\noexpand\use@mathgroup\noexpand#2%
4565 \number\csname c@mv@\math@version\endcsname}}%
4566 \global\advance\csname c@mv@\math@version\endcsname\@ne
4567 \else
4568 \let#1\relax
4569 \@latex@error{Too many math alphabets used in
4570 version \math@version}%
4571 \@eha
4572 \fi
4573 \else \expandafter\@non@alpherr\fi
4574 #1{#4}%
4575 }%
4576 }
4577 \def\document@select@group#1#2#3#4{%
4578 \ifx\math@bgroup\bgroup\else\relax\expandafter\@firstofone\fi
4579 {%
4580 \ifmmode
4581 \ifnum\csname c@mv@\math@version\endcsname<\@cclvi
4582 \begingroup
4583 \escapechar\m@ne
4584 \getanddefine@fonts{\csname c@mv@\math@version\endcsname}#3%
4585 \globaldefs\@ne \math@fonts
4586 \endgroup
4587 \expandafter\extract@alph@from@version
4588 \csname mv@\math@version\expandafter\endcsname
4589 \expandafter{\number\csname
4590 c@mv@\math@version\endcsname}%
4591 #1%
4592 \global\advance\csname c@mv@\math@version\endcsname\@ne
4593 \else
4594 \let#1\relax
4595 \@latex@error{Too many math alphabets used
4596 in version \math@version}%
4597 \@eha
4598 \fi
4599 \else \expandafter\@non@alpherr\fi
4600 #1{#4}%
4601 }%
4602 }
4603 \ExplSyntaxOn
4604 \bool_set_false:N \g__fontspec_math_bool
4605 \tl_map_inline:nn
4606 {
4607 \new@mathgroup\c@p@list\c@p@elt\DeclareMathSizes

```



```

4608 \@DeclareMathSizes\newmathalphabet\newmathalphabet@@\newmathalphabet@@@
4609 \DeclareMathVersion\define@mathalphabet\define@mathgroup\addtoversion
4610 \version@list\version@elt\alpha@list\alpha@elt
4611 \restore@mathversion\init@restore@version\dorestore@version\process@table
4612 \new@mathversion\DeclareSymbolFont\group@list\group@elt
4613 \new@symbolfont\SetSymbolFont\SetSymbolFont@get@cdp
4614 \DeclareMathAlphabet\new@mathalphabet\SetMathAlphabet\SetMathAlphabet@
4615 \DeclareMathAccent\set@mathaccent\DeclareMathSymbol\set@mathchar
4616 \set@mathsymbol\DeclareMathDelimiter\@xxDeclareMathDelimiter
4617 \@DeclareMathDelimiter\@xDeclareMathDelimiter\set@mathdelimiter
4618 \set@@@mathdelimiter\DeclareMathRadical\mathchar@type
4619 \DeclareSymbolFontAlphabet\DeclareSymbolFontAlphabet@
4620 }
4621 {
4622 \tl_remove_once:Nn \@preamblecmds {\do#1}
4623 }
4624 \ExplSyntaxOff
4625 \newcommand\xepersian@PackageInfo[1]{\PackageInfo{xepersian-mathsdigitspec}{#1}}
4626 \newcommand\SetMathCode[4]{%
4627 \Umathcode#1="\mathchar@type#2 \csname sym#3\endcsname #4\relax}
4628 \newcommand\SetMathCharDef[4]{%
4629 \Umathchardef#1="\mathchar@type#2 \csname sym#3\endcsname #4\relax}
4630 \ExplSyntaxOn
4631 \cs_new_eq:NN \orig_mathbf:n \mathbf
4632 \cs_new_eq:NN \orig_mathit:n \mathit
4633 \cs_new_eq:NN \orig_mathrm:n \mathrm
4634 \cs_new_eq:NN \orig_mathsf:n \mathsf
4635 \cs_new_eq:NN \orig_mathtt:n \mathtt
4636 \NewDocumentCommand \new@mathbf { m } {
4637 \orig_mathbf:n {
4638 \int_step_inline:nnnn { `0 } { \c_one } { `9 } {
4639 \mathcode ##1 = \numexpr "100 * \symnew@mathbf@font@digits + ##1 \relax
4640 }
4641 #1
4642 }
4643 }
4644 \NewDocumentCommand \new@mathit { m } {
4645 \orig_mathit:n {
4646 \int_step_inline:nnnn { `0 } { \c_one } { `9 } {
4647 \mathcode ##1 = \numexpr "100 * \symnew@mathit@font@digits + ##1 \relax
4648 }
4649 #1
4650 }
4651 }
4652 \NewDocumentCommand \new@mathrm { m } {
4653 \orig_mathrm:n {
4654 \int_step_inline:nnnn { `0 } { \c_one } { `9 } {
4655 \mathcode ##1 = \numexpr "100 * \symnew@mathrm@font@digits + ##1 \relax
4656 }
4657 #1

```




```

4658 }
4659 }
4660 \NewDocumentCommand \new@mathsf{ m } {
4661   \orig_mathsf:n {
4662     \int_step_inline:nnnn { `0 } { \c_one } { `9 } {
4663       \mathcode ##1 = \numexpr "100 * \symnew@mathsf@font@digits + ##1 \relax
4664     }
4665     #1
4666   }
4667 }
4668 \NewDocumentCommand \new@mathhtt{ m } {
4669   \orig_mathhtt:n {
4670     \int_step_inline:nnnn { `0 } { \c_one } { `9 } {
4671       \mathcode ##1 = \numexpr "100 * \symnew@mathhtt@font@digits + ##1 \relax
4672     }
4673     #1
4674   }
4675 }
4676 \DeclareDocumentCommand \setdigitfont { o m } {%
4677   \let\glb@currsize\relax
4678   \__fontspec_pass_args:nnn \__xepersian_setdigitfont:nn {#1} {#2} }
4679
4680 \cs_new:Nn \__xepersian_setdigitfont:nn
4681 {
4682   \fontspec_set_family:Nnn \xepersian@digits@family {Mapping=parsidigits,#1} {#2}
4683   \xepersian@PackageInfo{Defining the default Persian maths digits font as '#2'}
4684   \DeclareSymbolFont{OPERATORS} {EU1}{\xepersian@digits@family} {m}{n}
4685   \DeclareSymbolFont{new@mathbf@font@digits}{EU1}{\xepersian@digits@family}{bx}{n}
4686   \DeclareSymbolFont{new@mathit@font@digits}{EU1}{\xepersian@digits@family}{m}{it}
4687   \DeclareSymbolFont{new@mathrm@font@digits}{EU1}{\xepersian@digits@family}{m}{n}
4688   \def\persianmathsdigits{%
4689     \SetMathCode{`0}{\mathalpha}{OPERATORS}{`0}
4690     \SetMathCode{`1}{\mathalpha}{OPERATORS}{`1}
4691     \SetMathCode{`2}{\mathalpha}{OPERATORS}{`2}
4692     \SetMathCode{`3}{\mathalpha}{OPERATORS}{`3}
4693     \SetMathCode{`4}{\mathalpha}{OPERATORS}{`4}
4694     \SetMathCode{`5}{\mathalpha}{OPERATORS}{`5}
4695     \SetMathCode{`6}{\mathalpha}{OPERATORS}{`6}
4696     \SetMathCode{`7}{\mathalpha}{OPERATORS}{`7}
4697     \SetMathCode{`8}{\mathalpha}{OPERATORS}{`8}
4698     \SetMathCode{`9}{\mathalpha}{OPERATORS}{`9}
4699     \SetMathCharDef{\%}{\mathbin}{OPERATORS}{` }
4700
4701     \SetMathCharDef{\decimalseparator}{\mathord}{OPERATORS}{"066B}
4702     \cs_set_eq:NN \mathbf \new@mathbf
4703     \cs_set_eq:NN \mathit \new@mathit
4704     \cs_set_eq:NN \mathrm \new@mathrm
4705   }
4706 \DeclareDocumentCommand \setmathsfdigitfont { o m }
4707 { \__fontspec_pass_args:nnn \__xepersian_setmathsfdigitfont:nn {#1} {#2} }

```



```

4707
4708 \cs_new:Nn \__xepersian_setmathsfdigitfont:nn
4709 {
4710   \fontspec_set_family:Nnn \g_fontspec_mathsf_tl {Mapping=parsidigits,#1} {#2}
4711   \DeclareSymbolFont{new@mathsf@font@digits}{EU1}{\g_fontspec_mathsf_tl}{m}{n}
4712   \def\persianmathsfdigits{\cs_set_eq:NN \mathsf \new@mathsf}
4713 }
4714 \DeclareDocumentCommand \setmathttdigitfont { o m }
4715 { \__fontspec_pass_args:nnn \__xepersian_setmathttdigitfont:nn {#1} {#2} }
4716
4717 \cs_new:Nn \__xepersian_setmathttdigitfont:nn
4718 {
4719   \fontspec_set_family:Nnn \g_fontspec_mathtt_tl {Mapping=parsidigits,#1} {#2}
4720   \DeclareSymbolFont{new@mathtt@font@digits}{EU1}{\g_fontspec_mathtt_tl}{m}{n}
4721   \def\persianmathttdigits{\cs_set_eq:NN \mathtt \new@mathtt}
4722 }
4723 \ExplSyntaxOff
4724 \ifx\newcommand\undefined\else
4725   \newcommand{\ZifferAn}{}
4726 \fi
4727 \mathchardef\ziffer@DotOri="013A
4728 {\ZifferAn
4729   \catcode`\.=\active\gdef.{\begingroup\obeyspaces\futurelet\n\ziffer@dcheck}}
4730 \def\ziffer@dcheck{\ziffer@check\ZifferLeer\ziffer@DotOri}
4731 \def\ziffer@check#1#2{%
4732   \ifx\n1\endgroup#1\else
4733     \ifx\n2\endgroup#1\else
4734       \ifx\n3\endgroup#1\else
4735         \ifx\n4\endgroup#1\else
4736           \ifx\n5\endgroup#1\else
4737             \ifx\n6\endgroup#1\else
4738               \ifx\n7\endgroup#1\else
4739                 \ifx\n8\endgroup#1\else
4740                   \ifx\n9\endgroup#1\else
4741                     \ifx\n0\endgroup#1\else
4742                       \ifx\n\overline\endgroup#1\else
4743                         \endgroup#2%
4744                     \fi
4745                   \fi
4746                 \fi
4747               \fi
4748             \fi
4749           \fi
4750         \fi
4751       \fi
4752     \fi
4753   \fi
4754 }
4755 \mathcode`\.="8000\relax
4756 \def\ZifferLeer{\ifx\decimalseparator\undefined.\else\decimalseparator\fi}

```



```

4757 \def\DefaultMathsDigits{\def\SetMathsDigits{}}
4758 \def\PersianMathsDigits{\def\SetMathsDigits{%
4759 \ifx\persianmathsdigits\undefined\else\persianmathsdigits\fi%
4760 \ifx\persianmathsfdigits\undefined\else\persianmathsfdigits\fi%
4761 \ifx\persianmathttdigits\undefined\else\persianmathttdigits\fi}}
4762 \def\AutoMathsDigits{\def\SetMathsDigits{%
4763 \ifx\persianmathsdigits\undefined\else\if@Latin\else\persianmathsdigits\fi\fi%
4764 \ifx\persianmathsfdigits\undefined\else\if@Latin\else\persianmathsfdigits\fi\fi%
4765 \ifx\persianmathttdigits\undefined\else\if@Latin\else\persianmathttdigits\fi\fi}}
4766 \AutoMathsDigits
4767 \everymath\expandafter{\the\everymath\SetMathsDigits}
4768 \g@addto@macro\document{\everydisplay\expandafter{\the\everydisplay\SetMathsDigits}}

```

7.58 xepersian-multiplechoice.sty

```

4769 \NeedsTeXFormat{LaTeX2e}
4770 \ProvidesPackage{xepersian-multiplechoice}[2010/07/25 v0.2
4771 Multiple Choice Questionnaire class for Persian in XeLaTeX]
4772 \RequirePackage{pifont}
4773 \RequirePackage{fullpage}
4774 \RequirePackage{ifthen}
4775 \RequirePackage{calc}
4776 \RequirePackage{verbatim}
4777 \RequirePackage{tabularx}
4778 \def\@headerfont{\bfseries}
4779 \newcommand\headerfont[1]{\gdef\@headerfont{#1}}
4780 \def\@X{X}
4781 \newcommand\X[1]{\gdef\@X{#1}}
4782 \def\pbs#1{\let\tmp=\@#1\let\=\tmp}
4783 \newcolumntype{D}{>{\pbs\centering}X}
4784 \newcolumntype{Q}{>{\@headerfont}X}
4785
4786 \renewcommand\tabularxcolumn[1]{m{#1}}
4787 \newcommand\makeform@nocorrection{%
4788 \addtocontents{frm}{\protect\end{tabularx}}
4789 \@starttoc{frm}}
4790 \newcommand\makeform@correction{%
4791 \addtocontents{frm}{\protect\end{tabularx}}}
4792 \newcommand\makemask@nocorrection{%
4793 \addtocontents{msk}{\protect\end{tabularx}}
4794 \@starttoc{msk}}
4795 \newcommand\makemask@correction{%
4796 \addtocontents{msk}{\protect\end{tabularx}}}
4797 \newlength\questionspace
4798 \setlength\questionspace{0pt}
4799 \newcommand\answerstitle[1]{\gdef\@answerstitle{#1}}
4800 \def\@answerstitlefont{\bfseries}
4801 \newcommand\answerstitlefont[1]{\gdef\@answerstitlefont{#1}}
4802 \def\@answernumberfont{\bfseries}
4803 \newcommand\answernumberfont[1]{\gdef\@answernumberfont{#1}}

```



```

4804 \newcounter{question}\stepcounter{question}
4805 \newcounter{@choice}
4806 \def\@initorcheck{%
4807   \xdef\@choices{\the@choice}%
4808   \setcounter{@choice}{1}%
4809   \gdef\@arraydesc{|Q||}%
4810   \gdef\@headerline{%
4811     \whiledo{\not{\value{@choice}>\@choices}}{
4812       \xdef\@arraydesc{\@arraydesc D|}
4813       \def\@appendheader{\g@addto@macro\@headerline}
4814       \@appendheader{&\protect\@headerfont}
4815       \edef\@the@choice{\alph{@choice}}
4816       \expandafter\@appendheader\@the@choice
4817       \stepcounter{@choice}}%
4818   \addtocontents{frm}{%
4819     \protect\begin{tabularx}{\protect\linewidth}{\@arraydesc}
4820     \protect\hline
4821     \@headerline\protect\\\protect\hline\protect\hline}%
4822   \addtocontents{msk}{%
4823     \protect\begin{tabularx}{\protect\linewidth}{\@arraydesc}
4824     \protect\hline
4825     \@headerline\protect\\\protect\hline\protect\hline}%
4826   \gdef\@initorcheck{%
4827     \ifthenelse{\value{@choice} = \@choices}{}{%
4828       \ClassError{xepersian-multiplechoice}{Question \thequestion: wrong number of choices
4829         (\the@choice\space instead of \@choices)}{%
4830         Questions must all have the same number of proposed answers.%
4831         \MessageBreak
4832         Type X <return> to quit, fix your MCQ (multiple choice question) and rerun XeLaTeX.}}}%
4833 \newenvironment{question}[1]{%
4834   %% \begin{question}
4835   \begin{minipage}{\textwidth}
4836     \xdef\@formanswerline{\@questionheader}%
4837     \xdef\@maskanswerline{\@questionheader}%
4838     \fbox{\parbox[c]{\linewidth}{#1}}
4839     \vspace\questionspace\par
4840     {\@answerstitlefont\@answerstitle}
4841     \begin{list}{\@answernumberfont\alph{@choice}}~{\usecounter{@choice}}}%
4842   %% \end{question}
4843   \end{list}
4844   \@initorcheck%
4845   \addtocontents{frm}{\@formanswerline\protect\\\protect\hline}%
4846   \addtocontents{msk}{\@maskanswerline\protect\\\protect\hline}%
4847   \end{minipage}
4848   \stepcounter{question}}
4849 \def\@truesymbol{\ding{52}~}
4850 \def\@falsesymbol{\ding{56}~}
4851 \newcommand\truesymbol[1]{\gdef\@truesymbol{#1}}
4852 \newcommand\falsesymbol[1]{\gdef\@falsesymbol{#1}}
4853 \def\@true@nocorrection{\item}

```



```

4854 \def\@false@nocorrection{\item}
4855 \def\@true@correction{\item[\@true@symbol\refstepcounter{@choice}]}
4856 \def\@false@correction{\item[\@false@symbol\refstepcounter{@choice}]}
4857 \newcommand\true{%
4858   \xdef\@formanswerline{\@formanswerline&}%
4859   \xdef\@maskanswerline{\@maskanswerline&\@X}%
4860   \@true}%
4861 \newcommand\false{%
4862   \xdef\@formanswerline{\@formanswerline&}%
4863   \xdef\@maskanswerline{\@maskanswerline&}%
4864   \@false}%
4865 \def\@correctionstyle{\itshape}
4866 \newcommand\correctionstyle[1]{\gdef\@correctionstyle{#1}}
4867 \newenvironment{correction}{\@correctionstyle}{\@correctionstyle}{}
4868 \def\questionheader{\thequestion}
4869 \answerstyle{\:}
4870 \DeclareOption{nocorrection}{%
4871   \let\@true\@true@nocorrection
4872   \let\@false\@false@nocorrection
4873   \let\correction\comment
4874   \let\endcorrection\endcomment
4875   \def\makeform{\makeform@nocorrection}
4876   \def\makemask{\makemask@nocorrection}}
4877 \DeclareOption{correction}{%
4878   \let\@true\@true@correction
4879   \let\@false\@false@correction
4880   \let\correction\@correction
4881   \let\endcorrection\end@correction
4882   \def\makeform{\makeform@correction}
4883   \def\makemask{\makemask@correction}}
4884 \ExecuteOptions{nocorrection}
4885 \newcommand\questiontitle[1]{\gdef\@questiontitle{#1}}
4886 \def\@questiontitlefont{\bfseries}
4887 \newcommand\questiontitlefont[1]{\gdef\@questiontitlefont{#1}}
4888 \newlength\questiontitlespace
4889 \setlength\questiontitlespace{5pt}
4890 \newlength\questionsepspace
4891 \setlength\questionsepspace{20pt}
4892 \gdef\@questionsepspace{0pt}
4893 \let\old@question\question
4894 \let\old@endquestion\endquestion
4895 \renewenvironment{question}[1]{%
4896   %% \begin{question}
4897   \vspace\@questionsepspace
4898   \fbox{\parbox[c]{0.25\linewidth}{\@questiontitlefont\@questiontitle}}
4899   \nopagebreak\vspace\questiontitlespace\par
4900   \old@question{#1}}{%
4901   %% \end{question}
4902   \old@endquestion
4903   \gdef\@questionsepspace{\questionsepspace}}

```



```

4904 \questiontitle{ \thequestion:}
4905 \ProcessOptions

```

7.59 xepersian-persiancal.sty

```

4906 \NeedsTeXFormat{LaTeX2e}
4907 \ProvidesPackage{xepersian-persiancal}[2012/07/25 v0.2 provides Persian calendar]
4908
4909 \newif\ifXePersian@leap \newif\ifXePersian@kabiseh
4910 \newcount\XePersian@i \newcount\XePersian@y \newcount\XePersian@m \newcount\XePersian@d
4911 \newcount\XePersian@latini \newcount\XePersian@persiani
4912 \newcount\XePersian@latinii \newcount\XePersian@persianii
4913 \newcount\XePersian@latiniii \newcount\XePersian@persianiii
4914 \newcount\XePersian@latiniv \newcount\XePersian@persianiv
4915 \newcount\XePersian@latinvi \newcount\XePersian@persianvi
4916 \newcount\XePersian@latinvi \newcount\XePersian@persianvi
4917 \newcount\XePersian@latinvii \newcount\XePersian@persianvii
4918 \newcount\XePersian@latinviii \newcount\XePersian@persianviii
4919 \newcount\XePersian@latinix \newcount\XePersian@persianix
4920 \newcount\XePersian@latinx \newcount\XePersian@persianx
4921 \newcount\XePersian@latinxi \newcount\XePersian@persianxi
4922 \newcount\XePersian@latinxii \newcount\XePersian@persianxii
4923 \newcount\XePersian@persianxiii
4924
4925 \newcount\XePersian@temp
4926 \newcount\XePersian@temptwo
4927 \newcount\XePersian@tempthree
4928 \newcount\XePersian@yModHundred
4929 \newcount\XePersian@thirtytwo
4930 \newcount\XePersian@dn
4931 \newcount\XePersian@sn
4932 \newcount\XePersian@mminusone
4933
4934
4935 \XePersian@y=\year \XePersian@m=\month \XePersian@d=\day
4936 \XePersian@temp=\XePersian@y
4937 \divide\XePersian@temp by 100\relax
4938 \multiply\XePersian@temp by 100\relax
4939 \XePersian@yModHundred=\XePersian@y
4940 \advance\XePersian@yModHundred by -\XePersian@temp\relax
4941 \ifodd\XePersian@yModHundred
4942 \XePersian@leapfalse
4943 \else
4944 \XePersian@temp=\XePersian@yModHundred
4945 \divide\XePersian@temp by 2\relax
4946 \ifodd\XePersian@temp\XePersian@leapfalse
4947 \else
4948 \ifnum\XePersian@yModHundred=0%
4949 \XePersian@temp=\XePersian@y
4950 \divide\XePersian@temp by 400\relax

```



```

4951      \multiply\XePersian@temp by 400\relax
4952      \ifnum\XePersian@y=\XePersian@temp\XePersian@leaptrue\else\XePersian@leapfalse\fi
4953      \else\XePersian@leaptrue
4954      \fi
4955  \fi
4956 \fi
4957 \XePersian@latini=31\relax
4958 \ifXePersian@leap
4959   \XePersian@latinii = 29\relax
4960 \else
4961   \XePersian@latinii = 28\relax
4962 \fi
4963 \XePersian@latiniii = 31\relax
4964 \XePersian@latiniv = 30\relax
4965 \XePersian@latinvi = 31\relax
4966 \XePersian@latinvi = 30\relax
4967 \XePersian@latinvii = 31\relax
4968 \XePersian@latinviii = 31\relax
4969 \XePersian@latinix = 30\relax
4970 \XePersian@latinx = 31\relax
4971 \XePersian@latinxi = 30\relax
4972 \XePersian@latinxii = 31\relax
4973 \XePersian@thirtytwo=32\relax
4974 \XePersian@temp=\XePersian@y
4975 \advance\XePersian@temp by -17\relax
4976 \XePersian@temptwo=\XePersian@temp
4977 \divide\XePersian@temptwo by 33\relax
4978 \multiply\XePersian@temptwo by 33\relax
4979 \advance\XePersian@temp by -\XePersian@temptwo
4980 \ifnum\XePersian@temp=\XePersian@thirtytwo\XePersian@kabisehfalse
4981 \else
4982   \XePersian@temptwo=\XePersian@temp
4983   \divide\XePersian@temptwo by 4\relax
4984   \multiply\XePersian@temptwo by 4\relax
4985   \advance\XePersian@temp by -\XePersian@temptwo
4986   \ifnum\XePersian@temp=\z@\XePersian@kabisehtrue\else\XePersian@kabisehfalse\fi
4987 \fi
4988 \XePersian@tempthree=\XePersian@y % Number of Leap years
4989 \advance\XePersian@tempthree by -1
4990 \XePersian@temp=\XePersian@tempthree % T := (MY-1) div 4
4991 \divide\XePersian@temp by 4\relax
4992 \XePersian@temptwo=\XePersian@tempthree % T := T - ((MY-1) div 100)
4993 \divide\XePersian@temptwo by 100\relax
4994 \advance\XePersian@temp by -\XePersian@temptwo
4995 \XePersian@temptwo=\XePersian@tempthree % T := T + ((MY-1) div 400)
4996 \divide\XePersian@temptwo by 400\relax
4997 \advance\XePersian@temp by \XePersian@temptwo
4998 \advance\XePersian@tempthree by -611 % Number of Kabise years
4999 \XePersian@temptwo=\XePersian@tempthree % T := T - ((SY+10) div 33) * 8
5000 \divide\XePersian@temptwo by 33\relax

```



```

5001 \multiply\XePersian@temptwo by 8\relax
5002 \advance\XePersian@temp by -\XePersian@temptwo
5003 \XePersian@temptwo=\XePersian@tempthree %
5004 \divide\XePersian@temptwo by 33\relax
5005 \multiply\XePersian@temptwo by 33\relax
5006 \advance\XePersian@tempthree by -\XePersian@temptwo
5007 \ifnum\XePersian@tempthree=32\advance\XePersian@temp by 1\fi % if (SY+10) mod 33=32 then Inc(T);
5008 \divide\XePersian@tempthree by 4\relax % T := T - ((SY+10) mod 33) div 4
5009 \advance\XePersian@temp by -\XePersian@tempthree
5010 \advance\XePersian@temp by -137 % T := T - 137 Adjust the value
5011 \XePersian@persiani=31
5012 \advance\XePersian@persiani by -\XePersian@temp % now 31 - T is the persiani
5013 \XePersian@persianii = 30\relax
5014 \ifXePersian@kabiseh
5015 \XePersian@persianiii = 30\relax
5016 \else
5017 \XePersian@persianiii = 29\relax
5018 \fi
5019 \XePersian@persianiv = 31\relax
5020 \XePersian@persianv = 31\relax
5021 \XePersian@persianvi = 31\relax
5022 \XePersian@persianvii = 31\relax
5023 \XePersian@persianviii= 31\relax
5024 \XePersian@persianix = 31\relax
5025 \XePersian@persianx = 30\relax
5026 \XePersian@persianxi = 30\relax
5027 \XePersian@persianxii = 30\relax
5028 \XePersian@persianxiii= 30\relax
5029 \XePersian@dn= 0\relax
5030 \XePersian@sn= 0\relax
5031 \XePersian@mminusone=\XePersian@m
5032 \advance\XePersian@mminusone by -1\relax
5033 \XePersian@i=0\relax
5034 \ifnum\XePersian@i < \XePersian@mminusone
5035 \loop
5036 \advance \XePersian@i by 1\relax
5037 \advance\XePersian@dn by \csname XePersian@latin\romannumeral\the\XePersian@i\endcsname
5038 \ifnum\XePersian@i<\XePersian@mminusone \repeat
5039 \fi
5040 \advance \XePersian@dn by \XePersian@d
5041 \XePersian@i=1\relax
5042 \XePersian@sn = \XePersian@persiani
5043 \ifnum \XePersian@sn<\XePersian@dn
5044 \loop
5045 \advance \XePersian@i by 1\relax
5046 \advance\XePersian@sn by \csname XePersian@persian\romannumeral\the\XePersian@i\endcsname
5047 \ifnum \XePersian@sn<\XePersian@dn \repeat
5048 \fi
5049 \ifnum \XePersian@i < 4
5050 \XePersian@m = 9 \advance\XePersian@m by \XePersian@i

```




```

5051 \advance \XePersian@y by -622\relax
5052 \else
5053 \XePersian@m = \XePersian@i \advance \XePersian@m by -3\relax
5054 \advance \XePersian@y by -621\relax
5055 \fi
5056 \advance \XePersian@sn by -\csname XePersian@persian\romannumeral\the \XePersian@i%
5057 \endcsname
5058 \ifnum \XePersian@i = 1
5059 \XePersian@d = \XePersian@dn \advance \XePersian@d by 30 \advance \XePersian@d by -\XePersian@per
5060 \else
5061 \XePersian@d = \XePersian@dn \advance \XePersian@d by -\XePersian@sn
5062 \fi
5063 \newcommand*{\persiantoday}{\%
5064 \number \XePersian@d \space \%
5065 \XePersian@persian@month{\XePersian@m} \space \number \XePersian@y \%
5066 }
5067 \let \persianyear \XePersian@y
5068 \let \persianmonth \XePersian@m
5069 \let \persianday \XePersian@d
5070 \def \XePersian@persian@month#1{\ifcase#1\or \or \
5071 \or \
5072 \or \ or \
5073 \or \
5074 \or \ or \
5075 \or \ or \
5076 \or \ or \
5077 \fi \

```



Index

Symbols	
\!	2567
\%	4699
\.	1666, 4729
\@and	3234
\@if@newlist	1460, 1480, 3156, 3209
\@math	333
\@maybeautodot	2782, 2783, 2801, 2816, 2817, 2835, 2846, 2847, 2865
\@par	2094
\@Abjad	3242, 3250, 3251, 3653, 3654
\@Alph	2795, 2829, 2859, 3499, 3502, 3649, 3654
\@DeclareMathDelimiter	4617
\@DeclareMathSizes	4608
\@False	321, 323
\@LTRbidityftesidenote@sidenote	190
\@LTRfootnotetext	50, 66, 112, 127, 202, 209, 1526, 1543, 1736, 1751, 2124
\@LTRmarginparreset	3132
\@Latincitex	179, 180, 2358, 2367, 2557, 3140, 3141
\@Latinfalse	3122
\@Latintrue	3121, 3123, 3127
\@M	337, 1665, 1678, 1760, 3284, 3385, 3471
\@MM	20, 37, 56, 82, 99, 118, 1493, 1512, 1531, 1706, 1723, 1742
\@Mi	333
\@Mii	2017
\@Miii	2019
\@RTL@footnotefalse	3123, 3127, 3586
\@RTL@footnotetrue	3125, 3128, 3584
\@RTLbidityftesidenote@sidenote	217
\@RTLfalse	16, 52, 78, 114, 303, 315, 328, 1489, 1527, 1549, 1582, 1661, 1702, 1738, 3195, 3205, 3562, 3568
\@RTLfootnotetext	31, 65, 93, 126, 229, 236, 1507, 1542, 1717, 1750, 2125
\@RTLtrue	16, 33, 78, 95, 1489, 1508, 1549, 1567, 1661, 1702, 1719, 3195, 3205, 3560, 3566
\@Roman	2797, 2831, 2861
\@SepMark	1773, 1774, 1775, 1776, 1953
\@SetTab	2871
\@True	316, 322
\@X	4780, 4781, 4859
\@abjad	3460, 3479, 3480, 3648, 3649
\@acol	2249, 2257
\@acolampacol	2247, 2249, 2255, 2257
\@adadi	2793, 2827, 2857, 3258, 3260, 3263
\@addamp	2248, 2256
\@addtopreamble	2216
\@alph	2796, 2830, 2860, 2872, 3498, 3501, 3648, 3653
\@ampacol	2247, 2255
\@answernumberfont	4802, 4803, 4841
\@answerstitle	4799, 4840
\@answerstitlefont	4800, 4801, 4840
\@appendheader	4813, 4814, 4816
\@arrayclassz	2247
\@arraydesc	4809, 4812, 4819, 4823
\@arrayrule	2195, 2196, 2197, 2239, 2240, 2241
\@author	3955, 3967
\@autodottrue	2785, 2786, 2787, 2788, 2789, 2790, 2791, 2792, 2793,

2794, 2795, 2796, 2797, 2798,	\@chnum 2131, 2132, 2133,
2799, 2819, 2820, 2821, 2822,	2134, 2135, 2136, 2146, 2153,
2823, 2824, 2825, 2826, 2827,	2167, 2180, 2187, 2203, 2216,
2828, 2829, 2830, 2831, 2832,	2232, 2233, 2234, 2235, 2236,
2833, 2849, 2850, 2851, 2852,	2237, 2251, 2259, 2269, 2276,
2853, 2854, 2855, 2856, 2857,	2298
2858, 2859, 2860, 2861, 2862,	\@choices . 4807, 4811, 4827, 4829
2863	\@cite . . . 2346, 2353, 2365, 2381,
\@auxout 3146	2470, 3143
\@begin@tempboxa 2094	\@cite@ofmt 3151
\@begin@dv 3188	\@citea . . 2386, 2400, 2414, 2423,
\@biblabel . . . 1662, 2359, 2368	2424, 2425, 2430, 2445, 2453,
\@bibsetup 2360, 2369	2454, 2455, 2489, 2505, 2523,
\@bibtitlestyle 1658	3142, 3144
\@bidi@list@minipage@parbox@not@nobtr	\@citeb . . 2382, 2384, 2386, 2389,
. 2091, 2113	2391, 2392, 2394, 2417, 2448,
\@bidi@list@minipage@parboxtrue	2471, 2473, 2475, 2478, 2480,
. 2092, 2114	2481, 2483, 3143, 3145, 3146,
\@bidi@tufte@sidenote@citations	3147, 3150, 3151
. . . 192, 219, 246, 253	\@citex 2357, 2366
\@bidi@tufte@sidenote@infootnote@cite	\@classx 2213
. . . 191, 218, 245, 252	\@classz 2213
\@bidi@tufte@sidenote@margin@par	\@cleartopmattertags . . . 1796
. 247, 254	\@colht 3210
\@bidi@tufte@sidenote@marginfont	\@correction 4880
. 189	\@correctionstyle . . 4865, 4866,
\@bidi@tufte@sidenote@marginnote@font	4867
. 247, 254	\@ctrerr 3249, 3254
\@bidi@tufte@sidenote@marginnote@justified	\@curbox 2024, 2070, 2074, 2313,
. 247, 254	2317, 2323, 2327
\@bidi@tufte@sidenote@normal@cite	\@currentlabel 22, 39,
. . . 212, 239, 249, 256	58, 84, 101, 120, 1495, 1514,
\@bidi@tufte@sidenote@print@citations	1533, 1554, 1572, 1587, 1708,
. . . 211, 238, 248, 255	1725, 1744
\@bidi@tufte@sidenote@sidenote@vertical@offset	\@currsetenv . . . 2631, 2633, 2634
. . . 194, 196, 202, 209, 221,	\@customlogo 4055, 4064
223, 229, 236	\@custommagazinenam . . . 3824, 4057
\@bsphack 2016	\@customminilogo . . . 4056, 4070
\@capttype 2004, 2067, 2314, 2324	\@customwwwTxt . . . 3785, 3788, 3840
\@cclvi 4551, 4557, 4581	\@date 3958, 3968
\@chapapp 136, 269, 280, 287, 299,	\@dgroup 315
1441, 1453, 1959, 2749, 2756,	\@dmath 303, 332
2763, 2771, 2812, 2842	\@doendpe 2648
\@chclass 2129, 2137, 2145, 2160,	\@dseries 328
2174, 2179, 2194, 2210, 2230,	\@eha 4571, 4597
2238, 2268, 2291, 2305	\@empty 318, 1660, 1782,



2011, 2371, 2381, 2384, 2470, 2473, 2602, 3142, 3145, 3174, 3175, 3177, 3178, 3343, 3349, 3352, 3355, 3451, 3966, 3967, 3968, 3969	\@footnotetext . . . 14, 64, 76, 125, 1488, 1541, 1700, 1749, 2123
\@emptytoks 317	\@for 2382, 2471, 3143
\@enGroup 1366	\@formanswerline . . . 4836, 4845, 4858, 4862
\@enLabel . . 1357, 1358, 1359, 1360, 1361, 1362, 1363, 1364	\@fps 2005, 2006, 2008, 2011, 2028
\@enOther 1368	\@fpsadddefault 2009, 2012
\@enSpace 1365	\@freelist 2024
\@end@tempboxa 2109	\@gobble . . . 1367, 1468, 1469, 1470, 3184, 3185, 3186
\@endpbox 2223, 2224	\@harfi 12, 74, 137, 140, 149, 155, 161, 167, 270, 281, 288, 300, 1431, 1442, 1454, 1686, 1960, 2750, 2757, 2764, 2772, 2779, 2792, 2813, 2826, 2843, 2856, 3252, 3255, 3256
\@enhook 1369	\@headerfont . . . 4778, 4779, 4784, 4814
\@enloop@ 1356	\@headerline . . . 4810, 4813, 4821, 4825
\@entemp . . . 1357, 1358, 1359, 1360, 1361, 1362, 1363, 1364, 1365, 1366, 1367	\@idxitem 1675, 1680
\@enum@ 1367	\@ifclassloaded 3526, 3527, 3528, 3529, 3530, 3531, 3532, 3533, 3534, 3535, 3536, 3537, 3538, 3539, 3540, 3541, 3542, 3543, 3544, 3545, 3546, 3547, 3548, 3549, 3612, 3624, 3636
\@evenfoot 3172	\@ifdefinable 2666, 2668
\@evenhead 3171	\@ifdefinitionfileloaded 2001, 2144, 2177, 2267, 2308, 3509
\@extra@b@citeb 2386, 2392, 2394, 2417, 2448, 2475, 2481, 2483	\@ifempty 1761
\@extrafootnotefeaturesfalse 3606	\@ifnextchar . . . 2310, 2551, 2557, 3140
\@extrafootnotefeaturestrue 3604	\@ifnum . . . 2488, 2490, 2492, 2499, 2500, 2503, 2515, 2538, 2540
\@false 4864, 4872, 4879	\@ifpackageloaded 182, 1875, 1879, 2560, 2564, 2656, 2664, 3215, 3510, 3511, 3512, 3513, 3514, 3515, 3516, 3517, 3518, 3519, 3520, 3521, 3522, 3523, 3524, 3525, 3526
\@false@correction . 4856, 4879	\@ifstar 2550
\@false@nocorrection 4854, 4872	\@ifundefined . . . 178, 2386, 2392, 2475, 2481, 3147
\@falsesymbol . . 4850, 4852, 4856	
\@finalstrut . . . 1500, 1519, 1538, 1558, 1576, 1591	
\@firstampfalse 2249, 2257	
\@firstofone . . . 1639, 1640, 2384, 2473, 3145, 4554, 4578	
\@float@HH 2310, 2311	
\@float@Hx 2309, 2310	
\@float@ 2310, 2321	
\@floatboxreset 2080, 2319, 2329	
\@floatcapt 2314, 2324	
\@floatpenalty . . 2017, 2019, 2022	
\@flstylefalse 2316, 2326	
\@flstyletrue 2316, 2326	
\@fltovf 2072	
\@footnotemark 202, 209, 229, 236	



<code>\@ignoretrue</code>	339	<code>\@ne</code> .	1548, 1566, 1581, 2034, 2040, 2133, 2134, 2137, 2146, 2156, 2157, 2161, 2180, 2190, 2191, 2195, 2196, 2197, 2234, 2235, 2239, 2240, 2241, 2269, 2279, 2280, 2292, 2488, 2500, 2502, 2515, 2523, 3270, 3311, 3318, 3330, 3335, 3371, 3412, 3419, 3431, 3436, 4561, 4566, 4585, 4592
<code>\@iiiminipage</code>	2110	<code>\@newlistfalse</code>	1461, 3157
<code>\@iiiparbox</code>	2088	<code>\@next</code>	2024
<code>\@indexfile</code>	3614, 3626, 3638	<code>\@nextchar</code>	2152, 2154, 2155, 2156, 2157, 2158, 2159, 2161, 2162, 2163, 2164, 2165, 2168, 2169, 2170, 2171, 2172, 2173, 2186, 2188, 2189, 2190, 2191, 2192, 2193, 2195, 2196, 2197, 2198, 2199, 2200, 2201, 2204, 2205, 2206, 2207, 2208, 2209, 2221, 2223, 2224, 2275, 2277, 2278, 2279, 2280, 2281, 2282, 2283, 2284, 2285, 2286, 2287, 2288, 2289, 2290, 2292, 2293, 2294, 2295, 2296, 2299, 2300, 2301, 2303, 2304
<code>\@indextitlestyle</code>	1673	<code>\@nextchar</code>	2302
<code>\@initorcheck</code>	4806, 4826, 4844	<code>\@nil</code>	2577, 2581, 2582, 2587, 2589, 3301, 3304, 3402, 3405
<code>\@inlabelfalse</code>	306	<code>\@nodocument</code>	2003
<code>\@input@</code>	3616, 3628, 3640	<code>\@noitemerr</code>	1668
<code>\@lastchclass</code>	2129, 2130, 2146, 2147, 2148, 2149, 2151, 2180, 2181, 2182, 2183, 2185, 2230, 2231, 2247, 2255, 2269, 2270, 2271, 2272, 2274	<code>\@nx</code>	1791, 1792
<code>\@latex@error</code>	4569, 4595	<code>\@oddfoot</code>	3169, 3178
<code>\@latex@warning</code>	1668, 3149	<code>\@oddhead</code>	3169, 3177
<code>\@latinAlpha</code>	3499, 3502	<code>\@onelevel@sanitize</code>	2006
<code>\@latinalph</code>	2872, 3498, 3501	<code>\@outputbox</code>	1478, 3201
<code>\@listdepth</code>	2126	<code>\@outputpage</code>	1456, 3152
<code>\@m</code>	1666, 2363, 3144, 3283, 3384, 3469	<code>\@parboxrestore</code>	21, 38, 57, 83, 100, 119, 1461, 1494, 1513, 1532, 1553, 1571, 1586, 1707, 1724, 1743, 2079, 2094, 2121, 2318, 2328, 3158
<code>\@mainmatterfalse</code>	264, 275, 293, 1435, 2806	<code>\@parboxto</code>	2097, 2106
<code>\@makefnmark</code>	1693	<code>\@parmoderr</code>	2022
<code>\@makefntext</code>	24, 41, 60, 86, 103, 122, 1499, 1518, 1537, 1557, 1575, 1590, 1710, 1727, 1746	<code>\@pboxswfalse</code>	2090, 2112
<code>\@maketitle</code>	1787	<code>\@pboxswtrue</code>	2104
<code>\@maketitle@hook</code>	1785		
<code>\@maskanswerline</code>	4837, 4846, 4859, 4863		
<code>\@memfront</code>	1951		
<code>\@minipagefalse</code>	3137		
<code>\@minipagerestore</code>	2127		
<code>\@minipagetrue</code>	3136		
<code>\@mpLTRfootnotetext</code>	1580, 2124		
<code>\@mpRTLfootnotetext</code>	1565, 2125		
<code>\@mpargs</code>	2116		
<code>\@mpfn</code>	200, 206, 227, 233, 2122		
<code>\@mpfootins</code>	1549, 1550, 1567, 1568, 1582, 1583		
<code>\@mpfootnotetext</code>	1547, 2123		
<code>\@mplistdepth</code>	2126		
<code>\@namedef</code>	2340, 2394, 2483, 2647		
<code>\@nameuse</code>	3166		



\@plus 1676, 1754
\@pnumwidth 1767, 1769
\@ppsavesec 131
\@preamble 2250, 2258
\@preamblecmds 4622
\@preamerr 2140, 2174, 2210, 2244,
2305
\@questionheader ... 4836, 4837,
4868
\@questionsepspace . 4892, 4897,
4903
\@questiontitle 4885, 4898
\@questiontitlefont 4886, 4887,
4898
\@resetactivechars . 1459, 3155
\@resetspp 130, 1645, 1646
\@restonecolfalse 1671
\@restonecoltrue 1671
\@roman 2798, 2832, 2862
\@safe@activesfalse 2385, 2474
\@safe@activetrue . 2383, 2472
\@secpenalty 1759
\@setcopyright 1779
\@setfontsize
... 3755, 3761, 3763, 3766,
3773, 3779, 3780, 3781, 3782,
3783
\@setfpsbit .. 2044, 2047, 2050,
2053, 2056, 2059
\@setminipage 2128
\@setnobreak 2319, 2329
\@sharp .. 2252, 2253, 2254, 2260,
2261, 2262
\@smemfront 1952
\@specialpagefalse 3166
\@specialstyle 3166
\@sptoken 1365
\@startpbox 2223, 2224
\@startsection 1753
\@starttoc 3218, 4789, 4794
\@stop 2783, 2817, 2847
\@sx@xepersian@localize@verbatim
..... 2340
\@tabclassz 2255
\@tartibi 9, 70,
145, 151, 157, 163, 261, 272,
283, 295, 1427, 1437, 1449,
1683, 1954, 1955, 2745, 2752,
2759, 2767, 2775, 2794, 2808,
2828, 2838, 2858, 3364, 3366,
3369
\@tempa 1357, 1358,
1359, 1360, 1361, 1362, 1363,
1364, 1365, 1366, 1367, 1368,
1371, 1790, 1793, 2587, 2589,
2672, 2673, 2674, 2675, 2676,
2677, 2678, 2679, 2680, 2681,
2682
\@tempboxa 2117, 3191, 3198, 3199
\@tempc .. 2602, 2615, 2625, 2627,
2628, 2631, 2639
\@tempcnta 2026, 2032, 2034, 2038,
2040, 2062, 2063, 2069, 2070,
2214, 2497, 2498, 2499, 2502,
2503
\@tempcntb ... 2067, 2068, 2069
\@tempdima 1762, 1764, 1766, 1768,
2093, 2094, 2115, 2119
\@tempdimb 2096, 2097
\@tempswafalse 2515, 3140
\@tempswatrue 2514, 3140
\@temptokena
... 1788, 1792, 2588, 2595,
2600, 2606, 2613, 2623, 2637
\@testpach 2129, 2145, 2179, 2230,
2268
\@tfor 2027, 2672
\@thanks 3960, 3966
\@the@choice 4815, 4816
\@thefnmark 23, 40, 59, 85,
102, 121, 201, 207, 228, 234,
1496, 1515, 1534, 1555, 1573,
1588, 1695, 1709, 1726, 1745
\@thefoot . 3169, 3172, 3175, 3178,
3205
\@thehead . 3169, 3171, 3174, 3177,
3195
\@themargin 1474, 3170, 3172, 3190
\@title 3948, 3969
\@tocline 1756
\@tocpagenum 1769
\@topnum 1778



`\@true` 4860, 4871, 4878
`\@true@correction` . . 4855, 4878
`\@true@nocorrection` 4853, 4871
`\@truesymbol` . . . 4849, 4851, 4855
`\@verbatim` 2337, 2340, 2645, 2647,
2658
`\@vobeyspaces` 2337, 2645
`\@warning` 2644
`\@width` 1692
`\@x@xepersian@localize@verbatim`
. 2337
`\@xDeclareMathDelimiter` . 4617
`\@xepersian@info` . . . 2910, 2931,
2933
`\@xfloat` 2002, 2309, 2310
`\@xp` 1788
`\@xxDeclareMathDelimiter` 4616
`\@xxxii` 2068
`@\` 1981, 1982
`@` 1977, 1978, 1980
`@\` 2559
`] \` 2567
`\ \` 1789, 2334, 2567,
3916, 4231, 4232, 4494, 4497,
4546, 4782, 4821, 4825, 4845,
4846
`\{` 2333, 2567
`\}` 2333, 2567
`\]` 2567
`\^` 2568
`_` . 2965, 2967, 2982, 2984, 2999,
3001, 3014, 3016, 3059, 3061,
3068, 3070, 3077, 3079, 3086,
3088, 3095, 3097, 3104, 3106,
4678, 4680, 4706, 4708, 4715,
4717
`\|` 4232
`\~` 2568

`_` 1600, 1602, 3144, 3307, 3313, 3332,
3338, 3408, 3414, 3433, 3439,
3831, 3840

A
`\abj@num@i` 3465, 3482, 3489

`\abj@num@ii` . . . 3467, 3486, 3493
`\abj@num@iii` . . . 3469, 3490, 3496
`\abj@num@iv` 3471, 3494
`\Abjad` 3250
`\abjad` 3479
`\abjad@zero` 3481, 3485
`\Abjadnumeral` 3251
`\abjadnumeral` 3480
`\abovedisplayshortskip`
. . . 3758, 3759, 3769, 3770,
3776, 3777
`\abovedisplayskip` . . 3756, 3757,
3767, 3768, 3774, 3775
`\abstractname` 3231
`\active` 2568, 4729
`\adadi` . . . 1358, 2786, 2820, 2850,
3257
`\adadinumeral` 3263
`\addfontfeatures` . 303, 315, 328
`\addpenalty` 1759
`\addtocontents` 4788,
4791, 4793, 4796, 4818, 4822,
4845, 4846
`\addtolength`
. . . 3983, 3984, 3987, 4406,
4407, 4408, 4409, 4473
`\addtoversion` 4609
`\addvspace` 1759
`\adl@argarraydashrule` 2197, 2241
`\adl@arraydashrule` . 2196, 2240
`\adl@arrayrule` 2195, 2239
`\adl@box` 2221, 2223, 2224
`\adl@class@iiiorvii` 2227, 2264
`\adl@class@start` . . . 2226, 2263
`\adl@endmbox` 2222
`\adl@putlrc` 2218, 2219, 2220, 2252,
2253, 2254, 2260, 2261, 2262
`\adl@startmbox` 2221
`\advance` . 1603, 1663, 1766, 2034,
2040, 2063, 2069, 2502, 3747,
3751, 4019, 4022, 4566, 4592,
4940, 4975, 4979, 4985, 4989,
4994, 4997, 4998, 5002, 5006,
5007, 5009, 5010, 5012, 5032,
5036, 5037, 5040, 5045, 5046,
5050, 5051, 5053, 5054, 5056,



5059, 5061
 \aftergroup 1463, 1465, 3153, 3161,
 3162
 \ALG@name 5, 7
 \algorithmicensure 3
 \algorithmicrequire 2
 \ALGS@name 6, 7
 \aliasfontfeature 1891,
 1892, 1893, 1894, 1895, 1896,
 1897, 1898, 1899, 1900, 1901,
 1902, 1903, 1904, 1905, 1906,
 1907, 1908, 1909, 1910, 1911,
 1912, 1913, 1914, 1915, 1916,
 1917, 1918, 1919, 1920, 1921,
 1922, 1923, 1924, 1925, 1926,
 1927, 1928, 1929, 1930, 1931,
 1932, 1933, 1934, 1935, 1936,
 1937, 1938, 1939, 1940, 1941,
 1942, 1943
 \aliasfontfeatureoption . 1944,
 1945, 1946, 1947, 1948, 1949
 \alloc@ 4551
 \Alph 1360, 1632, 1633, 2788, 2822,
 2852
 \alph 1361, 2789, 2823, 2853, 2879,
 4815, 4841
 \alpha@elt 4610
 \alpha@list 4610
 \anappendixtrue 1961
 \and 3973
 \andify 1783
 \answernumberfont 4803
 \answerstitle 4799, 4869
 \answerstitlefont 4801
 \appendix 10, 71, 146,
 152, 158, 164, 266, 277, 284,
 296, 1428, 1438, 1450, 1629,
 1630, 1684, 1956, 2746, 2753,
 2760, 2768, 2776, 2809, 2839
 \appendixautorefname 1618
 \appendixname 11, 73,
 136, 269, 280, 287, 299, 1441,
 1453, 1685, 1959, 2749, 2756,
 2763, 2771, 2812, 2842, 3228
 \arabic ... 1364, 1660, 1773, 1774,
 1775, 1776
 \arrayrulewidth 4488
 \articlesep 4470
 \AtBeginDocument
 177, 1628, 1850, 2340,
 2547, 2652, 3745, 3749
 \AtEndOfClass 3743
 \author 3971
 \authorandplace 4444
 \autofootnoterule 3572
 \AutoMathsDigits ... 3552, 4762,
 4766
 B
 \backrefpagesname 169
 \baselineskip 247, 254, 1471, 3187,
 3202
 \begin 2561, 2562,
 3127, 3128, 3216, 3799, 3802,
 3855, 3870, 3883, 3889, 3910,
 3941, 3947, 3954, 3978, 4032,
 4038, 4110, 4113, 4118, 4125,
 4140, 4155, 4172, 4206, 4224,
 4229, 4249, 4256, 4257, 4278,
 4280, 4281, 4303, 4308, 4309,
 4345, 4346, 4354, 4380, 4388,
 4394, 4395, 4403, 4433, 4457,
 4489, 4490, 4505, 4517, 4531,
 4819, 4823, 4834, 4835, 4841,
 4896
 \beginingroup 205, 232, 311,
 1457, 1760, 1786, 2332, 2549,
 2565, 2645, 2647, 2937, 2939,
 3153, 4558, 4582, 4729
 \beginL .. 3137, 3195, 3205, 3831,
 4232
 \beginR .. 3195, 3205, 3835, 3836,
 3837, 3848, 3849, 3850, 4055,
 4056, 4057, 4075, 4096, 4097,
 4098, 4099, 4100, 4101, 4252,
 4347
 \belowdisplayshortskip .. 3759,
 3770, 3777
 \belowdisplayskip .. 3757, 3768,
 3775
 \bfseries 1755, 2387, 2476,
 3147, 3791, 3797, 3816, 3824,



3852, 3868, 3887, 3901, 3905,
 3930, 3935, 3939, 4064, 4070,
 4778, 4800, 4802, 4886
 \bgroup . . . 1366, 2077, 2117, 2318,
 2328, 4554, 4578
 \biblio font 1659
 \bibname 3235
 \bidi@AfterEndPreamble . . 3504
 \bidi@csdefcs 954, 1873
 \bidi@csletcs . . . 649, 1873, 1877,
 1878, 1881, 1882
 \bidi@footdir@footnote 64, 125,
 1541, 1749
 \bidi@isloaded . 1844, 1845, 1846,
 1847, 1848, 1849, 1852, 1855,
 1858, 1861, 1864, 1867
 \bidi@mpfootnoterule 1548, 1566,
 1581
 \bidi@newrobustcmd . 3121, 3122
 \bidi@reflect@box 3222
 \blacktriangleleft . 1598, 1600
 \blacktriangleright . 1598, 1600
 \bm@b 2085
 \bm@c 2082
 \bm@l 2083
 \bm@r 2084
 \bm@s 2087
 \bm@t 2086
 \bm@ 2086
 \bm@ 2084
 \bm@ 2085
 \bm@ 2082
 \bm@ 2083
 \bm@ 2087
 \bool 4604
 \boolean . 3732, 3744, 3753, 3857,
 3872, 3891, 3912, 4108, 4109,
 4139, 4171, 4205, 4223, 4247,
 4277, 4301, 4328
 \botmark 1483, 3212
 \box 317, 1478, 3199, 3201
 \BR@Latincitex 170, 180
 \BRorg@Latincitex 171, 179

C

\C 2569

\c . . 4638, 4646, 4654, 4662, 4670
 \c@book 1954
 \c@chapter 72,
 74, 137, 270, 281, 288, 300,
 1442, 1454, 1960, 2750, 2757,
 2764, 2772, 2813, 2843
 \c@footnote 1795
 \c@mpfootnote . . 1548, 1566, 1581,
 2122
 \c@part 9, 70, 145, 151, 157, 163, 261,
 272, 283, 295, 1427, 1437,
 1449, 1683, 1955, 2745, 2752,
 2759, 2767, 2775, 2808, 2838
 \c@section 10, 12, 72, 140,
 149, 155, 161, 167, 1431, 1684,
 1686, 2779
 \c@subsection 10, 1684
 \c@tocdepth 1757
 \catcode . 1871, 2332, 2333, 2334,
 2568, 4729
 \ccname 3237
 \cdp@elt 4607
 \cdp@list 4607
 \centering . . . 3994, 4282, 4783
 \cftchapname 2891
 \cftfigname 2897
 \cftparaname 2895
 \cftsecname 2892
 \cftsubfigname 2898
 \cftsubparaname 2896
 \cftsubsecname 2893
 \cftsubsubsecname 2894
 \cftsubtabname 2900
 \cfttabname 2899
 \chapterautorefname 1619
 \chaptername 73, 3236
 \chardef . . 1799, 1801, 1802, 1803,
 1804, 1805, 4551
 \charlist . . 1809, 1810, 1812, 1816
 \citation 3146
 \cite . 191, 212, 218, 239, 245, 249,
 252, 256
 \citenumfont 2526
 \citeyear 2348
 \citeyearpar 2348
 \ClassError 4129,



4161, 4195, 4215, 4236, 4261,
 4286, 4312, 4335, 4828
 \ClassWarning . . . 3714, 3716, 3718,
 3988, 4002
 \cleardoubleoddpaper 2805
 \cleardoublepage . . . 69, 263, 274,
 292, 1434
 \clearpage 2805, 4092
 \closeout 3614, 3626, 3638
 \clubpenalty 1665
 \color@begingroup . . . 1498, 1517,
 1536, 1556, 1574, 1589, 2118
 \color@endbox 3196, 3206
 \color@endgroup . . . 1501, 1520, 1539,
 1559, 1577, 1592
 \color@hbox 3193, 3203
 \color@vbox 2075, 2317, 2327
 \columnlines . . . 3688, 3689, 3721,
 4050
 \columnsep 1672, 3984, 4407
 \columnseprule 1672, 4050
 \columntitle 4401
 \columnwidth 20, 37, 56,
 82, 99, 118, 1494, 1513, 1532,
 1552, 1570, 1585, 1689, 1706,
 1723, 1742, 2078, 2120, 2318,
 2328, 3983, 4406
 \comment 4873
 \contentsname 3216, 3225
 \copyright 3840
 \correction 4873, 4880
 \correctionstyle 4866
 \count 2070, 3169, 4018, 4019, 4021,
 4022, 4031, 4037
 \count@ 2214
 \cs 2655, 2657, 2967, 2969, 2975,
 2978, 2984, 2986, 2992, 2996,
 2997, 3001, 3003, 3009, 3016,
 3018, 3024, 3061, 3070, 3079,
 3088, 3097, 3106, 4631, 4632,
 4633, 4634, 4635, 4680, 4701,
 4702, 4703, 4708, 4712, 4717,
 4721
 \csname 23,
 40, 59, 85, 102, 121, 206, 233,
 1496, 1515, 1534, 1555, 1573,

1588, 1709, 1726, 1745, 1762,
 1874, 2067, 2107, 2312, 2315,
 2322, 2325, 2342, 2649, 2666,
 2667, 2668, 2669, 2670, 2780,
 2814, 2844, 2938, 2941, 2947,
 2949, 3151, 3250, 3255, 3258,
 3364, 3479, 4557, 4560, 4565,
 4566, 4581, 4584, 4588, 4589,
 4592, 4627, 4629, 5037, 5046,
 5056
 \currenttime 3814
 \customlogo 4055
 \custommagazinenam 4057
 \customminilogo 4056
 \customwwwTxt 3785

D

\dollarbegin 2218, 2219, 2220
 \dollarend 2218, 2219, 2220
 \date 3813, 3824, 3972, 4441
 \datename 3233
 \day 4935
 \decimalseparator . . . 4700, 4756
 \DeclareDocumentCommand
 2964, 2981, 2998, 3013,
 3058, 3067, 3076, 3085, 3094,
 3103, 4676, 4705, 4714
 \DeclareMathAccent 4615
 \DeclareMathAlphabet 4614
 \DeclareMathDelimiter 4616
 \DeclareMathRadical 4618
 \DeclareMathSizes 4607
 \DeclareMathSymbol 4615
 \DeclareMathVersion 4609
 \DeclareOption
 3710, 3711, 3712, 3713,
 3715, 3717, 3719, 3720, 3721,
 3722, 3723, 4870, 4877
 \DeclareOptionX 3657
 \DeclareRobustCommand
 2548, 2972, 2989, 3006,
 3021, 3034, 3037, 3040, 3043,
 3046, 3049, 3139
 \DeclareSymbolFont 4612, 4684,
 4685, 4686, 4687, 4711, 4720
 \DeclareSymbolFontAlphabet . . 4619



<code>\DeclareSymbolFontAlphabet@</code> .	3370, 3379, 3405, 3418, 3429,
..... 4619	3443, 3450, 3460, 3479, 3481,
<code>\DeclareTextFontCommand</code>	3482, 3486, 3490, 3494, 3500,
.. 3052, 3053, 3054, 3055,	3647, 3652, 3785, 4055, 4056,
3056, 3057	4057, 4551, 4553, 4577, 4688,
<code>\def</code>	4712, 4721, 4730, 4731, 4756,
2, 3, 5, 6, 7,	4757, 4758, 4762, 4778, 4780,
10, 12, 14, 31, 50, 69, 71, 74,	4782, 4800, 4802, 4806, 4813,
76, 93, 112, 169, 170, 183, 190,	4849, 4850, 4853, 4854, 4855,
217, 259, 303, 315, 328, 335,	4856, 4865, 4868, 4875, 4876,
339, 1356, 1357, 1358, 1359,	4882, 4883, 4886, 5070
1360, 1361, 1362, 1363, 1364,	
1456, 1488, 1507, 1526, 1547,	<code>\def@NAT@last@yr</code> ... 2505, 2507
1565, 1580, 1595, 1597, 1599,	<code>\defaultfontfeatures</code> 3658
1601, 1612, 1613, 1614, 1615,	<code>\DefaultMathsDigits</code> 3554, 4757
1616, 1617, 1618, 1619, 1620,	<code>\define@choicekey</code>
1621, 1622, 1623, 1624, 1625,	.. 3550, 3558, 3564, 3570,
1626, 1627, 1630, 1641, 1646,	3582, 3588, 3594, 3598, 3602,
1668, 1671, 1680, 1681, 1682,	3608, 3621, 3633, 3645
1684, 1686, 1687, 1691, 1693,	<code>\define@key</code>
1700, 1717, 1736, 1753, 1756,	2671
1777, 1789, 1806, 1809, 1811,	<code>\define@mathalphabet</code> 4609
1812, 1817, 1841, 1842, 1964,	<code>\define@mathgroup</code>
1965, 1966, 1967, 1968, 1969,	4609
1970, 1971, 1972, 2002, 2004,	<code>\deflatinfont</code>
2005, 2007, 2088, 2110, 2116,	3013
2122, 2129, 2145, 2179, 2213,	<code>\defpersianfont</code>
2226, 2227, 2230, 2247, 2255,	2998
2263, 2264, 2268, 2310, 2311,	<code>\depth</code>
2314, 2321, 2324, 2337, 2338,	2679, 2680
2347, 2350, 2362, 2363, 2373,	<code>\dimexpr</code>
2376, 2389, 2404, 2434, 2466,	1689
2470, 2495, 2557, 2571, 2575,	<code>\ding</code>
2577, 2578, 2581, 2587, 2589,	4849, 4850
2591, 2607, 2610, 2626, 2627,	<code>\display@setup</code>
2630, 2643, 2645, 2648, 2665,	304, 329
2902, 2903, 2934, 2935, 2936,	<code>\divide</code> .. 4024, 4025, 4937, 4945,
2942, 2943, 2947, 3113, 3117,	4950, 4977, 4983, 4991, 4993,
3123, 3124, 3125, 3126, 3130,	4996, 5000, 5004, 5008
3131, 3132, 3141, 3144, 3152,	<code>\do</code> . 2029, 2382, 2471, 2672, 3143,
3221, 3223, 3224, 3225, 3226,	4622
3227, 3228, 3229, 3230, 3231,	<code>\document</code>
3232, 3233, 3234, 3235, 3236,	4768
3237, 3238, 3239, 3240, 3241,	<code>\document@select@group</code> .. 4577
3242, 3250, 3252, 3255, 3264,	<code>\dorestore@version</code>
3269, 3278, 3304, 3317, 3328,	4611
3342, 3348, 3351, 3354, 3358,	<code>\dosetclass</code> 1810, 1811, 1815
	<code>\doublebox</code>
	4363, 4416
	<code>\dp</code> 19, 36, 55, 81, 98, 117, 1493, 1512,
	1531, 1705, 1722, 1741, 3198
	<code>\dquad</code>
	337, 339
	<code>\dseries@display@setup</code> ... 329
	E
	<code>\edef</code> 1790, 2097, 2152, 2186, 2250,
	2258, 2275, 2384, 2473, 2633,



2910, 2932, 2941, 2944, 3145,	2351, 2364, 2396, 2401, 2410,
4815	2413, 2427, 2431, 2440, 2444,
\edition 4082	2447, 2459, 2463, 2464, 2485,
\editionFormat 3791, 3794	2506, 2520, 2522, 2525, 2539,
\editorialAuthorFormat . . . 3934,	2541, 2552, 2575, 2586, 2599,
4498	2601, 2604, 2619, 2621, 2627,
\editorialTitleFormat . . . 3932,	2635, 2643, 2670, 2673, 2674,
3933	2675, 2676, 2677, 2678, 2679,
\else 2, 3, 5, 7, 16, 25, 78, 87,	2680, 2681, 2784, 2805, 2818,
138, 169, 259, 307, 337, 1357,	2848, 2875, 2891, 2892, 2893,
1358, 1359, 1360, 1361, 1362,	2894, 2895, 2896, 2897, 2898,
1363, 1364, 1365, 1366, 1367,	2899, 2900, 2958, 3171, 3176,
1445, 1489, 1500, 1548, 1549,	3182, 3195, 3205, 3223, 3224,
1558, 1598, 1600, 1602, 1612,	3225, 3226, 3227, 3228, 3229,
1613, 1614, 1615, 1616, 1617,	3230, 3231, 3232, 3233, 3234,
1618, 1619, 1620, 1621, 1622,	3235, 3236, 3237, 3238, 3239,
1623, 1624, 1625, 1626, 1627,	3240, 3241, 3249, 3254, 3272,
1661, 1677, 1702, 1711, 1755,	3274, 3282, 3283, 3284, 3285,
1758, 1766, 1767, 1783, 1814,	3286, 3287, 3288, 3289, 3307,
1841, 1842, 1851, 1854, 1857,	3322, 3336, 3349, 3352, 3373,
1860, 1863, 1866, 1964, 1965,	3375, 3383, 3384, 3385, 3386,
1966, 1967, 1968, 1969, 1970,	3387, 3388, 3389, 3390, 3408,
1971, 1972, 2010, 2018, 2023,	3423, 3436, 3437, 3462, 3464,
2033, 2039, 2092, 2095, 2100,	3466, 3468, 3470, 3617, 3629,
2101, 2102, 2103, 2104, 2114,	3641, 4001, 4479, 4554, 4567,
2129, 2130, 2131, 2132, 2133,	4573, 4578, 4593, 4599, 4724,
2134, 2135, 2136, 2137, 2138,	4732, 4733, 4734, 4735, 4736,
2139, 2140, 2146, 2147, 2148,	4737, 4738, 4739, 4740, 4741,
2150, 2151, 2154, 2155, 2156,	4742, 4756, 4759, 4760, 4761,
2157, 2158, 2159, 2161, 2162,	4763, 4764, 4765, 4943, 4947,
2163, 2164, 2165, 2168, 2169,	4952, 4953, 4960, 4981, 4986,
2170, 2171, 2172, 2173, 2180,	5016, 5052, 5060
2181, 2182, 2184, 2185, 2188,	
2189, 2190, 2191, 2192, 2193,	\empty 1813
2195, 2196, 2197, 2198, 2199,	\enclname 3238
2200, 2201, 2204, 2205, 2206,	\end 1810, 1811, 1816,
2207, 2208, 2209, 2229, 2230,	1817, 2561, 2562, 2633, 2644,
2231, 2232, 2233, 2234, 2235,	3127, 3128, 3219, 3799, 3804,
2236, 2237, 2239, 2240, 2241,	3861, 3875, 3885, 3894, 3917,
2242, 2243, 2244, 2269, 2270,	3956, 3959, 3962, 3979, 4034,
2271, 2273, 2274, 2277, 2278,	4040, 4117, 4123, 4127, 4153,
2279, 2280, 2281, 2282, 2283,	4159, 4193, 4213, 4228, 4234,
2284, 2285, 2286, 2287, 2288,	4270, 4271, 4272, 4295, 4296,
2289, 2290, 2292, 2293, 2294,	4297, 4321, 4322, 4323, 4348,
2295, 2296, 2299, 2300, 2301,	4349, 4352, 4382, 4386, 4397,
2302, 2303, 2304, 2316, 2326,	4398, 4435, 4439, 4468, 4499,
	4500, 4514, 4526, 4539, 4788,



4791, 4793, 4796, 4842, 4843, 4847, 4901		\eq@startup	313
\end@correction	4881	\eq@wdCond	331
\endcomment	4874	\eqcommand	343, 344, 345, 346, 347, 348, 349, 350, 351, 352, 353, 354, 355, 356, 357, 358, 359, 360, 361, 362, 363, 364, 365, 366, 367, 368, 369, 370, 371, 372, 373, 374, 375, 376, 377, 378, 379, 380, 381, 382, 383, 384, 385, 386, 387, 388, 389, 390, 391, 392, 393, 394, 395, 396, 397, 398, 399, 400, 401, 402, 403, 404, 405, 406, 407, 408, 409, 410, 411, 412, 413, 414, 415, 416, 417, 418, 419, 420, 421, 422, 423, 424, 425, 426, 427, 428, 429, 430, 431, 432, 433, 434, 435, 436, 437, 438, 439, 440, 441, 442, 443, 444, 445, 446, 447, 448, 449, 450, 451, 452, 453, 454, 455, 456, 457, 458, 459, 460, 461, 462, 463, 464, 465, 466, 467, 468, 469, 470, 471, 472, 473, 474, 475, 476, 477, 478, 479, 480, 481, 482, 483, 484, 485, 486, 487, 488, 489, 490, 491, 492, 493, 494, 495, 496, 497, 498, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 532, 533, 534, 535, 536, 537, 538, 539, 540, 541, 542, 543, 544, 545, 546, 547, 548, 549, 550, 551, 552, 553, 554, 555, 556, 557, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576, 577, 578, 579, 580, 581, 582, 583, 584, 585, 586, 587, 588, 589, 590, 591, 592, 593, 594, 595, 596, 597, 598, 599, 600, 601, 602, 603, 604, 605,
\endcsname	23, 40, 59, 85, 102, 121, 206, 233, 1496, 1515, 1534, 1555, 1573, 1588, 1709, 1726, 1745, 1762, 1874, 2067, 2107, 2312, 2315, 2322, 2325, 2342, 2649, 2666, 2667, 2668, 2669, 2670, 2780, 2814, 2844, 2938, 2941, 2947, 2949, 3151, 3250, 3255, 3258, 3364, 3479, 4557, 4560, 4565, 4566, 4581, 4584, 4588, 4590, 4592, 4627, 4629, 5037, 5046, 5057		
\endgroup	208, 235, 1464, 1771, 1794, 2570, 2648, 2937, 2945, 3153, 3161, 4562, 4586, 4732, 4733, 4734, 4735, 4736, 4737, 4738, 4739, 4740, 4741, 4742, 4743		
\endL	3195, 3205, 3831, 4232		
\endlatin	3124		
\endlist	1669		
\endLTR	3124		
\endMakeFramed	1606		
\endmath	334		
\endpersian	3126		
\endquestion	4894		
\endR	3195, 3205, 3835, 3836, 3837, 3848, 3849, 3850, 4055, 4056, 4057, 4075, 4096, 4097, 4098, 4099, 4100, 4101, 4252, 4347		
\endRTL	3126		
\ends@math	334		
\endtrivlist	2338, 2648		
\end	2338, 2342, 2648, 2649		
\eq@addpunct	339		
\eq@group	307, 316		
\eq@GRP@first@dmath	316		
\eq@prelim	307, 324		
\eq@setnumber	310		
\eq@setup@a	312		



606, 607, 608, 609, 610, 611,
612, 613, 614, 615, 616, 617,
618, 619, 620, 621, 622, 623,
624, 625, 626, 627, 628, 629,
630, 631, 632, 633, 634, 635,
636, 637, 638, 639, 640, 641,
642, 643, 644, 645, 646, 647,
648, 650, 651, 652, 653, 654,
655, 656, 657, 658, 659, 660,
661, 662, 663, 664, 665, 666,
667, 668, 669, 670, 671, 672,
673, 674, 675, 676, 677, 678,
679, 680, 681, 682, 683, 684,
685, 686, 687, 688, 689, 690,
691, 692, 693, 694, 695, 696,
697, 698, 699, 700, 701, 702,
703, 704, 705, 706, 707, 708,
709, 710, 711, 712, 713, 714,
715, 716, 717, 718, 719, 720,
721, 722, 723, 724, 725, 726,
727, 728, 729, 730, 731, 732,
733, 734, 735, 736, 737, 738,
739, 740, 741, 742, 743, 744,
745, 746, 747, 748, 749, 750,
751, 752, 753, 754, 755, 756,
757, 758, 759, 760, 761, 762,
763, 764, 765, 766, 767, 768,
769, 770, 771, 772, 773, 774,
775, 776, 777, 778, 779, 780,
781, 782, 783, 784, 785, 786,
787, 788, 789, 790, 791, 792,
793, 794, 795, 796, 797, 798,
799, 800, 801, 802, 803, 804,
805, 806, 807, 808, 809, 810,
811, 812, 813, 814, 815, 816,
817, 818, 819, 820, 821, 822,
823, 824, 825, 826, 827, 828,
829, 830, 831, 832, 833, 834,
835, 836, 837, 838, 839, 840,
841, 842, 843, 844, 845, 846,
847, 848, 849, 850, 851, 852,
853, 854, 855, 856, 857, 858,
859, 860, 861, 862, 863, 864,
865, 866, 867, 868, 869, 870,
871, 872, 873, 874, 875, 876,
877, 878, 879, 880, 881, 882,

883, 884, 885, 886, 887, 888,
889, 890, 891, 892, 893, 894,
895, 896, 897, 898, 899, 900,
901, 902, 903, 904, 905, 906,
907, 908, 909, 910, 911, 912,
913, 914, 915, 916, 917, 918,
919, 920, 921, 922, 923, 924,
925, 926, 927, 928, 929, 930,
931, 932, 933, 934, 935, 936,
937, 938, 939, 940, 941, 942,
943, 944, 945, 946, 947, 948,
949, 950, 951, 952, 953, 955,
956, 957, 958, 959, 960, 961,
962, 963, 964, 965, 966, 967,
968, 969, 970, 971, 972, 973,
974, 975, 976, 977, 978, 979,
980, 981, 982, 983, 984, 985,
986, 987, 988, 989, 990, 991,
992, 993, 994, 995, 996, 997,
998, 999, 1000, 1001, 1002,
1003, 1004, 1005, 1006, 1007,
1008, 1009, 1010, 1011, 1012,
1013, 1014, 1015, 1016, 1017,
1018, 1019, 1020, 1021, 1022,
1023, 1024, 1025, 1026, 1027,
1028, 1029, 1030, 1031, 1032,
1033, 1034, 1035, 1036, 1037,
1038, 1039, 1040, 1041, 1042,
1043, 1044, 1045, 1046, 1047,
1048, 1049, 1050, 1051, 1052,
1053, 1054, 1055, 1056, 1057,
1058, 1059, 1060, 1061, 1062,
1063, 1064, 1065, 1066, 1067,
1068, 1069, 1070, 1071, 1072,
1073, 1074, 1075, 1076, 1077,
1078, 1079, 1080, 1081, 1082,
1083, 1084, 1085, 1086, 1087,
1088, 1089, 1090, 1091, 1092,
1093, 1094, 1095, 1096, 1097,
1098, 1099, 1100, 1101, 1102,
1103, 1104, 1105, 1106, 1107,
1108, 1109, 1110, 1111, 1112,
1113, 1114, 1115, 1116, 1117,
1118, 1119, 1120, 1121, 1122,
1123, 1124, 1125, 1126, 1127,
1128, 1129, 1130, 1131, 1132,



1133, 1134, 1135, 1136, 1137,	1384, 1385, 1386, 1387, 1388,
1138, 1139, 1140, 1141, 1142,	1389, 1390, 1391, 1392, 1393,
1143, 1144, 1145, 1146, 1147,	1394, 1395, 1396, 1397, 1398,
1148, 1149, 1150, 1151, 1152,	1399, 1400, 1401, 1402, 1403,
1153, 1154, 1155, 1156, 1157,	1404, 1405, 1406, 1407, 1408,
1158, 1159, 1160, 1161, 1162,	1409, 1410, 1411, 1412, 1413,
1163, 1164, 1165, 1166, 1167,	1414, 1416, 1417, 1418, 1419,
1168, 1169, 1170, 1171, 1172,	1420, 1421, 1422, 1423, 1424,
1173, 1174, 1175, 1176, 1177,	1425, 1874
1178, 1179, 1180, 1181, 1182,	<code>\eqstyle</code> 309
1183, 1184, 1185, 1186, 1187,	<code>\equal</code> . . . 4030, 4185, 4357, 4362,
1188, 1189, 1190, 1191, 1192,	4367, 4372, 4377, 4410, 4415,
1193, 1194, 1195, 1196, 1197,	4420, 4425, 4430
1198, 1199, 1200, 1201, 1202,	<code>\equationautorefname</code> 1612
1203, 1204, 1205, 1206, 1207,	<code>\escapechar</code> . . 2940, 4559, 4583
1208, 1209, 1210, 1211, 1212,	<code>\evensidemargin</code> 3172
1213, 1214, 1215, 1216, 1217,	<code>\everydisplay</code> 304, 4768
1218, 1219, 1220, 1221, 1222,	<code>\everyjob</code> 2932, 2933
1223, 1224, 1225, 1226, 1227,	<code>\everymath</code> 4767
1228, 1229, 1230, 1231, 1232,	<code>\everypar</code> 3137
1233, 1234, 1235, 1236, 1237,	<code>\ExecuteOptions</code> 4884
1238, 1239, 1240, 1241, 1242,	<code>\ExecuteOptionsX</code> 3663
1243, 1244, 1245, 1246, 1247,	<code>\exp</code> . 2972, 2974, 2975, 2989, 2991,
1248, 1249, 1250, 1251, 1252,	2992, 3006, 3008, 3009, 3021,
1253, 1254, 1255, 1256, 1257,	3023, 3024
1258, 1259, 1260, 1261, 1262,	<code>\expandafter</code>
1263, 1264, 1265, 1266, 1267,	304, 1810, 1816, 2027, 2028,
1268, 1269, 1270, 1271, 1272,	2152, 2186, 2275, 2312, 2315,
1273, 1274, 1275, 1276, 1277,	2322, 2325, 2342, 2384, 2473,
1278, 1279, 1280, 1281, 1282,	2589, 2594, 2595, 2600, 2605,
1283, 1284, 1285, 1296, 1297,	2606, 2612, 2613, 2614, 2615,
1298, 1299, 1300, 1301, 1302,	2622, 2623, 2624, 2625, 2627,
1303, 1304, 1305, 1306, 1307,	2636, 2637, 2638, 2639, 2649,
1308, 1309, 1310, 1311, 1312,	2666, 2667, 2668, 2669, 2937,
1313, 1314, 1315, 1316, 1317,	2938, 2941, 2944, 2945, 2947,
1318, 1319, 1320, 1321, 1322,	2948, 3145, 3250, 3255, 3258,
1323, 1324, 1325, 1326, 1327,	3273, 3279, 3364, 3374, 3380,
1328, 1329, 1330, 1331, 1332,	3465, 3467, 3469, 3471, 3479,
1333, 1334, 1335, 1336, 1337,	4554, 4573, 4578, 4587, 4588,
1338, 1339, 1340, 1341, 1342,	4589, 4599, 4767, 4768, 4816
1343, 1344, 1345, 1346, 1347,	<code>\expandedtitle</code> 4351
1348, 1349, 1350, 1351, 1352,	<code>\ExplSyntaxOff</code> . 2341, 2663, 3112,
1353, 1354, 1873	4624, 4723
<code>\eqenvironment</code> 1373,	<code>\ExplSyntaxOn</code> . 2339, 2651, 2963,
1374, 1375, 1376, 1377, 1378,	4603, 4630
1379, 1380, 1381, 1382, 1383,	<code>\extract@alph@from@version</code> . .



.....	4587	2486, 2508, 2516, 2524, 2525,
F		2534, 2535, 2541, 2544, 2554,
\false	4861	2575, 2590, 2608, 2628, 2641,
\falsesymbol	4852	2644, 2670, 2682, 2785, 2786,
\fancyfoot	4095, 4099, 4100, 4101	2787, 2788, 2789, 2790, 2791,
\fancyhead	4094, 4096, 4097, 4098	2792, 2793, 2794, 2795, 2796,
\FancyVerbLineautorefname	1625	2797, 2798, 2799, 2800, 2805,
\fbox	3979, 3994, 4209, 4838, 4898	2819, 2820, 2821, 2822, 2823,
\fboxrule	1595, 1597, 1599, 1601,	2824, 2825, 2826, 2827, 2828,
	4051	2829, 2830, 2831, 2832, 2833,
\fboxsep	1595, 1597,	2834, 2849, 2850, 2851, 2852,
	1599, 1601, 3982, 4175, 4207,	2853, 2854, 2855, 2856, 2857,
	4279, 4307, 4355, 4404	2858, 2859, 2860, 2861, 2862,
\fi	2, 3, 5, 7,	2863, 2864, 2877, 2891, 2892,
	16, 25, 78, 87, 141, 169, 174,	2893, 2894, 2895, 2896, 2897,
	259, 303, 305, 306, 307, 315,	2898, 2899, 2900, 2951, 2952,
	326, 328, 337, 1370, 1445,	2960, 3146, 3167, 3173, 3174,
	1489, 1500, 1548, 1549, 1558,	3175, 3177, 3178, 3179, 3182,
	1566, 1581, 1598, 1600, 1602,	3195, 3205, 3223, 3224, 3225,
	1612, 1613, 1614, 1615, 1616,	3226, 3227, 3228, 3229, 3230,
	1617, 1618, 1619, 1620, 1621,	3231, 3232, 3233, 3234, 3235,
	1622, 1623, 1624, 1625, 1626,	3236, 3237, 3238, 3239, 3240,
	1627, 1661, 1671, 1677, 1680,	3241, 3249, 3254, 3276, 3290,
	1681, 1682, 1702, 1711, 1755,	3302, 3307, 3308, 3311, 3313,
	1766, 1767, 1772, 1784, 1815,	3314, 3326, 3330, 3332, 3333,
	1841, 1842, 1853, 1856, 1859,	3335, 3338, 3340, 3346, 3349,
	1862, 1865, 1868, 1964, 1965,	3352, 3356, 3361, 3377, 3391,
	1966, 1967, 1968, 1969, 1970,	3403, 3408, 3409, 3412, 3414,
	1971, 1972, 2013, 2014, 2020,	3415, 3427, 3431, 3433, 3434,
	2035, 2036, 2041, 2042, 2045,	3436, 3439, 3441, 3448, 3454,
	2048, 2051, 2054, 2057, 2060,	3472, 3473, 3474, 3475, 3476,
	2064, 2065, 2073, 2091, 2092,	3477, 3484, 3485, 3488, 3489,
	2098, 2105, 2108, 2113, 2114,	3492, 3493, 3495, 3496, 3557,
	2133, 2134, 2135, 2136, 2140,	3563, 3569, 3581, 3587, 3593,
	2141, 2142, 2156, 2157, 2158,	3597, 3601, 3607, 3619, 3620,
	2159, 2174, 2175, 2190, 2191,	3631, 3632, 3643, 3644, 3656,
	2192, 2193, 2210, 2211, 2225,	3675, 4004, 4005, 4210, 4227,
	2234, 2235, 2236, 2237, 2244,	4391, 4465, 4484, 4511, 4536,
	2245, 2249, 2254, 2257, 2262,	4554, 4572, 4573, 4578, 4598,
	2265, 2279, 2280, 2281, 2282,	4599, 4726, 4744, 4745, 4746,
	2305, 2306, 2316, 2326, 2338,	4747, 4748, 4749, 4750, 4751,
	2356, 2374, 2395, 2397, 2408,	4752, 4753, 4754, 4756, 4759,
	2412, 2421, 2422, 2426, 2438,	4760, 4761, 4763, 4764, 4765,
	2443, 2447, 2451, 2452, 2456,	4952, 4954, 4955, 4956, 4962,
	2461, 2462, 2463, 2464, 2484,	4986, 4987, 5007, 5018, 5039,
		5048, 5055, 5062, 5077



\figureautorefname	1615
\figurename	3223
\finishsetclass	1813, 1817
\firstarticle ..	4106, 4130, 4131, 4133
\FirstFrameCommand	1597
\firstimage	4203, 4216, 4217, 4219
\firstmark	1483, 3212
\firstTextFormat ...	3864, 3866
\firstTitleFormat .	3852, 3858, 3859
\float@box	2313, 2323
\float@endH	2312, 2322
\floatingpenalty ...	20, 37, 56, 82, 99, 118, 1493, 1512, 1531, 1706, 1723, 1742
\flushright ...	3852, 3871, 3890
\fontencoding .	2974, 2991, 3008, 3023
\fontfamily 2975, 2992, 3009, 3024, 3036, 3039, 3042, 3045, 3048, 3051
\fontsize	1695
\fontspec	2340, 2658, 2969, 2986, 3003, 3018, 3063, 3072, 3081, 3090, 3099, 3108, 4682, 4710, 4719
\foot	3847
\footdir@debugfalse	3592
\footdir@debugtrue	3590
\footdir@ORG@xepersian@amsart@footnotetext	64
\footdir@ORG@xepersian@amsart@LTRfootnotetext	66
\footdir@ORG@xepersian@amsart@RTLfootnotetext	65
\footdir@ORG@xepersian@amsbook@footnotetext	125
\footdir@ORG@xepersian@amsbook@LTRfootnotetext	127
\footdir@ORG@xepersian@amsbook@RTLfootnotetext	126
\footdir@ORG@xepersian@footnotetext	1541
\footdir@ORG@xepersian@imsproc@footnotetext	1749
\footdir@ORG@xepersian@imsproc@LTRfootnotetext	1751
\footdir@ORG@xepersian@imsproc@RTLfootnotetext	1750
\footdir@ORG@xepersian@LTRfootnotetext	1543
\footdir@ORG@xepersian@RTLfootnotetext	1542
\footdir@temp	64, 65, 66, 125, 126, 127, 1541, 1542, 1543, 1749, 1750, 1751
\footins	15, 32, 51, 77, 94, 113, 1488, 1507, 1526, 1701, 1718, 1737
\footnote	3944
\footnoteautorefname	1613
\footnoterule	3943
\footnotesep ..	19, 25, 36, 42, 55, 61, 81, 87, 98, 104, 117, 123, 1492, 1500, 1511, 1519, 1530, 1538, 1558, 1576, 1591, 1690, 1692, 1705, 1711, 1722, 1728, 1741, 1747
\footnotesize	17, 34, 53, 79, 96, 115, 1445, 1446, 1447, 1490, 1509, 1528, 1551, 1569, 1584, 1679, 1703, 1720, 1739, 3772, 3773, 3807, 3840, 3905, 3929, 3930, 3942
\footskip	3202
\textfont	1445
\FrameCommand	1595
\FrameRestore	1603
\frenchspacing	2337, 2645
\frenchbatter ..	69, 262, 273, 291, 1433, 2804
\futurelet	2580, 4729
G	
\g ..	2974, 2991, 3008, 3023, 4604, 4710, 4711, 4719, 4720
\g@addto@macro	4768, 4813
\G@refundefinedtrue	3148
\gdef	149, 155, 161, 167, 192, 219, 246, 253,

269, 270, 280, 281, 287, 288, 299, 300, 1431, 1441, 1442, 1453, 1454, 1632, 1633, 1648, 1650, 1959, 1960, 2749, 2750, 2756, 2757, 2763, 2764, 2771, 2772, 2779, 2812, 2813, 2842, 2843, 3785, 4055, 4056, 4057, 4729, 4779, 4781, 4799, 4801, 4803, 4809, 4810, 4826, 4851, 4852, 4866, 4885, 4887, 4892, 4903	
\get@cdp	4613
\getanddefine@fonts	4560, 4584
\Gin@boolkey	2665
\glb@currsize	4677
\global	179, 180, 306, 316, 317, 318, 319, 320, 321, 322, 323, 331, 1460, 1461, 1480, 1548, 1549, 1566, 1567, 1581, 1582, 2070, 2074, 2394, 2483, 3156, 3157, 3166, 3209, 3210, 3964, 3965, 3966, 3967, 3968, 3969, 3970, 3971, 3972, 3973, 4566, 4592
\globaldefs	4561, 4585
\glossary	1470, 3186
\glsaddprotectedpagefmt	1608, 1609, 1610
\goodbreak	4542
\grid	3746, 3750, 4012
\Grot@x	2673, 2674, 2675, 2676
\Grot@y	2677, 2678, 2679, 2680, 2681, 2682
\group	2658
\group@elt	4612
\group@list	4612
\grp@aligned	322
\GRP@box	317
\grp@eqs@numbered	321
\grp@hasNumber	326
\GRP@label	318
\grp@linewidth	320
\GRP@queue	317
\grp@setnumber	326
\grp@shiftnumber	323
\grp@wdL	319
\grp@wdNum	320
\grp@wdR	319
\grp@wdT	319
\gsetlength	194, 196, 221, 223
H	
\hangindent	1680, 1681, 1682
\harfi	1357, 1953, 2785, 2819, 2849, 3255
\harfinumeral	3256
\hb@xt@	3195, 3205
\hbox	247, 254, 1689, 1695, 1769, 2221, 3147, 3221, 3222
\headDateTimeFormat	3811, 3813
\headerfont	4779
\headheight	1476, 3191, 4045
\heading	3834
\headrulewidth	4046, 4102
\headsep	1477, 3200
\headtoname	3240
\height	2677, 2678
\hfil	1769, 2217, 2218, 2219, 2220, 2252, 2253, 2254, 2260, 2261, 2262, 3174, 3175, 3177, 3178
\hline	4495, 4820, 4821, 4824, 4825, 4845, 4846
\hrule	1692, 1807, 4378, 4384, 4431, 4437, 4482, 4522
\hrulefill	1689, 4060, 4065, 4079
\hsize	20, 37, 56, 82, 99, 118, 1494, 1513, 1532, 1552, 1570, 1585, 1603, 1706, 1723, 1742, 2078, 2094, 2119, 2120, 2318, 2328
\hskip	1689, 1768, 1807, 2219, 2220, 2262
\hspace	1681, 1682, 3813, 3831, 4060, 4066, 4078, 4080, 4258
\hss	2106
\Huge	3783, 3852, 3908
\huge	3782
\Hy@AlphNoErr	1648, 1650
\Hy@appendixstring	1634, 1652
\Hy@backout	175, 183
\Hy@chapapp	1634, 1652
\HyOrg@appendix	1629, 1635



\HyOrg@resets@pp . . . 1645, 1653
\hyper@natlinkbreak 2416, 2447
\hyper@natlinkstart 183
\hyphenpenalty 1678, 1760

I

\if 307, 326, 2031, 2037, 2043, 2046,
2049, 2052, 2055, 2058, 2061,
2092, 2099, 2100, 2101, 2102,
2114, 2131, 2132, 2133, 2134,
2135, 2136, 2137, 2138, 2139,
2140, 2154, 2155, 2156, 2157,
2158, 2159, 2161, 2162, 2163,
2164, 2165, 2168, 2169, 2170,
2171, 2172, 2173, 2188, 2189,
2190, 2191, 2192, 2193, 2195,
2196, 2197, 2198, 2199, 2200,
2201, 2204, 2205, 2206, 2207,
2208, 2209, 2232, 2233, 2234,
2235, 2236, 2237, 2239, 2240,
2241, 2242, 2243, 2244, 2277,
2278, 2279, 2280, 2281, 2282,
2283, 2284, 2285, 2286, 2287,
2288, 2289, 2290, 2292, 2293,
2294, 2295, 2296, 2299, 2300,
2301, 2302, 2303, 2304, 2399,
2429, 2447, 2457, 2463, 2464,
2525, 2541, 2573, 2593, 2599,
2601, 2611, 2619, 2621, 2643,
2673, 2674, 2675, 2676, 2677,
2678, 2679, 2680, 2681, 2682
\if@bidi@algorithmicloaded@ .
. 1851
\if@bidi@algorithmloaded@ 1854
\if@bidi@backrefloaded@ . 1857
\if@bidi@csprimitive 1873
\if@bidi@csundef . . . 3459, 3505
\if@bidi@enumerateloaded@ 1860
\if@bidi@tocloftloaded@ . 1863
\if@bidi@urlloaded@ 1866
\if@chapter@pp 134
\if@extrafootnotefeatures 3672
\if@files@w 3146
\if@inlabel 306
\if@Latin 4763, 4764, 4765
\if@LTRbibitems 1661

\if@newlist . . . 1460, 1480, 2338,
3156, 3209
\if@noskipsec 305
\if@pboxsw 2108
\if@RTL 2, 3, 5, 7, 169, 259, 303, 315,
328, 1598, 1600, 1602, 1612,
1613, 1614, 1615, 1616, 1617,
1618, 1619, 1620, 1621, 1622,
1623, 1624, 1625, 1626, 1627,
1661, 1677, 1680, 1681, 1682,
1755, 1766, 1767, 1841, 1842,
1964, 1965, 1966, 1967, 1968,
1969, 1970, 1971, 1972, 2092,
2114, 2891, 2892, 2893, 2894,
2895, 2896, 2897, 2898, 2899,
2900, 3223, 3224, 3225, 3226,
3227, 3228, 3229, 3230, 3231,
3232, 3233, 3234, 3235, 3236,
3237, 3238, 3239, 3240, 3241
\if@RTL@footnote . 16, 25, 78, 87,
1445, 1489, 1500, 1548, 1549,
1558, 1702, 1711
\if@RTLbibitems 1661
\if@RTLmain . . . 3182, 3195, 3205
\if@RTLtab 2091,
2113, 2133, 2134, 2135, 2136,
2156, 2157, 2158, 2159, 2190,
2191, 2192, 2193, 2234, 2235,
2236, 2237, 2279, 2280, 2281,
2282
\if@specialpage 3165
\if@temp@swa 2516
\if@twocolumn 1671
\if@twoside 2805, 3168
\ifadl@usingarypkg 2178
\ifbidi@autofootnoterule 1548,
1566, 1581
\ifBR@verbose 172
\ifcase . . 2216, 2247, 2251, 2255,
2259, 2398, 2428, 2521, 3243,
3252, 3280, 3343, 3349, 3352,
3355, 3359, 3381, 3444, 3451,
3483, 3487, 3491, 3495, 3551,
3559, 3565, 3571, 3583, 3589,
3595, 3599, 3603, 3609, 3622,
3634, 3646, 5070



<code>\ifdim</code>	336, 3992, 4477		2631, 2670, 2783, 2785, 2786,
<code>\ifhmode</code>	2015		2787, 2788, 2789, 2790, 2791,
<code>\ifinner</code>	2021		2792, 2793, 2794, 2795, 2796,
<code>\ifmmode</code>	2103, 4556, 4580		2797, 2798, 2799, 2817, 2819,
<code>\ifNAT@full</code>	2396, 2485		2820, 2821, 2822, 2823, 2824,
<code>\ifNAT@longnames</code>	2392, 2481		2825, 2826, 2827, 2828, 2829,
<code>\ifNAT@numbers</code>	2345, 2552		2830, 2831, 2832, 2833, 2847,
<code>\ifNAT@super</code>	2346		2849, 2850, 2851, 2852, 2853,
<code>\ifNAT@swa</code> 2398, 2463, 2487, 2539			2854, 2855, 2856, 2857, 2858,
<code>\ifnum</code> . 337, 1548, 1566, 1581, 1757,			2859, 2860, 2861, 2862, 2863,
2062, 2129, 2130, 2146, 2147,			2938, 2946, 3174, 3175, 3177,
2148, 2149, 2151, 2180, 2181,			3178, 4554, 4578, 4724, 4732,
2182, 2183, 2185, 2230, 2231,			4733, 4734, 4735, 4736, 4737,
2269, 2270, 2271, 2272, 2274,			4738, 4739, 4740, 4741, 4742,
2873, 2956, 3270, 3272, 3281,			4756, 4759, 4760, 4761, 4763,
3282, 3283, 3284, 3285, 3286,			4764, 4765
3287, 3288, 3305, 3307, 3309,		<code>\ifXePersian@kabiseh</code> 4909, 5014	
3311, 3313, 3318, 3329, 3330,		<code>\ifXePersian@leap</code> . . 4909, 4958	
3332, 3334, 3335, 3338, 3371,		<code>\ifxetex</code> 3985, 4208, 4225	
3373, 3382, 3383, 3384, 3385,		<code>\ignorespaces</code>	
3386, 3387, 3388, 3389, 3406,		. . . 25, 42, 61, 87, 104, 123,	
3408, 3410, 3412, 3414, 3419,		213, 240, 340, 1500, 1519,	
3430, 3431, 3433, 3435, 3436,		1538, 1558, 1576, 1591, 1711,	
3439, 3461, 3463, 3465, 3467,		1728, 1747, 1789, 2320, 2330,	
3469, 3471, 3485, 3489, 3493,		3065, 3074, 3083, 3092, 3101,	
3496, 4389, 4463, 4509, 4534,		3110, 3803, 3856, 3866, 3871,	
4557, 4581, 4948, 4952, 4980,		3879, 3884, 3890, 3898, 4158,	
4986, 5007, 5034, 5038, 5043,		4184, 4333	
5047, 5049, 5058		<code>\image</code> 3980	
<code>\ifodd</code> 2032, 2038, 3169, 4941, 4946		<code>\immediate</code> 3146, 3614, 3615, 3626,	
<code>\ifthenelse</code> 193, 198, 220,		3627, 3638, 3639	
225, 3732, 3744, 3753, 3857,		<code>\includegraphics</code> . . . 3995, 4209,	
3872, 3891, 3912, 4030, 4108,		4226	
4109, 4139, 4171, 4185, 4205,		<code>\index</code> 1469, 3185	
4223, 4247, 4277, 4301, 4328,		<code>\indexEntryFormat</code> . . 3801, 3803	
4357, 4362, 4367, 4372, 4377,		<code>\indexEntryPageFormat</code> . . . 3807,	
4410, 4415, 4420, 4425, 4430,		3809	
4827		<code>\indexEntryPageTxt</code> . 3806, 3809	
<code>\ifwritexviii</code> . . 2955, 3611, 3623,		<code>\indexEntrySeparator</code> 3805, 4333	
3635		<code>\indexFormat</code> 3797, 3799	
<code>\ifx</code> 1357, 1358,		<code>\indexitem</code> 4326, 4336, 4337, 4339	
1359, 1360, 1361, 1362, 1363,		<code>\indexname</code> 3229	
1364, 1365, 1366, 1367, 1782,		<code>\init@restore@version</code> 4563, 4611	
1813, 2008, 2011, 2095, 2315,		<code>\innerAuthorFormat</code> . 3929, 4446	
2325, 2402, 2403, 2405, 2432,		<code>\innerPlaceFormat</code> . . 3930, 4446	
2433, 2435, 2504, 2522, 2582,		<code>\innerSubtitleFormat</code> 3919, 3920	



<code>\mathsurround</code>	333	<code>\NAT@citesuper</code>	2346
<code>\mathtt</code>	4635, 4721	<code>\NAT@citeundefined</code> ..	2387, 2477
<code>\mbox</code>	2352	<code>\NAT@citex</code>	2366
<code>\meaning</code>	2941, 2944	<code>\NAT@citexnum</code>	2357
<code>\MessageBreak</code>		<code>\NAT@close</code>	2361, 2372
..	2407, 2408, 2437, 2438,	<code>\NAT@cmprs</code>	2492, 2538
3506, 4130, 4162, 4196, 4216,		<code>\NAT@cmt</code>	2463, 2541
4237, 4240, 4262, 4287, 4313,		<code>\NAT@ctype</code> ..	2398, 2428, 2488, 2490,
4336, 4339, 4831		2521, 2529, 2531, 2540, 2549	
<code>\MidFrameCommand</code>	1599	<code>\NAT@date</code> ..	2372, 2389, 2399, 2400,
<code>\minilogo</code>	4069, 4283	2411, 2419, 2424, 2429, 2442,	
<code>\minraggedcols</code>		2449, 2454, 2457, 2464	
..	3708, 3709, 3747, 3751,	<code>\NAT@def@citea</code> ..	2426, 2458, 2519
4389, 4463, 4509, 4534		<code>\NAT@def@citea@box</code>	2527
<code>\mlfttitle</code>	1968	<code>\NAT@def@citea@close</code>	2460
<code>\mltttitle</code>	1969	<code>\NAT@exlab</code> ..	2405, 2409, 2435, 2439
<code>\month</code>	4935	<code>\NAT@fullfalse</code>	2550
<code>\moveright</code>	1474, 3190	<code>\NAT@fulltrue</code>	2550
<code>\mtctitle</code>	1967	<code>\NAT@hyper@</code>	2400, 2409,
<code>\multido</code>	4031, 4037	2411, 2414, 2423, 2424, 2425,	
<code>\multiplefootnotemarker</code> ..	214,	2430, 2439, 2442, 2445, 2453,	
215, 241, 242		2454, 2455, 2490, 2526	
<code>\multiply</code> ..	2068, 4938, 4951, 4978,	<code>\NAT@hyper@citea@space</code> ..	2529,
4984, 5001, 5005		2531, 2533	
<code>\mylogo</code>	4074	<code>\NAT@idtxt</code>	2361, 2372
N			
<code>\n</code> ..	4729, 4732, 4733, 4734, 4735,	<code>\NAT@ifcat@num</code>	2493, 2496
4736, 4737, 4738, 4739, 4740,		<code>\NAT@last@nm</code> ..	2390, 2402, 2432,
4741, 4742		2479, 2522	
<code>\NAT@@close</code>	2464, 2543	<code>\NAT@last@num</code> ..	2479, 2496, 2497,
<code>\NAT@@Latin@@citetp</code> ..	2551, 2555,	2515	
2556, 2557		<code>\NAT@last@yr</code> ..	2390, 2403, 2433,
<code>\NAT@@open</code>	2447, 2523	2470, 2504, 2538	
<code>\NAT@alias</code> ..	2425, 2455, 2490, 2533	<code>\NAT@last@yr@mbox</code> ..	2500, 2510
<code>\NAT@all@names</code> ..	2393, 2396, 2482,	<code>\NAT@Latin@cites</code> ..	2550, 2551
2485		<code>\NAT@Latin@citex</code> ..	2367, 2375,
<code>\NAT@aysep</code>	2417	2376	
<code>\NAT@biblabel</code>	2368	<code>\NAT@Latin@citexnum</code> ..	2358, 2465,
<code>\NAT@biblabelnum</code>	2359	2466	
<code>\NAT@bibsetnum</code>	2360	<code>\NAT@mbox</code> ..	2347, 2352, 2523, 2526,
<code>\NAT@bibsetup</code>	2369	2543	
<code>\NAT@cite</code>	2365	<code>\NAT@merge</code>	2500, 2515
<code>\NAT@cite@list</code>	2382, 2471	<code>\NAT@name</code> ..	2361, 2372, 2393, 2397,
<code>\NAT@citea@mbox</code>	2516	2482, 2486	
<code>\NAT@citenum</code>	2353	<code>\NAT@nm</code> ..	2381, 2390, 2396, 2397,
		2400, 2402, 2415, 2423, 2430,	
		2432, 2446, 2453, 2470, 2479,	



2485, 2486, 2494, 2495, 2499,
 2503, 2522
 \NAT@nmfmt 2400, 2415, 2423, 2430,
 2446, 2453
 \NAT@num . 2361, 2470, 2479, 2493,
 2494, 2515, 2526
 \NAT@open 2361, 2372
 \NAT@parse 2391, 2480
 \NAT@partrue 2549
 \NAT@penalty . . 2363, 2371, 2507,
 2522
 \NAT@reset@citea . . . 2380, 2469
 \NAT@reset@parser . . 2378, 2467
 \NAT@set@cites 2344, 2547
 \NAT@sort@cites 2379, 2468
 \NAT@space 2349, 2354, 2370, 2522
 \NAT@spacechar 2354, 2361, 2370,
 2372, 2410, 2417, 2441, 2447,
 2523, 2525
 \NAT@super@kern 2350, 2355, 2523
 \NAT@swafalse 2553
 \NAT@swatruet 2549
 \NAT@temp 2404, 2405, 2434, 2435
 \NAT@test 2490, 2523, 2529, 2531
 \NAT@year 2381, 2390, 2403, 2433
 \NAT@yrsep . . . 2402, 2432, 2522
 \natexlab 2362, 2373
 \navardefault . . 3031, 3045, 3081
 \navarfamily . . 3043, 3044, 3055
 \NeedsTeXFormat 2901, 3679, 4548,
 4769, 4906
 \new@mathalphabet 4614
 \new@mathbf 4636, 4701
 \new@mathgroup . 4551, 4552, 4607
 \new@mathit 4644, 4702
 \new@mathrm 4652, 4703
 \new@mathsf 4660, 4712
 \new@mathtt 4668, 4721
 \new@mathversion 4612
 \new@symbolfont 4613
 \newboolean . . 3690, 3692, 3694,
 3696, 3698, 3700, 3702
 \newcolumnntype 4783, 4784
 \newcommand
 1837, 1838, 1871, 1873, 1874,
 1876, 1880, 2375, 2465, 2551,
 2556, 2879, 3028, 3029, 3030,
 3031, 3032, 3033, 3214, 3257,
 3260, 3363, 3366, 3687, 3742,
 3786, 3787, 3790, 3791, 3792,
 3797, 3798, 3801, 3802, 3805,
 3806, 3807, 3808, 3811, 3812,
 3816, 3817, 3820, 3821, 3822,
 3823, 3826, 3829, 3834, 3839,
 3842, 3844, 3847, 3852, 3853,
 3864, 3865, 3868, 3869, 3877,
 3878, 3881, 3882, 3887, 3888,
 3896, 3897, 3899, 3900, 3901,
 3902, 3905, 3906, 3908, 3909,
 3919, 3920, 3921, 3922, 3923,
 3924, 3929, 3930, 3931, 3932,
 3933, 3934, 3935, 3936, 3937,
 3938, 3939, 3940, 3975, 3980,
 4012, 4044, 4058, 4069, 4074,
 4082, 4106, 4137, 4169, 4203,
 4222, 4326, 4344, 4351, 4393,
 4401, 4444, 4450, 4470, 4487,
 4516, 4541, 4625, 4626, 4628,
 4724, 4725, 4779, 4781, 4787,
 4790, 4792, 4795, 4799, 4801,
 4803, 4851, 4852, 4857, 4861,
 4866, 4885, 4887, 5063
 \newcount 3704, 3705, 3708,
 4010, 4011, 4910, 4911, 4912,
 4913, 4914, 4915, 4916, 4917,
 4918, 4919, 4920, 4921, 4922,
 4923, 4925, 4926, 4927, 4928,
 4929, 4930, 4931, 4932
 \newcounter 4804, 4805
 \newdimen 4008, 4009
 \NewDocumentCommand 4636, 4644,
 4652, 4660, 4668
 \newenvironment 1657, 1874,
 2561, 2562, 3127, 3128, 3977,
 4083, 4245, 4275, 4299, 4453,
 4502, 4528, 4833, 4867
 \newfam 4552
 \newfontface 2869
 \newfontlanguage 2962
 \newfontscript 2961
 \newif 2955, 4909
 \newlength 3682, 3683, 3684, 3685,



3686, 3688, 4797, 4888, 4890
`\newmathalphabet` 4608
`\newmathalphabet@@` 4608
`\newmathalphabet@@@` 4608
`\newpage` . 3613, 3625, 3637, 4093
`\newsavebox` 3976
`\newsection` 4450
`\next` 1813,
 1815, 1816, 2574, 2575, 2576,
 2580, 2582, 2585, 2589, 2590,
 2592, 2598, 2603, 2607, 2609,
 2618, 2620, 2626, 2629, 2633,
 2640, 2642
`\nobreak` . . 1768, 1770, 1806, 2347
`\noexpand` 1458, 2573, 2593, 2599,
 2601, 2611, 2619, 2621, 2633,
 2634, 2643, 3154, 4564
`\nohyphens` 3858, 3873, 3892, 3913
`\noindent` 247,
 254, 3803, 3818, 3856, 3866,
 3871, 3879, 3884, 3890, 3898,
 3903, 3907, 3911, 4060, 4077,
 4158, 4184, 4209, 4256, 4333,
 4347, 4381, 4396, 4434, 4491,
 4519, 4544, 4546
`\non@alpherr` 4573, 4599
`\nopagebreak` 4899
`\normalcolor` . . 2076, 2317, 2327,
 3194, 3204
`\normalfont` 17, 34, 53,
 79, 96, 115, 1659, 1695, 1703,
 1720, 1739, 1755, 2979, 3064,
 3073, 3082, 3091, 3100, 3109,
 3114, 3115, 3118, 3119
`\normalparindent` . 21, 38, 57, 83,
 100, 119, 1707, 1724, 1743
`\normalsfcodes` 1467, 3183
`\normalsize` 1467, 3135, 3181, 3754,
 3755, 3801, 4396, 4434
`\NOT` 193, 220
`\not` 4811
`\not@math@alphabet` 3035, 3038,
 3041, 3044, 3047, 3050
`\null` 3945, 3961
`\number` . . 1762, 3270, 3272, 3273,
 3371, 3373, 3374, 3465, 3467,

3469, 3471, 4565, 4589, 5064,
 5065
`\numexpr` . 4639, 4647, 4655, 4663,
 4671

O

`\obeyspaces` 4729
`\oddsidemargin` 3170
`\old@endquestion` . . . 4894, 4902
`\old@question` 4893, 4900
`\or` . 2218, 2219, 2220, 2222, 2223,
 2247, 2248, 2249, 2253, 2254,
 2255, 2256, 2257, 2261, 2262,
 2423, 2424, 2425, 2453, 2454,
 2455, 2528, 2530, 2532, 3243,
 3244, 3245, 3246, 3247, 3248,
 3252, 3253, 3254, 3291, 3292,
 3293, 3294, 3295, 3296, 3297,
 3298, 3299, 3300, 3304, 3343,
 3344, 3345, 3346, 3349, 3352,
 3355, 3356, 3359, 3360, 3361,
 3392, 3393, 3394, 3395, 3396,
 3397, 3398, 3399, 3400, 3401,
 3405, 3444, 3445, 3446, 3447,
 3448, 3451, 3452, 3453, 3454,
 3483, 3484, 3487, 3488, 3491,
 3492, 3495, 3553, 3555, 3561,
 3567, 3573, 3575, 3577, 3579,
 3585, 3591, 3605, 3651, 5070,
 5071, 5072, 5073, 5074, 5075,
 5076

`\orig` 4631, 4632, 4633, 4634, 4635,
 4637, 4645, 4653, 4661, 4669
`\originaltoday` 3129, 3130
`\Ovalbox` 4373, 4426
`\ovalbox` 4368, 4421
`\overline` 4742

P

`\p@` . . 1672, 1676, 1688, 1690, 1691,
 1692, 2350, 3946
`\p@enumiv` 1660
`\PackageError` . . 1852, 1855, 1858,
 1861, 1864, 1867, 3220, 3265,
 3506, 3612, 3618, 3624, 3630,
 3636, 3642



`\PackageInfo` 173, 185, 4625
`\PackageWarning` 2388, 2477, 3457, 3610
`\PackageWarningNoLine` . . . 2405, 2435
`\page@free` 3990, 3992
`\pageautorefname` 1627
`\pagegoal` 4472
`\pagename` 3239
`\pagenumbering` 69, 265, 276, 294, 1436, 1952, 2806
`\pageref` 3831, 4329
`\pagesFormat` 3905, 3907
`\pagestyle` 4048
`\pagetotal` 4473
`\par` . 10, 25, 42, 61, 71, 87, 104, 123, 130, 146, 152, 158, 164, 266, 277, 284, 296, 954, 1428, 1438, 1450, 1680, 1681, 1682, 1684, 1711, 1728, 1747, 1759, 1769, 1777, 1956, 2746, 2753, 2760, 2768, 2776, 2809, 2839, 3948, 3950, 3956, 3958, 3959, 4448, 4533, 4839, 4899
`\paragraphautorefname` . . . 1623
`\parallel` 3813
`\parbox` 4838, 4898
`\parfillskip` 1767
`\parindent` 21, 38, 57, 83, 100, 119, 1676, 1707, 1724, 1743, 1766
`\parskip` 1676
`\part` 1753
`\partautorefname` 1617
`\partname` 3232
`\PassOptionsToClass` 3710, 3711, 3712
`\pbs` 4782, 4783
`\pdfstringdefDisableCommands` 1638
`\penalty` . . . 333, 339, 2363, 3144
`\persian` 3125
`\PersianAlphs` . . 3125, 3128, 3647, 3652, 3678
`\persianday` 5069
`\persianfont` 42, 104, 229, 236, 254, 1447, 1519, 1576, 1728, 2969, 2972, 2975, 3118, 3120, 3122
`\PersianMathsDigits` 3556, 4758
`\persianmathsdigits` 4688, 4759, 4763
`\persianmathsfdigits` 4712, 4760, 4764
`\persianmathttdigits` 4721, 4761, 4765
`\persianmonth` 5068
`\persiansfdefault` . 3028, 3036, 3063
`\persiansffamily` . . 3034, 3035, 3052
`\persiantoday` 3131, 5063
`\persianttddefault` . 3029, 3039, 3072
`\persiantttfamily` . . 3037, 3038, 3053
`\persianyear` 5067
`\pictureCaptionFormat` . . . 3901, 3903
`\plftitle` 1965
`\plq` 2935
`\plttitle` 1966
`\pookdefault` . . 3032, 3048, 3090
`\pookfamily` . . 3046, 3047, 3056
`\postmath` 339
`\PrefixCurrentTab` 2879
`\premath` 335
`\prepnext@tok` 2215, 2225
`\printindex` . . . 3613, 3625, 3637
`\process@table` 4611
`\ProcessOptions` . . . 3724, 4905
`\ProcessOptionsX` 3670
`\proofname` 3241
`\protect` 1458, 3154, 4130, 4131, 4133, 4162, 4163, 4165, 4196, 4197, 4199, 4216, 4217, 4219, 4237, 4238, 4240, 4336, 4337, 4339, 4788, 4791, 4793, 4796, 4814, 4819, 4820, 4821, 4823, 4824, 4825, 4845, 4846
`\protected@edef` 22, 39, 58, 84, 101, 120, 1495, 1514, 1533, 1554, 1572, 1587, 1708,



1725, 1744
\protected@xdef 201, 228
\providecommand 3456
\ProvidesClass 3680
\ProvidesFile 1, 4, 8, 68, 129, 144,
150, 156, 162, 168, 188, 258,
260, 271, 282, 290, 302, 342,
1295, 1355, 1372, 1415, 1426,
1432, 1444, 1448, 1455, 1484,
1593, 1607, 1611, 1656, 1798,
1840, 1843, 1870, 1950, 1963,
1973, 2343, 2744, 2751, 2758,
2766, 2774, 2803, 2837, 2867,
2870, 2890
\ProvidesPackage . . . 2904, 4549,
4770, 4907
\prq 2934
\ptctitle 1964

Q

\question 4893
\questionsepspace . . 4890, 4891,
4903
\questionspace . 4797, 4798, 4839
\questiontitle 4885, 4904
\questiontitlefont 4887
\questiontitlespace 4888, 4889,
4899

R

\raggedFormat . 3742, 4390, 4464,
4510, 4535
\RaggedLeft 3742
\raggedleft 1677, 1755
\raggedright 1677, 1755
\raise 1695
\raisebox 3788, 3793
\refname 259, 3230
\refstepcounter 4855, 4856
\relax . . 206, 215, 233, 242, 1659,
1676, 1689, 1756, 1762, 1764,
1766, 1768, 1871, 2063, 2095,
2230, 2231, 2252, 2253, 2254,
2315, 2325, 2349, 2355, 2399,
2429, 2457, 2464, 2470, 2497,
2504, 2515, 2670, 2783, 2817,

2847, 2868, 2873, 2938, 2956,
3551, 3559, 3565, 3571, 3583,
3589, 3595, 3599, 3603, 3609,
3622, 3634, 3646, 3724, 3943,
3964, 3965, 3970, 3971, 3972,
3973, 4554, 4568, 4578, 4594,
4627, 4629, 4639, 4647, 4655,
4663, 4671, 4677, 4755, 4937,
4938, 4940, 4945, 4950, 4951,
4957, 4959, 4961, 4963, 4964,
4965, 4966, 4967, 4968, 4969,
4970, 4971, 4972, 4973, 4975,
4977, 4978, 4983, 4984, 4991,
4993, 4996, 5000, 5001, 5004,
5005, 5008, 5013, 5015, 5017,
5019, 5020, 5021, 5022, 5023,
5024, 5025, 5026, 5027, 5028,
5029, 5030, 5032, 5033, 5036,
5041, 5045, 5051, 5053, 5054
\renewcommand 9, 70,
130, 136, 137, 140, 145, 146,
151, 152, 157, 158, 163, 164,
244, 251, 261, 262, 266, 272,
273, 277, 283, 284, 291, 295,
296, 1427, 1428, 1433, 1437,
1438, 1445, 1446, 1447, 1449,
1450, 1660, 1683, 1773, 1774,
1775, 1776, 1951, 1953, 1954,
1955, 1956, 2344, 2361, 2372,
2745, 2746, 2752, 2753, 2759,
2760, 2767, 2768, 2775, 2776,
2782, 2804, 2808, 2809, 2816,
2838, 2839, 2846, 2871, 2891,
2892, 2893, 2894, 2895, 2896,
2897, 2898, 2899, 2900, 3613,
3625, 3637, 3754, 3761, 3763,
3765, 3772, 3779, 3780, 3781,
3782, 3783, 3835, 3836, 3837,
3848, 3849, 3850, 3941, 4046,
4082, 4102, 4441, 4451, 4456,
4786
\renewenvironment . . 1594, 4895
\repeat 5038, 5047
\RequirePackage
. . . 2906, 2907, 2908, 2909,
3681, 3726, 3727, 3728, 3729,



3730, 3731, 3733, 3735, 3737,
 3738, 3739, 3740, 3741, 4772,
 4773, 4774, 4775, 4776, 4777
 \reserved@a 2027, 2031, 2037, 2043,
 2046, 2049, 2052, 2055, 2058,
 2061
 \reserved@b 2007, 2008
 \reset@font 1467, 1490,
 1509, 1528, 1551, 1569, 1584,
 2387, 2476, 3115, 3119, 3133,
 3147, 3180
 \resetlatinfont 3113, 3123, 3127,
 3182
 \restore@mathversion 4611
 \restoreapp 142
 \right@footnoterule 1548, 1566,
 1687
 \rightfootnoterule 3576
 \rightline 4445
 \rightskip 1766, 1767
 \rl 1640, 3122, 3131
 \RLE 3122
 \rmdefault 2978
 \Roman ... 1363, 2790, 2824, 2854
 \roman ... 1362, 2791, 2825, 2855
 \romannumeral . 2799, 2833, 2863,
 5037, 5046, 5056
 \RTL 3125
 \RTLbidiuftesidenotemarginpar
 254
 \RTLfoottextfont 1447
 \RTLmarginnote 251
 \rule 25, 42, 61, 87, 104, 123, 1500,
 1519, 1538, 1558, 1576, 1591,
 1711, 1728, 1747, 3805, 3931,
 4033, 4039, 4126, 4158

S

\sayehdefault . 3033, 3051, 3099
 \sayehfamily .. 3049, 3050, 3057
 \scriptsize 3763
 \secondarticle . 4137, 4162, 4163,
 4165
 \secondSubtitleFormat ... 3877,
 3879
 \secondTextFormat .. 3881, 3884

\secondTitleFormat . 3868, 3873,
 3874
 \section 3216
 \sectionautorefname 1620
 \sectionname 11, 1685
 \select@group 4553
 \selectfont
 .. 2975, 2992, 3009, 3024,
 3036, 3039, 3042, 3045, 3048,
 3051
 \set@mathdelimiter 4618
 \set@mathaccent 4615
 \set@mathchar 4615
 \set@mathdelimiter 4617
 \set@mathsymbol 4616
 \set@typeset@protect 1462, 1466,
 3160, 3162
 \setboolean 2880, 2881, 3691, 3693,
 3695, 3697, 3699, 3701, 3703,
 3719, 3720, 3722, 3723, 4085,
 4103, 4248, 4273, 4302, 4324
 \setbox 317, 1549, 1567, 1582, 2074,
 2117, 2221, 2223, 2224, 2314,
 2317, 2324, 2327, 3191
 \setclass . 1809, 1819, 1820, 1821,
 1822, 1823, 1824, 1825, 1826
 \setcounter .. 133, 135, 139, 147,
 148, 153, 154, 159, 160, 165,
 166, 267, 268, 278, 279, 285,
 286, 297, 298, 1429, 1430,
 1439, 1440, 1451, 1452, 1482,
 1957, 1958, 2747, 2748, 2754,
 2755, 2761, 2762, 2769, 2770,
 2777, 2778, 2810, 2811, 2840,
 2841, 2874, 2878, 2882, 2883,
 2884, 2885, 2886, 2887, 2888,
 3963, 4808
 \setdigitfont 4676
 \setiranicfont 3103
 \setkeys 308, 325
 \setlatinmonofont 2997
 \setlatinsansfont 2996
 \setlatinfont .. 2981, 3677
 \setlength 2093, 2096,
 2115, 3689, 3721, 3756, 3757,
 3758, 3759, 3767, 3768, 3769,



3770, 3774, 3775, 3776, 3777,
 3982, 3986, 4027, 4028, 4045,
 4050, 4051, 4175, 4207, 4279,
 4304, 4307, 4355, 4356, 4404,
 4405, 4471, 4472, 4488, 4798,
 4889, 4891
 \setLTRcitationfont 189
 \SetMathAlphabet 4614
 \SetMathAlphabet@ 4614
 \SetMathCharDef 4628, 4699, 4700
 \SetMathCode
 . . . 4626, 4689, 4690, 4691,
 4692, 4693, 4694, 4695, 4696,
 4697, 4698
 \SetMathsDigits 4757, 4758, 4762,
 4767, 4768
 \setmathsfdigitfont 4705
 \setmathttdigitfont 4714
 \setmonofont 2997
 \setnavarfont 3076
 \setpersianfont 3117, 3125, 3128,
 3182
 \setpersianmonofont 3067
 \setpersiansansfont 3058
 \setpookfont 3085
 \setsansfont 2996
 \setsayehfont 3094
 \SetSymbolFont 4613
 \SetSymbolFont@ 4613
 \setttextfont 2964, 3507
 \setthsection 1953
 \settowidth 1662
 \sf@size 1695
 \sfcode 1666
 \sffamily 3786
 \shadowbox 4358, 4411
 \shadowsize . . . 4356, 4405, 4409
 \shipout 1462, 3159
 \shortarticleitem 4541
 \shortarticleItemTitleFormat .
 3939, 3940
 \shortarticleSubtitleFormat .
 3937, 3938
 \shortarticleTitleFormat 3935,
 3936
 \shortauthors . . . 1782, 1783, 1788
 \shorttitle 1781, 1782, 1788
 \sixt@n 2026, 2063
 \slftitle 1971
 \sloppy 21, 38, 57, 83, 100, 119,
 1665, 1707, 1724, 1743
 \sltttitle 1972
 \small 3217, 3765, 3766, 3820, 3824,
 3830, 3901, 3923, 3942
 \smash 3221
 \SOUL@tt 2868, 2869
 \space 2389, 2478, 2904, 3150, 3463,
 3989, 3990, 4130, 4131, 4133,
 4162, 4163, 4165, 4196, 4197,
 4199, 4216, 4217, 4219, 4237,
 4238, 4240, 4336, 4337, 4339,
 4446, 4829, 5064, 5065
 \SplitFootnoteRule 3578
 \splitmaxdepth 19, 36, 55,
 81, 98, 117, 1493, 1512, 1531,
 1705, 1722, 1741
 \splittopskip 19, 36, 55,
 81, 98, 117, 1492, 1511, 1530,
 1705, 1722, 1741
 \stctitle 1970
 \stepcounter . . . 132, 200, 227, 1481,
 2876, 3211, 4804, 4817, 4848
 \string 173, 2152, 2186, 2275, 2644,
 3146
 \strut 25, 42, 61, 87, 104, 123, 1711,
 1728, 1747
 \strutbox 19, 36, 55,
 81, 98, 117, 1493, 1500, 1512,
 1519, 1531, 1538, 1558, 1576,
 1591, 1705, 1722, 1741
 \subitem 1681
 \subparagraphautorefname 1624
 \subsectionautorefname . . . 1621
 \subsubitem 1682
 \subsubsectionautorefname 1622
 \symnew@mathbf@font@digits . .
 4639
 \symnew@mathit@font@digits . .
 4647
 \symnew@mathrm@font@digits . .
 4655
 \symnew@mathsf@font@digits . .



..... 4663
\symnew@mathtt@font@digits 4671

T

\tableautorefname 1616
\tablename 3224
\tabularxcolumn 4786
\tartibi . 1359, 2787, 2821, 2851,
3363
\tartibinumeral 3369
\test 1812, 1813, 1814
\textbf 2, 3, 1596, 1598, 1600, 1602,
4347, 4381, 4396, 4434
\textblockorigin 4007
\textdegree 3821
\textheight ... 3210, 4014, 4039
\textiranic 3054
\textit 3932
\textnavar 3055
\textpersiansf 3052
\textpersiantt 3053
\textpook 3056
\textsayeh 3057
\textsc 3934
\textsuperscript 2347
\texttt 3791
\textwidth 2120, 3195, 3205, 4013,
4033, 4345, 4835
\textwidthfootnoterule ... 3580
\thanks 3944, 3964
\the 304, 309,
1791, 1792, 1807, 2097, 2595,
2600, 2606, 2613, 2623, 2637,
2932, 3989, 3990, 4475, 4767,
4768, 5037, 5046, 5056
\the@choice 4807, 4829
\thebook 1954
\thechapter 74,
137, 270, 281, 288, 300, 1442,
1454, 1953, 1960, 2750, 2757,
2764, 2772, 2813, 2843
\theclasse 1809, 1814
\theenumiv 1660, 1662
\theHchapter 1633, 1650
\theHsection 1632, 1648
\theindex 1671

\thempfn 201, 207, 228, 234, 2122
\thempfootnote 2122
\theoremautorefname 1626
\thepage . 2389, 2406, 2436, 2478,
3150, 3831
\theparagraph 1775, 1776
\thepart 9, 70, 145, 151, 157, 163, 261,
272, 283, 295, 1427, 1437,
1449, 1683, 1955, 2745, 2752,
2759, 2767, 2775, 2808, 2838
\thequestion .. 4828, 4868, 4904
\thesection 12, 140, 149, 155, 161,
167, 1431, 1686, 1773, 2779
\thesubparagraph 1776
\thesubsection 1773, 1774
\thesubsubsection .. 1774, 1775
\thirdarticle .. 4169, 4196, 4197,
4199
\thirdSubtitleFormat 3896, 3898
\thirdTextFormat ... 3899, 3900
\thirdTitleFormat .. 3887, 3892,
3893
\thispagestyle . 1674, 1780, 4086,
4091
\thr@@ 2149, 2168, 2169, 2183, 2204,
2205, 2231, 2243, 2244, 2272,
2299, 2300
\timestamp 3924, 4121, 4151, 4187
\timestampFormat ... 3923, 3925
\timestampSeparator 3922, 3927
\timestampTxt 3921, 3926
\tiny 3761
\title 3970
\TitleBarFrame . 1596, 1598, 1600,
1602
\tl 4605, 4622
\tmp 4782
\today 3129, 3131, 4442
\toks 1789, 1791
\toks@ 1788, 1792
\topmargin 1474, 3189
\TPHorizModule
... 3802, 4027, 4126, 4158,
4209, 4256, 4257, 4280, 4281,
4304
\TPVertModule 4028



<code>\true</code>	4857	<code>\verbatim@startline</code>	2572, 2584, 2597, 2617
<code>\truesymbol</code>	4851	<code>\version@elt</code>	4610
<code>\tw@</code>	2044, 2047, 2129, 2135, 2136, 2138, 2148, 2158, 2159, 2182, 2192, 2193, 2230, 2236, 2237, 2242, 2271, 2281, 2282, 2490	<code>\version@list</code>	4610
<code>\twocolumnstableofcontents</code>	3214	<code>\vfil</code>	3192, 3945, 3961
<code>\typeout</code>	2931, 2933, 3975	<code>\voidb@x</code>	317
U		<code>\vrb@catcodes</code>	2566
<code>\Umathchardef</code>	4629	<code>\vskip</code>	1474, 1476, 1477, 3189, 3200, 3946, 3949, 3951, 3957
<code>\Umathcode</code>	4627	<code>\vspace</code>	247, 254, 3981, 4000, 4062, 4072, 4115, 4119, 4142, 4145, 4149, 4156, 4174, 4178, 4182, 4191, 4250, 4254, 4310, 4331, 4379, 4383, 4402, 4432, 4436, 4481, 4483, 4493, 4496, 4521, 4523, 4543, 4545, 4839, 4897, 4899
<code>\undefined</code>	1984, 4724, 4756, 4759, 4760, 4761, 4763, 4764, 4765	<code>\vss</code>	2106
<code>\unhbox</code>	2106	<code>\vtop</code>	2101, 2102, 2223
<code>\unpenalty</code>	339	W	
<code>\unrestored@protected@xdef</code>	207, 234	<code>\weatherFormat</code>	3816, 3818
<code>\unskip</code>	25, 42, 61, 87, 104, 123, 213, 240, 336, 1711, 1728, 1747, 2260, 2261, 2262, 2347, 2410, 2441	<code>\weatheritem</code> ..	4222, 4237, 4238, 4240
<code>\unvbox</code> ...	1550, 1568, 1583, 2106	<code>\weatherTempFormat</code> ..	3820, 4230
<code>\uppercasenonmath</code>	1781	<code>\weatherUnits</code>	3821, 4232
<code>\use</code>	2970, 2975, 2987, 2992, 3004, 3009, 3019, 3024	<code>\whiledo</code>	4811
<code>\use@mathgroup</code>	4564	<code>\widowpenalty</code>	1665
<code>\usebox</code>	3979	<code>\width</code>	1604, 2675, 2676
<code>\usecounter</code>	1664, 4841	<code>\write</code> ...	3146, 3615, 3627, 3639
V		<code>\writexviiiifalse</code>	2959
<code>\value</code>	2873, 4811, 4827	<code>\writexviii>true</code>	2957
<code>\vbox</code>	1462, 1475, 1549, 1567, 1582, 2077, 2094, 2099, 2100, 2117, 2224, 2314, 2318, 2324, 2328, 3159, 3190, 3191, 4518, 4544	X	
<code>\vcenter</code>	2103, 2104	<code>\X</code>	4781
<code>\verbatim@addtoline</code> 2579, 2594, 2605, 2612, 2614, 2622, 2624, 2636, 2638	<code>\x</code>	2941, 2946
<code>\verbatim@finish</code>	2632	<code>\xdef</code>	1634, 1652, 4564, 4807, 4812, 4836, 4837, 4858, 4859, 4862, 4863
<code>\verbatim@processline</code> ...	2583, 2596, 2616	<code>\XePersian</code>	1641, 3221, 3840
		<code>\xepersian</code>	2653, 2655
		<code>\xepersian@@adadi</code> ..	3279, 3304
		<code>\xepersian@@adadi@tartibi</code>	3380, 3405
		<code>\xepersian@A</code> ...	1804, 1819, 1833, 1835



\expersian@adadi ... 3273, 3278
\expersian@adadi@tartibi 3374,
3379
\expersian@cmds@temp 2936, 2954
\expersian@coltitsize
... 3683, 4406, 4407, 4408,
4409, 4412, 4417, 4422, 4427
\expersian@cx ... 4010, 4015, 4032
\expersian@cy ... 4011, 4016, 4038
\XePersian@d ... 4910, 4935, 5040,
5059, 5061, 5064, 5069
\expersian@D 1801,
1821, 1822, 1823, 1824, 1828,
1829, 1830, 1832, 1833
\expersian@dahgan ... 3337, 3358,
3438
\expersian@digits@family 4682,
4684, 4685, 4686, 4687
\XePersian@dn
... 4930, 5029, 5037, 5040,
5043, 5047, 5059, 5061
\expersian@dx . 4008, 4013, 4024,
4027
\expersian@dy . 4009, 4014, 4025,
4028
\expersian@edition . 3790, 3794,
3830, 3950, 4082
\expersian@editionLogo ... 3792,
4060, 4078
\expersian@editorialTit . 4487,
4506
\expersian@editorialTitle 3933,
4492
\expersian@everyjob 2932, 2933
\expersian@firstText 3865, 4121
\expersian@firstTitle 3853, 4116
\expersian@fmbox ... 3976, 3978,
3979
\expersian@footcenter ... 3842,
3849, 4101
\expersian@footleft 3844, 3848,
4100
\expersian@footright 3839, 3850,
4099
\expersian@gridcolumns ... 3705,
3707, 3746, 3750
\expersian@gridrows 3704, 3706,
3746, 3750
\expersian@headcenter ... 3826,
3836, 4098
\expersian@headDateTime . 3812,
4066, 4080
\expersian@headleft 3823, 3835,
4097
\expersian@headright 3829, 3837,
4096
\XePersian@i
... 4910, 5033, 5034, 5036,
5037, 5038, 5041, 5045, 5046,
5049, 5050, 5053, 5056, 5058
\expersian@imgsize 3682, 3983,
3984, 3986, 3995, 3996
\expersian@incolumntitle 4393,
4412, 4417, 4422, 4427
\expersian@indexEntry ... 3802,
4329
\expersian@indexEntryPage 3808,
4329
\expersian@indexFrameTitle ..
..... 3798, 4305
\expersian@indexwidth ... 3686,
3805, 4304, 4308, 4309
\expersian@inexpandedtitle ..
... 4344, 4359, 4364, 4369,
4374
\expersian@innerSubtitle 3920,
4460
\expersian@innerTitle ... 3909,
4459
\XePersian@kabisehfalse . 4980,
4986
\XePersian@kabisehtrue .. 4986
\expersian@kashida . 1806, 1828,
1829, 1830, 1831, 1832, 1833,
1834
\expersian@L ... 1802, 1825, 1829,
1830, 1831, 1834, 1835
\XePersian@latini .. 4911, 4957
\XePersian@latinii . 4912, 4959,
4961
\XePersian@latiniii 4913, 4963
\XePersian@latiniv . 4914, 4964



\XePersian@latinix . 4919, 4969
\XePersian@latiniv . . 4915, 4965
\XePersian@latinvi . 4916, 4966
\XePersian@latinvii 4917, 4967
\XePersian@latinviii 4918, 4968
\XePersian@latinix . . 4920, 4970
\XePersian@latinxi . 4921, 4971
\XePersian@latinxii 4922, 4972
\XePersian@leapfalse 4942, 4946,
4952
\XePersian@leaptrue 4952, 4953
\XePersian@localize@verbatim@
. . . 2574, 2575, 2577, 2585,
2598, 2607, 2618, 2626, 2640
\XePersian@localize@verbatim@
. 2577, 2578
\XePersian@localize@verbatim@@
. 2580, 2581
\XePersian@localize@verbatim@@testend
. 2620, 2630
\XePersian@localize@verbatim@rescan
. 2634, 2643
\XePersian@localize@verbatim@start
. 2571, 2646, 2647, 2658
\XePersian@localize@verbatim@test
. . . 2589, 2591, 2592
\XePersian@localize@verbatim@testend
. 2603, 2610
\XePersian@m . . . 4910, 4935, 5031,
5050, 5053, 5065, 5068
\XePersian@milyoongan . . . 3306,
3317
\XePersian@milyoongan@tartibi
. 3407, 3418
\XePersian@mminusone 4932, 5031,
5032, 5034, 5038
\XePersian@ncol 4037, 4038
\XePersian@ncolumns 3687, 4388,
4389, 4456
\XePersian@nrow 4031, 4032
\XePersian@numberoutofrange .
. . . 3264, 3275, 3376
\XePersian@numberstring . 3261,
3269
\XePersian@numberstring@tartibi
. 3367, 3370
\XePersian@PackageInfo . . 4625,
4683
\XePersian@pageleft 3685, 4472,
4473, 4475, 4477
\XePersian@pageneed
. . . 3684, 3986, 3987, 3989,
3992, 4471, 4477
\XePersian@pages 3906, 4141, 4173,
4458
\XePersian@persian@month 5065,
5070
\XePersian@persiani . 4911, 5011,
5012, 5042, 5059
\XePersian@persianii 4912, 5013
\XePersian@persianiii . . . 4913,
5015, 5017
\XePersian@persianiv 4914, 5019
\XePersian@persianix 4919, 5024
\XePersian@persianv 4915, 5020
\XePersian@persianvi 4916, 5021
\XePersian@persianvii . . . 4917,
5022
\XePersian@persianviii . . 4918,
5023
\XePersian@persianx 4920, 5025
\XePersian@persianxi 4921, 5026
\XePersian@persianxii . . . 4922,
5027
\XePersian@persianxiii . . 4923,
5028
\XePersian@pictureCaption 3902,
3998, 4212
\XePersian@R . . . 1803, 1820, 1832,
1834
\XePersian@sadgan . . 3310, 3315,
3319, 3323, 3328, 3411, 3424
\XePersian@sadgan@tartibi 3416,
3420, 3429
\XePersian@say 3975, 4455, 4475,
4478, 4480, 4504, 4530
\XePersian@secondSubtitle 3878,
4147
\XePersian@secondText 3882, 4151
\XePersian@secondTitle . . 3869,
4143
\XePersian@section . 3822, 3827,



445¹
 \xepersian@shellescape . . . 2956
 \xepersian@shortarticleItemTitle
 3940, 4544
 \xepersian@shortarticleSubtitle
 3938, 4524
 \xepersian@shortarticleTit . .
 4516, 4531¹
 \xepersian@shortarticleTitle .
 3936, 4520
 \XePersian@sn
 . . . 4931, 5030, 5042, 5043,
 5046, 5047, 5056, 5061
 \xepersian@tartibi . . 3367, 3443
 \XePersian@temp
 . . . 4925, 4936, 4937, 4938,
 4940, 4944, 4945, 4946, 4949,
 4950, 4951, 4952, 4974, 4975,
 4976, 4979, 4980, 4982, 4985,
 4986, 4990, 4991, 4994, 4997,
 5002, 5007, 5009, 5010, 5012
 \xepersian@tempa
 . . . 3550, 3558, 3564, 3570,
 3582, 3588, 3594, 3598, 3602,
 3608, 3621, 3633, 3645
 \xepersian@tempb
 . . . 3550, 3551, 3558, 3559,
 3564, 3565, 3570, 3571, 3582,
 3583, 3588, 3589, 3594, 3595,
 3598, 3599, 3602, 3603, 3608,
 3609, 3621, 3622, 3633, 3634,
 3645, 3646
 \XePersian@tempthree
 . . . 4927, 4988, 4989, 4990,
 4992, 4995, 4998, 4999, 5003,
 5006, 5007, 5008, 5009
 \XePersian@temptwo
 . . . 4926, 4976, 4977, 4978,
 4979, 4982, 4983, 4984, 4985,
 4992, 4993, 4994, 4995, 4996,
 4997, 4999, 5000, 5001, 5002,
 5003, 5004, 5005, 5006
 \xepersian@thirdSubtitle 3897,
 4180
 \xepersian@thirdText 3900, 4187
 \xepersian@thirdTitle . . . 3888,
 4176
 \XePersian@thirtytwo 4929, 4973,
 4980
 \xepersian@V 1805, 1826
 \xepersian@weather . . 3817, 4252
 \xepersian@www 3787, 4060
 \xepersian@wwwFormat 3786, 3788
 \XePersian@y
 . . . 4910, 4935, 4936, 4939,
 4949, 4952, 4974, 4988, 5051,
 5054, 5065, 5067
 \xepersian@yekani . . 3310, 3338,
 3342, 3349, 3352, 3411
 \xepersian@yekanii . . 3261, 3323,
 3348, 3424
 \xepersian@yekaniiiii 3319, 3351,
 3420
 \xepersian@yekaniv . . 3330, 3354,
 3431
 \xepersian@yekanv . . 3439, 3450
 \XePersian@yModHundred . . 4928,
 4939, 4940, 4941, 4944, 4948
 \xepersian@zwj . . 1799, 1806, 1807
 \xepersiandate 2903, 2904, 2920
 \xepersianInit 3743, 4044
 \xepersianversion . . 2902, 2904,
 2920
 \XeTeXcharclass 1814
 \XeTeXcharglyph 1807
 \XeTeXglyphbounds 1807
 \XeTeXinterchartokenstate 1837,
 1838
 \XeTeXinterchartoks 1828, 1829,
 1830, 1831, 1832, 1833, 1834,
 1835
 \xpg@warning . . . 3456, 3461, 3463

 Y
 \y 2942, 2944, 2946
 \year 4935

 Z
 \z 2943, 2944
 \z@ 10, 25, 42, 61, 72, 87,
 104, 123, 319, 320, 331, 333,
 1473, 1500, 1519, 1538, 1558,



1576, 1591, 1672, 1676, 1684,	\	1981
1695, 1711, 1728, 1747, 1754,	\	1975, 1979
1766, 1778, 1795, 2022, 2122,	\	2337, 2645
2126, 2131, 2132, 2140, 2150,	\	2559
2154, 2155, 2160, 2174, 2184,	\	1982, 2334, 2335
2188, 2189, 2194, 2210, 2232,		
2233, 2244, 2262, 2273, 2277,	\	1974
2278, 2291, 2305, 2492, 2538,	\	1977
2540, 2549, 2673, 2674, 2681,	\	1976, 1978
2682, 3169, 3187, 3198, 3305,		
3307, 3309, 3313, 3329, 3332,		
3338, 3406, 3408, 3410, 3414,		
3430, 3433, 3439, 3463, 3485,		
3489, 3493, 3496, 4986		
\z@skip	1471, 1472, 3187	
\ziffer@check	4730, 4731	
\ziffer@dcheck	4729, 4730	
\ziffer@DotOri	4727, 4730	
\ZifferAn	4725, 4728	
\ZifferLeer	4730, 4756	
\	1286, 1962, 2558	
\	1986, 1988, 1991, 1998	
\	1991	
\ ..	1976, 1983, 1984, 1987, 1988,	
	1996, 1998	
\	1981, 1982, 1986, 1993	
\ 1974, 1980, 1981, 1986, 1991, 1992		
\ ..	1287, 1288, 1289, 1290, 1291,	
	1292, 1293, 1294, 1984	
\ .	1986, 1987, 1992, 1993, 1995,	
	1996	
\	1986, 1991	
\	1986, 1987, 1992, 1996	
\	1981, 1982	
\	1986, 1988, 1993, 1998	
@ \	1975, 1979	
@ \ ..	2683, 2684, 2685, 2686,	
	2687, 2688, 2689, 2690, 2691,	
	2692, 2693, 2694, 2695, 2696,	
	2697, 2698, 2699, 2700, 2701,	
	2702, 2703, 2704	
@ \	1975	



8 Change History

v13.1	General: Added implementation of the package.	0
v13.2	General: Replaced <code>\reflect</code> with <code>\bidi@reflect@box</code>	123
v13.5	General: Fixed the extra space after Persian decimal separator. . . .	152
v13.6	General: Used <code>\XeTeXglyphbounds</code> to find the true height and depth of the Kashida character.	93

